```
Authentication with OAuth
Specifying Filter Parameters
Timezone Offsets
Fields
Updating Specific Fields
Pagination
Webhooks
Rate Limits
HTTP Response Codes
API Clients
RESOURCES
Advanced Filtering
Leads
Contacts
Activities
  Call
  Created
  Email
  EmailThread
  LeadStatusChange
  Meeting
  Note
  OpportunityStatusChange
  SMS
  TaskCompleted
Opportunities
Tasks
Memberships
Users
Organizations
Roles
Custom Fields
  Lead Custom Fields
  Contact Custom Fields
  Opportunity Custom Fields
  Activity Custom Fields
  Shared Custom Fields
  Custom Field Schemas
Lead Statuses
Opportunity Statuses
Pipelines
Groups
Reporting
Email Templates
SMS Templates
Connected Accounts
Send As
Sequences
Dialer
Smart Views
Bulk Actions
Integration Links
Exports
Phone Numbers
Event Log
  List of Events
  Retrieve Events
Webhook Subscriptions
  Webhook Filters
Scheduling Links
  User Scheduling Links
  Shared Scheduling Links
  Scheduling Link Associations
Custom Activities
  Custom Activity Types
  Custom Activity Instances
```

Close Docs

Close API Documentation

X COLLAPSE ALL

Introduction

GETTING STARTED

Authentication with API keys

CHANGELOG API Changelog Product Changelog 🖸

QUICK LINKS Log in to Close 🖸 Visit our Homepage 🖸 Close Support Documentation 🖸 The Making of Close 🖸

Bulk Actions

Bulk actions are used to perform an "action" (send an email, update a lead status, etc.) on a number of leads.

Lead filtering

^

To initiate bulk actions for a subset of leads you need to provide the structured filtering values that you would normally send to the Advanced Filtering API endpoint such as query, results_limit, and sort fields.

The only difference is that Bulk Actions endpoints require you to rename the query field to s_query (shorthand for structured query).

For example, this is the payload that you would send to the Advanced Filtering API endpoint:

```
Copy
        "query": {
            "queries": [
                . . .
            ],
        "results_limit": 100,
        "sort": [
13 }
```

and this is the equivalent payload you would send to Bulk Actions endpoints (note the renamed query -> s_query field):

```
Сору
"s_query": {
    "queries": [
    ],
"results_limit": 100,
"sort": [
        . . .
```

Pausing and resuming

You can pause an in-progress bulk action by sending { 'status': 'paused' }. You can also resume it afterwards ({ 'status': 'resuming' }), unless more than 7 days passed since you paused the action.

Receiving an email after you're done

Use "send_done_email": false if you don't want to get a confirmation email after a bulk action is done.

List bulk emails.

GET /bulk_action/email/

```
✓ Example Request/Response
```

Initiate a new bulk email.

POST /bulk_action/email/

contact_preference can be set to lead (only email the primary/first contact email of the lead) or contact (email the first contact email of each contact of the lead).

```
✓ Example Request/Response
```

Fetch a single bulk email object.

GET /bulk_action/email/{id}/

```
✓ Example Request/Response
```

List bulk sequence subscriptions.

GET /bulk_action/sequence_subscription/

```
✓ Example Request/Response
```

Initiate a new bulk sequence subscription.

POST /bulk_action/sequence_subscription/

action_type must be one of:

- subscribe to create a new sequence subscription for contacts that have never received the given sequence.
- resume to resume any paused sequence subscriptions for the given sequence or all sequences if sequence_id is not provided.
- resume_finished to resume any finished sequence subscriptions for the given sequence or all sequences if sequence_id is not provided.
- pause to pause any active sequence subscriptions for the given sequence or all sequences if sequence_id is not provided.

sequence_id, sender_account_id, sender_name, sender_email and contact_preference are required if action_type is subscribe.

contact_preference can be set to:

- lead to only subscribe the primary/first contact email of the lead.
- contact to subscribe the primary email of each contact of the lead.

```
✓ Example Request/Response
```

Fetch a single bulk sequence subscription object.

```
GET /bulk_action/sequence_subscription/{id}/
```

✓ Example Request/Response

```
GET /bulk_action/delete/
```

Initiate a new bulk delete.

✓ Example Request/Response

POST /bulk_action/delete/

List bulk deletes.

Use "send_done_email": false if you don't want to get a confirmation email after the bulk action is done.

```
✓ Example Request/Response
```

Fetch a single bulk delete object.

```
GET /bulk_action/delete/{id}/
```

```
✓ Example Request/Response
```

```
List bulk edits.
GET /bulk_action/edit/
```

```
✓ Example Request/Response
```

Initiate a new bulk edit.

POST /bulk_action/edit/

Pass additional parameters depending on which type is passed:

- set_lead_status will set the Lead Status on all leads. It expects: • lead_status_id - ID of the Lead Status to use.
- clear_custom_field will clear/remove/unset a specific custom field from all leads. It expects:
- custom_field_id or custom_field_name ID or exact name of the custom field to remove.

Use "send_done_email": false if you don't want to get a confirmation email after the bulk action is done.

- set_custom_field will set/update/add a specific custom field on all leads. It expects: • custom_field_id or custom_field_name - ID or exact name of the custom field to set/update.
- custom_field_operation replace, add, or remove (defaults to replace). Only applicable for custom fields that accept multiple values.

• custom_field_value - New value. Use custom_field_values to pass multiple values to custom fields that support it.

```
✓ Example Request/Response
```

```
Fetch a single bulk edit object.
```

```
GET /bulk_action/edit/{id}/
```

Smart Views

```
✓ Example Request/Response
```