

GETTING STARTED

^

Introduction

Authentication with API keys

Authentication with OAuth

Specifying Filter Parameters

Timezone Offsets

Fields

Updating Specific Fields

Pagination

Webhooks

Rate Limits

HTTP Response Codes

API Clients

RESOURCES

^

Advanced Filtering

Leads

Contacts

Activities

Call

Created

Email

EmailThread

LeadStatusChange

Meeting

Note

OpportunityStatusChange

SMS

TaskCompleted

Opportunities

Tasks

Memberships

Users

Organizations

Roles

Custom Fields

Lead Custom Fields

Contact Custom Fields

Opportunity Custom Fields

Activity Custom Fields

Shared Custom Fields

Custom Field Schemas

Lead Statuses

Opportunity Statuses

Custom Activity Instances

List or filter all Custom Activity instances.

```
GET /activity/custom/{?lead_id, user_id, date_created__gt, date_created__lt, custom_activity_type_id, custom_activity_type_id__in}
```

Custom Fields appear in the format: `custom.{custom_field_id}`. See [Custom Fields](#).

If you're filtering by `custom_activity_type_id` or `custom_activity_type_id__in` parameter, the `lead_id` parameter will be required as well. If you want to retrieve all Custom Activity instances of a specific type regardless of the lead, you will need to get leads that contain such an activity type using [Advanced Filtering](#) and provide those Lead IDs one at a time to this endpoint.

▼

Example Request/Response

Create a new Custom Activity instance.

```
POST /activity/custom/
```

Custom Activity instances will be created by default with the 'published' status. All required fields will be validated in this status. To create an activity without setting all required fields, you can use the "draft" status.

▼

Example Request/Response

Retrieve a single Custom Activity instance.

```
GET /activity/custom/{id}/
```

▼

Example Request/Response

Updating a Custom Activity instance.

```
PUT /activity/custom/{id}/
```

A Custom Activity can be updated to add, change or remove any Custom Fields and to change the status between "draft" and "published".

▼

Example Request/Response

Delete a Custom Activity instance.

```
DELETE /activity/custom/{id}/
```

▼

Example Request/Response