

Software Testing: The Big Picture

Dr. Paul West

Department of Computer Science
College of Charleston

January 9, 2014

Engineering Process

- Sophisticated tools
 - amplify capabilities
 - but do not remove human error
- Engineering disciplines pair
 - construction activities with
 - activities that check intermediate and final products
- Software engineering is no exception: construction of high quality software requires construction and verification activities

Verification and Design Activities

- Verification and design activities take various forms
 - Suited to highly repetitive construction of non-critical items for mass markets
 - Highly customized or highly critical products.
- Appropriate verification activities(tools) depend on
 - Engineering discipline
 - Construction process
 - Final product
 - Quality requirements

Peculiarities of Software

Software has some characteristics that make V&V particularly difficult:

- Many different quality requirements
- Evolving (and deteriorating) structure
- Inherent non-linearity
- Uneven distribution of fault

Example

If an elevator can safely carry a load of 1000 kg, it can also safely carry any smaller load; If a procedure correctly sorts a set of 256 elements, it may fail on a set of 255 or 53 or 12 elements, as well as on 257 or 1023.

Impact of New Technologies

- Advanced development technologies can reduce the frequency of some classes of errors
- But do not eliminate errors
- New development approaches can introduce new kinds of faults

Examples

- Deadlock or race conditions for distributed software
- New problems due to the use of polymorphism, dynamic binding and private state in object-oriented software.

Approaches

- There are no fixed recipes
- Test designers must
 - Choose and schedule the right blend of techniques
 - To reach the required level of quality
 - Within cost constraints
 - Design a specific solution that suits
 - The problem
 - The requirements
 - The development environment

Basic Questions

- 1 When do verification and validation start? When are they complete?
- 2 What particular techniques should be applied during development?
- 3 How can we assess the readiness of a product?
- 4 How can we control the quality of successive releases?
- 5 How can the development process itself be improved?

When to Start and Complete V&V

- Start creating Tests from the beginning
 - Execution of tests is a small part of the verification and validation process
- V&V start as soon as we decide to build a software product, or even before
- V&V last far beyond the product delivery as long as the software is in use, to cope with evolution and adaptations to new conditions

Early Start: From Feasibility Study

- The feasibility study of a new project must take into account the required qualities and their impact on the overall cost
- At this stage, quality related activities include
 - Risk analysis
 - Measures needed to assess and control quality at each stage of development.
 - Assessment of the impact of new features and new quality requirements
 - Contribution of quality control activities to development cost and schedule.

Maintenance

- Maintenance activities include
 - Analysis of changes and extensions
 - Generation of new test suites for the added functionalities
 - Re-executions of tests to check for non regression of software functionalities after changes and extensions
 - Fault tracking and analysis

Techniques

No single Analysis/Testing technique can serve all purposes

The primary reasons for combining techniques are:

- Effectiveness for different classes of faults
example: analysis instead of testing for race conditions
- Applicability at different points in a project
example: inspection for early requirements validation
- Differences in purpose
example: statistical testing to measure reliability
- Tradeoffs in cost and assurance
example: expensive technique for key properties

Readiness of a Product

- A&T during development aims at revealing faults
- We cannot reveal and remove all faults
- A&T cannot last indefinitely: we want to know if products meet the quality requirements
- We must specify the required level of dependability and determine when that level has been attained.

Dependability

- Availability measures the quality of service in terms of running versus down time
- Mean time between failures (MTBF) measures the quality of the service in terms of time between failures
- Reliability indicates the fraction of all attempted operations that complete successfully

Dependability Examples

Web application

- 50 interactions terminating with a credit card charge.
- The software always operates flawlessly up to the point that a credit card is to be charged, but on half the attempts it charges the wrong amount.

What is the reliability of the system?

- If we count the fraction of individual interactions that are correctly carried out, only one operation in 100 fail: The system is 99% reliable.
- If we count entire sessions, only 50% reliable, since half the sessions result in an improper credit card charge

Assessing Dependability

- Randomly generated tests following an operational profile
- Alpha test: tests performed by users in a controlled environment, observed by the development organization
- Beta test: tests performed by real users in their own environment, performing actual tasks without interference or close monitoring

Software Quality

- Software test and analysis does not stop at the first release.
- Software products operate for many years, and undergo many changes:
 - They adapt to environment changes
 - They evolve to serve new and changing user requirements.
- Quality tasks after delivery
 - test and analysis of new and modified code
 - re-execution of system tests
 - extensive record-keeping

Process Improvement

- The same defects are encountered in project after project
- A third goal of the improving the quality process is to improve the process by
 - Identify and remove weaknesses in the development process
 - Identify and remove weaknesses in test and analysis that allow them to remain undetected

Four Step Process Improvement

- 1 Define the data to be collected and implementing procedures for collecting them
- 2 Analyze collected data to identify important fault classes
- 3 Analyze selected fault classes to identify weaknesses in development and quality measures
- 4 Adjust the quality and development process

Process Improvement Example

- 1 Faults that affect security were given highest priority
- 2 During A&T we identified several buffer overflow problems that may affect security
- 3 Faults were due to bad programming practice and were revealed late due to lack of analysis
- 4 Action plan: Modify programming discipline and environment and add specific entries to inspection checklists

Summary

- The quality process has three different goals:
 - Improving a software product
 - assessing the quality of the software product
 - improving the quality process
- We need to combine several A&T techniques through the software process
- A&T depend on organization and application domain.
- Cost-effectiveness depends on the extent to which techniques can be re-applied as the product evolves.
- Planning and monitoring are essential to evaluate and refine the quality process.

Chapter 1 Assignment

Choose and complete any two Chapter 1 Exercises (pg 13-14)
Due in the dropbox by January 23, 2014 2359