

# Lexic.txt

Alphabet:

- a. Upper (A-Z) and lower case letters (a-z)
- b. Underline character '\_'
- c. Decimal digits (0-9)

Lexic:

a. Special symbols:

- operators: + - \* / < > = <= >= == %
- separators: ( ) [ ] { } : ; space
- reserved words: be number integer string char bool check  
readFromConsole showInConsole stopWhen for function

b. Identifiers:

- it is a sequence and chars and digits, the first letter being a letter:
  - letter = "a" | "b" | ... | "z" | "A" | "B" | ... | "Z"
  - digit = "0" | "1" | "2" | ... | "9"
  - identifier = letter | letter {letter} {digit}

c. Constants:

- number:  
number = ["-"]digit {digit}
- char:  
char = 'letter' | 'digit'
- string:  
char = letter | digit  
string = char {string}

# token.in

(

)

\*

-

+

/

:

;

[

]

{

}

%

=

<

>

&

|

be

number

integer

bool

string

char

check  
readFromConsole  
showInConsole  
stopWhen  
function  
for  
space

# Syntax.in

program ::=

decllist ::= declaration | declaration decllist

declaration ::= "be" IDENTIFIER type

type1 ::= "bool" | "char" | "integer" | "number" | "string"

arraydecl ::= type1 "[" nr "]"

type ::= type1 | arraydecl

cmpdstmt ::= stmtlist

stmtlist ::= stmt | stmt stmtlist

stmt ::= simplstmt | structstmt

simplstmt ::= assignstmt | iostmt

assignstmt ::= IDENTIFIER "=" expression

expression ::= expression ("+" | "-") term | term

term ::= term ("\*" | "/" | "%") factor | factor

factor ::= "(" expression ")" | CONST | IDENTIFIER

iostmt ::= "readFromConsole" "(" IDENTIFIER ")" | "showInConsole" "(" IDENTIFIER ")"

structstmt ::= cmpdstmt | ifstmt | whilestmt

ifstmt ::= "check" "(" condition ")" "{" cmpdstmt "}" "else" "{" cmpdstmt "}"

whilestmt ::= "stopwhen" "(" condition ")" "{" cmpdstmt "}"

condition ::= expression relation expression ("|" | "&&" condition)

relation::= "<" | "<=" | "==" | "!=" | ">=" | ">"