

✓ Congratulations! You passed!

Next Item



1 / 1  
points

1. Suppose your training examples are sentences (sequences of words). Which of the following refers to the  $j^{th}$  word in the  $i^{th}$  training example?

☒  $x^{(i)<j>}$

Correct

We index into the  $i^{th}$  row first to get the  $i^{th}$  training example (represented by parentheses), then the  $j^{th}$  column to get the  $j^{th}$  word (represented by the brackets).

☐  $x^{<i>(j)}$


☐  $x^{(j)<i>}$

☐  $x^{<j>(i)}$



1 / 1  
points

2. Consider this RNN:



This specific type of architecture is appropriate when:

☒  $T_x = T_y$

Correct

It is appropriate when every input should be matched to an output.

☐  $T_x < T_y$


☐  $T_x > T_y$

☐  $T_x = 1$



1 / 1  
points

3. To which of these tasks would you apply a many-to-one RNN architecture? (Check all that apply).



- ☐ Speech recognition (input an audio clip and output a transcript)

Un-selected is correct

- ☒ Sentiment classification (input a piece of text and output a 0/1 to denote positive or negative sentiment)

Correct

- ☐ Image classification (input an image and output a label)

Un-selected is correct


- ☒ Gender recognition from speech (input an audio clip and output a label indicating the speaker's gender)

Correct



4. You are training this RNN language model.

1 / 1  
points



At the  $t^{th}$  time step, what is the RNN doing? Choose the best answer.

- ☐ Estimating  $P(y^{<1>}, y^{<2>}, \dots, y^{<t-1>})$
- ☐ Estimating  $P(y^{<t>})$
- ☒ Estimating  $P(y^{<t>} | y^{<1>}, y^{<2>}, \dots, y^{<t-1>})$


Correct

- ☐ Estimating  $P(y^{<t>} | y^{<1>}, y^{<2>}, \dots, y^{<t>})$



5. You have finished training a language model RNN and are using it to sample random sentences, as follows:

1 / 1  
points



What are you doing at each time step  $t$ ?

- ☐ (i) Use the probabilities output by the RNN to pick the highest probability word for that time-step as  $\hat{y}^{<t>}$ . (ii) Then pass the ground-truth word from the training set to the next time-step.
- ☐ (i) Use the probabilities output by the RNN to randomly sample a chosen word for that time-step as  $\hat{y}^{<t>}$ . (ii) Then pass the ground-truth word from the training set to the next time-step.
- ☐ (i) Use the probabilities output by the RNN to pick the highest probability word for that time-step as  $\hat{y}^{<t>}$ . (ii) Then pass this selected word to the next time-step.
- ☒ (i) Use the probabilities output by the RNN to randomly sample a chosen word for that time-step as  $\hat{y}^{<t>}$ . (ii) Then pass this selected word to the next time-step.



1 / 1 points

6. You are training an RNN, and find that your weights and activations are all taking on the value of NaN ("Not a Number"). Which of these is the most likely cause of this problem?

- ☐ Vanishing gradient problem.
- ☒ Exploding gradient problem.

Correct

- ☐ ReLU activation function  $g(\cdot)$  used to compute  $g(z)$ , where  $z$  is too large.
- ☐ Sigmoid activation function  $g(\cdot)$  used to compute  $g(z)$ , where  $z$  is too large.



1 / 1 points

7. Suppose you are training a LSTM. You have a 10000 word vocabulary, and are using an LSTM with 100-dimensional activations  $a^{<t>}$ . What is the dimension of  $\Gamma_u$  at each time step?

- ☐ 1
- ☒ 100

Correct

- ☐ 300
- ☐ 10000



1 / 1 points

8. Here're the update equations for the GRU.

## GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

Alice proposes to simplify the GRU by always removing the  $\Gamma_u$ , i.e., setting  $\Gamma_u = 1$ . Betty proposes to simplify the GRU by removing the  $\Gamma_r$ , i.e., setting  $\Gamma_r = 1$  always. Which of these models is more likely to work without vanishing gradient problems even when trained on very long input sequences?

- ☐ Alice's model (removing  $\Gamma_u$ ), because if  $\Gamma_r \approx 0$  for a timestep, the gradient can propagate back through that timestep without much decay.
- ☐ Alice's model (removing  $\Gamma_u$ ), because if  $\Gamma_r \approx 1$  for a timestep, the gradient can propagate back through that timestep without much decay.
- ☒ Betty's model (removing  $\Gamma_r$ ), because if  $\Gamma_u \approx 0$  for a timestep, the gradient can propagate back through that timestep without much decay.

Correct

- ☐ Betty's model (removing  $\Gamma_r$ ), because if  $\Gamma_u \approx 1$  for a timestep, the gradient can propagate back through that timestep without much decay.

1 / 1  
points

9. Here are the equations for the GRU and the LSTM:

## GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

## LSTM

$$\tilde{c}^{<t>} = \tanh(W_c[a^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[a^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_f = \sigma(W_f[a^{<t-1>}, x^{<t>}] + b_f)$$

$$\Gamma_o = \sigma(W_o[a^{<t-1>}, x^{<t>}] + b_o)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + \Gamma_f * c^{<t-1>}$$

$$a^{<t>} = \Gamma_o * c^{<t>}$$

From these, we can see that the Update Gate and Forget Gate in the LSTM play a role similar to \_\_\_\_\_ and \_\_\_\_\_ in the GRU. What should go in the the blanks?

☒  $\Gamma_u$  and  $1 - \Gamma_u$

Correct

☐  $\Gamma_u$  and  $\Gamma_r$

☐  $1 - \Gamma_u$  and  $\Gamma_u$

☐  $\Gamma_r$  and  $\Gamma_u$

1 / 1  
points

10. You have a pet dog whose mood is heavily dependent on the current and past few days' weather. You've collected data for the past 365 days on the weather, which you represent as a sequence as  $x^{<1>}, \dots, x^{<365>}$ . You've also collected data on your dog's mood, which you represent as  $y^{<1>}, \dots, y^{<365>}$ . You'd like to build a model to map from  $x \rightarrow y$ . Should you use a Unidirectional RNN or Bidirectional RNN for this problem?

☐ Bidirectional RNN, because this allows the prediction of mood on day  $t$  to take into account more information.

☐ Bidirectional RNN, because this allows backpropagation to compute more accurate gradients.

☒ Unidirectional RNN, because the value of  $y^{<t>}$  depends only on  $x^{<1>}, \dots, x^{<t>}$ , but not on  $x^{<t+1>}, \dots, x^{<365>}$

Correct

☐ Unidirectional RNN, because the value of  $y^{<t>}$  depends only on  $x^{<t>}$ , and not other days' weather.