

✓ **Congratulations! You passed!**

Next Item



1 / 1
points

1.

Which notation would you use to denote the 3rd layer's activations when the input is the 7th example from the 8th minibatch?



$a^{[3]\{7\}}(8)$



$a^{[3]\{8\}}(7)$



Correct



$a^{[8]\{7\}}(3)$



$a^{[8]\{3\}}(7)$



0 / 1
points

2.

Which of these statements about mini-batch gradient descent do you agree with?



You should implement mini-batch gradient descent without an explicit for-loop over different mini-batches, so that the algorithm processes all mini-batches at the same time (vectorization).



One iteration of mini-batch gradient descent (computing on a single mini-batch) is faster than one iteration of batch gradient descent.

Optimization algorithms

Quiz, 10 questions



Training one epoch (one pass through the training set) using mini-batch gradient descent is faster than training one epoch using batch gradient descent.

8/10 points (80%)



This should not be selected



1 / 1
points

3.

Why is the best mini-batch size usually not 1 and not m , but instead something in-between?



If the mini-batch size is 1, you lose the benefits of vectorization across examples in the mini-batch.



Correct



If the mini-batch size is 1, you end up having to process the entire training set before making any progress.



Un-selected is correct



If the mini-batch size is m , you end up with batch gradient descent, which has to process the whole training set before making progress.



Correct



If the mini-batch size is m , you end up with stochastic gradient descent, which is usually slower than mini-batch gradient descent.



Un-selected is correct




points

Optimization algorithms

Quiz, 10 questions

8/10 points (80%)

Suppose your learning algorithm's cost J , plotted as a function of the number of iterations, looks like this:



Which of the following do you agree with?



If you're using mini-batch gradient descent, this looks acceptable. But if you're using batch gradient descent, something is wrong.



Correct



If you're using mini-batch gradient descent, something is wrong. But if you're using batch gradient descent, this looks acceptable.



Whether you're using batch gradient descent or mini-batch gradient descent, this looks acceptable.



Whether you're using batch gradient descent or mini-batch gradient descent, something is wrong.



1 / 1
points

Optimization algorithms

8/10 points (80%)

Quiz, 10 questions

5.

Suppose the temperature in Casablanca over the first three days of January are the same:

Jan 1st: $\theta_1 = 10^\circ C$

Jan 2nd: $\theta_2 = 10^\circ C$

(We used Fahrenheit in lecture, so will use Celsius here in honor of the metric world.)

Say you use an exponentially weighted average with $\beta = 0.5$ to track the temperature: $v_0 = 0$, $v_t = \beta v_{t-1} + (1 - \beta)\theta_t$. If v_2 is the value computed after day 2 without bias correction, and $v_2^{corrected}$ is the value you compute with bias correction. What are these values? (You might be able to do this without a calculator, but you don't actually need one. Remember what is bias correction doing.)



$v_2 = 7.5, v_2^{corrected} = 10$



Correct



$v_2 = 10, v_2^{corrected} = 10$



$v_2 = 7.5, v_2^{corrected} = 7.5$



$v_2 = 10, v_2^{corrected} = 7.5$



1 / 1
points

6.

Which of these is NOT a good learning rate decay scheme? Here, t is the epoch number.



$\alpha = 0.95^t \alpha_0$



$\alpha = e^t \alpha_0$



Correct

Optimization algorithms

Quiz, 10 questions

☐ $\alpha = \frac{1}{\sqrt{t}} \alpha_0$

☐ $\alpha = \frac{1}{1+2*t} \alpha_0$

8/10 points (80%)




0 / 1
points

7.

You use an exponentially weighted average on the London temperature dataset. You use the following to track the temperature:

$$v_t = \beta v_{t-1} + (1 - \beta) \theta_t.$$

The red line below was computed using $\beta = 0.9$. What would happen to your red curve as you vary β ? (Check the two that apply)



Decreasing β will shift the red line slightly to the right.



Un-selected is correct



Increasing β will shift the red line slightly to the right.



This should be selected

Optimization algorithms

Quiz, 10 questions

8/10 points (80%)



Decreasing β will create more oscillation within the red line.

Correct

True, remember that the red line corresponds to $\beta = 0.9$. In lecture we had a yellow line $\beta = 0.98$ that had a lot of oscillations.



Increasing β will create more oscillations within the red line.

This should not be selected


False. Increasing β will cause fewer oscillations



1 / 1
points

8.

Consider this figure:



These plots were generated with gradient descent; with gradient descent with momentum ($\beta = 0.5$) and gradient descent with momentum ($\beta = 0.9$). Which curve corresponds to which algorithm?



(1) is gradient descent with momentum (small β), (2) is gradient descent with momentum (small β), (3) is gradient descent



(1) is gradient descent. (2) is gradient descent with momentum (small β). (3) is gradient descent with momentum (large β)

Correct



Optimization algorithms

Quiz, 10 questions

(1) is gradient descent with momentum (small β). (2) is gradient descent. (3) is gradient descent with momentum (large β)

8/10 points (80%)



(1) is gradient descent. (2) is gradient descent with momentum (large β) . (3) is gradient descent with momentum (small β)



1 / 1
points

9.

Suppose batch gradient descent in a deep network is taking excessively long to find a value of the parameters that achieves a small value for the cost function $\mathcal{J}(W^{[1]}, b^{[1]}, \dots, W^{[L]}, b^{[L]})$. Which of the following techniques could help find parameter values that attain a small value for \mathcal{J} ? (Check all that apply)

☐

Try better random initialization for the weights



Correct

☐

Try using Adam



Correct

☐

Try mini-batch gradient descent



Correct

☐

Try initializing all the weights to zero



Un-selected is correct

☐

Try tuning the learning rate α



Correct

Optimization algorithms



1 / 1
points

8/10 points (80%)

Quiz, 10 questions

10.

Which of the following statements about Adam is False?



Adam should be used with batch gradient computations, not with mini-batches.



Correct



Adam combines the advantages of RMSProp and momentum



The learning rate hyperparameter α in Adam usually needs to be tuned.



We usually use “default” values for the hyperparameters β_1, β_2 and ε in Adam ($\beta_1 = 0.9, \beta_2 = 0.999, \varepsilon = 10^{-8}$)

