

# DESIGN OF REAR WING OF AN ELECTRIC RACE CAR



Steffan Johan Kirk – S170816  
Carl-Emil Grøn Christensen – S170817  
Department of Mechanical Engineering, Technical University of Denmark

Supervisor:  
Jens Walther  
Department of Mechanical Engineering, Technical University of Denmark

August 2018

# Acknowledgements

We would like to thank our supervisors Jens Walther and Robert Mikkelsen, who allowed us to learn intricate details about our own personal project. A special thanks to everyone on the team of Vermilion Racing, who in less than a year managed to take a dream and make it reality. Vermilion Racing is going to compete at the Silverstone race track the 10<sup>th</sup> of July, where all of our ideas and designs are going to be tested to the limit.

Thanks to Rasmus Himborg from Philips Lighting Denmark, for helping us machine a 1/4 scale wing used in the wind tunnel tests.

Thanks to Bo Tranberg for assisting with graphical setup of the report and making sure our figures are beautiful.

Thanks to Nicolai Boertmann and Daniel Rasmussen for the help building the composite wings.

Thanks to DTU Skylab, and especially Martin Meister, Rasmus Bruun, Ralle Malone and Tonja Kramer for always having the time to help us when things looked most dire.

Lastly, a thank to Nenad Mijatovic. Nenad is the overall supervisor for Vermilion Racing and is a significant reason we recently became a DTU Blue Dot project - a highly prestigious title that will ensure that the team will survive for many years to come.



**DTU Skylab**  
- where it begins

Technical University  
of Denmark



**POWERFINN™**

PART OF MICROPOWER GROUP



**NØRDEA  
FONDEN**

Vi støtter gode liv



**SIEMENS** | Fonden



**SKF**



**IWAKI**

**Tranes Fond**



**LiLITHIUM BALANCE**  
BATTERY MANAGEMENT SYSTEMS

**Karl Pedersen & Hustru Fond**

**Mogens Balslevs Fond**



## **Abstract**

Race cars wooo! Formula studee3333nt



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Design Philosophy . . . . .	2
<b>2</b>	<b>Aerodynamic Effects on Vehicle Performance</b>	<b>3</b>
2.1	Drag Effects on Straights . . . . .	3
2.1.1	Downforce Effects on Cornering . . . . .	4
2.1.2	Load Distribution . . . . .	5
<b>3</b>	<b>Airfoils and Inverted Wings</b>	<b>7</b>
3.1	Airfoil theory . . . . .	7
3.1.1	Pressure distribution . . . . .	7
3.1.2	Lift and Drag Coefficient . . . . .	7
3.1.3	Which parameters does an airfoil have? What can we change . . . . .	8
3.1.4	Angle of Attack . . . . .	8
3.1.5	Ground Effects . . . . .	8
3.1.6	Aspect Ratio and End Plates . . . . .	8
<b>4</b>	<b>Concept Design</b>	<b>10</b>
4.1	Comparison of Airfoils . . . . .	10
4.2	Multi elements? How many is enough . . . . .	10
4.3	Product Design Specification (PDS) . . . . .	11
4.4	Initial Design . . . . .	11
4.5	Optimization Tools . . . . .	11
<b>5</b>	<b>Wind Tunnel Experiment</b>	<b>12</b>
5.1	Aerodynamical Theory . . . . .	12
5.1.1	Similarity of Flows . . . . .	12
5.2	Equipment . . . . .	13
5.2.1	Instrumentation . . . . .	13
5.2.2	Manufacturing the 1/4 Scale Rear Wing . . . . .	14
5.3	Experimental Procedure . . . . .	17
5.4	Results . . . . .	17
<b>6</b>	<b>Simulation</b>	<b>18</b>
6.1	Star-CCM+ . . . . .	18
6.2	Finite Volume method . . . . .	18

6.3	Mesh Generation . . . . .	18
6.4	The Rear Wing . . . . .	18
6.4.1	Verification of Simulation Results . . . . .	18
6.4.2	Multi-Element Wing Optimization . . . . .	19
6.5	The Aerodynamics Package . . . . .	19
6.5.1	Undertray, Diffuser, Front Wing and Driver . . . . .	19
6.5.2	Everything Together Now . . . . .	19
6.6	Results . . . . .	19
<b>7</b>	<b>Construction</b>	<b>20</b>
7.1	Requirements . . . . .	20
7.1.1	Dimensional Requirements . . . . .	20
7.1.2	Strength Requirements . . . . .	21
7.2	Material Selection . . . . .	22
7.3	Composites . . . . .	22
7.3.1	Sandwich Structure . . . . .	22
7.3.2	Wing Deflection . . . . .	22
7.4	Final Design of Rear Wing . . . . .	22
7.4.1	Blue Prints . . . . .	22
7.5	Manufacturing Final Design . . . . .	22
7.5.1	Polystyrene Molds . . . . .	22
7.5.2	Hand Layup . . . . .	22
7.5.3	Surface Finish . . . . .	22
7.5.4	Implementation and Testing . . . . .	22
7.6	Testing and Inspection . . . . .	22
7.6.1	Reinforcing the mounting . . . . .	22
<b>8</b>	<b>Discussion</b>	<b>27</b>
<b>9</b>	<b>Conclusion</b>	<b>28</b>
9.1	Drag Reductive System . . . . .	29
9.2	Slats, Flaps, Gills and Cutaway . . . . .	29
9.3	Suspension Integration . . . . .	29
<b>A</b>	<b>Appendix</b>	<b>31</b>
<b>Bibliography</b>		<b>32</b>

# Introduction

*Vermilion Racing* is a newly started Electric race car team building their first vehicle: The Eevee [1]. The teams' purpose is competing against other Universities at the Silverstone race track from the 11<sup>th</sup> to the 16<sup>th</sup>. As members of the team, the purpose of this report is to document the design process of the rear wing of the first car, the Eevee, and provide an aerodynamic package documenting drag and downforce.

Aerodynamics is a major decider in racing today. Cornering, not top speed is the deciding factor amongst the teams, and aerodynamics is the key. Drag, lift and side force are the three cornerstones to vehicle aerodynamics. A car's ability to handle depends on the grip of the tyres, and downforce directly increases grip by increasing the downwards load on the tyres without adding a weight penalty. Additionally, drag directly decreases the speed of a vehicle by increasing air resistance, but is of less importance as the car's in this class have far more accelerative power than the tyres can handle [2]. Designing the bodyworks of Eevee is therefore a dance of downforce.

This bachelor thesis attempts to lay down the ground work for designing, optimizing and manufacturing the car's rear wing. Our advisor, Jens Honore Walther, proposed simulating the wing geometry in order to both cheapen and quicken the optimization process, but also gain insight into how flow in front of the rear wing affects lift performance. The purpose of the numerical simulations are ultimately to create an easily producable wing in a very short timespan, that produces ample amounts of negative lift for the time spent in production.

As this is the first year the team building a car, time and money for production is sparse. To ensure the simulated optimizations are true, a wind tunnel test is performed on a down-scaled wing using Flow Similarity theory. The measurements are compared with the results from a computational fluid dynamics simulation performed in Star-CCM+ to verify the preciseness of the simulations. Based on this, the size,  $x$ - and  $y$ -distance between the multi-element wings, angle of attack and height relative to the chassis is then optimized for maximum downforce. The multi-element wing is taken from theoretical abstraction to reality with a physical design of the wing. The position, deflection and dimensions of the wing is thoroughly described by the rules of the Formula Student competition, guiding the final design process. In the final chapter, theories regarding strength of sandwich structured composites and carbon fiber

Fixme Note: wrt  
what has been d

molding are handled, in order to describe the production choices made. Finally, the end result is discussed and possible improvements to the wing and mounting system is listed.

Measurements and tests have been carried out at the DTU Wind laboratory's Red wind tunnel with the help of our supervisor Robert Flemming Mikkelsen the 19<sup>th</sup> of June.

The entire project is publicly available on [https://github.com/carlegroen/bachelor\\_project\\_racecar\\_aero](https://github.com/carlegroen/bachelor_project_racecar_aero), where all work files, data, various notes and CAD drawings can be found. The Formula Student team at DTU: Vermilion Racing can be followed on <fb.com/FSDTU>.

### 1.1 Design Philosophy

Designing a car with hundreds, if not thousands different factors is incredibly difficult. Therefore, analyzing which things matters and which don't is crucial to the teams' success. First, the deadline for finishing the wing is soon. This sets a limit on the complexity of the wing's dimensions. Secondly, this is the first iteration of the car, thus no decision can be based on prior experience, and optimization has to wait for the next iteration. Finally, the finances of the car is tight. This forces us to go with a low-cost solution. We therefore have to go for a simple, low cost wing, basing the design solely on litterature and experience other teams have done.

The wing has to have as low weight as possible, in order to ensure optimum acceleration of the car. Thereto, drag has to be kept low, but the effect from drag is near negligible, which will be explained in section 2.1. Lastly, we have to maximize the downforce provided by the wing, but also ensure that the center of pressure is kept as constant as possible. If the frontwing, undertray and rear wing's downforce don't scale equally with speed, the center of pressure will move during acceleration. This will make the car's handling unpredictable, and potentially limit the driver's confidence in the car.

# 2

## Aerodynamic Effects on Vehicle Performance

The first argument to the importance of aerodynamics is based around two facts: The fact that drag is negligible in regards to the Formula Student vehicle's top speed on straights, and the fact that aerodynamically increasing the vehicle's *effective* mass due to downforce increases tyre grip, which in turn allows for higher cornering velocities.

The second part of this chapter covers the importance of centering the effective mass increase due to aerodynamic devices close to the center of gravity – otherwise handling characteristics becomes a function of velocity.

### 2.1 Drag Effects on Straights

First, let's explain what makes a car fast, and what parameters we can change to improve the speed of our car.. The car's acceleration can be described by Newton's second law as:

$$\sum F_x = m\ddot{x} = F \quad (2.1)$$

Where the sum of forces in the x-direction (the direction of travel) can be expressed as the force already pertained by the vehicle, minus the drag force:

$$F - C_D \left( \frac{1}{2} \rho \dot{x}^2 A \right) = m\ddot{x} \quad (2.2)$$

Where  $C_D$  is the drag coefficient of the vehicle,  $\rho$  is the density of the fluid it moves in and  $A$  is frontal area of the vehicle. Assuming we're moving at a steady speed, the acceleration is 0, hence

$$F = C_D \left( \frac{1}{2} \rho \dot{x}^2 A \right) \quad (2.3)$$

As we were interested in the speed of the car, let's solve for the velocity. The force is given by  $F = \frac{P}{\dot{x}}$ , where  $P$  is the power of the car, which gives:

$$\dot{x} = \left( \frac{2P}{C_D (\rho A)} \right)^{\frac{1}{3}} \quad (2.4)$$



Figure 2.1: Frontal area of the car with a dummy wing inserted into the CAD model, in order to get an estimate of the drag coefficient  $C_D$ .

This is assuming we're traveling at terminal velocity – that is, the point where the Driving Force = Friction Force. The terminal velocity of the racer is then easily calculated, as the competition restricts the maximum amount of power to 80 kW, and the frontal area of the car is approximated from the CAD drawing seen in figure 2.1.

Fixme Note: fix calculation to us instead of 1.2  
Fixme Note: mis radiators

$$\dot{x}_{\max} = \left( \frac{2 \cdot 80 \text{ kW}}{0.85 (1.225 \text{ kg m}^{-3} 1.2 \text{ m}^2)} \right)^{\frac{1}{3}} = 50 \text{ m s}^{-1} = 181.4 \text{ km h}^{-1} \quad (2.5)$$

however, given the ruleset a forecasted maximum of 110 km h<sup>-1</sup> allows a much larger drag coefficient  $C_D$ :

$$C_D = \frac{2P}{\dot{x}^3 (\rho A)} = \frac{2 \cdot 80 \text{ kW}}{(120 \text{ km h}^{-1})^3 (1.225 \text{ kg m}^{-3} 1.2 \text{ m}^2)} = 2.82 \quad (2.6)$$

Thus, the car's top speed will only be limited by a drag factor  $> 2.82$ , which is far above the Fixme Note: ins drag introduced by the aerodynamic devices.

From this derivation, it is clear that the car's abilities at maximum speeds far exceed the requirement of the track. Therefore, the next step is to improve cornering speeds which depend strongly on the tyre's grip on the surface of the road [2].

### 2.1.1 Downforce Effects on Cornering

Shown before, drag does not limit the car's performance on straights. During cornering, drag is not an issue either, but the grip of the tyres limits the maximum velocity before the vehicle loses traction due to the centripetal force which is given by: [3]

$$F_{\text{centripetal}} = \frac{m\dot{x}^2}{r} \quad (2.7)$$

where  $r$  is the distance to the center of the cornering circle. The frictional force the car exerts due to downforce and tyre grip is given by:

$$F_{\text{friction}} = \mu F_{\text{normal}} \quad (2.8)$$

where the normal force is given by both the weight and (negative) lift of the car, which serves as an effective mass increase:

$$F_{\text{friction}} = \mu \left( mg + \frac{1}{2} \rho C_L A \dot{x}^2 \right) \quad (2.9)$$

The vehicle will lose traction when the frictional force is less than the centripetal force.

$$\frac{m \dot{x}^2}{r} > \mu \left( mg + \frac{1}{2} \rho C_L A \dot{x}^2 \right) \quad (2.10)$$

Giving the maximum velocity for a given corner radius before the car skids out:

$$\Rightarrow \dot{x} < \left( \frac{2\mu m g r}{m - \mu C_L \rho r A} \right)^{\frac{1}{2}} \quad (2.11)$$

Again, the forecasted variation in radii of corners is prescribed by the rules to be between 3 m to 50 m [4]. Plotting this for various  $C_L$  values between 1.5 to 2.6 [5], assuming  $m = 300 \text{ kg}$ ,  $\mu = 1.5$  [6] and  $A = 0.99 \text{ m}^2$  as previously used. The result can be seen in figure 2.2.

## 2.1.2 Load Distribution

The scope of this thesis is not to incorporate a full aerodynamic package, but a quick overview of load distribution is essential to understanding the behaviour of the car.

The effective mass added from negative lift depends on the lift coefficient. It is evident that different items on the car carry different lift coefficients, thus making the lifting forces over the cars length a function of relative speed. For the unexperienced driver, this is not easily managed as handling characteristics change with velocity. Therefore, it is desirable to have the aerodynamic center of pressure close to the car's center of gravity, in order to have similar handling at all velocities. While this is not handled in this thesis, it is ideal for future iterations and essential for a full aerodynamical package.




Figure 2.2: Cornering speed as a function of turn radius for various lift coefficients.

# 3

# Airfoils and Inverted Wings

Achieving a large negative lift coefficient  $C_L$  can be done in many ways. Inspecting race cars throughout the years show that airfoils have been used as early as 1966 when Jim Hall attached a rear wing to his Chaparral 2E [7]. Since then, the inverted wings have been a staple in the racing industry with various three dimensional geometries affecting the overall performance even further.

This chapter covers the pressure distribution of various airfoils, the selection criterions of the competition, three dimensional geometrical effects and the tools of the optimization trade.

## 3.1 Airfoil theory

An airfoils is the 2-dimensional cross section of a wing, that's characteristic of the wing's lifting characteristics. It is important to know the nomenclature: The leading edge is the most forward point of the wing, the trailing edge is the most rearward point of the wing. Camber is how much the wing "flexes".

Theory of airfoils from katz book, to be written tuesday 19.

FiXme Note: Mo  
laminar flow, bo  
layer mustn't tri  
create bubbles,

### 3.1.1 Pressure distribution

### 3.1.2 Lift and Drag Coefficient

Lift coefficient:

$$C_L = C_{L_\alpha}(\alpha + \alpha_{L_0}) \quad (3.1)$$

where  $\alpha$  is the lift per angle of attack in radians,  $\alpha_{L_0}$  is the airfoil's camber, which acts as a additional angle of attack effect, also in radians.  $C_{L_\alpha}$  is given by:

$$C_{L_\alpha} = \frac{2}{1 + \frac{2}{AR}} \quad (3.2)$$

FiXme Note: so  
about Navier Sto  
equations.



Figure 3.1: The trailing tip vortex is clearly seen to the right. Thanks to the NASA's Wake Vortex Study for the photo [8].

### 3.1.3 Which parameters does an airfoil have? What can we change

### 3.1.4 Angle of Attack

### 3.1.5 Ground Effects

Fixme Note: uns

### 3.1.6 Aspect Ratio and End Plates

An important identifier when describing an actual finite wing is, apart from chord length and airfoil design, the width. The definition used for describing the physical span is called Aspect Ratio, and for a rectangular wing is:

$$AR_{\text{actual}} = \frac{b}{c} \quad (3.3)$$

Where  $b$  is the width of the wing and  $c$  is the chord length.

The effect of having a finite length is very important in race aerodynamics. As pressure is lowered and increased on the different sides, air is going to travel around the edge of the wing in a rolling motion. This creates a vortex, which is shown in figure 3.1. The phenomenon is called tip vortices, and the magnitude of the vortex is proportional to the lift coefficient of the

wing. The area these vortices cover is very large and for wings with a small span will greatly reduces the lifting powers.

These vortices are created by an effect called *downwash* when talking aeroplanes. As the wing bends the air slightly downwards, it creates an opposite force due to Newton's second law which is lift. However, the sheet of air that passes over the length of the wing has a downward velocity component and will thus force air in that direction. This presses other air out of the way, allowing air above it to rush downwards to fill the gap. The same phenomenon is what happens at the edge of the wing, and again is what is shown in figure 3.1. When the wing *bends* the airflow downward, drag is induced. While drag is almost negligible in our case, it is never wanted [9]. For an elliptical wing, the induced drag coefficient is given by:

$$C_{d_{\text{induced}}} = \frac{C_L^2}{\epsilon \pi A} \quad (3.4)$$

Where  $\epsilon = 1$  for an ellipse, and generally  $\epsilon < 1$  for anything else. For a rectangular wing,  $\epsilon = 0.7$  [10].

A way to combat this phenomenon is the addition of end plates. End plates adds a virtual additional length by adding a physical wall between the low- and high pressure surfaces. The vortices that usually go around the wing and reduce lift is severely hindered. A corrected aspect ratio can be found for wings with side plates as:

$$A = A_{\text{actual}} \left( 1 + 1.9 \frac{h}{b} \right) \quad (3.5)$$

where  $h$  is the height of the end plate, and  $b$  is the width of the wing as in equation 3.3 [2]. The addition of end plates gives an increased aspect ratio. Inserting this back into 3.2 shows that end plates yields an increase in lift.

# 4

# Concept Design

The following contains the conceptual design of a rear wing based on the previous chapters. First, a walkthrough of different airfoil profiles and their benefits is followed by selection of one particular. Secondly, analyzing the amount of elements the wing should consist of with regards to production time and ease of construction. A Product Design Specification (PDS) is set up to make sure that the design solution addresses all the problems it attempts to solve. Based on the PDS, an initial design is proposed, followed by a section describing the various possible methods of optimization.

## 4.1 Comparison of Airfoils

Choosing the MSHD wing. To be written from MSHD article on tuesday 19.

## 4.2 Multi elements? How many is enough

From katz book, written tuesday 19.

Based on the previous section, a conceptual design of an aerodynamically

## 4.3 Product Design Specification (PDS)

Issue	Requirement	Criteria
Weight	Must not move CM above halfway point	As low as possible
Safety	Must be in compliance with FSAE rules	
Durability	Must have no fatigue limit, has to be waterproof	
Performance	High downforce & soft stall characteristic	Must retain performance despite tripping
Dimensioning	Must be within area defined by FSAE rules	Easily mounted to current chassis
Production	Low time and monetary cost	

## 4.4 Initial Design

## 4.5 Optimization Tools

Also from katz book to be written tuesday 19.

Building physical models is cool, wind tunnel time is expensive though

Let's use CFD!

To make sure CFD works, we need to perform experiments to verify simulations work.

Let's make a small scale wind tunnel test and simulate the rest!

# 5

# Wind Tunnel Experiment

Verifying the simulated aerodynamic effects is crucial to ensuring the correctness of the numerical analysis. In order to assess the reliability of the previously conducted simulations, a physical measurement of the pressure along the down-scaled wing will provide results for comparison.

Measurements and tests have been carried out at the DTU Wind laboratory's Red wind tunnel with the help of our supervisor Robert Flemming Mikkelsen the 19<sup>th</sup> to the 20<sup>th</sup> of June.

FIXme Note: somehow awful. fix

## 5.1 Aerodynamical Theory

The theories explaining how fluid effects scale between varying wing sizes is explained, in order to justify using a down-scaled model as evaluation to a real size wing.

### 5.1.1 Similarity of Flows

In order to perform tests on the rear wing, it has to be scaled down to fit inside the wind tunnel. This reduces the physical size of the wing, which under equal circumstances changes the flow around it. In order to correctly emulate the simulated flow inside a wind tunnel, the Reynolds number and Euler number have to be the same, assuming incompressible flows:

$$Re_m = Re \quad (5.1)$$

$$Eu_m = Eu \quad (5.2)$$

Mathematically, the Reynolds- and Euler number are defined as:

$$Eu = \frac{p_u - p_d}{\rho v^2} \quad (5.3)$$

where  $v$  is the characteristic velocity of the flow,  $p_u$  denotes upstream pressure, and  $p_d$  denotes downstream pressure, and:

$$Re = \frac{uL}{\nu} \quad (5.4)$$

where  $u$  is the velocity relative to the object,  $L$  is the characteristic length and  $\nu$  is the kinematic viscosity of the fluid.

For a down-scaled model, matching Reynolds- and Euler number requires an increase in velocity, inversely proportional to the increase in length

FiXme Note: skr  
ud plx.

$$\begin{aligned}\frac{u_m L_m}{\nu} &= \frac{u L}{\nu} \\ \Rightarrow u_m &= \frac{L}{L_m} u\end{aligned}\quad (5.5)$$

Given the nature of the competition, the average cornering speeds are around  $55 \text{ km h}^{-1} = 15.28 \text{ m s}^{-1}$ , which is where downforce is of most importance. As shown in section 5.1.1, the desired velocity in the wind tunnel for the scale model can be found from equation 5.5

$$u_m = \frac{0.6 \text{ m}}{0.15 \text{ m}} 15.28 \text{ m s}^{-1} = 61.12 \text{ m s}^{-1}$$

Which in accordance to the range of The Red wind tunnel.

## 5.2 Equipment

The equipment required for performing a wind tunnel test can be seen below:

- The Red wind tunnel ( $60 \text{ m s}^{-1}$  to  $65 \text{ m s}^{-1}$ )
- 1/4 scale wing
- Syringe inserts
- Rubber tubing
- Pressure transducer

The instrumentation and the Red wind tunnel is described below, along with a thorough description of the scale wing designed and produced for the experiment.

### 5.2.1 Instrumentation

Instrumentation to perform the experiments were graciously provided to us by DTU Wind Energy. The following contains a description of the wind tunnel, datalogging devices and software used to perform the measurements.

#### The Red Wind Tunnel

The red wind tunnel is an open loop wind tunnel located at DTU Lyngby. A picture of the wind tunnel with our supervisor Robert Mikkelsen can be seen in figure 5.1. It measures  $0.5 \text{ m} \times 0.5 \text{ m} \times 1.3 \text{ m}$  in the test section, with a maximum wind speed of  $65 \text{ m s}^{-1}$ . The wind tunnel functions in low Reynolds number, which fits with the chosen MSHD aerofoil.



Figure 5.1: Robert Mikkelsen posing in front of the Red wind tunnel. To the left is the air inlet, followed by the test section.

### Pressure Measurements

The Red wind tunnel is equipped with data logging equipment measuring up to 64 pressure probes on a wing profile, the Angle of Attack (AOA), a force gauge measuring the lift forces, a pitot rake measuring the pressure in the wing's wake, the dynamic pressure in the wind tunnel, the operational speed of the wind tunnel, the air density and the time of measurement. The measurement equipment was connected to a connected to the data-logging software LabVIEW on a nearby computer.

FiXme Note: uns  
Check document

### 5.2.2 Manufacturing the 1/4 Scale Rear Wing

After the initial analysis of airfoils, this design was chosen based on preliminary research. From CITE SOMETHING HERE , a rule of thumb for multi element design is that the first element should be around 70% of the total chord length, and the second element around 30%. From [2], the initial position of the elements was chosen. Having the perfect position is not essential, as the experiment is a simply a verification method of the computational method, which will be used to optimize the final deisng.

FiXme Note: ma  
blueprint to be r  
sexy/english  
FiXme Note: Ins

The 1/4 scale rear wing was machined at Philips Lighting by Rasmus Himborg based on the technical drawings presented below.




Figure 5.2: Blueprints of the centerpiece of the wing containing the pressure taps for generating a pressure distribution profile.

## Blueprints

The wing requires a series of special holes for the measurements needed. 15 holes have to be made along the very narrow wing profile, in order to measure the pressure on the wing's surface. The pressure taps have to be 0.8 mm on the outside, with an inner bore hole with 1.2 mm, in order to have a syringe inserted. Secondly, the wing needs to be separated into smaller parts, as drilling pressure outlets through the entire wing is very difficult. Thus, the large wing is dissected into three parts. Two regular wings, and a central part with 15 pressure taps. The middle section contains the pressure outlets, where syringes serve as a connectors to rubber pressure tubes, which has to be lead out through the center of the wings adjacent of the pressure-measuring wing. Furthermore, aligning the three wing sections has to be fairly accurate. The center wing thus carries threaded holes, and the adjacent wings have M4 holes where a threaded rod can pass through and be tightened. The final design of the centerpiece can be seen in figure 5.2.

Material selection is based on the ease of machinability - a CNC-miller was provided to us, along with ample amounts of aluminium. This scale wing is not to be used in the actual race car, so weight is not a concern. Constructing the 1/4 scale wing is not completely trivial. High precision is required for the surface finish, and the pressure taps have to be small in diameter: 0.8 mm.

The manufactured parts can be seen in 5.3, taken shortly after receiving the parts back from




Figure 5.3: Pieces of the downscaled wing before assembly. Additional H7 holes had to be drilled in order to mount the wing to the force gauge securely.

Rasmus Himborg. The width of the centerpiece is based around the fact that potential upstream interference from misalignment of the wing profile sections would not cause issues around the pressure taps.

### 3D-printed parts

Due to machining cost and production time, the second element was 3D-printed on Zortrax M200 3D printers at DTU Skylab.

### Assembly

In figure 5.4 the down-scaled wing post-production with pressure tubes inserted can be seen with pressure-taps along the centerpiece. The wing is assembled by lasercutting the two end plates with holes for mounting, as well as the H7 mounting hole and exits for the pressure tubes.

In order to strengthen the construction and smoothen the surface, the 3D-printed rearwing was reinforced using tape. The tape is red (as seen in figure 5.4), and is additionally supported by a wooden centerpiece holding the two wings together at the right distance. Lastly, the small wing is reinforced further by attaching screws through the end plate, ensuring the wing does not flex.




Figure 5.4: Down-scaled wing assembled with a zoom in on the pressure taps. The length of the entire wing is approximately 250 mm with a total chord length of 150 mm.

### 5.3 Experimental Procedure

The model wing's 8 mm hole is fitted with a rod at the end as seen to the left in figure 5.4, which is then mounted to the force gauge at the bottom of the wind tunnel. The pressure measurement tubes are passed through a hole in the bottom of the test section, and the pressure rake's height is adjusted to measure the wing's wake. Connection is established to the LabVIEW software running on a nearby computer. A picture of the data collection UI can be found in appendix

The wing is positioned with a  $0^\circ$  angle of attack. Measurements are taken with  $10 \text{ m s}^{-1}$  increments in the range of  $10 \text{ m s}^{-1}$  to  $60 \text{ m s}^{-1}$ , with an angular sweep at  $20 \text{ m s}^{-1}$  and  $40 \text{ m s}^{-1}$ , in order to compare the optimum angle of attack with literature.

However, due to the wing covering a relatively large area of the wind tunnel, the final test could only go to  $59.2 \text{ m s}^{-1}$ .

Fixme Note: what level of obstruction?

### 5.4 Results

# 6

# Simulation

The simulation will run in several parts. First, the wings relative placement between each other will be optimized in a 2-dimensional environment. This involves, size,  $x$ - and  $y$ -distance between the multi-element wings, angle of attack and height relative to the chassis to give a good estimate of the wings placement range. Secondly, a 3-dimensional analysis of the entire wing with endplates will be performed. Endplate dimensions will be optimized, and further optimization of the height relative to the entire chassis to finalize the design and placement. Lastly, a complete computational solution to the entire car will finalize the aerodynamical package, and yield the total amount of drag and downforce.

## 6.1 Star-CCM+

## 6.2 Finite Volume method

Star-CCM+ employs the finite volume method, which will be covered briefly in this report.

## 6.3 Mesh Generation

The mesh has to be structured in accordance to best practice. Areas with high velocity and pressure gradients have to be dissolved in acceptable resolutions, in order to ensure correct results. Running an initial test on a generic mesh shows us where the wing requires greater resolution. Gradients are easily visible around the wing's leading edge, and generally around the solid bodies. Furthermore, aligning the mesh with the flow improves accuracy and rate of convergence. .

Fixme Note: No  
konvergens und  
Måske også grid  
sensitivity test.

## 6.4 The Rear Wing

### 6.4.1 Verification of Simulation Results

Comparison with wind tunnel test.

## Evaluation of Verification Simulation

### 6.4.2 Multi-Element Wing Optimization

Wing was moved around to optimize lift. Here's the results changing the variables.

## 6.5 The Aerodynamics Package

### 6.5.1 Undertray, Diffuser, Front Wing and Driver

### 6.5.2 Everything Together Now

## 6.6 Results

# 7

# Construction

This chapter concerns the construction of the rear wing. The step from theoretical abstraction to a real product. This includes dimensioning, material selection and finalizing the design. The simulated rear wing lacks a proper mounting method design, which is also included in this chapter.

## 7.1 Requirements

The formula student competition has a clear ruleset dictating the dimensional requirements of aerodynamic devices. The most crucial elements are outlined below:

### 7.1.1 Dimensional Requirements

Height Restrictions:

T7.3.1 All aerodynamic devices rearward of a vertical plane through the rearmost portion of the front face of the driver head restraint support, excluding any padding, set to its most rearward position must be lower than 1.2 m from the ground.

Width Restrictions:

T7.3.2 All aerodynamic devices higher than 500 mm from the ground, must not extend outboard of the most inboard point of the rear wheel/tire.

Length Restrictions:

T7.3.3 All aerodynamic devices must not extend further rearward than 250 mm from the rearmost part of the rear tires

Minimum Edge Radii of Aerodynamic Devices:

T7.4 All forward facing edges of aerodynamic devices that could contact a pedestrian must have a minimum radius of 5 mm for all horizontal edges and 3 mm for vertical edges.

The dimensional requirements from the rules was sketched on the front plane of the car's CAD drawing. This allows positioning the wing in the square seen in figure 7.1.



Figure 7.1: The ruleset above drawn against the design of the car. The marked square is the area where the wing can be freely placed.

### 7.1.2 Strength Requirements

#### Aerodynamic Devices Stability and Strength:

- T7.5.1 Any aerodynamic device must be able to withstand a force of 200 N distributed over a minimum surface of  $225 \text{ cm}^2$  and not deflect more than 10 mm in the load carrying direction.
- T7.5.2 Any aerodynamic device must be able to withstand a force of 50 N applied in any direction at any point and not deflect more than 25 mm.

As the wing will be mounted against the end plates, it can be considered a simply supported beam. The elastic deflection is thus described by:

$$u = \frac{FL^3}{48EI} \quad (7.1)$$

where  $u$  is the deflection at the midpoint,  $F$  is the force applied,  $L$  is the length of the beam (the same as  $b$  for wings),  $E$  is the elastic modulus of the wing and  $I$  is the moment of inertia of the cross section.

## 7.2 Material Selection

Selecting a fitting material depends on the maximum deformation and weight. The car has to be as light as possible, and for

FiXme Note: Overall  
(for flair jo)

## 7.3 Composites

The strength of composites come from the fibers

### 7.3.1 Sandwich Structure

### 7.3.2 Wing Deflection

## 7.4 Final Design of Rear Wing

### 7.4.1 Blue Prints

## 7.5 Manufacturing Final Design

### 7.5.1 Polystyrene Molds

The molds for the wings were chosen as positive molds, meaning polystyrene molds of the actual wings were cut out and overlaid with resin coated carbon fiber. In order to do this, we devised a hotwire-based specialized tool for the job. This can be seen in figure 7.2, and the name of the job is to do it slowly in order to receive a clean surface.

FiXme Note: Pre  
of CAD Drawing  
method of how  
get to this result  
FiXme Note: Re

### 7.5.2 Hand Layup

### 7.5.3 Surface Finish

### 7.5.4 Implementation and Testing

FiXme Note: Show  
we did the hand  
What went wrong  
went well.

## 7.6 Testing and Inspection

### 7.6.1 Reinforcing the mounting




Figure 7.2: The hot wire melts the styrofoam while sliding along the wooden template.



Figure 7.3: Steffan and Nicolai performing a hand layup of the carbon fiber mats around a polystyrene foam core.



Figure 7.4: Curing the wing in a flat position let the resin pool in the center of the wing, making the surface very rough.



Figure 7.5: Sanding the wing clears the surface roughness, but requires a new layer of sealant. Using epoxy or a lacquer was investigated before settling on epoxy.

8

## Discussion

9

# Conclusion

bla

# Perspective

The Eevee has to be rebuilt next year, and in order to help the effort along for future students, a list of potential upgrades are listed below, with estimates of how valuable each change is in regards to downforce/drag reduction gain.

## 9.1 Drag Reductive System

A drag reductive system (DRS) is well-known from Formula 1, and has in the recent years been gaining traction (or lack therof :))) ) in the Formula Student. It is a natural extension to the aerodynamics of the car, as Formula Student has much less restrictions on aerodynamics than Formula 1. Automatically adaptive DRS, that measures the car's relative downforce and the angle of the steering column could give a big edge on straights, as flipping the wing up to reduce drag increases the top speed.

## 9.2 Slats, Flaps, Gills and Cutaway

<https://www.jmranalytical.com/single-post/2017/04/06/Rear-Wing-Investigation>

We already have a multi element wing, but increasing the amount of elements increases the amount of downforce we can pull out of the same design.

## 9.3 Suspension Integration

- Nice to have downforce directly on the wheels - Gives more unsprung mass though. That might be an issue.

# **Media**

The project gained a lot of media attraction. For the interested reader, more can be found below.

A

## Appendix

# Bibliography

- [1] Bulbapedia. <http://bulbapedia.bulbagarden.net/wiki/Eevee>, may 2016.
- [2] Joseph Katz. *Race Car Aerodynamics*. BentleyPublishers, 2nd edition, 2003.
- [3] J.R. Taylor. *Classical Mechanics*. University Science Books, 2005.
- [4] IMechE: Institution of Mechanical Engineers. *Formula Student Rules*. 2018.
- [5] lcdesign. Formula sae aerodynamics. <https://sites.google.com/site/lcdesignwork/case-studies/automotive-case-studies/formula-sae>.
- [6] HPWizard. Tire friction and rolling resistance coefficients. <http://hpwizard.com/tire-friction-coefficient.html>.
- [7] Hucho W. *Aerodynamics of road vehicles*. Warrendale, 4th edition, 1998.
- [8] NASA Langley Research Center. Vortex created by the passage of an aircraft wing. [https://en.wikipedia.org/wiki/Vortex#/media/File:Airplane\\_vortex\\_edit.jpg](https://en.wikipedia.org/wiki/Vortex#/media/File:Airplane_vortex_edit.jpg).
- [9] Peter Kämpf. Lift creation and induced drag. <https://aviation.stackexchange.com/questions/8556/is-a-winglet-better-than-an-equal-span-extension/8579#8579>.
- [10] NASA. Induced drag coefficient. <https://www.grc.nasa.gov/www/k-12/airplane/induced.html>.