

Making All Four of Your Addresses Work

Namecheap DNS and GitHub Pages

The Four Addresses

If you are using a custom domain, then four addresses should *all work*.

- <http://carlislerainey.com>
- <https://carlislerainey.com>
- <http://www.carlislerainey.com>
- <https://www.carlislerainey.com>

Your site may have one or more that does not work.

Testing

Open the **Terminal** tab in RStudio, replace my domain with yours in the script below, and paste the script into the Terminal.

```
D=carlislerainey.com
for u in http://$D https://$D http://www.$D https://www.$D
do
    printf "%-30s " $u
    curl -s -o /dev/null -m 20 -w "%{http_code} %{redirect_url}\n" $u
done
```

- 200 means the page loaded.
- 301 means the URL redirected.
- 000 means the request failed.

If things work, the output should look like this (3 redirected; one loaded):

```
http://carlislerainey.com      301 https://www.carlislerainey.com/
https://carlislerainey.com    301 https://www.carlislerainey.com/
http://www.carlislerainey.com 301 https://www.carlislerainey.com/
https://www.carlislerainey.com 200
```

Adding GitHub Pages Records in Namecheap

In Namecheap, go to **Domain List** → **Manage** → **Advanced DNS**.

You need nine records.

Type	Host	Value
A Record	@	185.199.108.153
A Record	@	185.199.109.153
A Record	@	185.199.110.153

A Record	@	185.199.111.153
AAAA Record	@	2606:50c0:8000::153
AAAA Record	@	2606:50c0:8001::153
AAAA Record	@	2606:50c0:8002::153
AAAA Record	@	2606:50c0:8003::153
CNAME Record	www	USERNAME.github.io

A new Namecheap domain has records already in the list. Delete all of them before you add the records above.

The CNAME file picks your real address

Your repository needs a file named CNAME with a single line that contains your domain. In the RStudio console, run this to create the file (replace my domain with yours):

```
| writeLines("www.carlislerainey.com", "CNAME")
```

This file belongs in the project root (e.g., alongside `_quarto.yml`). Quarto will copy it into docs/ each time you render the site.

Whatever you write in that file is your real address, and GitHub redirects the other form to it. If you write `carlislerainey.com`, then the `www` address redirects to the bare. If you write `www.carlislerainey.com`, then the bare redirects to the `www`.

Turn on HTTPS

Render the site, then commit and push in GitHub Desktop.

Go to your website repository on github.com and click **Settings** → **Pages**. Type your domain into **Custom domain** and click **Save**.

GitHub runs a DNS check. This usually takes a few minutes (but can take up to a day). When it passes, check **Enforce HTTPS**.