AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.6, AD-2.10, AD-2.11, AD-2.14, AD-2.15, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPSM AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RPSM - MAASIN COMMUNITY AIRPORT

RPSM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	**ARP coordinates and site at AD**	101113.5957N 1244658.4615E.
2	**Direction and distance from (city)**	3.5KM NW.
3	**Elevation/Reference temperature**	100M AMSL.
4	**Geoid undulation at AD ELEV PSN**	Nil.
5	**MAG VAR/Annual Change**	0.9° W (2014) / 2.8’ increasing.
6	**AD Operator, address, telephone, telefax, telex, AFS**	Civil Aviation Authority of the Philippines Maasin Airport, Panan-awan, Maasin 6600 Southern Leyte.
7	**Types of traffic permitted (IFR/VFR)**	VFR.
8	**Remarks**	Nil.

RPSM AD 2.3 OPERATIONAL HOURS

1	**AD Operator**	HJ.
2	**Customs and immigration**	Nil.
3	**Health and sanitation**	Nil.
4	**AIS Briefing Office**	Nil.
5	**ATS Reporting Office (ARO)**	Nil.
6	**MET Briefing Office**	Nil.
7	**ATS**	Nil.
8	**Fuelling**	Nil.
9	**Handling**	Nil.
10	**Security**	Nil.
11	**De-icing**	Nil.
12	**Remarks**	Nil.

RPSM AD 2.5 PASSENGER FACILITIES

1	**Hotels**	In town.
2	**Restaurants**	In town.
3	**Transportation**	Vehicle for hire.
4	**Medical facilities**	In town.
5	**Bank and Post Office**	In town.
6	**Tourist Office**	In town.
7	**Remarks**	All passengers facilities in town.

RPSM AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	**Types of clearing equipment**	Grass cutter.
2	**Clearance priorities**	Aircraft movement area.
3	**Remarks**	Clearing obstruction at all times.

RPSM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	**Apron surface and strength**	Surface: MACADAM. Strength: 17.010KG/0.5MPa.
2	**Taxiway width, surface and strength**	Width: 24M. Surface: MACADAM. Strength: Nil.
3	**Altimeter checkpoint location and elevation**	Location: Nil. Elevation: 23M.
4	**VOR checkpoints**	Nil.
5	**INS checkpoints**	Nil.
6	**Remarks**	Nil.

RPSM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	**Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands**	Nil.
2	**RWY and TWY markings and LGT**	RWY: Only runway markers. TWY: Nil.
3	**Stop bars**	Only stopway markers.
4	**Remarks**	Nil.

RPSM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
16	165º 02' GEO 165º 37' MAG	1110M X 30M	17010KG/0.5MPa CONC	Nil	Nil
34	345º 02' GEO 345º 37' MAG	1110M X 30M	17010KG/0.5MPa CONC	Nil	Nil
Slope of RWY-SWY	**SWY dimensions**	**CWY dimensions**	**Strip dimensions**	**OFZ**	**Remarks**
7	8	9	10	11	12
Nil	60M X 30M	140M	Nil	Nil	Nil
Nil	60M X 30M	60M	Nil	Nil	Nil

RPSM AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
16	1110M	1250M	1170M	1110M	C A O W W
34	1110M	1170M	1170M	1110M	C A O W W

RPSM AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Airport Regulations

1.1 Pilots are advised to fly over the field prior to entering traffic pattern.

1.2 Exercise extreme caution during landing/takeoff due to the following restrictions:

a. presence of high tension wire at approach of RWY16;

b. presence of hill at approach of RWY34;

c. incomplete runway markers/perimeter fence.

INTENTIONALLY
LEFT
BLANK