AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.6, AD-2.11, AD-2.16, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPUO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RPUO - BASCO PRINCIPAL AIRPORT (Class 2)

RPUO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	**ARP coordinates and site at AD**	202705N 1215849E.
2	**Direction and distance from (city)**	Adjacent to eastern side of town proper.
3	**Elevation/Reference temperature**	94M (309FT).
4	**Geoid undulation at AD ELEV PSN**	30M (99FT).
5	**MAG VAR/Annual Change**	3.0ºW (2014) / 2.4’ increasing.
6	**AD Operator, address, telephone, telefax, telex, AFS**	Civil Aviation Authority of the Philippines Basco Airport, Basco 3900 Batanes
7	**Types of traffic permitted (IFR/VFR)**	VFR.
8	**Remarks**	Nil.

RPUO AD 2.3 OPERATIONAL HOURS

1	**AD Operator**	0000 - 0900.
2	**Customs and immigration**	Nil.
3	**Health and sanitation**	Nil.
4	**AIS Briefing Office**	Nil.
5	**ATS Reporting Office (ARO)**	2300 - 0700. For extension of SER, one (1) day PN is required.
6	**MET Briefing Office**	Nil.
7	**ATS**	0000 - 0900.
8	**Fuelling**	Nil.
9	**Handling**	Nil.
10	**Security**	H24.
11	**De-icing**	Nil.
12	**Remarks**	Airport Operations: 2300 - 0700.

RPUO AD 2.5 PASSENGER FACILITIES

1	**Hotels**	Near the AD.
2	**Restaurants**	Near the AD.
3	**Transportation**	Public/Private Vehicle.
4	**Medical facilities**	Near the AD.
5	**Bank and Post Office**	Near the AD.
6	**Tourist Office**	Nil.
7	**Remarks**	Nil.

RPUO AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	**Types of clearing equipment**	Manual.
2	**Clearance priorities**	RWY.
3	**Remarks**	Nil.

RPUO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	**Apron surface and strength**	Surface: CONC+ASPH. Strength: Nil.
2	**Taxiway width, surface and strength**	Width: 30M. Surface: ASPH. Strength: Nil.
3	**Altimeter checkpoint location and elevation**	Nil.
4	**VOR checkpoints**	Nil.
5	**INS checkpoints**	Nil.
6	**Remarks**	No designated TWY, instead, aircraft uses active RWY as TWY to APN.

RPUO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	**Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands**	Only TWY and parking guide lines are available.
2	**RWY and TWY markings and LGT**	RWY: CL, THR markings, RWY designation number and side markers. TWY: Nil.
3	**Stop bars and RWY guard lights**	Nil.
4	**Other RWY protection measures**	Nil.
5	**Remarks**	Nil.

RPUO AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	**Obstacle type Elevation Markings/LGT**	**Coordinates**	**Obstacle type Elevation Markings/LGT**	**Coordinates**	
a	**b**	**c**	**a**	**b**	
06	Tamulong Hill 56M AMSL	Nil	Nil	Nil	APRX 1KM FM RWY06
24/Towards	Mt. Iraya 3000FT	Nil	Nil	Nil	APRX 1KM FM tip of RWY

RPUO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
06	055.47°	1244M X 30M	PCN 24 F/B/Y/T RWY: ASPH SWY: ASPH	202653.76N 1215831.13E (30M/99FT)	THR 40M/130FT TDZ 52M/170FT	4.398% uphill towards THR24
24	235.48°	1244M X 30M	PCN 24 F/B/Y/T RWY: ASPH SWY: ASPH	202716.70N 1215906.51E (30M/99FT)	THR 94M/309FT TDZ 94M/309FT	

SWY dimensions	CWY dimensions	Strip dimensions	RESA dimensions	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
Nil	120M X 80M	1452M X 82M	Nil	Nil	Nil	CWY: Start FM THR24
97M X 22M	135M X 80M	1452M X 82M	Nil	Nil	Nil	CWY: Start FM THR06

RPUO AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
06	1244M	1364M	1244M	1244M	Nil
24	1244M	1379M	1341M	1244M	Nil

RPUO AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type, LEN, INTST	THR LGT colour, WBAR	VASIS, (MEHT), PAPI	TDZ, LGT LEN
1	2	3	4	5
06	Nil	Nil	PAPI Left/Right 3.0º (26.55M)	Nil
24	Nil	Nil	Nil	Nil

RWY Centre Line LGT Length, spacing, colour, INTST	RWY edge LGT LEN, spacing, colour, INTST	RWY End LGT colour, WBAR	SWY LGT LEN, colour	Remarks
6	7	8	9	10
Nil	Nil	Nil	Nil	Path WID: 0.29º. VIS RG: 5.0NM. VER OBST CLR: 2.28º. Horizontal OBST CLR: Clear at > 10º on both sector FM RWY CL. DIST FM THR: 270M.
Nil	Nil	Nil	Nil	Nil

RPUO AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	**ABN/IBN location, characteristics and hours of operation**	Nil.
2	**LDI location and LGT Anemometer location and LGT**	Nil.
3	**TWY edge and centre line lighting**	Nil.
4	**Secondary power supply/switch-over time**	Secondary power supply to all lighting at AD.
5	**Remarks**	Nil.

RPUO AD 2.17 ATS AIRSPACE

1	**Designation and lateral limits**	BASCO AERODROME ADVISORY ZONE (AAZ): A circle radius 5NM centered on 202705N 1215849E (ARP).
2	**Vertical limits**	AAZ: SFC up to but excluding 2000FT.
3	**Airspace classification**	G.
4	**ATS unit call sign Language(s)**	Basco Radio. English.
5	**Transition altitude**	Nil.
6	**Hours of applicability**	Nil.
7	**Remarks**	Nil.

RPUO AD 2.18 ATS COMMUNICATION FACILITIES

Service Designation	Call Sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
FSS	Basco Radio	122.0MHZ 5062.5KHZ 3608KHZ	2300 - 0700	A/G FREQ. P/P PRI FREQ (Laoag Network). P/P SRY FREQ. For extension of SER, one (1) day PN is required.

RPUO AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OP(for VOR/ILS/MLS, give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
NDB	BS	276KHZ	2300 - 0700	202705.3N 1215829.3E	Nil	Output: 50W. 320M left of RWY06 CL.
DME	BS	CH107X	HJ	202658.1N 1215828.1E	Nil	DME Output: 1KW.

RPUO AD 2.20 LOCAL AERODROME REGULATIONS

1. Airport Regulations

1.1 Number of aircraft in the traffic pattern limited to two (2) at any given time.

1.2 Pilots are advised to avoid tight turning on the asphalted portion of the runway.

INTENTIONALLY
LEFT
BLANK