

---

## **ENR 1.3 INSTRUMENT FLIGHT RULES**

### **1. General**

#### **1.1 Aircraft Equipment**

- 1.1.1 Aircraft shall be equipped with suitable instruments and with navigation equipment appropriate to the route to be flown.

Note:

1. Passenger aircraft shall be provided with dual VOR and single ADF, or dual ADF and a single VOR supplemented by at least two (2) other navigational equipment, e.g. DME, Radar, Transponder.
2. Cargo aircraft shall be provided with dual VOR and single ADF or dual ADF or a single VOR.

#### **1.2 Minimum Heights**

- 1.2.1 Except when necessary for take-off or landing, or except when specifically authorized by the appropriate authority, an IFR flight shall be flown:

- a. over high terrain or in mountainous areas, at a level which is at least 600 meters (2 000 feet) above the highest obstacle located within 8KM (5 miles) of the estimated position of the aircraft;
- b. elsewhere than as specified in (a), at a level which is at least 300 meters (1 000 feet) above the highest obstacle located within 8KM (5 miles) of the estimated position of the aircraft.

Note: The estimated position of the aircraft will take account of the navigational accuracy which can be achieved on the relevant route segment, having regard to the navigational facilities available on the ground and in the aircraft.

#### **1.3 Change from IFR flight to VFR flight**

- 1.3.1 An aircraft electing to change the conduct of its flight from compliance with the instrument flight rules to compliance with the visual flight rules shall, if a flight plan was submitted, notify the appropriate air traffic services unit specifically that the IFR flight is cancelled and communicate thereto the changes to be made to its current flight plan.

- 1.3.2 When an aircraft operating under the instrument flight rules is flown in or encounters visual meteorological conditions, it shall not cancel its IFR flight unless it is anticipated, and intended, that the flight will be continued for a reasonable period of time in uninterrupted visual meteorological conditions.

- 1.3.3 Change from IFR flight to VFR flight is only acceptable when a message initiated by the pilot-in-command containing the specific expression "CANCELLING MY IFR FLIGHT", together with the changes, if any, to be made to his current flight plan, is received by an air traffic services unit. No invitation to change from IFR to VFR flight is to be made either directly or by inference. No reply, other than the acknowledgement "IFR FLIGHT CANCELLED AT ..... (time)", should normally be made by an air traffic services unit.

### **2. Rules applicable to IFR Flights within controlled airspace**

- 2.1 IFR flights shall comply with the requirements of the air traffic control service when operated in controlled airspace.

2.2 The cruising levels to be used by IFR flights for operation in controlled airspace shall be selected from:

- a. The Table of Cruising Levels in Appendix 2, or
- b. A modified table of cruising levels, when so prescribed in accordance with ENR 1.8 section 2.2.4 FLAS with adjacent FIRs for flight above FL290, except that the correlation of levels to track prescribed therein shall not apply whenever otherwise indicated in air traffic control clearances or specified in the Aeronautical Information Publication.

### **3. Rules applicable to IFR Flights outside controlled airspace**

#### **3.1 Cruising Levels**

3.1.1 An IFR flight operating in level cruising flight outside of controlled airspace shall be flown at a cruising level appropriate to its track as specified in:

- a. The Table of Cruising Levels in Appendix 2, except when otherwise specified by the appropriate ATS authority for flight at or below 900 meters (3 000 feet) above mean sea level; or
- b. A modified table of cruising levels as prescribed in accordance with ENR 1.8 section 2.2.4 FLAS with adjacent FIRs for flight above FL290.

#### **3.2 Communications**

3.2.1 When so prescribed by the appropriate ATS authority, an IFR flight operating within specified areas or along specified routes outside controlled airspace shall maintain a listening watch on the appropriate radio frequency and establish two-way communication, as necessary, with the air traffic services unit providing flight information service.

#### **3.3 Position Reports**

3.3.1 An IFR flight operating outside controlled airspace and required by the appropriate ATS authority to:

- a. submit a flight plan;
- b. maintain a listening watch on the appropriate radio frequency and establish two-way communication, as necessary, with the air traffic service unit providing flight information service; and
- c. shall report position as required for controlled flights. (See 3.6.3 ICAO Annex 2) Position and Air-reports Reporting Procedures).

Note: Aircraft electing to use the air traffic advisory service whilst operating IFR within specified advisory airspace are expected to comply with the requirements of the air traffic control service, except that the flight plan and changes thereto, are not subjected to clearances and that two-way communication will be maintained with the unit providing the air traffic advisory service.

**Table 1: APPENDIX 2 - TABLE OF CRUISING LEVELS FOR IFR FLIGHTS (FL280 AND BELOW)**

| TRACK             |          |        |                   |          |        |
|-------------------|----------|--------|-------------------|----------|--------|
| From 000° to 179° |          |        | From 180° to 359° |          |        |
| FL                | ALTITUDE |        | FL                | ALTITUDE |        |
|                   | Meters   | Feet   |                   | Meters   | Feet   |
| -90               |          |        | 0                 |          |        |
| 10                | 300      | 1 000  | 20                | 600      | 2 000  |
| 30                | 900      | 3 000  | 40                | 1 200    | 4 000  |
| 50                | 1 500    | 5 000  | 60                | 1 850    | 6 000  |
| 70                | 2 150    | 7 000  | 80                | 2 450    | 8 000  |
| 90                | 2 750    | 9 000  | 100               | 3 050    | 10 000 |
| 110               | 3 350    | 11 000 | 120               | 3 650    | 12 000 |
| 130               | 3 950    | 13 000 | 140               | 4 250    | 14 000 |
| 150               | 4 550    | 15 000 | 160               | 4 900    | 16 000 |
| 170               | 5 200    | 17 000 | 180               | 5 500    | 18 000 |
| 190               | 5 800    | 19 000 | 200               | 6 100    | 20 000 |
| 210               | 6 400    | 21 000 | 220               | 6 700    | 22 000 |
| 230               | 7 000    | 23 000 | 240               | 7 300    | 24 000 |
| 250               | 7 600    | 25 000 | 260               | 7 900    | 26 000 |
| 270               | 8 250    | 27 000 | 280               | 8 550    | 28 000 |

INTENTIONALLY  
LEFT  
BLANK