

ENR 3.2 AREA NAVIGATION ROUTES

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
A341	(1) RNP10 approval required for FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) MRP - ATS/MET reporting point.							
▲ ZAMBOANGA DVOR/DME (ZAM)	065528.9N 1220319.7E							
	<u>257°</u> 077°	25.0	<u>UNL</u> 4000 FT	4000 FT	10/50	Even	Odd	(1)(2)(3)(4)
▲ PILAS	064920.2N 1213857.5E							
	<u>257°</u> 077°	40.0	<u>UNL</u> FL080	FL080	10/50	Even	Odd	(1)(2)(3)(4)
▲ ANKUR	063929.1N 1210005.0E							
	<u>257°</u> 077°	152.0	<u>UNL</u> FL080	FL080	10/50	Even	Odd	(1)(2)(3)(4)
VIMAG	060136.0N 1183236.0E						(5)	

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
A461	(1) RNP10 approval required for FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) Thirty (30) NM procedural longitudinal separation minima for RNP4-approved and ADS-C/CPDLC connected aircraft pair. FPL Item 10a: R, J, P2, Item 10b: D1, Item 18: PBN/L1 SUR/RSP180 COM/RCP240. (6) MRP - ATS/MET reporting point. (7) Flights exiting Manila FIR must contact Hong Kong ACC 5 minutes prior to FIR boundary waypoint. If unable to transmit AIREP, submit report to MET Office upon arrival. For One-way Air Traffic Flow between Manila and the Southern Portion of the Philippines, see page ENR 6.1-2. For non-RNAV, limitations on ZAM DVOR/DME see page ENR 4.1-5.							
NOMAN	200000.0N 1164018.0E						(6)(7)	
	135° 315°	86.0	UNL FL090	FL090	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ MUMOT	190142.9N 1174723.0E							
	136° 316°	91.0	UNL FL090	FL090	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ AVMUP	175936.1N 1185731.1E							
	136° 316°	110.0	UNL FL090	FL090	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ SANRO	164342.0N 1202129.0E							
	156° 336°	84.0	UNL FL100	FL100	10	Odd	Even	(1)(2)(3)(4)(5)
▲ CABANATUAN DVOR/DME (CAB)	152856.2N 1210127.5E							
	183° 003°	58.0	UNL 7000 FT	7000 FT	10	Odd	Even	(1)(2)(3)(4)
▲ MANILA DVOR/DME (MIA)	143028.7N 1210118.2E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	<u>182°</u> 002°	28.0	<u>UNL</u> 7000 FT	7000 FT	10	Odd	Even	(1)(2)(3)(4)
▲ TAALA	140248.9N 1210134.9E							
	<u>182°</u> 002°	32.0	<u>UNL</u> 8000 FT	8000 FT	10	Odd	Even	(1)(2)(3)(4)
▲ VERDE	133013.2N 1210154.4E							
	<u>181°</u> 001°	15.0	<u>UNL</u> FL110	FL110	10	Odd	Even	(1)(2)(3)(4)
▲ TAPAP	131505.6N 1210203.4E							
	<u>181°</u> 001°	53.0	<u>UNL</u> FL110	FL110	10	Odd	Even	(1)(2)(3)(4)
▲ SAN JOSE DVOR/DME (SAJ)	122137.1N 1210235.1E							
	<u>171°</u> 351°	83.0	<u>UNL</u> FL070	FL070	10/50	Odd	Even	(1)(2)(3)(4)
▲ PUSIT	105955.5N 1211759.1E							
	<u>171°</u> 351°	29.0	<u>UNL</u> FL070	FL070	10/50	Odd	Even	(1)(2)(3)(4)
▲ OCORO	103106.2N 1212329.6E							
	<u>172°</u> 352°	40.0	<u>UNL</u> FL070	FL070	10/50	Odd	Even	(1)(2)(3)(4)
△ WAKAN	095146.5N 1213049.2E							
	<u>172°</u> 352°	8.0	<u>UNL</u> FL070	FL070	10/50	Odd	Even	(1)(2)(3)(4)
▲ LIMAN	094342.9N 1213219.1E							
	<u>172°</u> 352°	145.0	<u>UNL</u> FL070	FL070	10/50	Odd	Even	(1)(2)(3)(4)
▲ TINDO	072011.3N 1215847.5E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	171° 351°	25.0	UNL 6000 FT	6000 FT	10/50	Odd	Even	(1)(2)(3)(4)
▲ ZAMBOANGA DVOR/DME (ZAM)	065528.9N 1220319.7E							
	151° 331°	25.0	UNL 5000 FT	5000 FT	10/50	Odd	Even	(1)(2)(3)(4)
▲ TANAL	063340.3N 1221547.7E							
	151° 331°	176.0	UNL FL070	FL070	10/50	Odd	Even	(1)(2)(3)(4)
NITIP	040000.0N 1234306.0E						(6)	

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
A582 (Uni- Directional)	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
	(6) Southwest bound uni-directional route from FL280 and above. For FL Series refer to ENR 1.8-6 Table 2.2.4.							
	(7) MRP - ATS/MET reporting point.							
BISIG	210000.0N 1251600.0E						(7)	
	213°	230.6	UNL FL070	FL070	50/10	Even		(1)(3)(4)(5)(6)
▲ EXOMI	173616.6N 1232011.6E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	211°	80.7	<u>UNL</u> FL070	FL070	50/10	Even		(1)(2)(4)(5)(6)
▲ PIBEM	162441.2N 1224043.2E							
	211°	94.7	<u>UNL</u> FL070	FL070	50/10	Even		(1)(2)(4)(5)(6)
▲ POLIO	150030.0N 1215500.0E							
	210°	57.5	<u>UNL</u> FL090	FL090	50/10	Even		(1)(2)(4)(5)(6)
▲ SABIG	140918.7N 1212727.6E							
	212°	28.0	<u>UNL</u> FL090	FL090	50/10	Even		(1)(2)(4)(5)(6)
▲ NUMRU	134457.9N 1211306.3E							
	212°	59.3	<u>UNL</u> FL110	FL110	50/10	Even		(1)(2)(4)(5)(6)
▲ TELEN	125317.8N 1204249.7E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
A583	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
	(6) MRP - ATS/MET reporting point.							
(7) Flight exiting Manila FIR must contact Hong Kong ACC 5 minutes prior to FIR boundary waypoint.								
If unable to transmit AIREP, submit report to MET Office upon arrival.								
SABNO	185906.0N 1155042.0E						(6)(7)	
	155° 335°	81.0	UNL FL060	FL060	50	Odd	Even	(1)(3)(4)(5)
▲ DALRA	174640.2N 1163007.2E							
	156° 336°	88.0	UNL FL060	FL060	50	Odd	Even	(1)(3)(4)(5)
AKOTA	162743.3N 1171224.3E						(6)	
	156° 336°	144.0	UNL FL060	FL060	50	Odd	Even	(1)(2)(4)(5)
▲ IBOBI	141842.0N 1182008.9E							
	155° 335°	48.0	UNL FL150	FL150	50	Odd	Even	(1)(2)(4)(5)
▲ REKEL	133525.6N 1184231.9E							
	155° 335°	38.0	UNL FL150	FL150	50	Odd	Even	(1)(2)(4)(5)
▲ LEGED	130113.2N 1190006.9E							
	155° 335°	88.0	UNL FL150	FL150	50	Odd	Even	(1)(2)(4)(5)
▲ TOKON	114201.9N 1194028.9E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	<u>155°</u> 335°	45.0	<u>UNL</u> FL150	FL150	50	Odd	Even	(1)(2)(4)(5)
▲ PALOS	110142.7N 1200056.5E							
	<u>155°</u> 335°	53.0	<u>UNL</u> FL150	FL150	50	Odd	Even	(1)(2)(4)(5)
▲ MARAN	101401.7N 1202457.7E							
	<u>156°</u> 336°	33.0	<u>UNL</u> FL070	FL070	50	Odd	Even	(1)(2)(4)(5)
▲ KALAH	094404.4N 1203956.0E							
	<u>155°</u> 335°	162.0	<u>UNL</u> FL070	FL070	50	Odd	Even	(1)(2)(4)(5)
▲ MASUN	071801.6N 1215214.3E							
	<u>155°</u> 335°	25.0	<u>UNL</u> 6000 FT	6000 FT	50/10	Odd	Even	(1)(2)(4)(5)
▲ ZAMBOANGA DVOR/DME (ZAM)	065528.9N 1220319.7E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
A590	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (6) MRP - ATS/MET reporting point.							
GURAG	210000.0N 1272500.0E							(6)
	223° 043°	275.0	UNL FL070	FL070	WI MIA OCA	Even	Odd	(1)(3)(4)(5)
VIGOR	172211.2N 1242536.6E							(6)
	221° 041°	130.0	UNL FL070	FL070	WI MIA OCA	Even	Odd	(1)(2)(4)(5)
▲ MUPOB	153811.8N 1230317.9E							
	221° 041°	70.0	UNL FL070	FL070	WI MIA OCA	Even	Odd	(1)(2)(4)(5)
▲ JOMALIG DVOR/DME (JOM)	144217.5N 1221947.9E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
B462	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1.							
	(3) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(4) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(5) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(6) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
	(7) MRP - ATS/MET reporting point.							
MEVIN	210000.0N 1223300.0E							(7)
	219° 039°	174.0	UNL FL090	FL090	50/10	Even	Odd	(1)(3)(5)(6)
▲ MINIO	183543.9N 1204920.0E							
	217° 037°	15.0	UNL 7000 FT	7000 FT	10	Odd	Even	(1)(3)(5)(6)
▲ TADAO	182314.0N 1204031.7E							
	217° 037°	15.0	UNL 4000 FT	4000 FT	10	Odd	Even	(1)(3)(5)(6)
▲ LAOAG DVOR/DME (LAO)	181043.7N 1203144.6E							
	173° 353°	10.0	UNL 4000 FT	4000 FT	10	Odd	Even	(1)(3)(5)(6)
▲ PAYAS	180050.7N 1203335.1E							
	173° 353°	20.0	UNL 7000 FT	7000 FT	10	Odd	Even	(1)(3)(5)(6)
▲ DULUD	174104.2N 1203714.3E							
	173° 353°	25.0	UNL FL130	FL130	10	Odd	Even	(1)(3)(5)(6)
▲ ESSYL	171621.3N 1204147.6E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	<u>173°</u> 353°	108.6	<u>UNL</u> FL130	FL130	10	Odd	Even	(1)(3)(5)(6)
▲ CABANATUAN DVOR/DME (CAB)	152856.2N 1210127.5E							
	<u>183°</u> 003°	58.0	<u>UNL</u> 7000 FT	7000 FT	50	Odd	Even	(1)(3)(5)(6)
▲ MANILA DVOR/DME (MIA)	143028.7N 1210118.2E							
	<u>133°</u> 313°	17.0	<u>UNL</u> 4000 FT	4000 FT	50	Odd	Even	(1)(3)(5)(6)
▲ CAMBA	141926.6N 1211457.4E							
	<u>133°</u> 313°	16.0	<u>UNL</u> 6000 FT	6000 FT	50	Odd	Even	(1)(3)(5)(6)
▲ SABIG	140918.7N 1212727.6E							
	<u>133°</u> 313°	27.0	<u>UNL</u> 10000 FT	10000 FT	50	Odd	Even	(1)(3)(5)(6)
▲ IPATA	135157.4N 1214848.0E							
	<u>132°</u> 312°	139.0	<u>UNL</u> FL100	FL100	50	Odd	Even	(1)(3)(5)(6)
▲ MASBA	122209.2N 1233749.8E							
	<u>132°</u> 312°	48.0	<u>UNL</u> FL060	FL060	50	Odd	Even	(1)(3)(5)(6)
▲ ARREX	115137.4N 1241526.5E							
	<u>132°</u> 312°	33.8	<u>UNL</u> 6000 FT	6000 FT	50	Odd	Even	(1)(3)(5)(6)
▲ MASAG	112957.8N 1244158.8E							
	<u>132°</u> 312°	25.0	<u>UNL</u> 4000 FT	4000 FT	50	Odd	Even	(1)(3)(5)(6)
▲ TACLOBAN DVOR/DME (TAC)	111355.2N 1250133.6E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	140° 320°	25.0	UNL 3000 FT	3000 FT	50	Odd	Even	(2)(3)(5)(6)
▲ SADOK	105519.3N 1251838.7E							
	140° 320°	502.0	UNL FL150	FL150	50	Odd	Even	(2)(4)(5)(6)
△ POXEL	043909.1N 1305536.2E							
	140° 320°	52.0	UNL FL150	FL150	50	Odd	Even	(2)(4)(5)(6)
BIDOR	040000.0N 1313000.0E						(7)	

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
B472	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
▲ LIGPA	135722.4N 1210736.1E							
	160° 340°	13.5	UNL 9000 FT	9000 FT	10	Odd	Even	(1)(2)(3)(4)
▲ NUMRU	134457.9N 1211306.3E							
	160° 340°	13.4	UNL 9000 FT	9000 FT	10	Odd	Even	(1)(2)(3)(4)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ IBAGO	133237.8N 1211834.3E							
	159° 339°	77.0	UNL FL090	FL090	10	Odd	Even	(1)(2)(3)(4)
▲ TAPER	122156.7N 1214939.1E							
	159° 339°	78.0	UNL 9000 FT	9000 FT	10	Odd	Even	(1)(2)(3)(4)
▲ LAMBO	110943.5N 1222103.4E							
	159° 339°	21.0	UNL 9000 FT	9000 FT	10	Odd	Even	(1)(2)(3)(4)
▲ ILOILO DVOR/DME (IOO)	105007.4N 1222931.5E							
	157° 337°	30.0	UNL 5000 FT	5000 FT	10/50	Odd	Even	(1)(2)(3)(4)
▲ GULFO	102255.6N 1224223.1E							
	157° 337°	14.0	UNL 10000 FT	10000 FT	10/50	Odd	Even	(1)(2)(3)(4)
▲ BSAYA	101018.8N 1224820.0E							
	157° 337°	25.0	UNL 10000 FT	10000 FT	10/50	Odd	Even	(1)(2)(3)(4)
▲ NANAS	094725.8N 1225906.3E							
	157° 337°	44.4	UNL FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ ALDIN	090701.2N 1231803.9E							
	157° 337°	128.0	UNL FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ COTABATO VOR/DME (COT)	071003.1N 1241232.8E							
	148° 328°	60.0	UNL FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ SURAH	061934.3N 1244525.4E							
	<u>148°</u> 328°	14.0	<u>UNL</u> FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ TBOLI	060807.3N 1245252.0E							
	<u>148°</u> 328°	28.0	<u>UNL</u> FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ ANIMU	054450.4N 1250759.1E							
	<u>148°</u> 328°	124.0	<u>UNL</u> FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ SELSO	040000.0N 1261554.0E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
B473	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (6) MRP - ATS/MET reporting point.							
▲ LIGPA	135722.4N 1210736.1E							
	149° 329°	28.0	UNL FL080	FL080	50	Odd	Even	(1)(2)(4)(5)
▲ LAIYA	133418.9N 1212340.4E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	<u>148°</u> 328°	87.0	<u>UNL</u> FL080	FL080	50	Odd	Even	(1)(2)(4)(5)
▲ MINOR	122206.0N 1221404.2E							
	<u>148°</u> 328°	55.0	<u>UNL</u> 5000 FT	5000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ ROXAS DVOR/DME (ROX)	113548.9N 1224518.4E							
	<u>152°</u> 332°	18.0	<u>UNL</u> 5000 FT	5000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ BUNGA	112025.2N 1225422.7E							
	<u>152°</u> 332°	25.0	<u>UNL</u> 5000 FT	5000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ VICTA	105827.9N 1230716.9E							
	<u>152°</u> 332°	16.0	<u>UNL</u> FL110	FL110	50	Odd	Even	(1)(2)(4)(5)
▲ DUDAR	104420.6N 1231533.8E							
	<u>152°</u> 332°	7.0	<u>UNL</u> 11000 FT	11000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ KARPU	103754.9N 1231919.2E							
	<u>152°</u> 332°	24.0	<u>UNL</u> 9000 FT	9000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ RASEC	101720.6N 1233120.0E							
	<u>152°</u> 332°	27.0	<u>UNL</u> 9000 FT	9000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ LAMOK	095357.5N 1234459.1E							
	<u>152°</u> 332°	29.0	<u>UNL</u> 6000 FT	6000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ LOWAY	092835.0N 1235944.1E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	152° 332°	7.0	UNL FL060	FL060	50	Odd	Even	(1)(2)(4)(5)
▲ FORTA	092228.9N 1240315.3E							
	152° 332°	24.0	UNL FL060	FL060	50	Odd	Even	(1)(2)(4)(5)
▲ LIRYX	090132.6N 1241524.5E							
	151° 331°	42.0	UNL FL060	FL060	50	Odd	Even	(1)(2)(4)(5)
▲ LUMVI	082456.5N 1243633.0E							
	142° 322°	34.4	UNL FL130	FL130	50	Odd	Even	(1)(2)(4)(5)
▲ ANOXI	075806.8N 1245825.3E							
	142° 322°	44.4	UNL 8500 FT	8500 FT	50	Odd	Even	(1)(2)(4)(5)
▲ RABIV	072329.6N 1252634.5E							
	142° 322°	20.0	UNL 5500 FT	5500 FT	50	Odd	Even	(1)(2)(4)(5)
▲ DAVAO DVOR/DME (DAO)	070752.5N 1253914.3E							
	143° 323°	20.0	UNL 4000 FT	4000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ EDLOR	065202.0N 1255136.8E							
	143° 323°	11.5	UNL 4000 FT	4000 FT	50	Odd	Even	(1)(2)(4)(5)
▲ DAPEL	064255.5N 1255843.1E							
	143° 323°	205.0	UNL FL130	FL130	50	Odd	Even	(1)(3)(4)(5)
ELNIT	040000.0N 1280500.0E							(6)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
G467	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) Class A radar surveillance airspace from JOM until 150 NM to the East. VHF radio as primary DCPC.							
	(3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
	(6) MRP - ATS/MET reporting point.							
▲ JOMALIG DVOR/DME (JOM)	144217.5N 1221947.9E							
	096° 276°	214.0	UNL FL070	FL070	10/50	Odd	Even	(1)(2)(4)(5)
▲ DILIS	143107.1N 1260005.1E							
	096° 276°	233.0	UNL FL070	FL070	10/50	Odd	Even	(1)(3)(4)(5)
ENDAX	141500.0N 1300000.0E							(6)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
G578	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1.							
	(3) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(4) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(5) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(6) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
	(7) MRP - ATS/MET reporting point.							
GURAG	210000.0N 1272500.0E							(7)
	196° 016°	237.0	UNL FL080	FL080	50	Even	Odd	(2)(4)(5)(6)
▲ OMDOB	170705.3N 1263302.7E							
	195° 015°	159.0	UNL FL080	FL080	50	Even	Odd	(2)(4)(5)(6)
▲ DILIS	143107.1N 1260005.1E							
	198° 018°	80.0	UNL FL080	FL080	50	Even	Odd	(2)(4)(5)(6)
▲ TODEK	131333.8N 1253650.7E							
	198° 018°	53.0	UNL FL080	FL080	50	Even	Odd	(2)(4)(5)(6)
▲ TAGPI	122204.2N 1252136.4E							
	198° 018°	45.6	UNL 8000 FT	8000 FT	50	Even	Odd	(2)(4)(5)(6)
▲ SAMLI	113802.6N 1250838.2E							
	198° 018°	25.0	UNL 4000 FT	4000 FT	50	Even	Odd	(2)(3)(5)(6)
▲ TACLOBAN DVOR/DME (TAC)	111355.2N 1250133.6E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	<u>230°</u> 050°	32.0	<u>UNL</u> 6000 FT	6000 FT	10	Even	Odd	(1)(3)(5)(6)
▲ POXOS	105220.4N 1243706.2E							
	<u>230°</u> 050°	9.0	<u>UNL</u> 6000 FT	6000 FT	10	Even	Odd	(1)(3)(5)(6)
▲ KAWIT	104618.8N 1243017.5E							
	<u>230°</u> 050°	16.0	<u>UNL</u> 6000 FT	6000 FT	10	Even	Odd	(1)(3)(5)(6)
▲ PACIN	103535.2N 1241811.0E							
	<u>230°</u> 050°	25.0	<u>UNL</u> 4000 FT	4000 FT	10	Even	Odd	(1)(3)(5)(6)
▲ MACTAN DVOR/DME (MCT)	101848.8N 1235917.9E							
	<u>212°</u> 032°	28.0	<u>UNL</u> 4000 FT	4000 FT	10/50	Even	Odd	(1)(3)(5)(6)
▲ LAMOK	095357.5N 1234459.1E							
	<u>212°</u> 032°	21.0	<u>UNL</u> 6000 FT	6000 FT	10/50	Even	Odd	(1)(3)(5)(6)
▲ AROLA	093600.5N 1233440.2E							
	<u>212°</u> 032°	33.0	<u>UNL</u> 8000 FT	8000 FT	10/50	Even	Odd	(1)(3)(5)(6)
▲ ALDIN	090701.2N 1231803.9E							
	<u>211°</u> 031°	125.0	<u>UNL</u> FL080	FL080	10/50	Even	Odd	(1)(3)(5)(6)
▲ PARAL	071721.3N 1221541.7E							
	<u>210°</u> 030°	25.0	<u>UNL</u> 6000 FT	6000 FT	10/50	Even	Odd	(1)(3)(5)(6)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ ZAMBOANGA DVOR/DME (ZAM)	065528.9N 1220319.7E							
	205° 025°	25.0	UNL 5000 FT	5000 FT	10/50	Even	Odd	(1)(3)(5)(6)
▲ TABUL	063236.6N 1215256.3E							
	205° 025°	167.0	UNL FL080	FL080	10/50	Even	Odd	(1)(3)(5)(6)
GORAI	040000.0N 1204400.0E							(1)(3)(5)(6)(7)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
L625	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (6) Northeast bound uni-directional route. For FL Series refer to ENR 1.8-6 Table 2.2.4 (7) MRP - ATS/MET reporting point.							
ARESI	135824.0N 1142700.0E							(7)
	050°	218.0	<u>UNL</u> FL150	FL150	50			(1)(3)(4)(5)(6)
AKOTA	162743.3N 1171224.3E							(7)
	050°	136.0	<u>UNL</u> FL150	FL150	50			(1)(2)(4)(5)(6)
▲ AVMUP	175936.1N 1185731.1E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	051°	54.0	<u>UNL</u> FL150	FL150	50			(1)(2)(4)(5)(6)
▲ ALDIS	183552.4N 1193949.0E							
	051°	73.0	<u>UNL</u> FL150	FL150	50			(1)(2)(4)(5)(6)
▲ ABVAR	192450.8N 1203742.5E							
	052°	144.0	<u>UNL</u> FL150	FL150	50			(1)(2)(4)(5)(6)
MEVIN	210000.0N 1223300.0E							(7)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
L628	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
	(6) For FL Series refer to ENR 1.8-6 Table 2.2.4							
	(7) MRP - ATS/MET reporting point.							
▲ MANILA DVOR/DME (MIA)	143028.7N 1210118.2E							
	269° 089°	15.0	UNL 6000 FT	6000 FT	10/50			(1)(2)(4)(5)(6)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ DILAN	142925.9N 1204552.7E							
	$\frac{269^\circ}{089^\circ}$	18.0	$\frac{\text{UNL}}{7000 \text{ FT}}$	7000 FT	10/50			(1)(2)(4)(5)(6)
▲ ATMIG	142808.0N 1202705.6E							
	$\frac{269^\circ}{089^\circ}$	7.0	$\frac{\text{UNL}}{7000 \text{ FT}}$	7000 FT	10/50			(1)(2)(4)(5)(6)
▲ SIRCA	142738.3N 1202002.3E							
	$\frac{269^\circ}{089^\circ}$	23.0	$\frac{\text{UNL}}{7000 \text{ FT}}$	7000 FT	10/50			(1)(2)(4)(5)(6)
▲ KARAG	142558.9N 1195643.9E							
	$\frac{269^\circ}{089^\circ}$	9.0	$\frac{\text{UNL}}{7000 \text{ FT}}$	7000 FT	10/50			(1)(2)(4)(5)(6)
▲ SILAG	142517.6N 1194712.3E							
	$\frac{269^\circ}{089^\circ}$	16.0	$\frac{\text{UNL}}{\text{FL070}}$	FL070	10/50			(1)(2)(4)(5)(6)
▲ DODUS	142404.1N 1193028.5E							
	$\frac{269^\circ}{089^\circ}$	68.0	$\frac{\text{UNL}}{\text{FL140}}$	FL140	10/50			(1)(2)(4)(5)(6)
▲ IBOBI	141842.0N 1182008.9E							
	$\frac{269^\circ}{089^\circ}$	83.0	$\frac{\text{UNL}}{\text{FL140}}$	FL140	10/50			(1)(2)(4)(5)(6)
▲ GUKUM	141144.0N 1165501.8E							
	$\frac{269^\circ}{089^\circ}$	145.0	$\frac{\text{UNL}}{\text{FL140}}$	FL140	10/50			(1)(3)(4)(5)(6)
ARESI	135824.0N 1142700.0E						(7)	

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
M501	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. (5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (6) For FL Series refer to ENR 1.8-6 Table 2.2.4. (7) MRP - ATS/MET reporting point.							
LIMLE	163942.0N 1300000.0E						(7)	
	281° 101°	200.3	UNL FL210	FL210	50			(1)(3)(4)(5)(6)
▲ OMDOB	170705.3N 1263302.7E							
	280° 100°	122.9	UNL FL210	FL210	50			(1)(3)(4)(5)(6)
VIGOR	172211.2N 1242536.6E						(7)	
	285° 105°	64.1	UNL FL210	FL210	50/10			(1)(2)(4)(5)(6)
▲ EXOMI	173616.6N 1232011.6E							
	285° 105°	64.8	UNL FL210	FL210	50/10			(1)(2)(4)(5)(6)
▲ DADNU	175010.2N 1221349.9E							
	285° 105°	99.0	UNL FL210	FL210	50/10			(1)(2)(4)(5)(6)
▲ LAOAG DVOR/DME (LAO)	181043.7N 1203144.6E							
	300° 120°	30.0	UNL 4000 FT	4000 FT	10/50			(1)(2)(4)(5)(6)
▲ EMSEL	182422.9N 1200338.4E							
	300° 120°	25.4	UNL 7000 FT	7000 FT	10/50			(1)(2)(4)(5)(6)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ ALDIS	183552.4N 1193949.0E							
	300° 120°	99.0	UNL FL090	FL090	10/50			(1)(2)(4)(5)(6)
▲ MIKIN	192006.7N 1180635.1E							
	299° 119°	91.0	UNL FL090	FL090	10/50			(1)(2)(4)(5)(6)
NOMAN	200000.0N 1164018.0E						(7)	

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
M646	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) For FL Series refer to ENR 1.8-6 Table 2.2.4 (6) MRP - ATS/MET reporting point.							
POTIB	210000.0N 1204530.0E							(6)
	188° 008°	95.0	UNL FL070	FL070	50/10			(1)(2)(3)(4)(5)
▲ ABVAR	192450.8N 1203742.5E							
	187° 007°	19.0	UNL FL070	FL070	50/10			(1)(2)(3)(4)(5)
▲ SAKIS	190546.9N 1203609.9E							
	187° 007°	25.0	UNL 7000 FT	7000 FT	50/10			(1)(2)(3)(4)(5)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ KAPOH	184045.5N 1203409.0E							
	187° 007°	30.0	UNL 4000 FT	4000 FT	50/10			(1)(2)(3)(4)(5)
▲ LAOAG DVOR/DME (LAO)	181043.7N 1203144.6E							
	189° 009°	10.0	UNL 4000 FT	4000 FT	50/10			(1)(2)(3)(4)(5)
▲ CURIM	180045.2N 1203033.6E							
	189° 009°	20.0	UNL 7000 FT	7000 FT	50/10			(1)(2)(3)(4)(5)
▲ KINLA	174048.1N 1202811.9E							
	189° 009°	25.0	UNL 7000 FT	7000 FT	50/10			(1)(2)(3)(4)(5)
▲ MELAN	171551.6N 1202515.5E							
	189° 009°	32.0	UNL FL070	FL070	50/10			(1)(2)(3)(4)(5)
▲ SANRO	164342.0N 1202129.0E							
	167° 347°	65.0	UNL FL100	FL100	10			(1)(2)(3)(4)(5)
▲ ESCAN	154112.2N 1204018.1E							
	167° 347°	12.0	UNL 10000 FT	10000 FT	10			(1)(2)(3)(4)(5)
▲ ALPAS	152910.7N 1204352.3E							
	167° 347°	38.0	UNL 6000 FT	6000 FT	10			(1)(2)(3)(4)(5)
▲ RADEG	145221.3N 1205449.6E							
	167° 347°	23.0	UNL 6000 FT	6000 FT	10			(1)(2)(3)(4)(5)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ MANILA DVOR/DME (MIA)	143028.7N 1210118.2E							
	208° 028°	21.0	UNL 6000 FT	6000 FT	10			(1)(2)(3)(4)(5)
▲ INDAN	141124.9N 1205203.0E							
	208° 028°	19.0	UNL 6000 FT	6000 FT	10			(1)(2)(3)(4)(5)
▲ BALAY	135409.6N 1204342.0E							
	208° 028°	20.0	UNL 6000 FT	6000 FT	10			(1)(2)(3)(4)(5)
▲ BUCAL	133559.6N 1203456.0E							
	208° 028°	19.0	UNL FL090	FL090	10			(1)(2)(3)(4)(5)
▲ OLRAX	131858.3N 1202644.5E							
	207° 027°	107.0	UNL FL170	FL170	10/50			(1)(2)(3)(4)(5)
▲ TOKON	114201.9N 1194028.9E							
	207° 027°	89.0	UNL FL080	FL080	10/50			(1)(2)(3)(4)(5)
▲ NOMYO	102050.2N 1190257.2E							
	207° 027°	40.0	UNL 8000 FT	8000 FT	10/50			(1)(2)(3)(4)(5)
▲ PUERTO PRINCESA DVOR/DME (PR)	094423.3N 1184613.5E							
	218° 038°	49.0	UNL FL150	FL150	10/50			(1)(2)(3)(4)(5)
▲ MIKEL	090434.1N 1181717.7E							
	218° 038°	102.0	UNL FL150	FL150	10/50			(1)(2)(3)(4)(5)

Route Designator									[Route Usage Notes]									
Significant Point Name			Significant Point Coordinates						Remarks									
			Track MAG		Dist (NM)		Upper limit / Lower limit		Minimum flight altitude		Lateral limits (NM)		FL series		Controlling unit Remarks			
													↓		↑			
OSANU			074124.0N 1171736.0E													(6)		

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
M754	(1) RNP10 exclusive. FPL Item 10a: R, Item18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) For FL Series refer to ENR 1.8-6 Table 2.2.4 (6) MRP - ATS/MET reporting point.							
AKOTA	162743.3N 1171224.3E							(6)
	190° 010°	136.0	UNL FL140	FL140	50			(1)(2)(3)(4)(5)
▲ GUKUM	141144.0N 1165501.8E							
	189° 009°	85.0	UNL FL140	FL140	50			(1)(2)(3)(4)(5)
▲ NOBEN	124712.1N 1164424.6E							
	189° 009°	98.0	UNL FL140	FL140	50			(1)(2)(3)(4)(5)
▲ LULBU	110936.1N 1163217.7E							
	189° 009°	113.0	UNL FL140	FL140	50			(1)(2)(3)(4)(5)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series ↓ ↑		Controlling unit Remarks
▲ TENON	091628.0N 1161825.3E							
	189° 009°	38.0	UNL FL140	FL140	50			(1)(2)(3)(4)(5)
VINIK	083830.0N 1161348.0E						(6)	

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
						FL series		
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	↓	↑	Controlling unit Remarks
M765	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (6) For FL Series refer to ENR 1.8-6 Table 2.2.4. (7) MRP - ATS/MET reporting point.							
▲ MANILA DVOR/DME (MIA)	143028.7N 1210118.2E							
	251° 071°	20.0	UNL 4000 FT	4000 FT	10/50			(1)(2)(4)(5)(6)
▲ BORGA	142259.8N 1204210.6E							
	251° 071°	24.0	UNL 5000 FT	5000 FT	10/50			(1)(2)(4)(5)(6)
▲ KEERO	141355.9N 1201907.2E							
	251° 071°	9.0	UNL 6000 FT	6000 FT	10/50			(1)(2)(4)(5)(6)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ BETEL	141038.1N 1201046.1E							
	<u>251°</u> 071°	19.0	<u>UNL</u> 6000 FT	6000 FT	10/50			(1)(2)(4)(5)(6)
▲ EXOLO	140334.9N 1195256.8E							
	<u>250°</u> 070°	74.0	<u>UNL</u> FL 140	FL140	10/50			(1)(2)(4)(5)(6)
▲ REKEL	133525.6N 1184231.9E							
	<u>250°</u> 070°	125.0	<u>UNL</u> FL 140	FL140	10/50			(1)(2)(4)(5)(6)
▲ NOBEN	124712.1N 1164424.6E							
	<u>249°</u> 069°	175.0	<u>UNL</u> FL 140	FL140	10/50			(1)(3)(4)(5)(6)
PANDI	113806.0N 1140000.0E							(7)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
M767	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) Thirty (30) NM procedural longitudinal separation minima for RNP4-approved and ADS-C/CPDLC connected aircraft pair. FPL Item 10a: R, J, P2, Item 10b: D1, Item 18: PBN/L1 SUR/RSP180 COM/RCP240. (6) Southwest bound uni-directional route. For FL Series refer to ENR 1.8-6 Table 2.2.4.							
▲ JOMALIG DVOR/DME (JOM)	144217.5N 1221947.9E							
	224°	25.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ LABAY	142314.1N 1220241.5E							
	224°	67.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ GALER	133216.0N 1211715.7E							
	224°	23.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ TAPAP	131505.6N 1210203.4E							
	224°	29.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ TELEN	125317.8N 1204249.7E							
	224°	94.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ TOKON	114201.9N 1194028.9E							
	236°	59.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ AGWAT	110718.7N 1185202.6E							
	236°	78.0	UNL FL170	FL170	50			(1)(2)(3)(4)(5)(6)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ TOSOV	102109.8N 1174814.1E							
	236°	110.0	<u>UNL</u> FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ TENON	091628.0N 1161825.3E							
	236°	33.0	<u>UNL</u> FL170	FL170	50			(1)(2)(3)(4)(5)(6)
▲ TEGID	085656.0N 1155143.0E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
M772	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Eighty (80) NM or 10 minutes MNT procedural longitudinal separation minima. (6) North bound uni-directional route. For FL Series refer to ENR 1.8-6 Table 2.2.4. (7) MRP - ATS/MET reporting point.							
▲ ASOBA	172224.0N 1143412.0E							
	001°	88.0	FL460 FL240	FL240	50			(1)(3)(4)(5)(6)
▲ ATBUD	155401.9N 1143704.1E							
	001°	103.0	FL460 FL240	FL240	50			(1)(3)(4)(5)(6)
▲ DABGI	141040.3N 1144022.1E							
	001°	11.0	FL460 FL240	FL240	50			(1)(3)(4)(5)(6)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ EMPUL	135942.0N 1144043.0E							
	001°	122.0	FL460 FL240	FL240	50			(1)(3)(4)(5)(6)
▲ DODUG	115703.0N 1144433.8E							
	001°	27.0	FL460 FL240	FL240	50			(1)(3)(4)(5)(6)
▲ VAVUM	112945.0N 1144554.7E							
	001°	100.0	FL460 FL240	FL240	50			(1)(2)(4)(5)(6)
LAXOR	094937.0N 1144829.0E							(7)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
N884	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) Thirty (30) NM procedural longitudinal separation minima for RNP4-approved and ADS-C/CPDLC connected aircraft pair. FPL Item 10a: R, J, P2, Item 10b: D1, Item 18: PBN/L1 SUR/RSP180 COM/RCP240. (6) Northeast bound uni-directional route. For FL Series refer to ENR 1.8-6 Table 2.2.4. (7) MRP - ATS/MET reporting point.							
LAXOR	094937.0N 1144829.0E							(7)
	054°	130.0	UNL FL070	FL070	50			(1)(2)(3)(4)(5)(6)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ LULBU	110936.1N 1163217.7E							
	054°	183.0	<u>UNL</u> FL070	FL070	50			(1)(2)(3)(4)(5)(6)
▲ LEGED	130113.2N 1190006.9E							
	054°	81.6	<u>UNL</u> FL070	FL070	50			(1)(2)(3)(4)(5)(6)
▲ LUBAN	135114.9N 1200625.5E							
	031°	111.0	<u>UNL</u> FL210	FL210	50			(1)(2)(3)(4)(5)(6)
▲ CABANATUAN DVOR/DME (CAB)	152856.2N 1210127.5E							
	029°	96.2	<u>UNL</u> FL210	FL210	50			(1)(2)(3)(4)(6)
△ CAUAYAN DVOR/DME (CUY)	165553.8N 1214453.1E							
	029°	61.0	<u>UNL</u> FL210	FL210	50			(1)(2)(3)(4)(6)
▲ DADNU	175010.2N 1221349.9E							
	029°	212.0	<u>UNL</u> FL210	FL210	50			(1)(2)(3)(4)(6)
LEBIX	210000.0N 1235430.0E						(7)	

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
N892	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (6) Southwest bound uni-directional route. For FL Series refer to ENR 1.8-6 Table 2.2.4. (7) MRP - ATS/MET reporting point.							
KABAM	210000.0N 1195248.0E							(7)
	229°	141.0	UNL FL150	FL150	50			(1)(2)(4)(5)(6)
▲ MIKIN	192006.7N 1180635.1E							
	228°	26.0	UNL FL150	FL150	50			(1)(2)(4)(5)(6)
▲ MUMOT	190142.9N 1174723.0E							
	228°	105.0	UNL FL150	FL150	50			(1)(2)(4)(5)(6)
▲ DALRA	174640.2N 1163007.2E							
	227°	208.0	UNL FL150	FL150	50			(1)(3)(4)(5)(6)
▲ MIGUG	151624.0N 1140000.0E							

Route Designator [Route Usage Notes]								
Significant Point Name		Significant Point Coordinates						Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
P515	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) Class A radar surveillance airspace starts from 60 NM West of TODEK to the West. VHF radio as primary DCPC.							
	(3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit.							
	(4) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(5) Eighty (80) NM or 10 minutes MNT procedural longitudinal separation minima.							
	(6) West bound uni-directional route. FL400 only. Other flight levels subject to ATC approval.							
	(7) MRP - ATS/MET reporting point.							
	ENDAX	141500.0N 1300000.0E						
	259°	263.0	FL460 FL290	FL290	50	Even		(1)(3)(4)(5)(6)
▲ TODEK	131333.8N 1253650.7E							
	258°	299.0	FL460 FL290	FL290	50	Even		(1)(2)(4)(5)(6)
▲ KABOK	115811.9N 1204102.6E							
	257°	62.0	FL460 FL290	FL290	50	Even		(1)(2)(4)(5)(6)
▲ TOKON	114201.9N 1194028.9E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
R337	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Class A remote airspace. CPDLC as primary DCPC. HF radio as alternative communication channel via third-party ATS unit. (4) Flight crew option for datalink ADS-C/CPDLC. FPL item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (5) Eighty (80) NM or 10 minutes MNT procedural longitudinal separation minima. (6) MRP - ATS/MET reporting point.							
▲ TACLOBAN DVOR/DME (TAC)	111355.2N 1250133.6E							
	114° 294°	25.0	UNL 3000 FT	3000 FT	10/50	Odd	Even	(1)(2)(4)(5)
▲ BIKAS	110441.8N 1252512.9E							
	114° 294°	23.0	UNL 7000 FT	7000 FT	10/50	Odd	Even	(1)(2)(4)(5)
▲ ALICO	105618.4N 1254638.6E							
	114° 294°	270.0	UNL FL070	FL070	10/50	Odd	Even	(1)(3)(4)(5)
ISGOG	091442.0N 1300000.0E							(6)

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
R590	(1) RNP10 approval required from FL290 and above. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC.							
▲ COTABATO VOR/DME (COT)	071003.1N 1241232.8E							
	161° 341°	60.0	UNL FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ SEBUL	061345.6N 1243252.3E							
	161° 341°	142.0	UNL FL100	FL100	10/50	Odd	Even	(1)(2)(3)(4)
▲ PEDNO	040000.0N 1252100.0E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
W16	(1) RNP10 approval required. FPL Item 10a: R, Item 18: PBN/A1.							
	(2) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240.							
	(4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair.							
	(5) Thirty (30) NM procedural longitudinal separation minima for RNP4-approved and ADS-C/CPDLC connected aircraft pair. FPL item 10a: R, J, P2, Item 10b: D1, Item 18: PBN/L1 SUR/RSP180 COM/RCP240.							
▲ AVMUP	175936.1N 1185731.1E							
	154° 334°	158.0	UNL FL090	FL090	50/10	Odd	Even	(1)(2)(3)(4)(5)

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
▲ TATIL	154027.4N 1201710.3E							
	154° 334°	11.0	UNL FL080	FL080	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ BIGBI	153046.1N 1202238.2E							
	154° 334°	7.0	UNL FL060	FL060	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ TADEL	152450.9N 1202558.3E							
	154° 334°	15.0	UNL 6000 FT	6000 FT	10	Odd	Even	(1)(2)(3)(4)(5)
▲ CLARK DVOR/DME (CIA)	151112.8N 1203338.3E							
	150° 330°	17.0	UNL 6000 FT	6000 FT	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ OLIVA	145657.8N 1204320.4E							
	150° 330°	17.0	UNL 6000 FT	6000 FT	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ VOTAS	144238.1N 1205304.2E							
	150° 330°	14.0	UNL 6000 FT	6000 FT	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ MANILA DVOR/DME (MIA)	143028.7N 1210118.2E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
W16A	(1) RNAV5 approved required. South bound uni-directional route FPL Item 10a: R, Item 18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima.							
▲ TATIL	154027.4N 1201710.3E							
	134°	9.6	<u>UNL</u> FL080	FL080	10	Odd		(1)(2)(3)
▲ PAYAD	153406.1N 1202436.6E							
	134°	5.0	<u>UNL</u> FL050	FL050	10	Odd		(1)(2)(3)
▲ BABAN	153048.2N 1202827.9E							
	134°	3.8	<u>UNL</u> 5000 FT	5000 FT	10	Odd		(1)(2)(3)
▲ NABAL	152817.0N 1203124.5E							
	135°	8.9	<u>UNL</u> 3000 FT	3000 FT	10	Odd		(1)(2)(3)
▲ ROSER	152223.2N 1203817.4E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
W23	(1) RNP10 exclusive. FPL Item 10a: R, Item 18: PBN/A1. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Flight crew option for datalink ADS-C/CPDLC. FPL Item 10a: J, P2, Item 10b: D1, Item 18: SUR/RSP180 COM/RCP240. (4) Fifty (50) NM procedural longitudinal separation minima for RNP10 aircraft pair in: a. radar surveillance airspace or, b. remote airspace using ADS-C/CPDLC. (5) For FL Series refer to ENR 1.8-6 Table 2.2.4.							
▲ GUKUM	141144.0N 1165501.8E							
	085° 265°	80.5	UNL FL140	FL140	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ SOMAR	142420.3N 1181713.2E							
	085° 265°	61.8	UNL FL140	FL140	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ KADUL	143337.5N 1191957.2E							
	085° 265°	23.6	UNL FL140	FL140	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ ZULUR	143707.0N 1194404.3E							
	085° 265°	39.0	UNL 7000 FT	7000 FT	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ NATIB	144247.2N 1202352.8E							
	021° 201°	6.1	UNL 7000 FT	7000 FT	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ RELUB	144837.6N 1202552.9E							
	021° 201°	23.7	UNL 7000 FT	7000 FT	50/10	Odd	Even	(1)(2)(3)(4)(5)
▲ CLARK DVOR/DME (CIA)	151112.8N 1203338.3E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
W24	(1) RNAV5 exclusive. FPL Item 10a: R Item 18: PBN/B1 or B2 or B3B4B5.							
	(2) Class A radar surveillance airspace. VHF radio as primary DCPC.							
	(3) Five (5) minutes procedural longitudinal separation minima.							
	(4) South bound uni-directional route.							
▲ VERDE	133013.2N 1210154.4E							
	147°	10.3	<u>UNL</u> FL070			Odd		(1)(2)(3)(4)
▲ SORVO	132141.8N 1210754.0E							
	147°	72.1	<u>UNL</u> FL070			Odd		(1)(2)(3)(4)
▲ TAPER	122156.7N 1214939.1E							

Route Designator								
[Route Usage Notes]								
Significant Point Name		Significant Point Coordinates						Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
W25 (1) RNAV5 exclusive. FPL Item 10a: R, Item 18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima. (4) South bound uni-directional route.								
▲ IPATA	135157.4N 1214848.0E							
	146°	114.2	UNL FL080			Odd		(1)(2)(3)(4)
▲ RAPEL	121930.0N 1225805.0E							
	146°	87.7	UNL FL080			Odd		(1)(2)(3)(4)
▲ BATAY	110819.3N 1235043.1E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
W26	(1) RNAV5 exclusive. FPL Item 10a: R, Item18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima. (4) South bound uni-directional route.							
▲ DINNO	133105.5N 1205054.3E							
	173°	24.3	<u>UNL</u> FL110			Odd		(1)(2)(3)(4)
▲ ONOLI	130703.3N 1205457.9E							
	173°	45.8	<u>UNL</u> FL110			Odd		(1)(2)(3)(4)
▲ SAN JOSE VOR/DME (SAJ)	122137.1N 1210235.1E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
Z151	(1) RNAV5 exclusive. FPL Item 10a: R, Item 18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima. (4) East bound uni-directional route.							
▲ KALAH	094404.4N 1203956.0E							
	083°	50.8	<u>UNL</u> FL080	FL080		Odd		(1)(2)(3)(4)
▲ WAKAN	095146.5N 1213049.2E							
	083°	26.8	<u>UNL</u> FL080	FL080		Odd		(1)(2)(3)(4)
▲ EMROR	095547.7N 1215740.8E							

Route Designator [Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	083°	26.1	<u>UNL</u> FL080	FL080		Odd		(1)(2)(3)(4)
▲ PALGI	095939.6N 1222351.5E							
	068°	26.0	<u>UNL</u> FL080	FL080		Odd		(1)(2)(3)(4)
▲ BSAYA	101018.8N 1224820.0E							
	068°	13.0	<u>UNL</u> FL080	FL080		Odd		(1)(2)(3)(4)
▲ RUXEM	101525.5N 1230006.7E							
	087°	8.0	<u>UNL</u> FL110	FL110		Odd		(1)(2)(3)(4)
▲ TADAG	101607.2N 1230839.0E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
Z152	(1) RNAV5 exclusive. FPL Item 10a: R, Item 18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima. (4) South bound uni-directional route.							
▲ TAPAP	131505.6N 1210203.4E							
	159°	103.1	<u>UNL</u> FL110	FL110	10	Odd		(1)(2)(3)(4)
▲ JULOR	113931.2N 1214245.5E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates							Remarks
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
Z153	(1) RNAV5 exclusive. FPL Item 10a: R, Item 18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima. (4) Southwest bound uni-directional route.							
▲ MUPOB	153811.8N 1230317.9E							
	244°	75.9	<u>UNL</u> FL090	FL090	10	Even		(1)(2)(3)(4)
▲ POLIO	150030.0N 1215500.0E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
Z154	(1) RNAV5 exclusive. FPL Item 10a: R, Item 18: PBN/B1 or B2 or B3B4B5. (2) Class A radar surveillance airspace. VHF radio as primary DCPC. (3) Five (5) minutes procedural longitudinal separation minima. (4) North bound uni-directional route.							
▲ BURCO	072027.0N 1220605.5E							
	358°	142.6	<u>UNL</u> FL090	FL090	10	Even		(1)(2)(3)(4)
▲ TENUK	094329.1N 1215821.0E							
	359°	12.3	<u>UNL</u> FL090	FL090	10	Even		(1)(2)(3)(4)
▲ EMROR	095547.7N 1215740.8E							
	359°	44.3	<u>UNL</u> FL090	FL090	10	Even		(1)(2)(3)(4)
▲ PASBU	104016.7N 1215515.1E							

Route Designator								
[Route Usage Notes]								
Significant Point Name	Significant Point Coordinates						Remarks	
	Track MAG	Dist (NM)	Upper limit / Lower limit	Minimum flight altitude	Lateral limits (NM)	FL series		Controlling unit Remarks
						↓	↑	
	359°	48.8	<u>UNL</u> FL090	FL090	10	Even		(1)(2)(3)(4)
▲ SEDKI	112911.8N 1215233.8E							
	359°	52.6	<u>UNL</u> FL090	FL090	10	Even		(1)(2)(3)(4)
▲ TAPER	122156.7N 1214939.1E							