

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.6, AD-2.7, AD-2.10, AD-2.11, AD-2.14, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPMI AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPMI - ILIGAN COMMUNITY AIRPORT****RPMI AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	080855.4697N 1241235.0439E.
2	Direction and distance from (city)	13KM.
3	Elevation/Reference temperature	Nil.
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	0.5° W (2014) / 2.7' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Iligan Airport, Baloi, Iligan City 9200 Lanao Del Norte
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPMI AD 2.3 OPERATIONAL HOURS

1	AD Operator	0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	Nil.
6	MET Briefing Office	Nil.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 2300 - 0800.

RPMI AD 2.5 PASSENGER FACILITIES

1	Hotels	Within the City.
2	Restaurants	Within the City.
3	Transportation	Vehicle for hire.
4	Medical facilities	Within the City.
5	Bank and Post Office	Within the City.
6	Tourist Office	Nil.
7	Remarks	Nil.

RPMI AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: CONC. Strength: Nil.
2	Taxiway width, surface and strength	Width: 18M. Surface: CONC. Strength: Nil.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPMI AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Nil.
2	RWY and TWY markings and LGT	RWY: RWY side stripe, designation, centerline, threshold markings SWY: SWY end markers. TWY: Nil.
3	Stop bars	Nil.
4	Remarks	Nil.

RPMI AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
02	020° GEO 020° MAG	1400M X 18M	PCN 29.2 R/B/W/T CONC	Nil	Nil
20	200° GEO 200° MAG	1400M X 18M	PCN 29.2 R/B/W/T CONC	Nil	Nil
Slope of RWY-SWY	SWY dimensions	CWY dimensions	Strip dimensions	OFZ	Remarks
7	8	9	10	11	12
Nil	200M X 18M	450M	Nil	Nil	Nil
Nil	100M X 18M	150M	Nil	Nil	Nil

RPMI AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
02	1400M	1850M	1600M	1400M	Nil
20	1400M	1550M	1500M	1400M	Nil

RPMI AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil.
2	LDI location and LGT Anemometer location and LGT	Nil.
3	TWY edge and centre line lighting	Nil.
4	Secondary power supply/switch-over time	Secondary power supply to all lighting at AD.
5	Remarks	Nil.

INTENTIONALLY
LEFT
BLANK