

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.7, AD-2.9, AD-2.11, AD-2.15, AD-2.16, AD-2.17, AD-2.19, AD-2.21, AD-2.22, AD-2.23, AD-2.24, AD-2.25

RPMN AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPMN - SANGA-SANGA PRINCIPAL AIRPORT (Class 1)****RPMN AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	050255N 1194437E.
2	Direction and distance from (city)	10 KM.
3	Elevation/Reference temperature	29 FT.
4	Geoid undulation at AD ELEV PSN	204 FT.
5	MAG VAR/Annual Change	1°W (2021) / 6.0' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Sanga-Sanga Airport Bongao, Tawi-Tawi 7500 Sulu
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPMN AD 2.3 OPERATIONAL HOURS

1	AD Operator	HJ.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	2200 - 0600.
6	MET Briefing Office	Nil.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	Nil.
11	De-icing	Nil.
12	Remarks	Airport Operations: 2200 - 0600.

RPMN AD 2.5 PASSENGER FACILITIES

1	Hotels	Within the town proper.
2	Restaurants	Within the town proper.
3	Transportation	Vehicle for hire.
4	Medical facilities	Within the town proper.
5	Bank and Post Office	Within the town proper.
6	Tourist Office	Within the town proper.
7	Remarks	Nil.

RPMN AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT VI.
2	Rescue equipment	Two (2) fire trucks [SIDES (9500 liters) and SIDES (2500 liters)].
3	Capability for removal of disabled aircraft	Removal of disabled aircraft is to be done by aircraft owner or operator.
4	Remarks	Nil.

RPMN AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: CONC. Strength: PCN 39 R/A/W/U.
2	Taxiway width, surface and strength	Nil.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Apron directly connected to runway. Taxilane provided.

RPMN AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
20	Coconut Tree 87 FT	050337.8N 1194454.9E	Nil	Nil	Nil
	Coconut Tree 85 FT	050334.2N 1194446.2E			
	Tree 81 FT	050339.1N 1194454.1E			
	Tree 71 FT	050337.5N 1194447.3E			
	Tree 70 FT	050353.5N 1194454.1E			
	Electric Post 43 FT	050335.6N 1194449.7E			
	Tree 41 FT	050327.8N 1194448.6E			
	Electric Post 40 FT	050331.0N 1194448.9E			
	Electric Post 39 FT	050331.1N 1194446.8E			
	Electric Post 39 FT	050337.6N 1194450.5E			

RPMN AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY (M)	Strength (PCR) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
02	017.05°	1860 X 30	419/R/B/W/U CONC	050226.48N 1194427.26E 204 FT	15 FT	0.4420% uphill towards THR 20
20	197.05°	1860 X 30	419/R/B/W/U CONC	050323.95N 1194446.29E 204 FT	22 FT	
SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
Nil	Nil	Nil	Nil	Nil	Nil	Nil
60 X 30	60 X 150	Nil	Nil	Nil	Nil	Nil

RPMN AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
02	1860	1860	1860	1860	Nil
20	1860	1920	1920	1860	Nil

RPMN AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type, LEN, INTST	THR LGT colour, WBAR	VASIS, (MEHT), PAPI	TDZ, LGT LEN
1	2	3	4	5
02	Nil	Nil	PAPI 3.0° Left (42.51 FT)	Nil
20	Nil	Nil	PAPI 3.0° Right (45.72 FT)	Nil

RWY Centre Line LGT LEN, spacing, colour, INTST	RWY Edge LGT LEN, spacing, colour, INTST	RWY End LGT colour, WBAR	SWY LGT LEN, colour	Remarks
6	7	8	9	10
Nil	Nil	Nil	Nil	Path width: 0.33°. Visibility range: 6 NM. Horizontal angular CLR: Clear. Distance from THR: 265 M.
Nil	Nil	Nil	Nil	Path width: 0.33°. Visibility range: 6 NM. Horizontal angular CLR: Clear. Distance from THR: 285 M.

RPMN AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	SANGA-SANGA AERODROME ADVISORY ZONE (AAZ): A circle radius 5 NM centered on 050255N 1194437E (ARP).
2	Vertical limits	AAZ: SFC up to but excluding 2000 FT.
3	Airspace classification	G.
4	ATS unit call sign Language(s)	Sanga-Sanga Radio. English.
5	Transition altitude	Nil.
6	Hours of applicability	Nil.
7	Remarks	Nil.

RPMN AD 2.18 ATS COMMUNICATION FACILITIES

Service Designation	Call Sign	Frequency	SATVOICE number	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
FSS	Sanga-Sanga Radio	122.1 MHZ	Nil	Nil	2200 - 0600	A/G FREQ. For extension of service, one (1) day prior notice is required.

RPMN AD 2.20 LOCAL AERODROME REGULATIONS

1. Airport Regulations

- 1.1 Number of aircraft in the traffic pattern limited to two (2) at any given time.
- 1.2 Runway closed to aircraft operations when an A320 or same category aircraft is parked at the ramp area.
- 1.3 Local Flying Restrictions
 - 1.3.1 The presence of 1122 FT Bongao Peak at the end of RWY 20 poses as hazard to both departing aircraft on RWY 20 and landing aircraft on RWY 02, hence the following should be observed:
 - 1.3.1.1 Departing RWY 20
 - a. Advise to make a right downwind departure upon airborne.
 - b. May be allowed to do other maneuvers as requested, subject to pilot's discretion.
 - 1.3.1.2 Landing RWY 02
 - a. Advise to join with the left traffic pattern for RWY 02, but may be allowed to do other maneuvers as requested, subject to pilot's discretion.

INTENTIONALLY
LEFT
BLANK