

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.7, AD-2.11, AD-2.14, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPMW AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPMW - TANDAG PRINCIPAL AIRPORT (Class 2)****RPMW AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	090355N 1261005E.
2	Direction and distance from (city)	3KM from the town.
3	Elevation/Reference temperature	5M (16FT) AMSL.
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	0.6°W (2014) / 3' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Tandag Airport, Tandag 8300 Surigao del Sur Phone: (086) 211-4186 AFS: RPMWYYX
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPMW AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - FRI: 0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	Nil.
6	MET Briefing Office	2200 - 1000.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 0100 - 0900.

RPMW AD 2.5 PASSENGER FACILITIES

1	Hotels	Within the town proper.
2	Restaurants	Within the town proper.
3	Transportation	Vehicle for hire.
4	Medical facilities	Within the town proper.
5	Bank and Post Office	Within the town proper.
6	Tourist Office	Nil.
7	Remarks	Nil.

RPMW AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT IV.
2	Rescue equipment	One (1) fire truck [SIDES (2400 liters)].
3	Capability for removal of disabled aircraft	Nil.
4	Remarks	Nil.

RPMW AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: CONC. Strength: Nil.
2	Taxiway width, surface and strength	Width: 18M. Surface: CONC. Strength: Nil.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPMW AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing guidance signs at intersection with TWY and RWY guide lines at apron.
2	RWY and TWY markings and LGT	RWY: Designation, THR, Center line markings. TWY: Center line markings.
3	Stop bars and RWY guard lights	Stop bars where appropriate.
4	Other RWY guard lights	Nil.
5	Remarks	Nil.

RPMW AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
03/APCH zone	Hill	Nil	Nil	Nil	Nil
21/APCH zone	Power line 3M (10FT)	090431.9N 1261035.0E	NDB Mast	090413.9N 1261017.0E	Nil

RPMW AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THRgeoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
03	026.00° GEO 026.60° MAG	1360M X 30M	PCN 24 R/B/X/T CONC	Nil	Nil	0.8% uphill to NE
21	206.00° GEO 206.60° MAG	1360M X 30M	PCN 24 R/B/X/T CONC	Nil	Nil	
SWY dimensions	CWY dimensions	Strip dimensions	RESA dimensions	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
100M X 30M	100M	Nil	Nil	Nil	Nil	Nil
100M X 30M	100M	Nil	Nil	Nil	Nil	Nil

RPMW AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
03	1360M	1460M	1460M	1360M	Nil
21	1360M	1460M	1460M	1360M	Nil

RPMW AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil.
2	LDI location and LGT Anemometer location and LGT	Nil.
3	TWY edge and centre line lighting	Nil.
4	Secondary power supply/switch-over time	Secondary power supply to all lighting at AD.
5	Remarks	Nil.

INTENTIONALLY
LEFT
BLANK