

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.6, AD-2.7, AD-2.10, AD-2.11, AD-2.14, AD-2.15, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPSB AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPSB - BANTAYAN COMMUNITY AIRPORT****RPSB AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	110944N 1234705E.
2	Direction and distance from (city)	2KM.
3	Elevation/Reference temperature	25M (82FT).
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	1.8°W (2020) / 6' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Mactan Cebu International Airport Authority (MCIAA) Bantayan Airport, Sta. Fe, Bantayan Island, 6052 Cebu, Philippines Phone: (+63) (032) 520-2316 Fax: (+63) (032) 341-1861 Email: pao.mciaa@gmail.com
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPSB AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - FRI: 0000 - 0900 SAT, SUN + HOL: On request.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	Nil.
6	MET Briefing Office	Nil.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 2200 - 1000.

RPSB AD 2.5 PASSENGER FACILITIES

1	Hotels	Within the town proper.
2	Restaurants	Within the town proper.
3	Transportation	Within the town proper.
4	Medical facilities	Within the town proper.
5	Bank and Post Office	Within the town proper.
6	Tourist Office	Within the town proper.
7	Remarks	Nil.

RPSB AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: MACADAM. Strength: Nil.
2	Taxiway width, surface and strength	TWY Bravo Width: 12M. Surface: CONC. Strength: PCN 77 R/B/W/T.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPSB AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Nil.
2	RWY and TWY markings and LGT	RWY designation, THR markings, RWY Center line, SWY end, TWY center line and TWY edge line.
3	Stop bars and RWY guard lights	Nil.
4	Other RWY protection measures	Nil.
5	Remarks	Nil.

RPSB AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
16	158.00° GEO 159.80° MAG	1200M X 18M	PCN 77 R/B/W/T CONC	111002.00N 1234658.00E	THR 21M/68FT	Nil
34	338.00° GEO 339.80° MAG	1200M X 18M	PCN 77 R/B/W/T CONC	110926.00N 1234712.00E	THR 25M/82FT	Nil
SWY dimensions	CWY dimensions	Strip dimensions	RESA dimensions	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
60M X 18M	Nil	Nil	60M X 18M	Nil	Nil	Nil
60M X 18M	Nil	Nil	60M X 18M	Nil	Nil	Nil

RPSB AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
16	1200M	1200M	1260M	1200M	Nil
34	1200M	1200M	1260M	1200M	Nil