

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.7, AD-2.10, AD-2.16, AD-2.21, AD-2.22, AD-2.23, AD-2.24, AD-2.25

RPUH AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPUH - SAN JOSE PRINCIPAL AIRPORT (Class 1)****RPUH AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	122142N 1210248E.
2	Direction and distance from (city)	2 KM Northwest.
3	Elevation/Reference temperature	12 FT.
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	2°W (2021) / 6.0' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines San Jose Airport, San Jose 5100 Occidental Mindoro Phone: (+63) (043) 742-5527 (Admin) AFS: RPUHYFYX
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Phone: (+63) (043) 732-0879 (ATS Building).

RPUH AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - FRI: 0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	2200 - 0600.
6	MET Briefing Office	H24.
7	ATS	2200 - 0600.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 2200 - 1000. All pilots are required to transmit their position report to Busuanga Tower beyond the hours of operations of San Jose FSS.

RPUH AD 2.5 PASSENGER FACILITIES

1	Hotels	Within the town proper.
2	Restaurants	Within the town proper.
3	Transportation	For hire at the parking area.
4	Medical facilities	Within the town proper.
5	Bank and Post Office	Within the town proper.
6	Tourist Office	Provincial Office Tourism Booth at the arrival area.
7	Remarks	Nil.

RPUH AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	Category 6.
2	Rescue equipment	Two (2) fire trucks [Oshkosh (6000 liters) and SIDES (2400 liters)].
3	Capability for removal of disabled aircraft	Disabled Aircraft Removal Plan (DARP) Capability to remove aircraft A320 and below. Removal of disabled aircraft is to be done by aircraft owner or operator. DARP Coordinator: San Jose Airport Administration Office Third Party Contractor: F A Torres Construction Phone: (+63) (043) 742-5527, 09177709262 (mobile).
4	Remarks	Foam Meeting Performance: Level B.

RPUH AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Main Apron Surface: CONC. Strength: 470/R/B/X/U.
2	Taxiway width, surface and strength	TWY East Width: 18 M. Surface: CONC+ASPH. Strength: 640/R/B/X/U. TWY West Width: 18 M. Surface: CONC+ASPH. Strength: 640/R/B/X/U.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPUH AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	TWY and APN nose wheel guide line markings.
2	RWY and TWY markings and LGT	RWY center line markings - White. TWY center line markings - Yellow.
3	Stop bars and RWY guard lights	Nil.
4	Other RWY protection measures	Nil.
5	Remarks	Nil.

RPUH AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	Philippine Atmospheric, Geophysical and Astronomical Services Administration (PAGASA).
2	Hours of service MET Office outside hours	H24. -
3	Office responsible for TAF preparation Periods of validity	PAGASA / FSS. -
4	Trend forecast Interval of issuance	Hourly. Every 12 hours.
5	Briefing/consultation provided	Personal, mobile phone.
6	Flight documentation Language(s) used	- English.
7	Charts and other information available for briefing or consultation	Nil.
8	Supplementary equipment available for providing information	Telephone, SSB.
9	ATS units provided with information	San Jose FSS.
10	Additional information (limitation of service, etc.)	Nil.

RPUH AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY (M)	Strength (PCR) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
10	105.00°	1836 X 45	640/R/B/X/U CONC+ASPH	122149.30N 1210218.26E	13 FT	Nil
28	285.00°	1836 X 45	640/R/B/X/U CONC+ASPH	122133.81N 1210316.96E	12 FT	Nil
SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
27 X 45	60 X 116	1954 X 116	Nil	Nil	Nil	Nil
61 X 45	80 X 116	1954 X 116	Nil	Nil	Nil	Nil

RPUH AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
10	1836	1896	1863	1836	Nil
28	1836	1916	1897	1836	Nil

RPUH AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type, LEN, INTST	THR LGT colour, WBAR	VASIS, (MEHT), PAPI	TDZ, LGT LEN
1	2	3	4	5
10	Nil	Nil	PAPI 3.0° Left (14.12 FT)	Nil
28	Nil	Nil	PAPI 3.0° Left (14.12 FT)	Nil
RWY Centre Line LGT LEN, spacing, colour, INTST	RWY Edge LGT LEN, spacing, colour, INTST	RWY End LGT colour, WBAR	SWY LGT LEN, colour	Remarks
6	7	8	9	10
Nil	Nil	Nil	Nil	Nil
Nil	Nil	Nil	Nil	Nil

RPUH AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil.
2	LDI location and LGT Anemometer location and LGT	Nil.
3	TWY edge and centre line lighting	Nil.
4	Secondary power supply/switch-over time	Secondary power supply to all lighting at aerodrome. Switch-over time 13 seconds.
5	Remarks	Nil.

RPUH AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	SAN JOSE AERODROME ADVISORY ZONE (AAZ): A circle 5 NM radius centered on 122142N 1210248E (ARP).
2	Vertical limits	AAZ: SFC up to but excluding 2000 FT.
3	Airspace classification	G.
4	ATS unit call sign Language(s)	San Jose Radio. English.
5	Transition altitude	Nil.
6	Hours of applicability	Nil.
7	Remarks	Nil.

RPUH AD 2.18 ATS COMMUNICATION FACILITIES

Service Designation	Call Sign	Frequency	SATVOICE number	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
FSS	San Jose Radio	118.3 MHZ 5447.5 KHZ 3834 KHZ	740110	San Jose FSS (User name)	2200 - 0600	A/G FREQ. P/P PRI FREQ. P/P SRY FREQ.

RPUH AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OP(for VOR/ILS/MLS, give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
DVOR/DME	SAJ	117.1 MHZ / CH118X	H24	122137.1N 1210235.1E	Nil	DVOR - 100 watts. DME - 1 KW. 224 M from North end RWY and 72 M from RWY CL.

RPUH AD 2.20 LOCAL AERODROME REGULATIONS

1. Airport Regulations

- 1.1 Number of aircraft in the traffic pattern limited to two (2) at any given time.
- 1.2 The allocation of airport slots for apron terminal, and runway shall be implemented to optimize air traffic flow and maximize airport resource utilization.
- 1.3 All airline operators are to secure airport slot approval from the respective airport managers for each scheduled flight. Additionally, all general aviation operators are to secure an airport clearance from the respective airport managers at least seventy-two (72) hours before the intended operation.
- 1.4 Crossing of runway is prohibited. An ATC clearance from the Air Traffic Management Officer (ATMO) on duty must be obtained in case there is a need to enter the aircraft movement area.
- 1.5 All CAA of the Philippines (CAAP) - San Jose Airport personnel and all the attached agencies performing duties at the airport particularly at Passenger Terminal Building (PTB) must have an access pass.

2. Parking

2.1 Assignment of Parking Bays

Bay Number	Coordinates	Aircraft Type	Restrictions/Remarks
1	Nil	A320 and lower category aircraft	First come, first serve basis.
2	Nil	A320 and lower category aircraft	First come, first serve basis.
3	Nil	ATR and lower category aircraft	First come, first serve basis.