

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.7, AD-2.11, AD-2.14, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPUM AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPUM - MAMBURAO COMMUNITY AIRPORT****RPUM AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	131215N 1203628E.
2	Direction and distance from (city)	2.4KM SE.
3	Elevation/Reference temperature	4M (13FT) AMSL.
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	1.4°W (2014) / 2.2' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Mamburao Airport, Mamburao 5106 Occidental Mindoro Phone: (043) 711-1008 AFS: RPUMYYYYX
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPUM AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - FRI: 0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	Nil.
6	MET Briefing Office	Nil.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 0000 - 0800.

RPUM AD 2.5 PASSENGER FACILITIES

1	Hotels	Limited at the town proper.
2	Restaurants	Limited at the town proper.
3	Transportation	Vehicle for hire.
4	Medical facilities	At the town proper.
5	Bank and Post Office	At the town proper.
6	Tourist Office	Nil.
7	Remarks	Nil.

RPUM AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT IV.
2	Rescue equipment	One (1) fire truck [SIDES (2400 liters)].
3	Capability for removal of disabled aircraft	Nil.
4	Remarks	Nil.

RPUM AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: CONC. Strength: Nil.
2	Taxiway width, surface and strength	Width: 18M. Surface: CONC. Strength: Nil.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPUM AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Nil.
2	RWY and TWY markings and LGT	RWY: Center line, Designation. TWY: Nil.
3	Stop bars and RWY guard lights	SWY and distance to go marker.
4	Other RWY protection measures	Nil.
5	Remarks	Nil.

RPUM AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
16/APCH zone	Trees	Nil	Nil	Nil	Nil

RPUM AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
16	165.00° GEO 166.40° MAG	1300M X 30M	RWY: PCN 9 F/C/Y/T CONC SWY: MACADAM	Nil	Nil	Eff. 0.44% uphill to the N.
34	345.00° GEO 346.40° MAG	1300M X 30M	RWY: PCN 9 F/C/Y/T CONC SWY: MACADAM	Nil	Nil	
SWY dimensions	CWY dimensions	Strip dimensions	RESA dimensions	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
100M X 30M	100M	Nil	Nil	Nil	Nil	Nil
100M X 30M	100M	Nil	Nil	Nil	Nil	Nil

RPUM AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
16	1300M	1400M	1400M	1300M	Nil
34	1300M	1400M	1400M	1300M	Nil

RPUM AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil.
2	LDI location and LGT Anemometer location and LGT	Nil.
3	TWY edge and centre line lighting	Nil.
4	Secondary power supply/switch-over time	Secondary power supply to all lighting at AD. Switch-over time of 15 seconds.
5	Remarks	Nil.

INTENTIONALLY
LEFT
BLANK