

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.16, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPUV AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPUV - VIRAC PRINCIPAL AIRPORT (Class 2)****RPUV AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	133437N 1241218E.
2	Direction and distance from (city)	4KM ENE to town proper.
3	Elevation/Reference temperature	47M.
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	1.6°W (2014) / 2.8' increasing
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Virac Airport 4800 Catanduanes Phone: (052) 811- 3511
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPUV AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - SAT: 0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	2200 - 0600. For extension of SER, one (1) day PN is required.
6	MET Briefing Office	2200 - 1000.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 2200 - 0600.

RPUV AD 2.5 PASSENGER FACILITIES

1	Hotels	In the town proper.
2	Restaurants	At the AD and in the town proper.
3	Transportation	Car for hire.
4	Medical facilities	In the town proper.
5	Bank and Post Office	In the town proper.
6	Tourist Office	Nil.
7	Remarks	Nil.

RPUV AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CAT VI.
2	Rescue equipment	Two (2) fire trucks [Oshkosh (6000 liters) and SIDES (2400 liters)].
3	Capability for removal of disabled aircraft	Nil.
4	Remarks	Nil.

RPUV AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Types of clearing equipment	3 units motorized grass cutters.
2	Clearance priorities	Clearing of brushes on RWY shoulders and premises of Terminal bldg.
3	Remarks	Nil.

RPUV AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: CONC. Strength: PCN 37.4 R/B/W/T.
2	Taxiway width, surface and strength	Width: TWY S 20M, TWY N 18M. Surface: CONC. Strength: PCN 37.4 R/B/W/T.
3	Altimeter checkpoint location and elevation	37 AMSL.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPUV AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing guidance signs at all intersections with TWY and RWY at holding positions. Guide lines at apron. Nose-in guidance at aircraft stands.
2	RWY and TWY markings and LGT	RWY: Designation, THR, TDZ, Center line, Edge, RWY end as appropriate, marked and LGTD.
3	Stop bars and RWY guard lights	Nil.
4	Other RWY protection measures	Nil.
5	Remarks	Nil.

RPUV AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
06	Mountain 130M	133353.9N 1241031.2E	Nil	Nil	2500.43M FM THR. 420M left of extended RWY CL.
	Nil	Nil	Radio Transmitter Antenna	Nil	600M left side of RWY06.
24	Trees	Nil	Nil	Nil	600M end of RWY24.

RPUV AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	PAGASA.
2	Hours of service MET Office outside hours	- -
3	Office responsible for TAF preparation Periods of validity	- -
4	Trend forecast Interval of issuance	- -
5	Briefing/consultation provided	Nil.
6	Flight documentation Language(s) used	- English.
7	Charts and other information available for briefing or consultation	Nil.
8	Supplementary equipment available for providing information	Nil.
9	ATS units provided with information	FSS.
10	Additional information (limitation of service, etc.)	Nil.

RPUV AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
06	060.47° GEO 062.07° MAG	1755M X 30M	PCN 37.4 R/B/Z/T CONC	133423.08N 1241152.23E	47M/153FT	0.892% uphill towards THR06
24	240.47° GEO 242.07° MAG	1755M X 30M	PCN 37.4 R/B/Z/T CONC	133451.22N 1241243.15E	31M/101FT	
SWY dimensions	CWY dimensions	Strip dimensions	RESA dimensions	Location/ description of arresting system	OFZ	Remarks
8	9	10	11	12	13	14
60M X 30M	60M	Nil	Nil	Nil	Nil	Nil
80M X 30M	80M	Nil	Nil	Nil	Nil	Nil

RPUV AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
06	1755M	1815M	1815M	1755M	Nil
24	1755M	1835M	1835M	1755M	Nil

RPUV AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT type, LEN, INTST	THR LGT colour, WBAR	VASIS, (MEHT), PAPI	TDZ, LGT LEN
1	2	3	4	5
06	Nil	Nil	PAPI Left 3.1° (15.72M)	Nil
24	Nil	Nil	PAPI Left 3.2° (13.62M)	Nil
RWY Centre Line LGT Length, spacing, colour, INTST	RWY edge LGT LEN, spacing, colour, INTST	RWY End LGT colour, WBAR	SWY LGT LEN, colour	Remarks
6	7	8	9	10
Nil	Nil	Nil	Nil	Path WID: 0.35°. VIS RG: 5NM. VER Obstruction CLNC: 1.0°
Nil	Nil	White Red	210M	Path WID: 0.35°. VIS RG: 1.5NM. VER Obstruction CLNC: <1.0°

RPUV AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and hours of operation	Nil.
2	LDI location and LGT Anemometer location and LGT	Nil.
3	TWY edge and centre line lighting	Nil.
4	Secondary power supply/switch-over time	Secondary power supply to all lighting at AD. Switch-over time of 15 SEC.
5	Remarks	Nil.

RPUV AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	VIRAC AERODROME ADVISORY ZONE (AAZ): A circle radius 5 NM centered on 133437N 1241218E (ARP).
2	Vertical limits	AAZ: SFC up to but excluding 2000 FT.
3	Airspace classification	G.
4	ATS unit call sign Language(s)	Virac Radio. English.
5	Transition altitude	Nil.
6	Hours of applicability	Nil.
7	Remarks	Nil.

RPUV AD 2.18 ATS COMMUNICATION FACILITIES

Service Designation	Call Sign	Frequency	SATVOICE number	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
FSS	Virac Radio	128.5 MHZ 5447.5 KHZ 3834 KHZ	Nil	Nil	2200 - 0600	A/G FREQ. P/P PRI FREQ (Manila Network). P/P SRY FREQ. For extension of SER, one (1) day prior notice is required.

RPUV AD 2.20 LOCAL AERODROME REGULATIONS

1. Airport Regulations

- 1.1 Number of aircraft in the traffic pattern limited to two (2) at any given time.