

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.6, AD-2.10, AD-2.11, AD-2.14, AD-2.15, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPVG AD 2.1 AERODROME LOCATION INDICATOR AND NAME**RPVG - GUIUAN COMMUNITY AIRPORT****RPVG AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	110211.7142N 1254434.0766E.
2	Direction and distance from (city)	0.8KM NE.
3	Elevation/Reference temperature	2.13M (7.01FT).
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	1.1°W (2014) / 3.0' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Guiuan Airport Canthay, Guiuan 6809 Eastern Samar
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPVG AD 2.3 OPERATIONAL HOURS

1	AD Operator	0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	Nil.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	Nil.
6	MET Briefing Office	Nil.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	Nil.
11	De-icing	Nil.
12	Remarks	Airport Operations: 0000-0900.

RPVG AD 2.5 PASSENGER FACILITIES

1	Hotels	Town proper (Guiuan).
2	Restaurants	Town proper.
3	Transportation	Vehicle for hire (bus, jeepney).
4	Medical facilities	Town proper.
5	Bank and Post Office	Town proper.
6	Tourist Office	Town proper.
7	Remarks	Nil.

RPVG AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Types of clearing equipment	Grass cutter.
2	Clearance priorities	Movement areas.
3	Remarks	Nil.

RPVG AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: ASPH. Strength: PCN 287 F/B/X/U.
2	Taxiway width, surface and strength	Width: Nil. Surface: Nil. Strength: PCN 28.7M AMSL.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPVG AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Nil.
2	RWY and TWY markings and LGT	RWY and TWY Markers.
3	Stop bars	Nil.
4	Remarks	For repainting.

RPVG AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
07	066.0° GEO 067.1° MAG	2134M X 50M	PCN 28.7 F/B/X/U ASPH	Nil	Nil
25	246.0° GEO 247.1° MAG	2134M X 50M	PCN 28.7 F/B/X/U ASPH	Nil	Nil
Slope of RWY-SWY	SWY dimensions	CWY dimensions	Strip dimensions	OFZ	Remarks
7	8	9	10	11	12
0.43% uphill to the NE.	152M X 50M 152M X 50M	152M 152M	Nil Nil	Nil Nil	Nil Nil

RPVG AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
07	2134M	2286M	2286M	2134M	Nil
25	2134M	2286M	2286M	2134M	Nil