

rGEDI Reference Manual

October 10, 2026

Type Package

Title NASA's Global Ecosystem Dynamics Investigation (GEDI) Data Visualization and Processing

Version 0.6.0

Description Tools for finding, downloading, reading, visualizing, sampling, modeling, and processing NASA Global Ecosystem Dynamics Investigation (GEDI) Level 1B, Level 2A, Level 2B, Level 3, Level 4A, and Level 4B data. Supports local files, NASA Earthdata Cloud access, and optional Google Earth Engine workflows for ancillary-data extraction and wall-to-wall mapping.

License GPL-3

Encoding UTF-8

Depends methods

Imports bit64,
curl,
data.table,
fs,
getPass,
ggplot2,
hdf5r,
jsonlite,
lazyeval,
RColorBrewer,
R6,
sf,
stats,
terra

Suggests gifski,
httr2,
lattice,
leaflet,
leafsync,
lidR,
maps,
plot3D,
png,
rasterVis,
randomForest,
reticulate,
stringr,

testthat (>= 3.0.0),
viridis

Roxygen list(markdown = TRUE)

BugReports <https://github.com/carlos-alberto-silva/rGEDI/issues>

URL <https://github.com/carlos-alberto-silva/rGEDI>

Config/testthat/edition 3

Config/roxygen2/version 8.1.0

Contents

rGEDI-package	4
addEEImage	5
aggregateLevel3	5
aggregateLevel4B	6
aspect	6
build_ee_forest	7
clip	7
clipLevel1B	9
clipLevel1BGeo	10
clipLevel1BGeoGeometry	12
clipLevel1BGeometry	13
clipLevel2A	14
clipLevel2AGeometry	16
clipLevel2AM	17
clipLevel2AMGeometry	18
clipLevel2B	19
clipLevel2BGeometry	21
clipLevel2BPAIProfile	22
clipLevel2BPAIProfileGeometry	23
clipLevel2BPAVDProfile	24
clipLevel2BPAVDProfileGeometry	26
clipLevel2BVPM	27
clipLevel2BVPMGeometry	28
clipLevel3	30
clipLevel4A	30
clipLevel4AGeometry	31
clipLevel4B	32
close,gedi.level1b-method	32
close,gedi.cloud_h5	33
earthdata_login	33
earthdata_s3_credentials	34
ee_build_AlphaEarth_embedding_terrain_stack	34
ee_build_hls_slc_terrain_stack	35
ee_check_task_status	35
ee_image_to_drive	36
ee_initialize	37
ee_rect_to_sf	37
extractEE	38
extractLevel3	38

extractLevel4B	39
ext_to_ee	39
fit_metrics	40
fit_model	40
gedi.fullwaveform-class	41
gedi.level1b-class	41
gedi.level2a-class	42
gedi.level2b-class	42
gedi.level4a-class	42
gediDownload	43
gediEE	44
gedifinder	45
gediWFMetrics	46
gediWFSimulator	47
geomSampling	49
getGEDITrack	49
getLevel1BGeo	50
getLevel1BWF	54
getLevel2AM	55
getLevel2BPAIProfile	56
getLevel2BPAVDProfile	57
getLevel2BVPM	58
getLevel4A	60
getTileUrl	61
get_catalog_id	61
glcmTexture	62
gridSampling	62
gridStatsLevel2AM	63
gridStatsLevel2BVPM	64
gridStatsLevel4A	66
map_create	66
map_download	67
map_view	67
mosaicLevel3	68
mosaicLevel4B	68
openGEDI	69
plot,gedi.fullwaveform,missing-method	69
plot_gedi_var_selection	70
plotLevel3	71
plotLevel4A	71
plotLevel4B	72
plotPAIProfile	72
plotPAVDProfile	73
plotWFMetrics	75
plot_gedi_orbit_animation	76
polyStatsLevel2AM	77
polyStatsLevel2BVPM	79
polyStatsLevel3	80
polyStatsLevel4A	80
polyStatsLevel4B	81
predictGEDI	82
predictGEDIH5	82

projectLevel3	83
projectLevel4B	83
randomSampling	84
rasterizeGEDI	84
rasterizeLevel4A	85
rasterSampling	85
readGEDICloud	86
readLevel1B	86
readLevel2A	87
readLevel2B	88
readLevel3	88
readLevel4A	89
readLevel4B	89
resampleLevel3	90
resampleLevel4B	90
rGEDI_configure	91
sampleGEDI	91
search_datasets	92
slope	92
spacedSampling	93
stratifiedSampling	93
to_vect	94
varSel	94
vect_as_ee	95
Index	96

rGEDI-package

rGEDI: An R Package for NASA's Global Ecosystem Dynamics Investigation (GEDI) Data Visualizing and Processing.

Description

The rGEDI package provides functions for i) downloading, ii) visualizing, iii) clipping, iv) gridding, iv) simulating and v) exporting GEDI data.

Note

See more details about GEDI data in <https://gedi.umd.edu/dataproducts/products/>.

Author(s)

Carlos A. Silva, Caio Hamamura, Ruben Valbuena, Steve Hancock, Adrian Cardil, Eben N. Broadbent, Danilo R. A. de Almeida, Celso H. L. Silva Junior and Carine Klauberg

See Also

For comprehensive examples refer to <https://github.com/carlos-alberto-silva/rGEDI/blob/master/README.md>

addEEImage	<i>Add an Earth Engine image to a Leaflet map</i>
------------	---

Description

Add an Earth Engine image to a Leaflet map

Usage

```
addEEImage(
  map,
  image,
  bands = NULL,
  min = 0,
  max = 1,
  palette = NULL,
  group = NULL,
  ...
)
```

Arguments

map	A Leaflet widget.
image	Earth Engine image.
bands	One or three bands.
min, max	Visualization limits.
palette	Optional palette.
group	Layer group.
...	Passed to <code>leaflet::addTiles()</code> .

Value

A Leaflet widget.

aggregateLevel3	<i>Aggregate a GEDI Level 3 raster</i>
-----------------	--

Description

Aggregate a GEDI Level 3 raster

Usage

```
aggregateLevel3(x, fact, fun = mean, ...)
```

Arguments

x	A raster path or <code>SpatRaster</code> .
fact	Aggregation factor.
fun	Aggregation function.
...	Passed to <code>terra::aggregate()</code> .

Value

A `terra::SpatRaster`.

aggregateLevel4B	<i>Aggregate a GEDI Level 4B raster</i>
------------------	---

Description

Aggregate a GEDI Level 4B raster

Usage

```
aggregateLevel4B(x, fact, fun = mean, ...)
```

Arguments

x	A raster path or <code>SpatRaster</code> .
fact	Aggregation factor.
fun	Aggregation function.
...	Passed to <code>terra::aggregate()</code> .

Value

A `terra::SpatRaster`.

aspect	<i>Earth Engine terrain aspect</i>
--------	------------------------------------

Description

Earth Engine terrain aspect

Usage

```
aspect(x)
```

Arguments

x	Earth Engine elevation image.
---	-------------------------------

Value

An Earth Engine image.

build_ee_forest	<i>Train a regression forest in Earth Engine</i>
-----------------	--

Description

Train a regression forest in Earth Engine

Usage

```
build_ee_forest(training, response, predictors, trees = 500L, seed = 1L)
```

Arguments

training	Earth Engine FeatureCollection containing predictors and the response.
response	Response property name, such as "agbd" or "rh98".
predictors	Predictor property names.
trees	Number of trees.
seed	Random seed.

Value

A trained Earth Engine classifier configured for regression.

clip	<i>Clip GEDI data with a common interface</i>
------	---

Description

clip() provides one clipping interface for open GEDI HDF5 products, extracted footprint tables, and GEDI Level 3 or Level 4B rasters. It follows the workflow used by ICESat2VegR while retaining rGEDI's coordinate order.

Usage

```
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level1b,numeric'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level1b,SpatExtent'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level1b,ANY'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level2a,numeric'
clip(x, clip_obj, ...)
```

```
## S4 method for signature 'gedi.level2a,SpatExtent'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level2a,ANY'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level2b,numeric'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level2b,SpatExtent'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level2b,ANY'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level4a,numeric'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level4a,SpatExtent'
clip(x, clip_obj, ...)

## S4 method for signature 'gedi.level4a,ANY'
clip(x, clip_obj, ...)

## S4 method for signature 'data.frame,numeric'
clip(x, clip_obj, ...)

## S4 method for signature 'data.frame,SpatExtent'
clip(x, clip_obj, ...)

## S4 method for signature 'data.frame,ANY'
clip(x, clip_obj, ...)

## S4 method for signature 'SpatRaster,ANY'
clip(x, clip_obj, ...)
```

Arguments

<code>x</code>	A <code>gedi.level1b</code> , <code>gedi.level2a</code> , <code>gedi.level2b</code> , or <code>gedi.level4a</code> object; a footprint <code>data.frame</code> / <code>data.table</code> ; or a terra::SpatRaster .
<code>clip_obj</code>	A numeric extent in the order <code>c(xmin, xmax, ymin, ymax)</code> , a terra::SpatExtent , or an <code>sf</code> , <code>sfc</code> , or terra::SpatVector polygon object.
<code>...</code>	Arguments used by the selected method. HDF5 methods accept output and geometry methods also accept <code>split_by</code> . Table geometry methods accept <code>split_by</code> . Raster methods accept filename and overwrite.

Details

Extracted tables are recognized from standard GEDI coordinates: `longitude_bin0/latitude_bin0`, `lon_lowestmode/lat_lowestmode`, or `longitude/latitude`. When the corresponding `longitude_lastbin` and `latitude_lastbin` fields exist, both waveform endpoints must fall inside a numeric extent.

This function masks `graphics::clip()`. Use `graphics::clip()` explicitly when changing a base graphics clipping region.

Value

The return type follows `x`. Open Level 1B, 2A, 2B, and 4A HDF5 inputs return clipped open GEDI objects; footprint tables return a `data.table::data.table`; and Level 3/4B rasters return a `terra::SpatRaster`. Geometry clipping with `split_by` returns a named list of HDF5-backed GEDI objects, one per polygon ID.

Examples

```
footprints <- data.frame(
  shot_number = 1:3,
  lon_lowestmode = c(-44.13, -44.12, -44.10),
  lat_lowestmode = c(-13.74, -13.73, -13.70)
)
clip(footprints, c(-44.14, -44.11, -13.75, -13.72))
```

clipLevel1B

Clip GEDI Level1B data by Coordinates

Description

This function clips GEDI Level1B data (geolocated waveforms) within a given bounding coordinates

Usage

```
clipLevel1B(level1b, xmin, xmax, ymin, ymax, output)
```

Arguments

level1b	A <code>gedi.level1b</code> object (output of <code>readLevel1B()</code> function). An S4 object of class <code>gedi.level1b</code> .
xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.
output	Optional character path where to save the new hdf5file. The default stores a temporary file only.

Value

Returns a list of S4 objects of class `gedi.level1b` containing clipped GEDI Level1B data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```
## Not run:
# Specifying the path to GEDI level1B data (zip file)
outdir <- tempdir()

level1B_fp_zip <- system.file("extdata",
  "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath = level1Bpath)

# Bounding rectangle coordinates
xmin <- -44.13
xmax <- -44.12
ymin <- -13.74
ymax <- -13.73

# Specifying output file and path
output <- file.path(outdir, "GEDI01_B_2019108080338_001964_T05337_02_003_01_clip")

# Clipping GEDI Level1B data by extent boundary box
level1b_clip <- clipLevel1B(level1b, xmin, xmax, ymin, ymax, output)

close(level1b)
close(level1b_clip)

## End(Not run)
```

clipLevel1BGeo

Clip GEDI Full Waveform Geolocations by Coordinates

Description

This function clips GEDI level1B extracted geolocation ([getLevel1BGeo\(\)](#)) data within given bounding coordinates

Usage

```
clipLevel1BGeo(level1BGeo, xmin, xmax, ymin, ymax)
```

Arguments

level1BGeo A [data.table::data.table](#) resulting from [getLevel1BGeo\(\)](#).

xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.

Value

Returns an S4 object of class `data.table::data.table`.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```
# Specifying the path to GEDI level1B data (zip file)
outdir <- tempdir()
level1B_fp_zip <- system.file("extdata",
  "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath = level1Bpath)

# Extracting GEDI Full Waveform Geolocations
level1bGeo <- getLevel1BGeo(level1b)

# Bounding rectangle coordinates
xmin <- -44.15036
xmax <- -44.10066
ymin <- -13.75831
ymax <- -13.71244

# Clipping GEDI Full Waveform Geolocations by boundary box extent
level1bGeo_clip <- clipLevel1BGeo(level1bGeo, xmin, xmax, ymin, ymax)

if (interactive() && requireNamespace("leaflet", quietly = TRUE)) {
  library(leaflet)
  leaflet() %>%
    addCircleMarkers(level1bGeo_clip$longitude_bin0,
      level1bGeo_clip$latitude_bin0,
      radius = 1,
      opacity = 1,
      color = "red"
    ) %>%
    addScaleBar(options = list(imperial = FALSE)) %>%
    addProviderTiles(providers$Esri.WorldImagery)
```

```

}

close(level1b)

```

```
clipLevel1BGeoGeometry
```

Clip GEDI Full Waveform Geolocations by geometry

Description

This function clips level1BGeo extracted geolocation (level1BGeo) data within a given geometry

Usage

```
clipLevel1BGeoGeometry(level1BGeo, polygon, split_by = "id")
```

Arguments

level1BGeo	A <code>data.table::data.table</code> resulting from <code>getLevel1BGeo()</code> function.
polygon	Polygon. An object of class <code>sf::sf</code> , which can be loaded as an ESRI shapefile using <code>sf::st_read</code> function in the <code>sf</code> package.
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the polygon id from table of attribute defined by the user.

Value

Returns an S4 object of class `data.table::data.table` containing the clipped GEDI level1B extracted geolocations.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```

# Specifying the path to GEDI level1B data (zip file)
outdir <- tempdir()
level1B_fp_zip <- system.file("extdata",
  "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath = level1Bpath)

# Extracting GEDI Full Waveform Geolocations
level1BGeo <- getLevel1BGeo(level1b, beams = "BEAM0001")

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

```

```

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Clipping GEDI Full Waveform Geolocations by Geometry
level1BGeo_clip <- clipLevel1BGeoGeometry(level1BGeo, polygon, split_by = "id")

if (interactive() && requireNamespace("leaflet", quietly = TRUE)) {
  library(leaflet)
  leaflet() %>%
    addCircleMarkers(level1BGeo_clip$longitude_bin0,
                      level1BGeo_clip$latitude_bin0,
                      radius = 1,
                      opacity = 1,
                      color = "red"
    ) %>%
    addScaleBar(options = list(imperial = FALSE)) %>%
    addPolygons(
      data = polygon, weight = 1, col = "white",
      opacity = 1, fillOpacity = 0
    ) %>%
    addProviderTiles(providers$Esri.WorldImagery)
}

close(level1b)

```

clipLevel1BGeometry	<i>Clip GEDI Level1B data by geometry</i>
---------------------	---

Description

This function clips GEDI Level1B (geolocated waveforms) data within a given bounding geometry

Usage

```
clipLevel1BGeometry(level1b, polygon, output = "", split_by = NULL)
```

Arguments

level1b	A gedi.level1b object (output of readLevel1B() function). An S4 object of class "gedi.level1b".
polygon	Polygon or Multipolygon. An object opened with <code>sf::st_read</code> ,
output	Optional character path where to save the new hdf5r::H5File . The default stores a temporary file only.
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the attribute specified by <code>split_by</code> from the attribute table.

Value

Returns a list of S4 object of class [gedi.level1b](#) containing clipped GEDI Level1B data.

Examples

```
## Not run:
outdir <- tempdir()

# Specifying the path to GEDI level1B data (zip file)
level1B_fp_zip <- system.file("extdata",
  "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath = level1Bpath)

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Specifying output file and path
output <- file.path(outdir, "GEDI01_B_2019108080338_001964_T05337_02_003_01_clip")

# clipping GEDI Level1B data by extent boundary box
level1b_clip <- clipLevel1BGeometry(level1b,
  polygon = polygon,
  output = output,
  split_by = "id"
)

close(level1b)
lapply(level1b_clip, close)

## End(Not run)
```

clipLevel2A

*Clip GEDI Level2A data by Coordinates***Description**

This function clips GEDI Level2A data within a given bounding coordinates

Usage

```
clipLevel2A(level2a, xmin, xmax, ymin, ymax, output)
```

Arguments

level2a A GEDI Level2A object (output of [readLevel2A\(\)](#) function). An S4 object of class "gedi.level2a".

xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.
output	Optional character path where to save the new hdf5file. The default stores a temporary file only.

Value

Returns a list of S4 objects of class "gedi.level2a" containing clipped GEDI Level2A data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
## Not run:
outdir <- tempdir()

# Specifying the path to GEDI level2A data (zip file)
level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath = level2Apath)

# Bounding rectangle coordinates
xmin <- -44.13
xmax <- -44.12
ymin <- -13.74
ymax <- -13.73

print(level2a)

# Specifying output file and path
output <- file.path(outdir, "GEDI02_A_2019108080338_001964_T05337_02_001_01_clip.h5")

# Clipping GEDI Level2A data by boundary box extent
level2a_clip <- clipLevel2A(level2a, xmin, xmax, ymin, ymax, output)

close(level2a)
close(level2a_clip)

## End(Not run)
```

clipLevel2AGeometry *Clip GEDI Level2A data by geometry*

Description

This function clips GEDI Level2A data within a given geometry

Usage

```
clipLevel2AGeometry(level2a, polygon, output = "", split_by = NULL)
```

Arguments

level2a	A GEDI Level2A object (output of <code>readLevel2A()</code> function). An S4 object of class "gedi.level2a".
polygon	Polygon. An object of class <code>sf::sf</code> , which can be loaded as an ESRI shapefile using <code>sf::st_read()</code> function in the <i>sf</i> package.
output	optional character path where to save the new h5file. Default "" (temporary file).
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the attribute specified by <code>split_by</code> from the attribute table.

Value

Returns a list of S4 object of class "gedi.level2a" containing clipped GEDI Level2A data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
## Not run:
outdir <- tempdir()

# Specifying the path to GEDI level2A data (zip file)
level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath = level2Apath)

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)
```

```
# Specifying output file and path
output <- file.path(outdir, "GEDI02_A_2019108080338_001964_T05337_02_001_01_clip")

# Clipping GEDI Level2A data by geometry
level2a_clip <- clipLevel2AGeometry(level2a,
  polygon = polygon,
  output = output,
  split_by = "id"
)
close(level2a)
lapply(level2a_clip, close)

## End(Not run)
```

clipLevel2AM

*Clip GEDI Elevation and Height Metrics by Coordinates***Description**

This function clips GEDI Level2A extracted Elevation and Height Metrics (Level2AM) within a given bounding coordinates

Usage

```
clipLevel2AM(level2AM, xmin, xmax, ymin, ymax)
```

Arguments

level2AM	A GEDI Level2A object (output of readLevel2A() function). An S4 object of class "gedi.level2a".
xmin	Numeric. West longitude (x) coordinate of bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of bounding rectangle, in decimal degrees.

Value

Returns an S4 object of class [data.table::data.table](#) containing the clipped elevation and relative heights metrics.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
# Specifying the path to GEDI level2A data (zip file)
outdir <- tempdir()
level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath = level2Apath)

# Extracting GEDI Elevation and Height Metrics
level2AM <- getLevel2AM(level2a, beams = "BEAM0001")

# Bounding rectangle coordinates
xmin <- -44.15036
xmax <- -44.10066
ymin <- -13.75831
ymax <- -13.71244

# Clipping GEDI data by boundary box extent
level2AM_clip <- clipLevel2AM(level2AM, xmin, xmax, ymin, ymax)

close(level2a)
```

clipLevel2AMGeometry *Clip GEDI Elevation and Height Metrics by Coordinates*

Description

This function clips GEDI Level2A extracted Elevation and Height Metrics (Level2AM) within a given bounding coordinates

Usage

```
clipLevel2AMGeometry(level2AM, polygon, split_by = "id")
```

Arguments

level2AM	A GEDI Level2A object (output of readLevel2A() function). An S4 object of class "data.table".
polygon	Polygon. An object of class <code>sf::sf</code> , which can be loaded as an ESRI shapefile using <code>sf::st_read</code> function in the <code>sf</code> package.
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the polygon id from table of attribute defined by the user

Value

Returns an S4 object of class `data.table::data.table` containing the clipped elevation and relative heights metrics.

Examples

```

# Specifying the path to GEDI level2A data (zip file)
outdir <- tempdir()
level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath = level2Apath)

# Extracting GEDI Elevation and Height Metrics
level2AM <- getLevel2AM(level2a, beams = "BEAM0001")

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Clipping GEDI data by Geometry
level2AM_clip <- clipLevel2AMGeometry(level2AM, polygon, split_by = "id")

hasLeaflet <- require(leaflet)

if (hasLeaflet) {
  leaflet() %>%
    addCircleMarkers(level2AM_clip$lat_lowestmode,
      level2AM_clip$lon_lowestmode,
      radius = 1,
      opacity = 1,
      color = "red"
    ) %>%
    addScaleBar(options = list(imperial = FALSE)) %>%
    addPolygons(
      data = polygon, weight = 1, col = "white",
      opacity = 1, fillOpacity = 0
    ) %>%
    addProviderTiles(providers$Esri.WorldImagery)
}

close(level2a)

```

clipLevel2B

*Clip GEDI Level2B data by Coordinates***Description**

This function extracts GEDI Level1B data a within given bounding coordinates

Usage

```
clipLevel2B(level2b, xmin, xmax, ymin, ymax, output = "")
```

Arguments

level2b	A GEDI Level2B object (output of <code>readLevel2B()</code> function). An S4 object of class "gedi.level2b".
xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.
output	Optional character path where to save the new hdf5 file. The default stores a temporary file only.

Value

Returns a list of S4 object of class "gedi.level2b" containing clipped GEDI Level2B data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```
## Not run:
outdir <- tempdir()

# Specifying the path to GEDI level2B data (zip file)
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Bounding rectangle coordinates
xmin <- -44.13
xmax <- -44.12
ymin <- -13.74
ymax <- -13.73

# Specifying output file and path
output <- file.path(outdir, "GEDI02_B_2019108080338_001964_T05337_02_001_01_clip")

# Clipping GEDI data by extent boundary box
```

```

level2b_clip <- clipLevel2B(level2b, xmin, xmax, ymin, ymax)

close(level2b)
close(level2b_clip)

## End(Not run)

```

clipLevel2BGeometry *Clip GEDI Level2B data by geometry*

Description

This function extracts GEDI Level1B data within a given geometry

Usage

```
clipLevel2BGeometry(level2b, polygon, output = "", split_by = NULL)
```

Arguments

level2b	A GEDI Level2B object (output of readLevel2B() function). An S4 object of class "gedi.level2b".
polygon	Polygon. An object of class sf::sf , which can be loaded as an ESRI shapefile using sf::st_read function in the <i>sf</i> package.
output	optional character path where to save the new h5file. Default "" (temporary file).
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the attribute specified by <code>split_by</code> from the attribute table.

Value

Returns a list of S4 objects of class "gedi.level2b" containing clipped GEDI Level2B data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```

## Not run:
outdir <- tempdir()

# Specifying the path to GEDI level2B data (zip file)
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

```

```

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Specifying output file and path
output <- file.path(outdir, "GEDI02_B_2019108080338_001964_T05337_02_001_01_clip")

# Clipping GEDI data by extent boundary box
level2b_clip <- clipLevel2BGeometry(level2b,
  polygon = polygon,
  output = output,
  split_by = "id"
)

close(level2b)
lapply(level2b_clip, close)

## End(Not run)

```

clipLevel2BPAIProfile *Clip GEDI Plant Area Index profile by Coordinates*

Description

This function clips GEDI level2B derived Plant Area Index profile a within given bounding coordinates

Usage

```
clipLevel2BPAIProfile(level2BPAIProfile, xmin, xmax, ymin, ymax)
```

Arguments

level2BPAIProfile	A GEDI Level2B object (output of getLevel2BPAIProfile() function). An S4 object of class "gedi.level2b".
xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.

Value

Returns an S4 object of class [data.table::data.table](#) containing the Plant Area Index profile data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Extracting GEDI Plant Area Index profile
level2BPAIProfile <- getLevel2BPAIProfile(level2b)

# Bounding rectangle coordinates
xmin <- -44.15036
xmax <- -44.10066
ymin <- -13.75831
ymax <- -13.71244

# Clipping GEDI Plant Area Index profile by extent boundary box
level2b_clip <- clipLevel2BPAIProfile(level2BPAIProfile, xmin, xmax, ymin, ymax)

close(level2b)
```

clipLevel2BPAIProfileGeometry

Clip GEDI Plant Area Index profile by geometry

Description

This function clips GEDI level2B derived Plant Area Index profile within a given geometry

Usage

```
clipLevel2BPAIProfileGeometry(level2BPAIProfile, polygon, split_by = NULL)
```

Arguments

level2BPAIProfile	A GEDI Level2B object (output of <code>getLevel2BPAIProfile()</code> function). An S4 object of class "data.table".
polygon	Polygon. An object of class <code>sf::sf</code> , which can be loaded as an ESRI shapefile using <code>sf::st_read</code> function in the <code>sf</code> package.
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the attribute specified by <code>split_by</code> from the attribute table.

Value

Returns an S4 object of class `data.table::data.table` containing the Plant Area Index profile data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Extracting GEDI Plant Area Index profile
level2BPAIProfile <- getLevel2BPAIProfile(level2b)

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Clipping GEDI Plant Area Index profile by geometry
level2b_clip_geometry <- clipLevel2BPAIProfileGeometry(
  level2BPAIProfile,
  polygon,
  split_by = "id"
)

close(level2b)
```

clipLevel2BPAVDProfile

Clip GEDI Plant Area Volume Density profile by Coordinates

Description

This function clips GEDI level2B derived Plant Area Volume Density profile within a given bounding coordinates

Usage

```
clipLevel2BPAVDProfile(level2BPAVDProfile, xmin, xmax, ymin, ymax)
```

Arguments

level2BPAVDProfile	A GEDI Level2B object (output of <code>getLevel2BPAVDProfile()</code> function). An S4 object of class "data.table".
xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.

Value

Returns an S4 object of class `data.table::data.table` containing the Plant Area Volume Density profile data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# specify the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Extracting GEDI Plant Area Volume Density profile
level2BPAVDProfile <- getLevel2BPAVDProfile(level2b)

# Bounding rectangle coordinates
xmin <- -44.15036
xmax <- -44.10066
ymin <- -13.75831
ymax <- -13.71244

# Clipping GEDI Plant Area Volume Density profile by boundary box extent
level2BPAVDProfile_clip <- clipLevel2BPAVDProfile(level2BPAVDProfile, xmin, xmax, ymin, ymax)

close(level2b)
```

clipLevel2BPAVDProfileGeometry

Clip GEDI Plant Area Volume Density profile by geometry

Description

This function clips GEDI level2B derived Plant Area Index profile within a given geometry

Usage

```
clipLevel2BPAVDProfileGeometry(level2BPAVDProfile, polygon, split_by = NULL)
```

Arguments

level2BPAVDProfile	A GEDI Level2B object (output of <code>getLevel2BPAIProfile()</code> function). An S4 object of class "gedi.level2b".
polygon	Polygon. An object of class <code>sf::sf</code> , which can be loaded as an ESRI shapefile using <code>sf::st_read</code> function in the <code>sf</code> package.
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the attribute specified by <code>split_by</code> from the attribute table.

Value

Returns an S4 object of class `data.table::data.table` containing the Plant Area Volume Density profile data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Extracting GEDI Plant Area Volume Density profile
level2BPAVDProfile <- getLevel2BPAVDProfile(level2b)

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
```

```

library(sf)
polygon <- sf::st_read(polygon_filepath)

# Clipping GEDI Plant Area Volume Density profile by geometry
level2BPAVDProfile_clip <- clipLevel2BPAVDProfileGeometry(
  level2BPAVDProfile,
  polygon,
  split_by = "id"
)

close(level2b)

```

clipLevel2BVPM

Clip GEDI Canopy Cover and Vertical Profile Metrics by Coordinates

Description

This function clips GEDI level2B derived Canopy Cover and Vertical Profile metrics a within given bounding coordinates

Usage

```
clipLevel2BVPM(level2BVPM, xmin, xmax, ymin, ymax)
```

Arguments

level2BVPM	A GEDI Level2B object (output of readLevel1B() function). An S4 object of class "data.table".
xmin	Numeric. West longitude (x) coordinate of the bounding rectangle, in decimal degrees.
xmax	Numeric. East longitude (x) coordinate of the bounding rectangle, in decimal degrees.
ymin	Numeric. South latitude (y) coordinate of the bounding rectangle, in decimal degrees.
ymax	Numeric. North latitude (y) coordinate of the bounding rectangle, in decimal degrees.

Value

Returns an S4 object of class [data.table::data.table](#) containing the Canopy Cover and Vertical Profile metrics.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```

# Specifying the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Extracting canopy cover and vertical profile metrics
beam <- grep("^BEAM", (level2b@h5)$ls(recursive = FALSE)$name,
  value = TRUE)[1]
level2BVPM <- getLevel2BVPM(level2b, beams = beam)

# Bounding rectangle coordinates
xmin <- -44.15036
xmax <- -44.10066
ymin <- -13.75831
ymax <- -13.71244

# Clipping level2BVPM by extent boundary box
level2b_clip <- clipLevel2BVPM(level2BVPM, xmin, xmax, ymin, ymax)

hasLeaflet <- require(leaflet)

if (hasLeaflet) {
  leaflet() %>%
    addCircleMarkers(level2b_clip$longitude_bin0,
      level2b_clip$latitude_bin0,
      radius = 1,
      opacity = 1,
      color = "red"
    ) %>%
    addScaleBar(options = list(imperial = FALSE)) %>%
    addProviderTiles(providers$Esri.WorldImagery)
}

close(level2b)

```

clipLevel2BVPMGeometry

Clip GEDI Canopy Cover and Vertical Profile Metrics by geometry

Description

This function clips GEDI level2B derived Canopy Cover and Vertical Profile metrics within a given geometry

Usage

```
clipLevel2BVPMGeometry(level2BVPM, polygon, split_by = NULL)
```

Arguments

level2BVPM	A GEDI Level2B object (output of readLevel1B() function). An S4 object of class "gedi.level2b".
polygon	Polygon. An object of class sf::sf , which can be loaded as an ESRI shapefile using sf::st_read function in the <i>sf</i> package.
split_by	Polygon id. If defined, GEDI data will be clipped by each polygon using the attribute specified by split_by from the attribute table.

Value

Returns an S4 object of class [data.table::data.table](#) containing the Canopy Cover and Vertical Profile metrics.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Extracting canopy cover and vertical profile metrics
beam <- grep("^BEAM", (level2b@h5)$ls(recursive = FALSE)$name,
  value = TRUE)[1]
level2BVPM <- getLevel2BVPM(level2b, beams = beam)

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Clipping level2BVPM by geometry
level2b_clip_geometry <- clipLevel2BVPMGeometry(level2BVPM, polygon, split_by = "id")

hasLeaflet <- require(leaflet)

if (hasLeaflet) {
  leaflet() %>%
```

```
addCircleMarkers(level2b_clip_geometry$longitude_bin0,
  level2b_clip_geometry$latitude_bin0,
  radius = 1,
  opacity = 1,
  color = "red"
) %>%
addScaleBar(options = list(imperial = FALSE)) %>%
addPolygons(
  data = polygon, weight = 1, col = "white",
  opacity = 1, fillOpacity = 0
) %>%
addProviderTiles(providers$Esri.WorldImagery)
}

close(level2b)
```

clipLevel3	<i>Clip a GEDI Level 3 raster</i>
------------	-----------------------------------

Description

Clip a GEDI Level 3 raster

Usage

```
clipLevel3(x, y, filename = "", overwrite = FALSE)
```

Arguments

- x A raster path or SpatRaster.
- y An extent c(xmin, xmax, ymin, ymax) or polygon object.
- filename Optional output filename.
- overwrite Logical.

Value

A [terra::SpatRaster](#).

clipLevel4A	<i>Clip GEDI Level 4A data by an extent</i>
-------------	---

Description

Clip GEDI Level 4A data by an extent

Usage

```
clipLevel4A(level4A, xmin, xmax, ymin, ymax, output = "")
```

Arguments

level4A	A <code>gedi.level4a</code> object returned by <code>readLevel4A()</code> or a table returned by <code>getLevel4A()</code> .
xmin, xmax, ymin, ymax	Bounding coordinates in longitude/latitude.
output	Optional output HDF5 path when level4A is a <code>gedi.level4a</code> object. A temporary file is used by default.

Value

A clipped `gedi.level4a` object for HDF5 input, or a `data.table::data.table` for table input.

clipLevel4AGeometry	<i>Clip GEDI Level 4A data by polygons</i>
---------------------	--

Description

Clip GEDI Level 4A data by polygons

Usage

```
clipLevel4AGeometry(level4A, polygon, split_by = NULL, output = "")
```

Arguments

level4A	A <code>gedi.level4a</code> object returned by <code>readLevel4A()</code> or a table returned by <code>getLevel4A()</code> .
polygon	An <code>sf</code> , <code>sfc</code> , or <code>SpatVector</code> polygon object.
split_by	Optional polygon attribute. For HDF5 input, one clipped file is returned per unique value. For table input, the value is copied to <code>poly_id</code> .
output	Optional output HDF5 path when level4A is a <code>gedi.level4a</code> object. A temporary file is used by default.

Value

A clipped `gedi.level4a` object (or a named list when `split_by` is used) for HDF5 input, or a `data.table::data.table` for table input.

clipLevel4B	<i>Clip a GEDI Level 4B raster</i>
-------------	------------------------------------

Description

Clip a GEDI Level 4B raster

Usage

```
clipLevel4B(x, y, filename = "", overwrite = FALSE)
```

Arguments

x	A raster path or SpatRaster.
y	An extent c(xmin, xmax, ymin, ymax) or polygon object.
filename	Optional output filename.
overwrite	Logical.

Value

A `terra::SpatRaster`.

close.gedi.level1b-method	<i>Safely closes the <code>gedi.level1b</code></i>
---------------------------	--

Description

Closing files will avoid locking HDF5 GEDI files.
 Closing files will avoid locking HDF5 GEDI files.
 Closing files will avoid locking HDF5 GEDI files.

Usage

```
## S4 method for signature 'gedi.level1b'
close(con, ...)

## S4 method for signature 'gedi.level2a'
close(con, ...)

## S4 method for signature 'gedi.level2b'
close(con, ...)

## S4 method for signature 'gedi.level4a'
close(con, ...)
```

Arguments

con	An object of class <code>gedi.level2b</code>
...	Inherited from base

close.gedi.cloud_h5	<i>Close a cloud HDF5 connection</i>
---------------------	--------------------------------------

Description

Close a cloud HDF5 connection

Usage

```
## S3 method for class 'gedi.cloud_h5'
close(con, ...)
```

Arguments

con	A gedi.cloud_h5 object returned by readGEDICloud() .
...	Reserved for compatibility with close() .

Value

Invisibly returns NULL.

earthdata_login	<i>Authenticate with NASA Earthdata</i>
-----------------	---

Description

Uses an existing bearer token, environment credentials, or .netrc file.

Usage

```
earthdata_login(persist = TRUE, netrc = Sys.getenv("NETRC", unset = ""))
```

Arguments

persist	Logical; allow Earthaccess to persist an interactive login.
netrc	Path to an Earthdata .netrc file.

Value

Invisibly returns TRUE after successful authentication.

earthdata_s3_credentials

Configure temporary NASA Earthdata S3 credentials

Description

Requests short-lived AWS credentials from Earthaccess and exports them for GDAL/terra. Direct S3 access to GEDI is available from AWS us-west-2.

Usage

```
earthdata_s3_credentials(daac = "ORNL")
```

Arguments

daac NASA DAAC short name. GEDI products are hosted by ORNL DAAC.

Value

Invisibly returns the credential list.

ee_build_AlphaEarth_embedding_terrain_stack

Build an AlphaEarth and terrain predictor stack

Description

Build an AlphaEarth and terrain predictor stack

Usage

```
ee_build_AlphaEarth_embedding_terrain_stack(
  geom,
  start_year,
  end_year,
  add_lonlat = TRUE
)
```

Arguments

geom Area of interest.
start_year, end_year Inclusive year range.
add_lonlat Add coordinate bands.

Value

An Earth Engine image.

ee_build_hls_slc_terrain_stack

Build an HLS and terrain predictor stack in Earth Engine

Description

Build an HLS and terrain predictor stack in Earth Engine

Usage

```
ee_build_hls_slc_terrain_stack(
  x,
  start_date,
  end_date,
  cloud_max = 20,
  buffer_m = 30
)
```

Arguments

x	Area of interest.
start_date, end_date	Date range.
cloud_max	Maximum HLS cloud cover.
buffer_m	AOI buffer in meters.

Value

An Earth Engine image.

ee_check_task_status *Check an Earth Engine task*

Description

Check an Earth Engine task

Usage

```
ee_check_task_status(task, quiet = TRUE)
```

Arguments

task	Earth Engine batch task.
quiet	Logical.

Value

Task status list.

ee_image_to_drive	<i>Export an Earth Engine image to Google Drive</i>
-------------------	---

Description

Creates a Google Earth Engine batch export task for a GeoTIFF in Google Drive. This is useful for images that exceed the direct download limit.

Usage

```
ee_image_to_drive(
  image,
  description = "rGEDI_export",
  folder = "EE_Exports",
  file_name_prefix = description,
  region,
  scale = 30,
  crs = "EPSG:4326",
  max_pixels = 1e+13,
  start = TRUE,
  ...
)
```

Arguments

image	Earth Engine image.
description	Task description shown in Earth Engine.
folder	Google Drive folder.
file_name_prefix	Output file prefix.
region	Area of interest accepted by ext_to_ee() .
scale	Pixel size in meters.
crs	Output CRS.
max_pixels	Maximum number of pixels allowed by Earth Engine.
start	Start the task immediately.
...	Additional arguments passed to Earth Engine's toDrive method.

Value

An Earth Engine batch task. Use [ee_check_task_status\(\)](#) to monitor it.

ee_initialize	<i>Initialize Google Earth Engine</i>
---------------	---------------------------------------

Description

Initialize Google Earth Engine

Usage

```
ee_initialize(  
    project = Sys.getenv("EE_PROJECT", unset = ""),  
    authenticate = TRUE,  
    quiet = FALSE  
)
```

Arguments

project	Google Cloud project ID.
authenticate	Authenticate when initialization fails.
quiet	Logical.

Value

Invisibly returns the Python Earth Engine module.

ee_rect_to_sf	<i>Convert an Earth Engine rectangle to sf</i>
---------------	--

Description

Convert an Earth Engine rectangle to sf

Usage

```
ee_rect_to_sf(aoi)
```

Arguments

aoi	Earth Engine geometry.
-----	------------------------

Value

An sf polygon.

extractEE	<i>Extract Earth Engine image values at GEDI footprints</i>
-----------	---

Description

Extract Earth Engine image values at GEDI footprints

Usage

```
extractEE(stack, geom, scale = 30, chunk_size = 1000L)
```

```
extractGEDIancillary(stack, geom, scale = 30, chunk_size = 1000L)
```

Arguments

stack	Earth Engine image or list of images.
geom	GEDI table, sf, or SpatVector points.
scale	Sampling scale in meters.
chunk_size	Number of points per request.

Value

A [data.table::data.table](#).

extractLevel3	<i>Extract GEDI Level 3 raster values</i>
---------------	---

Description

Extract GEDI Level 3 raster values

Usage

```
extractLevel3(x, y, ...)
```

Arguments

x	A raster path or SpatRaster.
y	Points or polygons accepted by terra::vect() .
...	Passed to terra::extract() .

Value

A data frame.

extractLevel4B	<i>Extract GEDI Level 4B raster values</i>
----------------	--

Description

Extract GEDI Level 4B raster values

Usage

```
extractLevel4B(x, y, ...)
```

Arguments

x	A raster path or SpatRaster.
y	Points or polygons accepted by <code>terra::vect()</code> .
...	Passed to <code>terra::extract()</code> .

Value

A data frame.

ext_to_ee	<i>Convert an extent to an Earth Engine geometry</i>
-----------	--

Description

Convert an extent to an Earth Engine geometry

Usage

```
ext_to_ee(x)
```

Arguments

x	A SpatExtent, raster/vector object, or numeric extent in c(xmin, xmax, ymin, ymax) order.
---	---

Value

An Earth Engine geometry.

fit_metrics	<i>Model fit metrics</i>
-------------	--------------------------

Description

Model fit metrics

Usage

```
fit_metrics(observed, predicted, plotstat = FALSE, unit = "", ...)
```

Arguments

observed, predicted	Numeric vectors.
plotstat	Draw an observed-versus-predicted plot.
unit	Unit label.
...	Passed to <code>graphics::plot()</code> .

Value

A data frame of accuracy statistics.

fit_model	<i>Fit a GEDI statistical or random-forest model</i>
-----------	--

Description

Fit a GEDI statistical or random-forest model

Usage

```
fit_model(
  x,
  y,
  method = c("randomForest", "lm"),
  test = c("none", "split", "kfold", "loocv", "bootstrap"),
  k = 5L,
  test_size = 0.3,
  iterations = 100L,
  seed = NULL,
  ...
)
```

Arguments

x	Predictor data frame.
y	Response vector or response column name in x.
method	"randomForest" or "lm".
test	Validation method: "none", "split", "kfold", "loocv", or "bootstrap".
k	Number of folds.
test_size	Fraction held out for split validation.
iterations	Bootstrap iterations.
seed	Optional random seed.
...	Model arguments.

Value

An object of class `gedi_model`.

`gedi.fullwaveform-class`

Class for GEDI level1B Full Waveform

Description

Class for GEDI level1B Full Waveform

Slots

dt Object of class `data.table` from *data.table* package containing the extracted GEDI full-waveform elevation and amplitude.

`gedi.level1b-class`

Class for GEDI level1B

Description

Class for GEDI level1B

Slots

h5 A local [H5File](#) or a cloud-backed GEDI HDF5 connection containing geolocated waveforms.

See Also

[H5File](#) in the `hdf5r` package and <https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

gedi.level2a-class	<i>Class for GEDI level2A</i>
--------------------	-------------------------------

Description

Class for GEDI level2A

Slots

h5 A local H5File or cloud-backed GEDI HDF5 connection containing ground elevation, canopy top height, and relative heights (RH).

See Also

[H5File](#) in the hdf5r package and <https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

gedi.level2b-class	<i>Class for GEDI level2B</i>
--------------------	-------------------------------

Description

Class for GEDI level2B

Slots

h5 A local [H5File](#) or cloud-backed GEDI HDF5 connection containing canopy cover, PAI, PAVD, and FHD.

See Also

[H5File](#) in the hdf5r package and <https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

gedi.level4a-class	<i>Class for GEDI Level 4A footprint biomass data</i>
--------------------	---

Description

Class for GEDI Level 4A footprint biomass data

Slots

h5 An open local or cloud-backed HDF5 connection containing a GEDI04_A granule.

See Also

https://daac.ornl.gov/GEDI/guides/GEDI_L4A_AGB_Density_V3.html

gediDownload	<i>Download GEDI data</i>
--------------	---------------------------

Description

Download GEDI data from LP DAAC Data Pool. Users will need to enter their Earth Explore login Information for downloading the data.

Usage

```
gediDownload(
  filepath,
  outdir = NULL,
  overwrite = FALSE,
  buffer_size = 512,
  timeout = 10,
  netrc = Sys.getenv("NETRC", unset = ""))
)

downloadGEDI(
  filepath,
  outdir = NULL,
  overwrite = FALSE,
  buffer_size = 512,
  timeout = 10,
  netrc = Sys.getenv("NETRC", unset = ""))
)
```

Arguments

filepath	Vector object; path to the GEDI data
outdir	Vector object, output directory for downloading GEDI data, default <code>tempdir()</code>
overwrite	logical; overwrite file if they already exists in destination, default FALSE
buffer_size	integer; the size of download chunk in KB to hold in memory before writing to file, default 512.
timeout	integer; connection timeout in seconds.
netrc	Optional path to an existing NASA Earthdata .netrc file. By default, uses the NETRC environment variable before prompting.

Value

The normalized paths of the downloaded files, invisibly. On failure the function stops with an error.

References

Credits to Cole Krehbiel. Code adapted from https://git.earthdata.nasa.gov/projects/LPDUR/repos/daac_data_download_r/browse/DAACDataDownload.R

Examples

```
## Not run:
# Set path to GEDI data
# herein we will only download xml metedata
filepath=c(paste0(
  "https://e4ftl01.cr.usgs.gov/GEDI/GEDI02_B.001",
  "/2019.04.18/GEDI02_B_2019108032534_001961_T03911_02_001_01.h5.xml"
),
  paste0("https://e4ftl01.cr.usgs.gov/GEDI/GEDI02_B.001",
    "/2019.04.18/GEDI02_B_2019108045815_001962_T01066_02_001_01.h5.xml"
  )
)

# Set dir to download files to
outdir=tempdir()

# Create .netrc file
netrc = file.path(outdir, ".netrc")
netrc_conn <- file(netrc)

writeLines(c("machine urs.earthdata.nasa.gov",
  sprintf("login %s", Sys.getenv("NASA_USER")),
  sprintf("password %s", Sys.getenv("NASA_PASSWORD"))
), netrc_conn)

close(netrc_conn)

#' Downloading GEDI data
gediDownload(filepath,outdir)

## End(Not run)
```

gediEE

Open a GEDI product in Google Earth Engine

Description

Open a GEDI product in Google Earth Engine

Usage

```
gediEE(
  product = names(.gedi_ee_catalog),
  start_date = NULL,
  end_date = NULL,
  aoi = NULL,
  quality = TRUE,
  max_granules = 200L
)
```

Arguments

product	GEDI Earth Engine product name.
start_date, end_date	Optional dates for image collections.
aoi	Optional spatial filter.
quality	Apply available quality masks.
max_granules	Maximum number of vector granules to merge. Vector GEDI products are stored as folders of per-granule feature collections in Earth Engine, so use dates and/or an AOI to keep the request focused.

Value

An Earth Engine image, image collection, or feature collection.

gedifinder	<i>Find GEDI granules through NASA CMR</i>
------------	--

Description

Find GEDI granules through NASA CMR

Usage

```
gedifinder(
  product,
  ul_lat = NULL,
  ul_lon = NULL,
  lr_lat = NULL,
  lr_lon = NULL,
  version = NULL,
  daterange = NULL,
  access = c("https", "s3", "opendap", "all"),
  cloud_hosted = TRUE,
  return = c("url", "table"),
  page_size = 2000L,
  cloud_computing = FALSE,
  persist = TRUE,
  orbit = NULL
)
```

Arguments

product	One of GEDI01_B, GEDI02_A, GEDI02_B, GEDI03, GEDI04_A, or GEDI04_B.
ul_lat, ul_lon, lr_lat, lr_lon	Bounding coordinates in decimal degrees.
version	Product version. NULL selects the current supported version.
daterange	Optional two-element date or date-time vector.
access	Requested link type: "https", "s3", "opendap", or "all".

cloud_hosted	Logical retained for backward compatibility. The current GEDI collection identifiers resolve to their Earthdata Cloud holdings.
return	Return a URL vector or a metadata table.
page_size	CMR page size.
cloud_computing	Logical. When TRUE, authenticate with Earthdata and return HTTPS granules marked for direct cloud streaming by <code>openGEDI()</code> or the product-specific <code>readLevel*()</code> function.
persist	Logical; allow Earthaccess to persist an interactive login when <code>cloud_computing = TRUE</code> .
orbit	Optional GEDI orbit number, such as 1964 or "001964". When supplied, the spatial bounding box is omitted so CMR returns every production granule belonging to that orbit.

Value

A character vector or `data.table::data.table`.

See Also

<https://cmr.earthdata.nasa.gov/search/site/docs/search/api.html>

gediWFMetrics

Compute metrics from GEDI or simulated full waveforms

Description

Compute metrics from GEDI or simulated full waveforms

Usage

```
gediWFMetrics(
  input,
  outRoot = NULL,
  rhRes = 5,
  ground = TRUE,
  rhoG = 0.4,
  rhoC = 0.57,
  ground_method = c("auto", "truth", "lowest_peak", "quantile"),
  ...
)
```

Arguments

input	A <code>gedi.level1b</code> object or list of such objects.
outRoot	Optional output filename root.
rhRes	Relative-height percentile spacing.
ground	Logical; include the estimated ground elevation.
rhoG, rhoC	Ground and canopy reflectance.

ground_method Ground estimator. "auto" uses the classified ground waveform when present and otherwise the lowest smoothed waveform peak.

... Compatibility arguments from the original native implementation.

Value

A `data.table::data.table` with waveform metrics.

gediWFSimulator	<i>Simulate GEDI-like full waveforms from airborne laser scanning data</i>
-----------------	--

Description

This portable implementation follows the core gediRat algorithm: Gaussian footprint weighting, optional return-density normalization, vertical binning, pulse convolution, separation of LAS class 2 ground returns, and unit-integral normalization. Vectorized binning replaces the original point loop while avoiding its native GSL/GDAL build stack.

Usage

```
gediWFSimulator(
  input,
  output = tempfile(fileext = ".h5"),
  ground = TRUE,
  ascii = FALSE,
  waveID = NULL,
  coords = NULL,
  listCoord = NULL,
  gridBound = NULL,
  gridStep = 30,
  pSigma = -1,
  pFWHM = 15,
  fSigma = 5.5,
  res = 0.15,
  decimate = 1,
  maxBins = 1024L,
  countOnly = FALSE,
  method = c("count", "intensity", "fraction"),
  normalize = TRUE,
  density_res = 1,
  intensity_threshold = 6e-04,
  noise = 0,
  keepOld = FALSE,
  seed = NULL,
  ...
)
```

Arguments

input	LAS/LAZ paths, a <code>lidR::LAS</code> , <code>SpatVector</code> , or table with X/Y/Z.
output	Output HDF5 path.
ground	Retained for compatibility; ground returns remain in the waveform.
ascii	Return/write a simple ASCII waveform instead of HDF5.
waveID	Optional waveform identifiers.
coords	A coordinate pair or matrix of footprint centers.
listCoord	Text file containing footprint centers.
gridBound	Optional <code>c(xmin, xmax, ymin, ymax)</code> simulation grid.
gridStep	Grid spacing in input coordinate units.
pSigma	Pulse sigma in meters. A negative value derives it from <code>pFWHM</code> .
pFWHM	Pulse full width at half maximum in nanoseconds.
fSigma	Footprint sigma in input coordinate units.
res	Vertical waveform resolution.
decimate	Probability of retaining an ALS return.
maxBins	Maximum number of waveform bins.
countOnly	Use count-based returns rather than ALS intensity. Gaussian footprint weights are still applied.
method	Waveform contribution: "count", "intensity", or "fraction". <code>countOnly = TRUE</code> selects "count" for compatibility.
normalize	Correct for local ALS sampling density, as in the original simulator's default behavior.
density_res	Cell size used for sampling-density normalization.
intensity_threshold	Smallest retained Gaussian footprint weight.
noise	Relative Gaussian noise standard deviation. For example, <code>noise = 0.03</code> adds noise with a standard deviation equal to three percent of the waveform maximum. Zero leaves the waveform unchanged.
keepOld	Do not overwrite an existing output file.
seed	Optional random seed.
...	Compatibility arguments accepted from the original simulator.

Value

A `gedi.level1b` object, or a waveform table when `ascii=TRUE`.

References

Hancock et al. (2019) [doi:10.1029/2018EA000506](https://doi.org/10.1029/2018EA000506)

geomSampling	<i>GEDI polygon-stratified sampling specification</i>
--------------	---

Description

GEDI polygon-stratified sampling specification

Usage

```
geomSampling(size, geom, split_id = NULL, lon = NULL, lat = NULL)
```

Arguments

size	Number or fraction per polygon.
geom	Polygon object.
split_id	Optional polygon ID column.
lon, lat	Optional coordinate column names.

getGEDITrack	<i>Extract a GEDI reference ground track</i>
--------------	--

Description

Standardizes footprint coordinates, acquisition order, and beam identifiers from any open point-level GEDI product or an extracted footprint table. The result can be plotted directly or passed to [plot_gedi_orbit_animation\(\)](#).

Usage

```
getGEDITrack(
  x,
  lon = NULL,
  lat = NULL,
  time = NULL,
  track = NULL,
  beams = NULL,
  every = 1L,
  segment_gaps = TRUE
)
```

Arguments

x	A data frame, data.table, sf or SpatVector containing GEDI footprint coordinates; an open gedi.level1b, gedi.level2a, gedi.level2b, or gedi.level4a object; or a list of these objects from consecutive production granules in one orbit.
lon, lat	Names of longitude and latitude columns. When NULL, common GEDI coordinate names are detected automatically.

time	Optional name of a column used to order footprints within each track. GEDI <code>delta_time</code> and <code>shot_number</code> columns are detected by default.
track	Optional name of a beam or track column. Separate tracks are colored independently.
beams	Optional beam names to read from an open GEDI object.
every	Keep every <code>nth</code> footprint after ordering. This is useful when plotting a complete orbit.
segment_gaps	Append segment numbers to track names when unusually large spatial gaps occur. Animation keeps this disabled so consecutive GEDI production granules remain one beam for a complete orbit.

Value

A `data.table::data.table` with longitude, latitude, sequence, track, and available time and shot identifiers.

Examples

```
shots <- data.frame(
  lon_lowestmode = seq(-44.2, -44.1, length.out = 10),
  lat_lowestmode = seq(-13.8, -13.7, length.out = 10),
  delta_time = seq_len(10), beam = "BEAM0000"
)
getGEDITrack(shots, every = 2)
```

getLevel1BGeo

Get GEDI Full Waveform Geolocations (GEDI Level1B)

Description

This function extracts Pulse Full Waveform Geolocations from GEDI `gedi.level1b` data

Usage

```
getLevel1BGeo(
  level1b,
  select = c("elevation_bin0", "elevation_lastbin"),
  beams = NULL
)
```

Arguments

level1b	A <code>gedi.level1b</code> object (output of <code>getLevel1BGeo()</code> function).
select	A character vector specifying the fields to extract from GEDI Level1B data. If NULL, by default it will extract <code>latitude_bin0</code> , <code>latitude_lastbin</code> , <code>longitude_bin0</code> , <code>longitude_lastbin</code> , and <code>shot_number</code> . See details for more options.
beams	Optional beam names. NULL reads every beam.

Details

Additional fields to be extracted from GEDI level 1B:

- *all_samples_sum* Sum of all values within the 10 km range window.
- *beam* Beam number Number.
- *channel* Channel number.
- *master_frac* Master time, fractional part.
- *master_int* Master time, integer part.
- *noise_mean_corrected* Noise mean.
- *noise_stddev_corrected* Corrected noise standard deviation.
- *nsemean_even* Noise mean of the beam's detector channel from even sub-converter.
- *nsemean_odd* Noise mean of the beam's odd sub-converter.
- *rx_energy* Integrated energy in receive (RX) waveform after subtracting the noise mean.
- *rx_offset* Time interval from first stored sample to first downloaded RX sample.
- *rx_open* Time interval from time 0 to first stored RX sample.
- *rx_sample_count* The number of sample intervals (elements) in each RX waveform.
- *rx_sample_start_index* The index in the rxwaveform dataset of the first element of each RX waveform starting at 1.
- *selection_stretchers_x* Commanded number of samples added to the algorithm section on the left.
- *selection_stretchers_y* Commanded number of samples added to the algorithm section on the right.
- *shot_number* Unique shot identifier.
- *stale_return_flag* Indicates that a "stale" cue point from the coarse search algorithm is being used.
- *th_left_used* Count values for the left threshold used in fine search where two consecutive points at or above this value indicate pulse detection.
- *tx_egamplitude* Amplitude of the extended Gaussian fit to the transmit (TX) waveform.
- *tx_egamplitude_error* Error on tx_egamplitude.
- *tx_egbias* Bias of the extended Gaussian fit to the TX waveform.
- *tx_egbias_error* Error on tx_egbias.
- *tx_egflag* Extended Gaussian fit status flag.
- *tx_eggamma* Gamma value of the extended Gaussian fit to the TX waveform.
- *tx_eggamma_error* Error on tx_eggamma.
- *tx_egsigma* Sigma of the extended Gaussian fit to the TX waveform.
- *tx_egsigma_error* Error on tx_egsigma.
- *tx_gloc* Location (mean) of the Gaussian fit to the TX waveform.
- *tx_gloc_error* Error on tx_gloc.
- *tx_pulseflag* Set to 1 if a pulse is detected in the TX waveform.
- *tx_sample_count* The number of sample intervals (elements) in each transmit waveform.
- *tx_sample_start_index* The index in the rxwaveform dataset of the first element of each RX waveform starting at 1.

- *altitude_instrument* Height of the instrument diffractive optical element (DOE) above the WGS84 ellipsoid.
- *altitude_instrument_error* Error on altitude_instrument.
- *bounce_time_offset_bin0* The difference between the TX time and the time at the start of the RX window.
- *bounce_time_offset_bin0_error* Error on bounce_time_offset_bin0.
- *bounce_time_offset_lastbin* The difference between the TX time and the time at the end of the RX window.
- *bounce_time_offset_lastbin_error* Error on bounce_time_offset_lastbin.
- *degrade* Greater than zero if the shot occurs during a degrade period, zero otherwise.
- *delta_time* Transmit time of the shot, measured in seconds since 2018-01-01.
- *digital_elevation_model* Digital elevation model height above the WGS84 ellipsoid.
- *elevation_bin0* Height of the start of the RX window, relative to the WGS-84 ellipsoid.
- *elevation_bin0_error* Error on elevation_bin0.
- *elevation_lastbin* Height of the end of the RX window, relative to the WGS-84 ellipsoid.
- *elevation_lastbin_error* Error on elevation_lastbin.
- *latitude_bin0* Latitude of the start of the RX window.
- *latitude_bin0_error* Error on latitude_bin0.
- *latitude_lastbin* Latitude of the end of the RX window.
- *latitude_lastbin_error* Error on latitude_lastbin.
- *latitude_instrument* Latitude of the instrument diffractive optical element (DOE) at laser transmit time.
- *latitude_instrument_error* Error on latitude_instrument.
- *local_beam_azimuth* Azimuth of the unit pointing vector for the laser in the local East, North, Up (ENU) frame.
- *local_beam_azimuth_error* Error on local_beam_azimuth.
- *local_beam_elevation* Elevation of the unit pointing vector for the laser in the local ENU frame.
- *local_beam_elevation_error* Error on local_beam_elevation.
- *longitude_bin0* Longitude of the start of the RX window.
- *longitude_bin0_error* Error on longitude_bin0.
- *longitude_lastbin* Longitude of the end of the RX window.
- *longitude_lastbin_error* Error on longitude_lastbin.
- *longitude_instrument* Longitude of the instrument diffractive optical element (DOE) at laser transmit time.
- *longitude_instrument_error* Error on longitude_instrument.
- *mean_sea_surface* Mean sea surface height above the WGS84 ellipsoid, includes the geoid .
- *neutat_delay_derivative_bin0* Change in neutral atmospheric delay per height change for the start of the RX window.
- *neutat_delay_derivative_lastbin* Change in neutral atmospheric delay per height change for the end of the RX window.
- *neutat_delay_total_bin0* Total neutral atmosphere delay correction (wet+dry) from the TX pulse to the start of the RX window.

- *neutat_delay_total_lastbin* Total neutral atmosphere delay correction (wet+dry) from the TX pulse to the end of the RX window.
- *range_bias_correction* The range bias applied to the range measurement.
- *shot_number* Unique shot identifier Number.
- *solar_azimuth* The azimuth of the sun position vector.
- *solar_elevation* The elevation of the sun position vector.
- *surface_type* Flags describing which surface types.
- *dynamic_atmosphere_correction* Dynamic Atmospheric Correction (DAC) includes inverted barometer (IB) effect.
- *geoid* Geoid height above WGS-84 reference ellipsoid.
- *tide_earth* Solid Earth tides.
- *tide_load* Load Tide - Local displacement due to Ocean Loading.
- *tide_ocean* Ocean Tides including diurnal and semi-diurnal, and longerperiod tides.
- *tide_ocean_pole* Oceanic surface rotational deformation due to polar motion.
- *tide_pole* Solid Earth Pole Tide. Rotational deformation due to polar motion.

Value

Returns an S4 object of class `data.table::data.table` containing the GEDI Full Waveform Geolocations

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```
# specify the path to GEDI level1B data (zip file)
outdir = tempdir()
level1B_fp_zip <- system.file("extdata",
                             "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath=level1Bpath)

# Extracting GEDI level1B geolocations
level1bGeo <- getLevel1BGeo(level1b, select=c("elevation_bin0", "elevation_lastbin"))
head(level1bGeo)

close(level1b)
```

getLevel1BWF

Get GEDI Pulse Full Waveform (GEDI Level1B)

Description

This function extracts the full waveform of a given pulse from GEDI Level1B data.

Usage

```
getLevel1BWF(level1b, shot_number)
```

Arguments

level1b	A GEDI Level1B object (output of <code>readLevel1B()</code> function). A S4 object of class "gedi.level1b".
shot_number	Shot number. A scalar representing the shot number of a giving pulse.

Details

Shot numbers can be extracted using `readLevel1B` function.

Value

Returns an S4 object of class "gedi.fullwaveform".

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi01-b-002>

Examples

```
# Specifying the path to GEDI level1B data (zip file)
outdir = tempdir()
level1B_fp_zip <- system.file("extdata",
                             "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath=level1Bpath)

# Extracting GEDI full waveform for a giving shotnumber
wf <- getLevel1BWF(level1b, shot_number="19640521100108408")

# Plotting GEDI Full waveform
oldpar <- par()
par(mfrow = c(1,2), cex.axis = 1.5)
plot(wf, relative=FALSE, polygon=TRUE, type="l", lwd=2, col="forestgreen",
     xlab="Waveform Amplitude", ylab="Elevation (m)")

plot(wf, relative=TRUE, polygon=TRUE, type="l", lwd=2, col="forestgreen",
```

```
xlab="Waveform Amplitude (%)", ylab="Elevation (m)")

par(oldpar)
close(level1b)
```

getLevel2AM

Get GEDI Elevation and Height Metrics (GEDI Level2A)

Description

This function extracts Elevation and Relative Height (RH) metrics from GEDI Level2A data.

Usage

```
getLevel2AM(level2a, beams = NULL, include_rh = TRUE)
```

Arguments

<code>level2a</code>	A GEDI Level2A object (output of readLevel2A() function). An S4 object of class "gedi.level2a".
<code>beams</code>	Optional beam names. NULL reads every beam.
<code>include_rh</code>	Logical. Include the 101 relative-height columns. Set to FALSE for a faster metadata-only cloud read.

Details

Characteristics. Flag indicating likely invalid waveform (1=valid, 0=invalid).

- *beam* Beam identifier
- *shot_number* Shot number
- *degrade_flag* Flag indicating degraded state of pointing and/or positioning information
- *quality_flag* Flag simplifying selection of most useful data
- *delta_time* Transmit time of the shot since Jan 1 00:00 2018
- *sensitivity* Maximum canopy cover that can be penetrated
- *solar_elevation* Solar elevation
- *lat_lowestmode* Latitude of center of lowest mode
- *lon_lowestmode* Longitude of center of lowest mode
- *elev_highestreturn* Elevation of highest detected return relative to reference ellipsoid Meters
- *elev_lowestmode* Elevation of center of lowest mode relative to reference ellipsoid
- *rh* Relative height metrics at 1% interval

Value

Returns an S4 object of class [data.table::data.table](#) containing the elevation and relative heights metrics.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
# Specifying the path to GEDI level2A data (zip file)
outdir = tempdir()
level2A_fp_zip <- system.file("extdata",
                             "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath=level2Apath)

# Extracting GEDI Elevation and Height Metrics
level2AM <- getLevel2AM(level2a)
head(level2AM)

close(level2a)
```

getLevel2BPAIProfile *Get GEDI Plant Area Index (PAI) Profile (GEDI Level2B)*

Description

This function extracts the Plant Area Index (PAI) Profile from GEDI Level2B data.

Usage

```
getLevel2BPAIProfile(level2b, beams = NULL)
```

Arguments

level2b	A GEDI Level2B object (output of readLevel2B() function). An S4 object of class "gedi.level2b".
beams	Optional beam names. NULL reads every beam.

Details

Characteristics. Flag indicating likely invalid waveform (1=valid, 0=invalid).

- *beam* Beam identifier
- *shot_number* Shot number
- *algorithmrun_flag* The L2B algorithm is run if this flag is set to 1 indicating data have sufficient waveform fidelity for L2B to run
- *l2b_quality_flag* L2B quality flag
- *delta_time* Transmit time of the shot since Jan 1 00:00 2018
- *lat_lowestmode* Latitude of center of lowest mode
- *lon_lowestmode* Longitude of center of lowest mode
- *elev_highestreturn* Elevation of highest detected return relative to reference ellipsoid
- *elev_lowestmode* Elevation of center of lowest mode relative to reference ellipsoid
- *height_lastbin* Height of the last bin of the pgap_theta_z, relative to the ground
- *pai_z* Plant Area Index profile

Value

Returns an S4 object of class `data.table::data.table` containing the elevation and relative heights.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir = tempdir()
level2B_fp_zip <- system.file("extdata",
                              "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
                              package="rGEDI")

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath=level2Bpath)

# Extracting GEDI Plant Area Index (PAI) Profile (GEDI Level2B)
level2BPAIProfile <- getLevel2BPAIProfile(level2b)
head(level2BPAIProfile)

close(level2b)
```

<code>getLevel2BPAVDProfile</code>	<i>Get GEDI Plant Area Volume Density (PAVD) Index Profile (GEDI Level2B)</i>
------------------------------------	---

Description

This function extracts the Plant Area Volume Density (PAVD) Profile from GEDI Level2B data.

Usage

```
getLevel2BPAVDProfile(level2b, beams = NULL)
```

Arguments

<code>level2b</code>	A GEDI Level2B object (output of <code>readLevel2B()</code> function). An S4 object of class "gedi.level2b".
<code>beams</code>	Optional beam names. NULL reads every beam.

Details

Characteristics. Flag indicating likely invalid waveform (1=valid, 0=invalid).

- *beam* Beam identifier
- *shot_number* Shot number

- *algorithmrun_flag* The L2B algorithm is run if this flag is set to 1 indicating data have sufficient waveform fidelity for L2B to run
- *l2b_quality_flag* L2B quality flag
- *delta_time* Transmit time of the shot since Jan 1 00:00 2018
- *lat_lowestmode* Latitude of center of lowest mode
- *lon_lowestmode* Longitude of center of lowest mode
- *elev_highestreturn* Elevation of highest detected return relative to reference ellipsoid
- *elev_lowestmode* Elevation of center of lowest mode relative to reference ellipsoid
- *height_lastbin* Height of the last bin of the pgap_theta_z, relative to the ground
- *pavd_z* Plant Area Volume Density profile

Value

Returns an S4 object of class `data.table::data.table` containing the Plant Area Volume Density Index.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir = tempdir()
level2B_fp_zip <- system.file("extdata",
                             "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath=level2Bpath)

# Extracting GEDI Plant Area Volume Density (PAVD) Index
level2BPAVDProfile <- getLevel2BPAVDProfile(level2b)
head(level2BPAVDProfile)

close(level2b)
```

getLevel2BVPM

Get GEDI Canopy Cover and Vertical Profile Metrics (GEDI Level2B)

Description

This function extracts information from GEDI Level2B data: Total Plant Area Index, Foliage Height Diversity, Foliage Clumping Index, Total Gap Probability (theta), and Total canopy cover.

Usage

```
getLevel2BVPM(
  level2b,
  cols = c("beam", "shot_number", "algorithmrun_flag", "l2b_quality_flag", "delta_time",
    "sensitivity", "solar_elevation", "latitude_lastbin", "latitude_bin0",
    "longitude_bin0", "longitude_lastbin", "elev_highestreturn", "elev_lowestmode",
    "rh100", "pai", "fhd_normal", "omega", "pgap_theta", "cover"),
  beams = NULL
)
```

Arguments

<code>level2b</code>	A GEDI Level2B object (output of <code>readLevel2B()</code> function). An S4 object of class "gedi.level2b".
<code>cols</code>	A character vector containing the list of columns to be extracted. See the default columns in the description.
<code>beams</code>	Optional beam names. NULL reads every beam.

Details

These are the biophysical variables and additional information extracted by default:

- *beam* Beam identifier
- *shot_number* Shot number
- *algorithmrun_flag* The L2B algorithm is run if this flag is set to 1 indicating data have sufficient waveform fidelity for L2B to run
- *l2b_quality_flag* L2B quality flag
- *delta_time* Transmit time of the shot since Jan 1 00:00 2018
- *sensitivity* Maximum canopy cover that can be penetrated
- *solar_elevation* Solar elevation
- *latitude_lastbin* Latitude of last bin of the *pgap_theta_z*, interpolated from L1B waveform coordinate
- *latitude_bin0* Latitude of first bin of the *pgap_theta_z*, interpolated from L1B waveform coordinate
- *elev_highestreturn* Elevation of highest detected return relative to reference ellipsoid
- *elev_lowestmode* Elevation of center of lowest mode relative to reference ellipsoid
- *rh100* RH100 slice
- *pai* Total Plant Area Index
- *fhd_normal* Foliage Height Diversity
- *omega* Foliage Clumping Index
- *pgap_theta* Total Gap Probability (theta)
- *cover* Total canopy cover

Every other columns in the GEDI2B product are also available, you can specify each column by using the `cols` parameter.

Value

Returns an S4 object of class `data.table::data.table` containing the Vegetation Profile Biophysical Variables.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir = tempdir()
level2B_fp_zip <- system.file("extdata",
                             "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath=level2Bpath)

# Extracting GEDI Vegetation Profile Biophysical Variables
level2BVPM <- getLevel2BVPM(level2b, cols=c("beam", "shot_number"))
head(level2BVPM)

close(level2b)
```

getLevel4A	<i>Extract GEDI Level 4A footprint metrics</i>
------------	--

Description

Extract GEDI Level 4A footprint metrics

Usage

```
getLevel4A(
  level4a,
  cols = .level4a_default_columns,
  quality = FALSE,
  beams = NULL
)
```

Arguments

level4a	A <code>gedi.level4a</code> object returned by <code>readLevel4A()</code> .
cols	Character vector of fields to return. NULL returns all datasets shared by the selected beams.
quality	Logical. If TRUE, retain observations accepted by the current Release 3 quality fields when present: • <code>l4a_quality_flag_rel3</code>

- degrade_include_flag
 - elev_highestreturn_outlier_flag
- Legacy Release 2 quality fields remain supported.
- beams Optional character vector of GEDI beam names.

Value

A [data.table::data.table](#) with one row per footprint.

getTileUrl	<i>Get an Earth Engine image tile URL</i>
------------	---

Description

Get an Earth Engine image tile URL

Usage

```
getTileUrl(image, vis = list())
```

Arguments

- image Earth Engine image.
- vis Visualization parameter list.

Value

Character tile URL.

get_catalog_id	<i>Return an Earth Engine catalog ID</i>
----------------	--

Description

Return an Earth Engine catalog ID

Usage

```
get_catalog_id(x)
```

Arguments

- x A GEDI product name, catalog search row, or catalog ID.

Value

A character catalog ID.

glcmTexture	<i>Earth Engine gray-level co-occurrence textures</i>
-------------	---

Description

Earth Engine gray-level co-occurrence textures

Usage

```
glcmTexture(x, size = 1L, kernel = NULL, average = TRUE)
```

Arguments

x	Earth Engine integer image.
size	Neighborhood size.
kernel	Optional Earth Engine kernel.
average	Average directional metrics.

Value

An Earth Engine image.

gridSampling	<i>GEDI grid-stratified sampling specification</i>
--------------	--

Description

GEDI grid-stratified sampling specification

Usage

```
gridSampling(size, grid_size, lon = NULL, lat = NULL)
```

Arguments

size	Number or fraction per cell.
grid_size	Grid size in decimal degrees.
lon, lat	Optional coordinate column names.

gridStatsLevel2AM	<i>Compute Grids with Descriptive Statistics of GEDI derived Elevation and Height Metrics (Level2A)</i>
-------------------	---

Description

This function computes a series of user defined descriptive statistics within each grid cell for GEDI derived Elevation and Height Metrics (Level2A)

Usage

```
gridStatsLevel2AM(level2AM, func, res)
```

Arguments

level2AM	A GEDI Level2AM object (output of <code>getLevel2AM()</code> function). An S4 object of class "data.table".
func	The function(s) to be applied to each cell
res	Spatial resolution in decimal degrees for the output stars raster layer

Value

Return a stars raster layer(s) of selected GEDI Elevation and Height Metric(s)

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
## Not run:
# specify the path to GEDI level2A data (zip file)
outdir <- tempdir()
level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath = level2Apath)

# Get GEDI derived Elevation and Height Metrics
level2AM <- getLevel2AM(level2a)
head(level2AM)

#' Define your own function
mySetOfMetrics <- function(x) {
  metrics <- list(
    min = min(x), # Min of z
    max = max(x), # Max of z
```

```

    mean = mean(x), # Mean of z
    sd = sd(x) # Sd of z
  )
  return(metrics)
}

#' Computing a serie of GEDI metrics
ZTstats <- gridStatsLevel2AM(
  level2AM = level2AM,
  func = mySetOfMetrics(elev_highestreturn),
  res = 0.005
)
if (interactive()) plot(ZTstats)

if (interactive()) {
  # Computing the maximum of RH100 only
  maxRH100 <- gridStatsLevel2AM(level2AM, mySetOfMetrics(rh100), res = 0.0005)
  plot(maxRH100)

  # Computing the mean of ZG only
  ZGmean <- gridStatsLevel2AM(level2AM, mean(elev_lowestmode), res = 0.005)
  plot(ZGmean)
}

close(level2a)

## End(Not run)

```

gridStatsLevel2BVPM	<i>Compute Grids with Descriptive Statistics of GEDI derived Canopy Cover and Vertical Profile Metrics (Level2B)</i>
---------------------	--

Description

This function computes a series of user defined descriptive statistics within each grid cell for GEDI derived Canopy Cover and Vertical Profile Metrics (Level2B)

Usage

```
gridStatsLevel2BVPM(level2BVPM, func, res)
```

Arguments

level2BVPM	A GEDI Level2AM object (output of getLevel2BVPM() function). An S4 object of class "data.table".
func	The function(s) to be applied to each cell
res	Spatial resolution in decimal degrees for the output stars raster layer

Value

Returns a stars raster layer(s) of selected GEDI Canopy Cover and Vertical Profile Metric(s)

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
## Not run:
# specify the path to GEDI level2B data (zip file)
outdir <- tempdir()
level2B_fp_zip <- system.file("extdata",
  "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath = level2Bpath)

# Get GEDI derived Canopy Cover and Vertical Profile Metrics
level2BVPM <- getLevel2BVPM(level2b)
head(level2BVPM)

#' Define your own function
mySetOfMetrics <- function(x) {
  metrics <- list(
    min = min(x), # Min of z
    max = max(x), # Max of z
    mean = mean(x), # Mean of z
    sd = sd(x) # Sd of z
  )
  return(metrics)
}

#' Computing a serie of statistics of GEDI derived canopy cover
cover_stats <- gridStatsLevel2BVPM(
  level2BVPM = level2BVPM,
  func = mySetOfMetrics(cover),
  res = 0.005
)
plot(cover_stats)

#' Computing the max of the Total Plant Area Index only
pai_max <- gridStatsLevel2BVPM(level2BVPM = level2BVPM, func = max(pai), res = 0.005)
plot(pai_max)

#' Computing the Foliage Height Diversity Index only
fhd_mean <- gridStatsLevel2BVPM(level2BVPM = level2BVPM, func = mean(fhd_normal), res = 0.005)
plot(fhd_mean)

close(level2b)

## End(Not run)
```

gridStatsLevel4A	<i>Grid GEDI Level 4A footprint metrics</i>
------------------	---

Description

Grid GEDI Level 4A footprint metrics

Usage

```
gridStatsLevel4A(level4A, metric = "agbd", fun = mean, res = 0.01, ...)
```

Arguments

level4A	A table returned by getLevel4A() .
metric	Metric column name.
fun	Aggregation function.
res	Output resolution in decimal degrees.
...	Additional arguments passed to fun.

Value

A [terra::SpatRaster](#).

map_create	<i>Apply an Earth Engine model to a predictor image</i>
------------	---

Description

Apply an Earth Engine model to a predictor image

Usage

```
map_create(model, stack, aoi = NULL, name = "prediction")
```

Arguments

model	A trained Earth Engine classifier or regressor.
stack	Earth Engine predictor image.
aoi	Optional area to clip.
name	Output band name.

Value

An Earth Engine image.

map_download	<i>Download an Earth Engine image</i>
--------------	---------------------------------------

Description

Download an Earth Engine image

Usage

```
map_download(  
  image,  
  filename,  
  region,  
  scale = 30,  
  crs = "EPSG:4326",  
  overwrite = FALSE  
)
```

Arguments

image	Earth Engine image.
filename	Destination GeoTIFF path.
region	Area of interest.
scale	Pixel size in meters.
crs	Output CRS.
overwrite	Logical.

Value

Invisibly returns filename.

map_view	<i>Display Earth Engine layers in Leaflet</i>
----------	---

Description

Display Earth Engine layers in Leaflet

Usage

```
map_view(layers, vis = list(), aoi = NULL)
```

Arguments

layers	Named list of Earth Engine images.
vis	Named list of visualization parameter lists.
aoi	Optional spatial object used to fit map bounds.

Value

A Leaflet widget.

mosaicLevel3	<i>Mosaic GEDI Level 3 rasters</i>
--------------	------------------------------------

Description

Mosaic GEDI Level 3 rasters

Usage

```
mosaicLevel3(x, fun = "mean", filename = "", overwrite = FALSE)
```

Arguments

x	Raster paths, a SpatRaster, or a list of rasters.
fun	Function used for overlapping cells.
filename	Optional output filename.
overwrite	Logical.

Value

A [terra::SpatRaster](#).

mosaicLevel4B	<i>Mosaic GEDI Level 4B rasters</i>
---------------	-------------------------------------

Description

Mosaic GEDI Level 4B rasters

Usage

```
mosaicLevel4B(x, fun = "mean", filename = "", overwrite = FALSE)
```

Arguments

x	Raster paths, a SpatRaster, or a list of rasters.
fun	Function used for overlapping cells.
filename	Optional output filename.
overwrite	Logical.

Value

A [terra::SpatRaster](#).

openGEDI

*Open GEDI data from local storage or Earthdata Cloud***Description**

Raster products are opened with GDAL through `terra::rast()`. HDF5 cloud granules are opened lazily with Python earthaccess and h5py.

Usage

```
openGEDI(x, product = NULL, stream = TRUE, cache_dir = tempdir())
```

Arguments

x	Local path, HTTPS URL, S3 URI, OPeNDAP URL, or an Earthaccess granule.
product	Optional product identifier.
stream	Logical; stream raster data rather than download it.
cache_dir	Download directory for non-streamed data.

Value

A `SpatRaster`, `gedi.cloud_h5`, or local GEDI object.

```
plot,gedi.fullwaveform,missing-method
```

Plot GEDI object*

Description

For `gedi.fullwaveform`: will plot the full waveform

Usage

```
## S4 method for signature 'gedi.fullwaveform,missing'
plot(x, relative = FALSE, polygon = FALSE, ...)
```

Arguments

x	An object of class <code>gedi.fullwaveform</code> (output of <code>getLevel1BWF()</code> function)
relative	if TRUE, the Waveform Amplitude will be showed in percentage (%)
polygon	if TRUE, the polygon will be added to the plot
...	will be passed to the main plot

Value

No return value

Examples

```

# Specifying the path to GEDI level1B data (zip file)
outdir <- tempdir()
level1B_fp_zip <- system.file("extdata",
  "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath = level1Bpath)

# Extracting GEDI Full-Waveform
wf <- getLevel1BWF(level1b, shot_number = "19640521100108408")

# Plotting GEDI Full-waveform
oldpar <- par()
par(mfrow = c(1, 2), cex.axis = 1.5)
plot(wf,
  relative = FALSE, polygon = TRUE, type = "l", lwd = 2, col = "forestgreen",
  xlab = "", ylab = "Elevation (m)")
)

rGEDI::plot(wf,
  relative = TRUE, polygon = TRUE, type = "l", lwd = 2, col = "forestgreen",
  xlab = "Waveform Amplitude (%)", ylab = "Elevation (m)")
)

par(oldpar)
close(level1b)

```

plot.gedi_var_selection

Plot GEDI variable selection results

Description

Plot GEDI variable selection results

Usage

```

## S3 method for class 'gedi_var_selection'
plot(x, which = c("importance", "rfe"), ...)

```

Arguments

x	A gedi_var_selection object.
which	Plot variable importance or RFE error.
...	Additional graphical parameters.

Value

The object, invisibly.

plotLevel3	<i>Plot GEDI Level 3 metrics</i>
------------	----------------------------------

Description

Plot GEDI Level 3 metrics

Usage

```
plotLevel3(x, ...)
```

Arguments

x	A raster path or SpatRaster.
...	Passed to <code>terra::plot()</code> .

Value

Invisibly returns the raster.

plotLevel4A	<i>Plot GEDI Level 4A footprint biomass</i>
-------------	---

Description

Plot GEDI Level 4A footprint biomass

Usage

```
plotLevel4A(level4A, metric = "agbd", ...)
```

Arguments

level4A	A table returned by <code>getLevel4A()</code> .
metric	Metric column to display.
...	Additional arguments passed to <code>graphics::plot()</code> .

Value

Invisibly returns level4A.

plotLevel4B	<i>Plot GEDI Level 4B metrics</i>
-------------	-----------------------------------

Description

Plot GEDI Level 4B metrics

Usage

```
plotLevel4B(x, ...)
```

Arguments

x	A raster path or SpatRaster.
...	Passed to <code>terra::plot()</code> .

Value

Invisibly returns the raster.

plotPAIProfile	<i>Plot GEDI Plant Area Index (PAI) Profile</i>
----------------	---

Description

This functions plots Plant Area Index (PAI) Profile (GEDI level2B)

Usage

```
plotPAIProfile(level2BPAIProfile, beam = "BEAM0101", elev = TRUE)
```

Arguments

level2BPAIProfile	A GEDI Level2B object (output of <code>getLevel2BPAIProfile()</code> function). An S4 object of class "data.table".
beam	Select GEDI beam. Default is "BEAM0101". See details section.
elev	If TRUE, elevation will be used for plotting the PAI profile. Otherwise, height will be used instead.

Details

list of GEDI beams. See the output of `getLevel2BPAIProfile()` function.

- *BEAM0000*
- *BEAM0001*
- *BEAM0010*
- *BEAM0011*

- *BEAM0101*
- *BEAM0110*
- *BEAM1000*
- *BEAM1011*

Value

Returns a ggplot object. See [ggplot2::ggplot](#) package.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# specify the path to GEDI level2B data (zip file)
outdir = tempdir()
level2B_fp_zip <- system.file("extdata",
                             "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b<-readLevel2B(level2Bpath=level2Bpath)

# Get Plant Area Volume Density profile
level2BPAIProfile<-getLevel2BPAIProfile(level2b)

# Plot Level2B PAI Profile
gprofile<-plotPAIProfile(level2BPAIProfile, beam="BEAM0101", elev=TRUE)

close(level2b)
```

plotPAVDProfile

Plot GEDI Plant Area Volume Density Profile

Description

This functions plots Plant Area Volume Density profile (GEDI level2B)

Usage

```
plotPAVDProfile(level2BPAVDProfile, beam = "BEAM0101", elev = TRUE)
```

Arguments

level2BPAVDProfile	A GEDI Level2B object (output of <code>getLevel2BPAVDProfile()</code> function). An S4 object of class "data.table".
beam	Select GEDI beam. Default is "BEAM0101". See details section.
elev	If TRUE, elevation will be used for plotting the PAVD profile. Otherwise, height will be used instead.

Details

list of GEDI beams. See the output of `getLevel2BPAVDProfile()` function.

- *BEAM0000*
- *BEAM0001*
- *BEAM0010*
- *BEAM0011*
- *BEAM0101*
- *BEAM0110*
- *BEAM1000*
- *BEAM1011*

Value

Returns a ggplot object. See `ggplot2::ggplot` package.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# specify the path to GEDI level2B data (zip file)
outdir = tempdir()
level2B_fp_zip <- system.file("extdata",
                             "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath=level2Bpath)

# Get Plant Area Volume Density profile
level2BPAVDProfile <- getLevel2BPAVDProfile(level2b)

# Plot Level2B PAVD Profile
gprofile <- plotPAVDProfile(level2BPAVDProfile, beam="BEAM0101", elev=TRUE)

close(level2b)
```

plotWFMetrics

*GEDI full waveform plot with metrics***Description**

Plots the waveform with overlaid RH metrics

Usage

```
plotWFMetrics(level1b, level2a, shot_number, rh=c(25, 50, 75),...)
```

Arguments

level1b	A GEDI Level1B object (output of readLevel1B() function). An S4 object of class "gedi.level1b".
level2a	A GEDI Level2A object (output of readLevel2A() function). An S4 object of class "gedi.level2a".
shot_number	Shot number. A scalar representing the shot number of a giving pulse.
rh	Integer vector. Specify which RH metrics to plot except rh0 and rh100, default c(25, 50, 75).
...	Will be passed to the main plot.

Value

Nothing

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# specify the path to GEDI level1B and Level2A data (zip file)
outdir <- tempdir()
level1B_fp_zip <- system.file("extdata",
  "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
  package = "rGEDI"
)

level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level1B and Level2A data (h5 file)
level1b <- readLevel1B(level1Bpath = level1Bpath)
level2a <- readLevel2A(level2Apath = level2Apath)
```

```

shot_number <- "19640521100108408"

plotWFMetrics(level1b, level2a, shot_number, rh = c(25, 50, 75, 90))

close(level1b)
close(level2a)

```

```
plot_gedi_orbit_animation
```

Animate a GEDI ground track around the Earth

Description

Creates an interactive 3D HTML animation or an animated GIF from GEDI footprint coordinates. The presentation follows the ICESat2VegR orbit animation, with a rotating Earth, a NASA ISS illustration carrying GEDI, and a red near-infrared laser and ground track. ISS motion follows the time-ordered geolocation of the most complete beam extracted from the supplied HDF5 object.

Usage

```

plot_gedi_orbit_animation(
  x,
  lon = NULL,
  lat = NULL,
  time = NULL,
  track = NULL,
  output_file = tempfile("rGEDI-orbit-", fileext = ".html"),
  title = "GEDI orbit animation",
  duration = 18,
  launch = interactive(),
  track_speed = 2,
  earth_rotation_speed = 2,
  beams = NULL,
  every = 1L
)

```

Arguments

x	A data frame, data.table, sf or SpatVector containing GEDI footprint coordinates; an open gedi.level1b, gedi.level2a, gedi.level2b, or gedi.level4a object; or a list of these objects from consecutive production granules in one orbit.
lon, lat	Names of longitude and latitude columns. When NULL, common GEDI coordinate names are detected automatically.
time	Optional name of a column used to order footprints within each track. GEDI delta_time and shot_number columns are detected by default.
track	Optional name of a beam or track column. Separate tracks are colored independently.
output_file	Path of the .html or .gif file to create. GIF output requires the suggested gifski package.

title	Title shown above the animation.
duration	Duration of one animation cycle in seconds.
launch	Open the animation in the default browser after it is written.
track_speed	Initial HTML track playback speed from 1 to 15.
earth_rotation_speed	Initial Earth rotation speed from 0 to 20.
beams	Optional beam names to read from open GEDI objects.
every	Keep every nth footprint after ordering. Increase this for a complete orbit to reduce animation size and rendering time.

Value

The normalized path to the HTML file, invisibly.

Examples

```
orbit <- data.frame(
  longitude = seq(-60, -45, length.out = 30),
  latitude = seq(-8, 5, length.out = 30),
  delta_time = seq_len(30), beam = "BEAM0101"
)
html <- plot_gedi_orbit_animation(
  orbit, output_file = tempfile(fileext = ".html")
)
file.exists(html)
```

polyStatsLevel2AM	<i>Compute descriptive statistics of GEDI Elevation and Height Metrics</i>
-------------------	--

Description

Computes a Series of Statistics from GEDI derived Elevation and Height Metrics (Level2A) within a given area defined or not by a polygon

Usage

```
polyStatsLevel2AM(level2AM, func, id=NULL)
```

Arguments

level2AM	A GEDI Level2AM object (output of getLevel2AM() function). An S4 object of class "data.table".
func	The function to be applied for computing the defined statistics
id	A vector containing the polygon id for each GEDI observation. Default is NULL

Value

Returns an S4 object of class [data.table::data.table](#) Containing Statistics of GEDI level2A defined metrics

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
# Specifying the path to GEDI level2A data (zip file)
outdir <- tempdir()
level2A_fp_zip <- system.file("extdata",
  "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
  package = "rGEDI"
)

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath = level2Apath)

# Specifying the path to shapefile
polygon_filepath <- system.file("extdata", "stands_cerrado.shp", package = "rGEDI")

# Reading shapefile as sf object
library(sf)
polygon <- sf::st_read(polygon_filepath)

# Extracting GEDI Eleveation and Relative Metrics (level2A)
level2AM <- getLevel2AM(level2a)
head(level2AM)

# Clipping GEDI data by geometry
level2AM_clip <- clipLevel2AMGeometry(level2AM, polygon, split_by = "id")

#' Define your own function
mySetOfMetrics <- function(x) {
  metrics <- list(
    min = min(x), # Min of x
    max = max(x), # Max of x
    mean = mean(x), # Mean of x
    sd = sd(x) # Sd of x
  )
  return(metrics)
}

# Computing the maximum of RH100
RH100max <- polyStatsLevel2AM(level2AM_clip, func = max(rh100))

# Computing the maximum of RH100 stratified by polygon
RH100max_poly <- polyStatsLevel2AM(level2AM_clip, func = max(rh100), id = "id")

# Computing a serie statistics for GEDI metrics stratified by polygon
RH100metrics <- polyStatsLevel2AM(level2AM_clip,
  func = mySetOfMetrics(rh100),
  id = "id"
)

head(RH100metrics)
```

```
close(level2a)
```

polyStatsLevel2BVPM	<i>Compute descriptive statistics of GEDI Canopy Cover and Vertical Profile Metrics</i>
---------------------	---

Description

Computes a Series of Statistics of GEDI derived Canopy Cover and Vertical Profile metrics within a given area defined or not by a polygon

Usage

```
polyStatsLevel2BVPM(level2BVPM, func, id=NULL)
```

Arguments

level2BVPM	A GEDI Level2BVPM object (output of <code>getLevel2BVPM()</code> function). An S4 object of class "data.table".
func	The function to be applied for computing the defined statistics
id	A vector containing the polygon id for each GEDI observation. Default is NULL

Value

Returns an S4 object of class `data.table::data.table` Containing Statistics of GEDI level2BVPM defined metrics

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-b-002>

Examples

```
# A small extracted Level 2B table
level2BVPM <- data.table::data.table(
  pai = c(1.1, 1.8, 2.2, 0.9, 1.5, 2.4),
  cover = c(0.31, 0.44, 0.52, 0.27, 0.39, 0.58),
  poly_id = rep(c("stand_1", "stand_2"), each = 3)
)
head(level2BVPM)

# Define your own function
mySetOfMetrics <- function(x) {
  metrics <- list(
    min = min(x), # Min of x
    max = max(x), # Max of x
    mean = mean(x), # Mean of x
    sd = sd(x) # Sd of x
  )
  return(metrics)
}
```

```
# Computing the max of the Total Plant Area Index
pai_max <- polyStatsLevel2BVPM(level2BVPM, func = max(pai), id = NULL)
pai_max

# Computing the max of the Total Plant Area Index stratified by polygon
pai_max_poly <- polyStatsLevel2BVPM(level2BVPM, func = max(pai), id = "poly_id")
head(pai_max_poly)

# Computing the serie of statistics of canopy cover stratified by polygon
cover_metrics <- polyStatsLevel2BVPM(level2BVPM,
  func = mySetOfMetrics(cover),
  id = "poly_id"
)
head(cover_metrics)
```

polyStatsLevel3	<i>Polygon summaries of GEDI Level 3 metrics</i>
-----------------	--

Description

Polygon summaries of GEDI Level 3 metrics

Usage

```
polyStatsLevel3(x, y, fun = mean, na.rm = TRUE, ...)
```

Arguments

- x A raster path or SpatRaster.
- y Points or polygons accepted by `terra::vect()`.
- fun Summary function.
- na.rm Logical.
- ... Passed to `terra::extract()`.

Value

A data frame.

polyStatsLevel4A	<i>Polygon statistics for GEDI Level 4A footprints</i>
------------------	--

Description

Polygon statistics for GEDI Level 4A footprints

Usage

```
polyStatsLevel4A(level4A, polygon, metric = "agbd", fun = mean, id = NULL, ...)
```

Arguments

level4A	A table returned by getLevel4A() .
polygon	An sf, sfc, or SpatVector polygon object.
metric	Metric column name.
fun	Aggregation function.
id	Optional polygon ID field.
...	Additional arguments passed to fun.

Value

A data table with one row per polygon.

polyStatsLevel4B	<i>Polygon summaries of GEDI Level 4B metrics</i>
------------------	---

Description

Polygon summaries of GEDI Level 4B metrics

Usage

```
polyStatsLevel4B(x, y, fun = mean, na.rm = TRUE, ...)
```

Arguments

x	A raster path or SpatRaster.
y	Points or polygons accepted by terra::vect() .
fun	Summary function.
na.rm	Logical.
...	Passed to terra::extract() .

Value

A data frame.

predictGEDI	<i>Predict GEDI footprint values</i>
-------------	--------------------------------------

Description

Predict GEDI footprint values

Usage

```
predictGEDI(model, data, name = "prediction")
```

Arguments

model	A gedi_model or fitted R model.
data	Predictor table.
name	Output column name.

Value

A data table containing input data and predictions.

predictGEDIH5	<i>Predict values and write them to HDF5</i>
---------------	--

Description

Predict values and write them to HDF5

Usage

```
predictGEDIH5(model, data, output, dataset = "prediction")
```

Arguments

model	A gedi_model or fitted R model.
data	Predictor table.
output	Output HDF5 filename.
dataset	Dataset name.

Value

Invisibly returns output.

projectLevel3	<i>Project a GEDI Level 3 raster</i>
---------------	--------------------------------------

Description

Project a GEDI Level 3 raster

Usage

```
projectLevel3(x, crs, method = "bilinear", ...)
```

Arguments

x	A raster path or SpatRaster.
crs	Target CRS.
method	Resampling method.
...	Passed to terra::project() .

Value

A [terra::SpatRaster](#).

projectLevel4B	<i>Project a GEDI Level 4B raster</i>
----------------	---------------------------------------

Description

Project a GEDI Level 4B raster

Usage

```
projectLevel4B(x, crs, method = "bilinear", ...)
```

Arguments

x	A raster path or SpatRaster.
crs	Target CRS.
method	Resampling method.
...	Passed to terra::project() .

Value

A [terra::SpatRaster](#).

randomSampling	<i>GEDI random sampling specification</i>
----------------	---

Description

GEDI random sampling specification

Usage

```
randomSampling(size)
```

Arguments

size	Number or fraction of observations to select.
------	---

rasterizeGEDI	<i>Rasterize GEDI footprint data</i>
---------------	--------------------------------------

Description

Rasterize GEDI footprint data

Usage

```
rasterizeGEDI(x, metric, res = 0.01, fun = mean, lon = NULL, lat = NULL, ...)
```

Arguments

x	GEDI footprint table.
metric	Metric column.
res	Resolution in decimal degrees.
fun	Aggregation function.
lon, lat	Optional coordinate columns.
...	Passed to terra::rasterize() .

Value

A [terra::SpatRaster](#).

rasterizeLevel4A	<i>Rasterize GEDI Level 4A footprints</i>
------------------	---

Description

Rasterize GEDI Level 4A footprints

Usage

```
rasterizeLevel4A(
  level4A,
  metric = "agbd",
  fun = mean,
  res = 0.01,
  filename = "",
  overwrite = FALSE,
  ...
)
```

Arguments

level4A	A table returned by getLevel4A() .
metric	Metric column name.
fun	Aggregation function.
res	Output resolution in decimal degrees.
filename	Optional output GeoTIFF path.
overwrite	Logical; overwrite filename when it exists.
...	Additional arguments passed to fun.

Value

A [terra::SpatRaster](#).

rasterSampling	<i>GEDI raster-stratified sampling specification</i>
----------------	--

Description

GEDI raster-stratified sampling specification

Usage

```
rasterSampling(size, raster, lon = NULL, lat = NULL)
```

Arguments

size	Number or fraction per raster class.
raster	A categorical SpatRaster.
lon, lat	Optional coordinate column names.

readGEDICloud	<i>Open a GEDI HDF5 granule through Earthaccess</i>
---------------	---

Description

Open a GEDI HDF5 granule through Earthaccess

Usage

```
readGEDICloud(x, product = NULL, cache_dir = tempdir())
```

Arguments

x	URL, S3 URI, or Earthaccess granule result.
product	Optional product identifier.
cache_dir	Used when cloud modules are unavailable and a URL is downloaded.

Value

An object of class `gedi.cloud_h5`.

readLevel1B	<i>Read GEDI Level1B data (Geolocated Waveforms)</i>
-------------	--

Description

This function reads GEDI level1B products: geolocated Waveforms

Usage

```
readLevel1B(level1Bpath)
```

Arguments

level1Bpath	Local file path or Earthdata Cloud URL pointing to a GEDI Level 1B HDF5 granule.
-------------	--

Value

Returns an S4 object of class `gedi.level1b` containing GEDI level1B data.

See Also

[hdf5r::H5File](#) in the *hdf5r* package and <https://www.earthdata.nasa.gov/data/catalog/lpccloud-gedi01-b-002>

Examples

```
# Specifying the path to GEDI level1B data (zip file)
outdir = tempdir()
level1B_fp_zip <- system.file("extdata",
                              "GEDI01_B_2019108080338_001964_T05337_02_003_01_sub.zip",
                              package="rGEDI")

# Unzipping GEDI level1B data
level1Bpath <- unzip(level1B_fp_zip, exdir = outdir)

# Reading GEDI level1B data (h5 file)
level1b <- readLevel1B(level1Bpath=level1Bpath)

close(level1b)
```

readLevel2A	<i>Read GEDI Level2A data (Basic Full Waveform derived Metrics)</i>
-------------	---

Description

This function reads GEDI level2A products: ground elevation, canopy top height, and relative heights (RH).

Usage

```
readLevel2A(level2Apath)
```

Arguments

level2Apath	Local file path or Earthdata Cloud URL pointing to a GEDI Level 2A HDF5 granule.
-------------	--

Value

Returns an S4 object of class `gedi.level2a` containing GEDI level2A data.

See Also

<https://www.earthdata.nasa.gov/data/catalog/lpcloud-gedi02-a-002>

Examples

```
# Specifying the path to GEDI level2A data (zip file)
outdir = tempdir()
level2A_fp_zip <- system.file("extdata",
                              "GEDI02_A_2019108080338_001964_T05337_02_001_01_sub.zip",
                              package="rGEDI")

# Unzipping GEDI level2A data
level2Apath <- unzip(level2A_fp_zip, exdir = outdir)

# Reading GEDI level2A data (h5 file)
level2a <- readLevel2A(level2Apath=level2Apath)

close(level2a)
```

readLevel2B	<i>Read GEDI Level2B data (Biophysical Variables)</i>
-------------	---

Description

This function reads GEDI level2B products: canopy cover, Plant Area Index (PAI), Plant Area Volume Density (PAVD), and Foliage Height Diversity (FHD).

Usage

```
readLevel2B(level2Bpath)
```

Arguments

level2Bpath	Local file path or Earthdata Cloud URL pointing to a GEDI Level 2B HDF5 granule.
-------------	--

Value

Returns an S4 object of class `gedi.level2b` containing GEDI level2B data.

Examples

```
# Specifying the path to GEDI level2B data (zip file)
outdir = tempdir()
level2B_fp_zip <- system.file("extdata",
                             "GEDI02_B_2019108080338_001964_T05337_02_001_01_sub.zip",
                             package="rGEDI")

# Unzipping GEDI level2A data
level2Bpath <- unzip(level2B_fp_zip, exdir = outdir)

# Reading GEDI level2B data (h5 file)
level2b <- readLevel2B(level2Bpath=level2Bpath)

close(level2b)
```

readLevel3	<i>Read GEDI Level 3 gridded metrics</i>
------------	--

Description

Read GEDI Level 3 gridded metrics

Usage

```
readLevel3(x, metrics = NULL)
```

Arguments

x	One or more local paths, GDAL-readable URLs, or a <code>SpatRaster</code> .
metrics	Optional layer names to retain.

Value

A `terra::SpatRaster`.

See Also

https://daac.ornl.gov/GEDI/guides/GEDI_L3_LandSurface_Metrics_V3.html

readLevel4A

Read a GEDI Level 4A granule

Description

Opens a GEDI04_A HDF5 granule containing footprint-level aboveground biomass density estimates.

Usage

```
readLevel4A(level4Apath)
```

Arguments

`level4Apath` Local file path or Earthdata Cloud URL pointing to a GEDI04_A HDF5 granule.

Value

A `gedi.level4a` object. Close it with `close()`.

See Also

https://daac.ornl.gov/GEDI/guides/GEDI_L4A_AGB_Density_V3.html

readLevel4B

Read GEDI Level 4B gridded biomass

Description

Read GEDI Level 4B gridded biomass

Usage

```
readLevel4B(x, metrics = NULL)
```

Arguments

`x` One or more local paths, GDAL-readable URLs, or a `SpatRaster`.
`metrics` Optional layer names to retain.

Value

A `terra::SpatRaster`.

See Also

[doi:10.3334/ORNLDAAAC/2299](https://doi.org/10.3334/ORNLDAAAC/2299)

resampleLevel3	<i>Resample a GEDI Level 3 raster</i>
----------------	---------------------------------------

Description

Resample a GEDI Level 3 raster

Usage

```
resampleLevel3(x, template, method = "bilinear", ...)
```

Arguments

x	A raster path or SpatRaster.
template	Target SpatRaster.
method	Resampling method.
...	Passed to terra::resample() .

Value

A [terra::SpatRaster](#).

resampleLevel4B	<i>Resample a GEDI Level 4B raster</i>
-----------------	--

Description

Resample a GEDI Level 4B raster

Usage

```
resampleLevel4B(x, template, method = "bilinear", ...)
```

Arguments

x	A raster path or SpatRaster.
template	Target SpatRaster.
method	Resampling method.
...	Passed to terra::resample() .

Value

A [terra::SpatRaster](#).

rGEDI_configure	<i>Configure optional rGEDI cloud and Earth Engine support</i>
-----------------	--

Description

Configure optional rGEDI cloud and Earth Engine support

Usage

```
rGEDI_configure(
  python = NULL,
  install = FALSE,
  earth_engine_project = Sys.getenv("EE_PROJECT", unset = ""),
  quiet = FALSE
)
```

Arguments

python	Optional Python executable or environment name.
install	Logical; install missing Python modules.
earth_engine_project	Optional Google Earth Engine project ID.
quiet	Logical.

Value

Invisibly returns a capability table.

sampleGEDI	<i>Sample GEDI footprint observations</i>
------------	---

Description

Sample GEDI footprint observations

Usage

```
sampleGEDI(x, method)
```

Arguments

x	A data frame or data table of GEDI footprints.
method	A specification returned by one of the sampling constructors.

Value

A [data.table::data.table](#).

search_datasets	<i>Search the GEDI datasets available in Earth Engine</i>
-----------------	---

Description

Search the GEDI datasets available in Earth Engine

Usage

```
search_datasets(..., operator = c("and", "or"))
```

Arguments

...	Words matched against the product name, catalog ID, and title.
operator	Use "and" or "or" when several words are supplied.

Value

A data table containing product, catalog ID, version, and title.

slope	<i>Earth Engine terrain slope</i>
-------	-----------------------------------

Description

Earth Engine terrain slope

Usage

```
slope(x)
```

Arguments

x	Earth Engine elevation image.
---	-------------------------------

Value

An Earth Engine image.

spacedSampling	<i>GEDI minimum-distance sampling specification</i>
----------------	---

Description

GEDI minimum-distance sampling specification

Usage

```
spacedSampling(size, radius, lon = NULL, lat = NULL)
```

Arguments

size	Number or fraction of observations to select.
radius	Minimum separation in meters.
lon, lat	Optional coordinate column names.

stratifiedSampling	<i>GEDI attribute-stratified sampling specification</i>
--------------------	---

Description

GEDI attribute-stratified sampling specification

Usage

```
stratifiedSampling(size, variable, breaks = NULL)
```

Arguments

size	Number or fraction per stratum.
variable	Column used as strata, or a numeric column to bin.
breaks	Optional breaks for a numeric variable.

to_vect	<i>Convert GEDI footprints to a spatial vector</i>
---------	--

Description

Convert GEDI footprints to a spatial vector

Usage

```
to_vect(x, lon = NULL, lat = NULL, crs = "EPSG:4326")
```

Arguments

x	GEDI footprint table.
lon, lat	Optional coordinate column names.
crs	Coordinate reference system.

Value

A `terra::SpatVector`.

varSel	<i>Select predictor variables for a GEDI model</i>
--------	--

Description

Select predictor variables for a GEDI model

Usage

```
varSel(
  x,
  y,
  method = c("correlation", "randomForest", "rfe"),
  threshold = 0.1,
  seed = NULL,
  ...
)
```

Arguments

x	Predictor data frame.
y	Response vector.
method	Selection method. "rfe" recursively removes the least important predictor and selects the smallest model whose out-of-bag error is within one standard error of the minimum.
threshold	Minimum absolute correlation or scaled Random Forest importance. For method = "rfe", it is applied after model selection; use 0 to retain the RFE-selected subset.
seed	Optional random seed.
...	Passed to randomForest when requested.

Value

An object of class `gedi_var_selection`.

vect_as_ee	<i>Convert a vector object to an Earth Engine feature collection</i>
------------	--

Description

Convert a vector object to an Earth Engine feature collection

Usage

```
vect_as_ee(x)
```

Arguments

`x` `sf`, `sfc`, `SpatVector`, or vector file path.

Value

An Earth Engine `FeatureCollection`.

Index

addEEImage, [2](#)
aggregateLevel3, [3](#)
aggregateLevel4B, [4](#)
aspect, [4](#)

build_ee_forest, [5](#)

clip, [5](#)
clip, data.frame, ANY-method (clip), [5](#)
clip, data.frame, numeric-method (clip), [5](#)
clip, data.frame, SpatExtent-method (clip), [5](#)
clip, gedi.level1b, ANY-method (clip), [5](#)
clip, gedi.level1b, numeric-method (clip), [5](#)
clip, gedi.level1b, SpatExtent-method (clip), [5](#)
clip, gedi.level2a, ANY-method (clip), [5](#)
clip, gedi.level2a, numeric-method (clip), [5](#)
clip, gedi.level2a, SpatExtent-method (clip), [5](#)
clip, gedi.level2b, ANY-method (clip), [5](#)
clip, gedi.level2b, numeric-method (clip), [5](#)
clip, gedi.level2b, SpatExtent-method (clip), [5](#)
clip, gedi.level4a, ANY-method (clip), [5](#)
clip, gedi.level4a, numeric-method (clip), [5](#)
clip, gedi.level4a, SpatExtent-method (clip), [5](#)
clip, SpatRaster, ANY-method (clip), [5](#)
clipLevel1B, [7](#)
clipLevel1BGeo, [8](#)
clipLevel1BGeoGeometry, [10](#)
clipLevel1BGeometry, [11](#)
clipLevel2A, [12](#)
clipLevel2AGeometry, [14](#)
clipLevel2AM, [15](#)
clipLevel2AMGeometry, [16](#)
clipLevel2B, [17](#)
clipLevel2BGeometry, [19](#)
clipLevel2BPAIProfile, [20](#)

clipLevel2BPAIProfileGeometry, [21](#)
clipLevel2BPAVDProfile, [22](#)
clipLevel2BPAVDProfileGeometry, [24](#)
clipLevel2BVPM, [25](#)
clipLevel2BVPMGeometry, [26](#)
clipLevel3, [28](#)
clipLevel4A, [28](#)
clipLevel4AGeometry, [29](#)
clipLevel4B, [30](#)
close(), [31](#), [87](#)
close, gedi.level1b-method, [30](#)
close, gedi.level2a-method (close, gedi.level1b-method), [30](#)
close, gedi.level2b-method (close, gedi.level1b-method), [30](#)
close, gedi.level4a-method (close, gedi.level1b-method), [30](#)
close, gedi.cloud_h5, [31](#)

data.table::data.table, [7–10](#), [15](#), [16](#), [20](#), [22–25](#), [27](#), [29](#), [36](#), [44](#), [45](#), [48](#), [51](#), [53](#), [55](#), [56](#), [58](#), [59](#), [75](#), [77](#), [89](#)
downloadGEDI (gediDownload), [41](#)

earthdata_login, [31](#)
earthdata_s3_credentials, [32](#)
ee_build_AlphaEarth_embedding_terrain_stack, [32](#)
ee_build_hls_s1c_terrain_stack, [33](#)
ee_check_task_status, [33](#)
ee_check_task_status(), [34](#)
ee_image_to_drive, [34](#)
ee_initialize, [35](#)
ee_rect_to_sf, [35](#)
ext_to_ee, [37](#)
ext_to_ee(), [34](#)
extractEE, [36](#)
extractGEDIAncillary (extractEE), [36](#)
extractLevel3, [36](#)
extractLevel4B, [37](#)

fit_metrics, [38](#)
fit_model, [38](#)

gedi.fullwaveform, [67](#)

- gedi.fullwaveform
 - (gedi.fullwaveform-class), 39
- gedi.fullwaveform-class, 39
- gedi.level1b, 7, 11, 30, 44, 46, 48, 84
- gedi.level1b (gedi.level1b-class), 39
- gedi.level1b-class, 39
- gedi.level2a, 85
- gedi.level2a (gedi.level2a-class), 40
- gedi.level2a-class, 40
- gedi.level2b, 86
- gedi.level2b (gedi.level2b-class), 40
- gedi.level2b-class, 40
- gedi.level4a, 29, 58, 87
- gedi.level4a (gedi.level4a-class), 40
- gedi.level4a-class, 40
- gediDownload, 41
- gediEE, 42
- gedifinder, 43
- gediWFMetrics, 44
- gediWFSimulator, 45
- geomSampling, 47
- get_catalog_id, 59
- getGEDITrack, 47
- getLevel1BGeo, 48
- getLevel1BGeo(), 8, 10, 48
- getLevel1BWF, 52
- getLevel1BWF(), 67
- getLevel2AM, 53
- getLevel2AM(), 61, 75
- getLevel2BPAIProfile, 54
- getLevel2BPAIProfile(), 20, 21, 24, 70
- getLevel2BPAVDProfile, 55
- getLevel2BPAVDProfile(), 23, 72
- getLevel2BVPM, 56
- getLevel2BVPM(), 62, 77
- getLevel4A, 58
- getLevel4A(), 29, 64, 69, 79, 83
- getTileUrl, 59
- ggplot2::ggplot, 71, 72
- glcmTexture, 60
- graphics::clip(), 7
- graphics::plot(), 38, 69
- gridSampling, 60
- gridStatsLevel2AM, 61
- gridStatsLevel2BVPM, 62
- gridStatsLevel4A, 64
- H5File, 39, 40
- hdf5r::H5File, 11, 84
- leaflet::addTiles(), 3
- map_create, 64
- map_download, 65
- map_view, 65
- mosaicLevel3, 66
- mosaicLevel4B, 66
- openGEDI, 67
- openGEDI(), 44
- plot, gedi.fullwaveform, missing-method, 67
- plot.gedi_var_selection, 68
- plot_gedi_orbit_animation, 74
- plot_gedi_orbit_animation(), 47
- plotLevel3, 69
- plotLevel4A, 69
- plotLevel4B, 70
- plotPAIProfile, 70
- plotPAVDProfile, 71
- plotWFMetrics, 73
- polyStatsLevel2AM, 75
- polyStatsLevel2BVPM, 77
- polyStatsLevel3, 78
- polyStatsLevel4A, 78
- polyStatsLevel4B, 79
- predictGEDI, 80
- predictGEDIH5, 80
- projectLevel3, 81
- projectLevel4B, 81
- randomSampling, 82
- rasterizeGEDI, 82
- rasterizeLevel4A, 83
- rasterSampling, 83
- readGEDICloud, 84
- readGEDICloud(), 31
- readLevel1B, 52, 84
- readLevel1B(), 7, 11, 25, 27, 52, 73
- readLevel2A, 85
- readLevel2A(), 12, 14–16, 53, 73
- readLevel2B, 86
- readLevel2B(), 18, 19, 54, 55, 57
- readLevel3, 86
- readLevel4A, 87
- readLevel4A(), 29, 58
- readLevel4B, 87
- resampleLevel3, 88
- resampleLevel4B, 88
- rGEDI-package, 2
- rGEDI_configure, 89
- sampleGEDI, 89
- search_datasets, 90
- sf::sf, 10, 14, 16, 19, 21, 24, 27

`sf::st_read`, [10](#), [16](#), [19](#), [21](#), [24](#), [27](#)
`sf::st_read()`, [14](#)
`slope`, [90](#)
`spacedSampling`, [91](#)
`stratifiedSampling`, [91](#)

`tempdir()`, [41](#)
`terra::aggregate()`, [3](#), [4](#)
`terra::extract()`, [36](#), [37](#), [78](#), [79](#)
`terra::plot()`, [69](#), [70](#)
`terra::project()`, [81](#)
`terra::rast()`, [67](#)
`terra::rasterize()`, [82](#)
`terra::resample()`, [88](#)
`terra::SpatExtent`, [6](#)
`terra::SpatRaster`, [3](#), [4](#), [6](#), [7](#), [28](#), [30](#), [64](#), [66](#),
 [81–83](#), [87](#), [88](#)
`terra::SpatVector`, [6](#), [92](#)
`terra::vect()`, [36](#), [37](#), [78](#), [79](#)
`to_vect`, [92](#)

`varSel`, [92](#)
`vect_as_ee`, [93](#)