

Technical Specification for Medical Claims Electronic Data Transfer (MCEDT) Service via Electronic Business Services (EBS)

Ministry of Health and Long-Term Care

March 2013

EBS-EDT SOAP Specification

Version 3.0

Table of Contents

Technical Specifications for Medical Claims Electronic Data Transfer (MCEDT) Service Via Electronic Business Services (EBS).....	4
Glossary.....	4
Notice and Disclaimer.....	6
Intended Audience for this Technical Specification Document.....	7
About This Document.....	8
Introduction	9
Medical Claims Electronic Data Transfer	9
Web Service Interface for MCEDT Service.....	9
Technical Interface.....	10
SOAP Message:	10
The Message WSDL.....	10
WSDL Definitions Table	10
Validation Message Schema	11
Data Specifications for Fields.....	11
Testing	25
APPENDIX A: Error Codes	26
APPENDIX B: The Message WSDL	27
APPENDIX C: Message Schema	42
APPENDIX D: MSA Model Message Example	53
APPENDIX E: IDP Model Message Example	58
MCEDT Currently Supported File/Resource Types Addendum	64
Claim File Upload Error Codes Addendum.....	66
OBEC File Upload Error Codes Addendum	67
Stale Dated Claims File Upload Error Codes Addendum	68

Technical Specifications for Medical Claims Electronic Data Transfer (MCEDT) Service Via Electronic Business Services (EBS)

1

Chapter 1

Techical Specifications for Medical Claims Electronic Data Transfer (MCEDT) Service Via Electronic Business Services (EBS)

Glossary

Term	Definition
Claim Submission Number (CSN) aka Billing Number	A unique identifier that is assigned to a Health Care Provider who is registered with MOHLTC for the purpose of submitting claims for insured services.
MCEDT Service Schedule	A Service Schedule to the Master Service agreement that forms part of the Agreement between the Service Requestor and MOHLTC and captures the roles and responsibilities that relate to the MCEDT via EBS.
Health Care Provider (HCP)	Individual, group or facility licensed to provide health care services to eligible residents of Ontario.
Health Information Custodian (HIC)	Health Information Custodian in or under <i>Personal Health & Information Privacy Act</i> (PHIPA).
Identity Provider (IDP)	A party or organization that creates, maintains, and manages identity information for <i>principals</i> and performs principal authentication for other parties or organizations.
Master Services Agreement (MSA)	The binding legal agreement through which MOHLTC accepts the identity of an end user at face value based on authenticating the end user's organization at the time of the service request.
MOHLTC	The Ontario Ministry of Health and Long-Term Care.
MOHLTC Electronic Business Services (EBS)	The Electronic Business Service is a framework which provides an electronic business gateway that exposes MOHLTC services to the Broader Health Sector and provides a full featured IAM suite of provisioning, business enrolment, business and IT federation agreements, technical specifications and terms of acceptable use governance.

Term	Definition
Message Transmission Optimization Mechanism (MTOM)	A method of efficiently sending binary data to and from web services. For more information refer to http://www.w3.org/TR/soap12-mtom/
Output (Response) Message Fields	Output (Response) Message fields are those fields which are returned by the Medical Claims Electronic Data Transfer web service.
Service Provider (SP)	Throughout this document, Service Provider refers exclusively to MOHLTC, as the provider of the Medical Claims Electronic Data Transfer service via EBS.
Simple Object Access Protocol (SOAP)	Simple Object Access Protocol: an Extensible Markup Language (XML)-based protocol for exchanging structured information between computer systems. For more information refer to http://www.w3.org/TR/soap/
Stakeholder Number (SN)	A unique identifier that is assigned to stakeholders of interest who are registered with the MOHLTC. The unique identifier is either 7 digits long or 8 digits long depending on the type of stakeholder to which it belongs.
UUID	A version 4 Universally Unique Identifier (UUID).
Web Services Description Language (WSDL)	Web Services Description Language: an XML-based language for describing web services and how to access them. For more information refer to http://www.w3.org/TR/wsdl

Notice and Disclaimer

All possible measures are exerted to ensure accuracy of the contents of this manual; however, the manual may contain typographical, printing or other errors. The reader is cautioned against complete reliance upon the contents of the manual without confirming the accuracy and currency of the information contained in it. The Crown in Right of Ontario, as represented by the Ministry of Health and Long-Term Care (MOHLTC), assumes no responsibility for errors or omissions in any of the information contained in this manual, or for any person's use of the material therein, or for any costs or damages associated with such use. In no event shall the Crown in Right of Ontario be liable for any errors or omissions, or for any damages including, without limitation, damages for direct, indirect, incidental, special, consequential or punitive damages arising out of or related to the use of information contained in this manual.

This technical specification is intended only to assist and guide the development of software to access the Medical Claims Electronic Data Transfer (MCEDT) web service via the MOHLTC Electronic Business Service (EBS).

Revisions to the specification will be made as required. The ministry will make every effort to give as much advance notice as possible for future revisions. It is essential that software developers keep current regarding any changes to this specification. The current version of the technical specification will be available for download at the following URL:

http://www.health.gov.on.ca/english/providers/pub/pub_menus/pub_ohip.html

For further details about MCEDT via EBS service including enrolment criteria please refer to the MCEDT Reference Manual posted at:

http://www.health.gov.on.ca/english/providers/pub/pub_menus/pub_ohip.html

This document **does not** describe the technical specifications of the specific files that can be uploaded and downloaded by the MCEDT application. For information on specific file format specifications please refer to the individual technical specification (EBS-EDT SOAP Specifications) at the following URL:

http://www.health.gov.on.ca/english/providers/pub/pub_menus/pub_ohip.html

Please direct any questions to the **Service Support Contact Centre (SSCC) at 1 800 262-6524** or SSContactCentre.MOH@ontario.ca

Intended Audience for this Technical Specification Document

This document is intended for use by developers of applications and products that support communication with MOHLTC's MCEDT via EBS (web service interface) a service provided by the ministry to support electronic data transfer. This service is built to the web services standards detailed in this document.

The ministry does not provide any support for automation of the public MCEDT web page.

This document is also intended to be read in the context of either a service agreement between the ministry and the Service Requestor or through an accepted IDP. The service agreement is defined by a Master Service Agreement (MSA) and an MCEDT Service Schedule between the ministry and the Service Requestor (SR).

This technical specification is also targeted to vendors of various software applications and products that have or plan to have modules that support MCEDT through a web service interface within the province of Ontario in Canada.

The document describes the web service, the SOAP message specification and aims to guide the users in the development of client application to integrate with this web service.

It is assumed that the reader has knowledge of web services and related protocols, SOAP and XML message formats/processing, relevant interoperability profiles and identity assertions and has read the '*MOHLTC EBS - Generic Security SOAP Specification*' document.

About This Document

The Ministry of Health and Long-Term Care Medical Claims Electronic Data Transfer service allows health care providers (HCP) to send and receive electronic data with the ministry.

This document is an extension of the “*MOHLTC EBS – Generic Security SOAP Specification*” document and is intended to provide the reader with sufficient information to implement service requestor software that can use the service.

The MCEDT service will only support the IDP security model in its first release.

The introduction provides an overview of the MCEDT service and provides a glossary of the terminology used throughout the document. Additional functional information and overview of the MCEDT process is provided in the MCEDT reference manual published at:

http://www.health.gov.on.ca/english/providers/pub/pub_menus/pub_ohip.html

The Simple Object Access Protocol (SOAP) Message Section provides the technical specifications of the SOAP message including:

- Message Web Services Description Language (WSDL);
- Validation message schema including the request and the response;
- Data specifications for fields; and
- MTOM will be used to transfer all attachments.

Appendices provide:

- Response codes;
- The Message WSDL; and
- SOAP message examples

Introduction

The Medical Claims Electronic Data Transfer service adheres to the EBS security models. As such, it requires that the unique ministry identifier for Service Requestor (SR) be a Stakeholder Number (SN), and for Service User (SU) be either a SN or a Claim Submission Number (CSN).

Although the ministry does provide a simple user interface for MCEDT all program to program interfaces **MUST** use this web service and should never interface to the user interface. The user interface can and will change time to time without notification.

Medical Claims Electronic Data Transfer

The MCEDT service is a framework which allows electronic file processing to and from the ministry's adjudication and reporting systems. Service users who are authenticated to the MCEDT service can upload (send) files to the ministry for processing. Related reports can also be retrieved through this information technology channel by authorized users or their agents (designates). Service users and their agents must first register and enroll for a set of new security credentials before they can be authenticated to the MCEDT service before they can upload (send) or download (receive) reports or files.

The contents and format of files remain exactly as transmitted from the service user or from the ministry's information technology systems.

For more information refer to the MCEDT Reference manual.

Web Service Interface for MCEDT Service

The Province of Ontario, via the Ministry of Health and Long-Term Care, offers MCEDT via EBS for users through third party or client software.

Technical Interface

The Province of Ontario is responsible and accountable for the service provider component.

The service interface uses the SOAP protocol for communication and the WS-Security (WSS) protocol for transaction security. There are several implementations of the WSS protocol available and it is suggested that one of those be used where possible. The following sections assume appropriate headers are included as defined by the “EBS – Generic Security SOAP Specification”.

The response message will be signed using the EBS certificate and the results object of the response will be encrypted using the AES128-CBC encryption algorithm and will need to be decrypted by the caller before using the returned data.

SOAP Message:

SOAP is an XML-based standard protocol that defines a message specification for transmitting XML documents via a network. Since this message specification does not depend on a particular programming language or operating system (OS), data transfer can be conducted among and between systems that use different languages or operating systems.

All attachments will be sent and received using the MTOM attachment protocol.

The Message WSDL

A WSDL is a specification for coding web services-related information (access point and interface specifications, etc.) in XML. Note that while WSDL does not define a protocol when sending/receiving messages, the ministry is using SOAP via HTTPS as the protocol for message transmission.

WSDL Definitions Table

The WSDL includes the following standard elements:

Variable	Description
MCEDT Service URI	The URI of the MCEDT web service in the form of:
	Internet Access: https://ws.ebs.health.gov.on.ca:1441/EDTService/EDTService
	ENA Access: https://intra.ws.ebs.health.gov.on.ca:1441/EDTService/EDTService

The complete WSDL is included in *Appendix B*.

Validation Message Schema

The MCEDT message schema includes definitions of both the request and the response elements. Schema elements are described below, and the full schema is included in *Appendix C*.

Data Specifications for Fields

The fields described in the message specification are necessarily generic in order to follow the XML data typing standards. However, in order to pass validation, some of the fields must be presented in the format expected by the ministry.

WS-Security will be used to encrypt the returning data. All returning attachments will be encrypted with the public key of the callers signing certificate. For more information please refer to the *'MOHLTC EBS – Generic Security Specification'* document. For information on the currently supported file/resource types refer to the 'MCEDT CURRENTLY SUPPORT FILE/RESOURCE TYPES' addendum.

The maximum attachment size that will be accepted by MCEDT is 10 megabytes.

Methods

Upload

The operation will be used to upload one or up to 5 documents from external users.

Input (Request) Message Fields

name="content" type="xs:base64Binary"

The content of the file being uploaded. The content is sent as an attachment using the MTOM protocol. The maximum attachment size of 10 megabytes.

name="description" type="xs:string"

A custom description of the file. The maximum length is 50 characters.

name="resourceType" type="xs:string"

A resource type as specified by the getTypeList method.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="description" type="xs:string"

The description sent in the input data for the file. The maximum length is 50 characters.

name="resourceID" type="xs:integer"

The EDT Identification of the resource uploaded.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0003	Resource Type Not Found
EEDTS0010	File Upload Failed
EEDTS0012	MOH ID not Valid

NOTE: Specific error response codes can be returned based on the type of file being uploaded. The error codes for specific file types can be found as addendums to this technical specification.

name="msg" type="xs:string"

The response code message for the request.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

Submit

The operation submits a list of documents to be processed by the ministry.

Input (Request) Message Fields

maxOccurs="100" minOccurs="1" name="resourceIds" type="xs:integer"

The list of file ids to submit.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="description" type="xs:string"

The custom description sent when the resource was uploaded or updated. Maximum length is 50 characters.

name="resourceID" type="xs:integer"

The file id of the file submitted.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0012	MOH ID not Valid
EEDTS0050	User not Allowed
EEDTS0051	No Data for Processing
EEDTS0052	Data Processing failed
EEDTS0054	User that is submitting the resource is not the same as the user that uploaded it.
EEDTS0055	The resource is not in the upload status so cannot be submitted
EEDTS0056	The resource id specified cannot be found.

name="msg" type="xs:string"

The response code message for the request.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

Download

The operation downloads a list of up to 5 documents from the ministry.

Input (Request) Message Fields

maxOccurs="5" minOccurs="1" name="resourceIDs" type="xs:integer"

The list of file ids to download.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="content" type="xs:base64Binary"

The content of the file being downloaded. The content is received as an attachment using the MTOM protocol.

name="resourceID" type="xs:integer"

The file id of the file downloaded.

name="resourceType" type="xs:string"

A resource type as specified by the getTypeList method.

name="description" type="xs:string"

The description sent in the input data for the file. The maximum length is 50 characters.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0012	MOH ID not Valid
EEDTS0050	User not Allowed
EEDTS0051	No Data for Processing
EEDTS0056	The resource id specified cannot be found.

name="msg" type="xs:string"

The response code message for the request.

List

The operation returns a list of document references and attributes as specified by the search criteria of the caller. The results are broken into pages of up to 50 items each.

Input (Request) Message Fields

Optional Fields

name="resourceType" type="xs:string"

A resource type as specified by the getTypeList method.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

name="pageNo" type="xs:integer"

The page number of the results page that is to be returned. Page numbers are 1 based and this should be 1 for the initial request.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="createTimestamp" type="xs:dateTime"

The timestamp when the file was uploaded.

name="description" type="xs:string"

The description sent in the input data when the file was uploaded. The maximum length is 50 characters.

name="resourceType" type="xs:string"

A resource type as specified by the getTypeList method.

name="modifyTimestamp" type="xs:dateTime"

The timestamp when the file was last modified.

name="resourceID" type="xs:integer"

The file id of the file uploaded/submitted.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0012	MOH ID not Valid
EEDTS0050	User not Allowed

name="msg" type="xs:string"

The response code message for the request.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

name="status" type="ts:integer"

This represents the total number of pages in the request.

Info

The operation returns a list of document attributes for the specified document ids.

Input (Request) Message Fields

maxOccurs="100" minOccurs="1" name="resourceIDs" type="xs:integer"

The list of file ids to get info on.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="createTimestamp" type="xs:dateTime"

The timestamp when the file was uploaded.

name="description" type="xs:string"

The description sent in the input data for the file when uploaded. The maximum length is 50 characters.

name="resourceType" type="xs:string"

A resource type as specified by the getTypeList method.

name="modifyTimestamp" type="xs:dateTime"

The timestamp when the file was last modified.

name="resourceID" type="xs:integer"

The file id of the file uploaded/submitted.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0012	MOH ID not Valid
EEDTS0050	User not Allowed
EEDTS0051	No Data for Processing
EEDTS0056	The resource id specified cannot be found.

name="msg" type="xs:string"

The response code message for the request.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

Delete

The operation will delete the specified documents from the MCEDT system. Files can only be deleted if they have been uploaded and/or updated but not submitted. Downloadable files cannot be deleted.

Input (Request) Message Fields

maxOccurs="100" minOccurs="1" name="resourceIDs" type="xs:integer"

The list of file ids to delete.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="description" type="xs:string"

The description sent in the input data for the file when uploaded. The maximum length is 50 characters.

name="resourceID" type="xs:integer"

The file id of the file deleted.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0012	MOH ID not Valid
EEDTS0050	User not Allowed
EEDTS0051	No Data for Processing
EEDTS0052	Data Processing failed
EEDTS0054	User that is deleting the resource is not the same as the user that uploaded it.
EEDTS0055	The resource is not in the upload status so cannot be deleted.
EEDTS0056	The resource id specified cannot be found.

name="msg" type="xs:string"

The response code message for the request.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

Update

The operation will replace up to 5 documents with the contents and attributes specified.

Input (Request) Message Fields

name="content" type="xs:base64Binary"

The content of the file being uploaded. The content is sent as an attachment using the MTOM protocol.

name="resourceID" type="xs:integer"

The file id of the file updated.

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="description" type="xs:string"

The description sent in the input data for the file when uploaded. Maximum length 50 characters.

name="resourceID" type="xs:integer"

The file id of the file updated.

name="code" type="xs:string"

The response code for the request.

Code	Description
IEDTS0001	Success
EEDTS0012	MOH ID not Valid
EEDTS0050	User not Allowed
EEDTS0051	No Data for Processing
EEDTS0052	Data Processing failed
EEDTS0054	User that is updating the resource is not the same as the user that uploaded it.
EEDTS0055	The resource is not in the upload status so cannot be updated
EEDTS0056	The resource id specified cannot be found.

name="msg" type="xs:string"

The response code message for the request.

name="status" type="tns:resourceStatus"

The current status of the resource. One of UPLOADED, SUBMITTED, WIP, DOWNLOADABLE, DELETED, APPROVED, DENIED.

getTypeList

The operation will return the list of resources a caller can access. This will provide information on how the resource is used. One of UPLOAD, DOWNLOAD or BOTH processes. It will also specify if additional Primary Group information is also required as part of those processes.

Input (Request) Message Fields

NA

Output (Response) Message Fields

name="auditID" type="xs:string" pattern=

"[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"

The audit UID is an identifier created by the service for each SOAP message processed. The UID returned is a version 4 Universally Unique Identifier (UUID). A UUID is a 16-byte (128-bit) number. In its canonical form, a UUID consists of 32 hexadecimal digits, displayed in 5 groups separated by hyphens, in the form 8-4-4-4-12 for a total of 36 characters (32 digits and 4 hyphens).

name="access" type="tns:resourceAccess"

The access permissions of the resource type. One of UPLOAD, DOWNLOAD, BOTH.

name="groupRequired" type="xs:boolean"

Set to true if a group claim submission number is required to use this file.

name="descriptionEn" type="xs:string"

name="descriptionFr" type="xs:string"

The description of the resource type specified in the "resource Type" field below.

name="resourceType" type="xs:string"

The resource type being defined. Maximum of 3 characters in length. See MCEDT CURRENTLY SUPPORTED FILE/RESOURCE TYPES ADDENDUM: for a list of the currently supported types.

name="csns" type="tns:csnData"

A list of csn/group pairs that represent what the user must specify to use the resource. A solo claim submission number will always be provided. A group will only be provided if access has been restricted to a specific group identity by a Service User.

name="code" type="xs:string"

The response code for the request.

Code	Description
EEDTS00102	MOH ID not Valid
EEDTS0050	User not Allowed

name="msg" type="xs:string"

The response code message for the request.

Testing

Conformance testing must be completed for MCEDT. For more details please refer to the Testing section in the *'MOHLTC EBS – Generic Security Specification'* document or Section 3 Conformance Testing in the *Medical Claims Electronic Data Transfer Reference Manual*.

APPENDIX A: Error Codes

Character based error codes are returned as well as textual descriptions of the error. All ministry specific error codes are 9 characters.

The following are the ministry specific error codes that may be returned within an EBS Fault accompanied by brief explanations.

EBS Fault Code	Error Comment
SMIDL0100	System not initialized correctly; contact your technical support or software vendor.
SMIDL0203	Service is not available; contact your technical support or software vendor.
SMIDL0204	General System Error; contact your technical support or software vendor.

APPENDIX B: The Message WSDL

```
<?xml version="1.0" encoding="UTF-8"?><!-- Generated by JAX-WS RI at http://jax-ws.dev.java.net. RI's version is JAX-WS RI 2.1.6
in JDK 6. --><definitions name="EDTCoreService" targetNamespace="http://edt.health.ontario.ca/"
xmlns="http://schemas.xmlsoap.org/wsdl/" xmlns:ebs="http://ebs.health.ontario.ca/" xmlns:edt="http://edt.health.ontario.ca/"
xmlns:idp="http://idp.ebs.health.ontario.ca/" xmlns:msa="http://msa.ebs.health.ontario.ca/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:sp="http://schemas.xmlsoap.org/ws/2005/07/securitypolicy"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/" xmlns:wsdlsoap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
wssecurity-secext-1.0.xsd" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```
<types>
```

```
<xsd:schema>
```

```
<xsd:import namespace="http://ebs.health.ontario.ca/" schemaLocation="EBSFault_schema.xsd"/>
```

```
<xsd:import namespace="http://ebs.health.ontario.ca/" schemaLocation="EBS_schema.xsd"/>
```

```
<xsd:import namespace="http://edt.health.ontario.ca/" schemaLocation="EDTService_schema.xsd"/>
```

```
<xsd:import namespace="http://msa.ebs.health.ontario.ca/" schemaLocation="MSA_schema.xsd"/>
```

```
<xsd:import namespace="http://idp.ebs.health.ontario.ca/" schemaLocation="IDP_schema.xsd"/>
```

```
</xsd:schema>
```

```
</types>
```

```
<wsp:Policy wsu:Id="request-policy">
```

```
<wsp:ExactlyOne>
```

```
<wsp:All>
```

```
<wsp:All>
```

```
<sp:SignedSupportingTokens>
```

```
<sp:UsernameToken>
```

```

        <wsp:Policy>
            <wsp:All>
                <sp:NoPassword/>
                <sp:WssUsernameToken10/>
            </wsp:All>
        </wsp:Policy>
    </sp:UsernameToken>
</sp:SignedSupportingTokens>
</wsp:All>
<wsp:ExactlyOne>
    <wsp:All>
        <sp:RequiredParts>
            <sp:Header Name="EBS" Namespace="http://ebs.health.ontario.ca/" />
        </sp:RequiredParts>
        <sp:RequiredParts>
            <sp:Header Name="MSA" Namespace="http://msa.ebs.health.ontario.ca/" />
        </sp:RequiredParts>
        <sp:RequiredParts>
            <sp:Header Name="SoftwareConformanceKey" Namespace="" />
        </sp:RequiredParts>
        <sp:RequiredParts>
            <sp:Header Name="AuditId" Namespace="" />
        </sp:RequiredParts>
        <sp:RequiredParts>
            <sp:Header Name="ServiceUserMUID" Namespace="" />
        </sp:RequiredParts>
    </wsp:All>
</wsp:ExactlyOne>

```

```
<sp:RequiredParts>
  <sp:Header Name="UserID" Namespace=""/>
</sp:RequiredParts>
<sp:RequiredParts>
  <sp:Header Name="Timestamp"
    Namespace="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
    utility-1.0.xsd"/>
</sp:RequiredParts>
</wsp:All>
</wsp:ExactlyOne>
<wsp:ExactlyOne>
  <wsp:All>
    <sp:SignedParts>
      <sp:Header Name="EBS" Namespace="http://ebs.health.ontario.ca/">
      <sp:Header Name="MSA" Namespace="http://msa.ebs.health.ontario.ca/">
      <sp:Header Name="Timestamp"
        Namespace="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
        utility-1.0.xsd"/>
      <sp:Header Name="UsernameToken"
        Namespace="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
        utility-1.0.xsd"/>
      <sp:Body/>
    </sp:SignedParts>
  </wsp:All>
</wsp:ExactlyOne>
</wsp:All>
<wsp:All>
```

```
<wsp:All>
  <sp:SignedSupportingTokens>
    <sp:UsernameToken>
      <wsp:Policy>
        <wsp:All>
          <sp:WssUsernameToken10/>
        </wsp:All>
      </wsp:Policy>
    </sp:UsernameToken>
  </sp:SignedSupportingTokens>
</wsp:All>
<wsp:ExactlyOne>
  <wsp:All>
    <sp:SignedParts>
      <sp:Header Name="EBS" Namespace="http://ebs.health.ontario.ca/" />
      <sp:Header Name="IDP" Namespace="http://idp.ebs.health.ontario.ca/" />
      <sp:Header Name="Timestamp"
        Namespace="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" />
      <sp:Header Name="UsernameToken"
        Namespace="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" />
      <sp:Body/>
    </sp:SignedParts>
  </wsp:All>
</wsp:ExactlyOne>
```

```
<wsp:ExactlyOne>
  <wsp:All>
    <sp:RequiredParts>
      <sp:Header Name="EBS" Namespace="http://ebs.health.ontario.ca/" />
    </sp:RequiredParts>
    <sp:RequiredParts>
      <sp:Header Name="IDP" Namespace="http://idp.ebs.health.ontario.ca/" />
    </sp:RequiredParts>
    <sp:RequiredParts>
      <sp:Header Name="SoftwareConformanceKey" Namespace="" />
    </sp:RequiredParts>
    <sp:RequiredParts>
      <sp:Header Name="AuditId" Namespace="" />
    </sp:RequiredParts>
    <sp:RequiredParts>
      <sp:Header Name="ServiceUserMUID" Namespace="" />
    </sp:RequiredParts>
    <sp:RequiredParts>
      <sp:Header Name="Timestamp"
        Namespace="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
        utility-1.0.xsd" />
    </sp:RequiredParts>
  </wsp:All>
</wsp:ExactlyOne>
</wsp:All>
</wsp:ExactlyOne>
```

```
</wsp:Policy>
```

```
    <wsdl:message name="EBSHeader">
      <wsdl:part element="ebs:EBS" name="ebsrequest_header"/>
    </wsdl:message>
    <wsdl:message name="MSAHeader">
      <wsdl:part element="msa:MSA" name="msarequest_header"/>
    </wsdl:message>
    <wsdl:message name="IDPHeader">
      <wsdl:part element="idp:IDP" name="idprequest_header"/>
    </wsdl:message>
```

```
<message name="upload">
  <part element="edt:upload" name="parameters"/>
</message>
<message name="uploadResponse">
  <part element="edt:uploadResponse" name="parameters"/>
</message>
<message name="submit">
  <part element="edt:submit" name="parameters"/>
</message>
<message name="submitResponse">
  <part element="edt:submitResponse" name="parameters"/>
</message>
<message name="list">
  <part element="edt:list" name="parameters"/>
```



```
</message>
<message name="listResponse">
  <part element="edt:listResponse" name="parameters"/>
</message>
<message name="info">
  <part element="edt:info" name="parameters"/>
</message>
<message name="infoResponse">
  <part element="edt:infoResponse" name="parameters"/>
</message>
<message name="update">
  <part element="edt:update" name="parameters"/>
</message>
<message name="updateResponse">
  <part element="edt:updateResponse" name="parameters"/>
</message>
<message name="download">
  <part element="edt:download" name="parameters"/>
</message>
<message name="downloadResponse">
  <part element="edt:downloadResponse" name="parameters"/>
</message>
<message name="delete">
  <part element="edt:delete" name="parameters"/>
</message>
<message name="deleteResponse">
```

```
<part element="edt:deleteResponse" name="parameters"/>
</message>
<message name="getTypeList">
  <part element="edt:getTypeList" name="parameters"/>
</message>
<message name="getTypeListResponse">
  <part element="edt:getTypeListResponse" name="parameters"/>
</message>
<message name="faultexception">
  <part element="ebs:EBSFault" name="Fault"/>
</message>

<portType name="EDTDelegate">
  <operation name="upload">
    <input message="edt:upload"/>
    <output message="edt:uploadResponse"/>
    <fault message="edt:faultexception" name="FaultException"/>
  </operation>
  <operation name="submit">
    <input message="edt:submit"/>
    <output message="edt:submitResponse"/>
    <fault message="edt:faultexception" name="FaultException"/>
  </operation>
  <operation name="list">
    <input message="edt:list"/>
    <output message="edt:listResponse"/>
  </operation>
</portType>
```

```
<fault message="edt:faultexception" name="FaultException"/>
</operation>
<operation name="info">
  <input message="edt:info"/>
  <output message="edt:infoResponse"/>
  <fault message="edt:faultexception" name="FaultException"/>
</operation>
<operation name="update">
  <input message="edt:update"/>
  <output message="edt:updateResponse"/>
  <fault message="edt:faultexception" name="FaultException"/>
</operation>
<operation name="download">
  <input message="edt:download"/>
  <output message="edt:downloadResponse"/>
  <fault message="edt:faultexception" name="FaultException"/>
</operation>
<operation name="delete">
  <input message="edt:delete"/>
  <output message="edt:deleteResponse"/>
  <fault message="edt:faultexception" name="FaultException"/>
</operation>
<operation name="getTypeList">
  <input message="edt:getTypeList"/>
  <output message="edt:getTypeListResponse"/>
  <fault message="edt:faultexception" name="FaultException"/>
```

```
</operation>
</portType>
<binding name="EDTPortBinding" type="edt:EDTDelegate">
  <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>

  <operation name="upload">
    <soap:operation soapAction=""/>
    <input>
      <wsp:PolicyReference URI="#request-policy"/>
      <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
      <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
      <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
      <soap:body parts="parameters" use="literal"/>
    </input>
    <output>
      <soap:body use="literal"/>
    </output>
    <fault name="FaultException">
      <soap:fault name="FaultException" use="literal"/>
    </fault>
  </operation>
  <operation name="submit">
    <soap:operation soapAction=""/>
    <input>
      <wsp:PolicyReference URI="#request-policy"/>
      <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
```

```
        <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
        <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
    <soap:body parts="parameters" use="literal"/>
</input>
<output>
    <soap:body use="literal"/>
</output>
<fault name="FaultException">
    <soap:fault name="FaultException" use="literal"/>
</fault>
</operation>
<operation name="list">
    <soap:operation soapAction=""/>
    <input>
        <wsp:PolicyReference URI="#request-policy"/>
        <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
        <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
        <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
        <soap:body parts="parameters" use="literal"/>
    </input>
    <output>
        <soap:body use="literal"/>
    </output>
    <fault name="FaultException">
        <soap:fault name="FaultException" use="literal"/>
    </fault>
</operation>
```

```
</operation>
<operation name="info">
  <soap:operation soapAction=""/>
  <input>
    <wsp:PolicyReference URI="#request-policy"/>
    <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
    <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
    <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
    <soap:body parts="parameters" use="literal"/>
  </input>
  <output>
    <soap:body use="literal"/>
  </output>
  <fault name="FaultException">
    <soap:fault name="FaultException" use="literal"/>
  </fault>
</operation>
<operation name="update">
  <soap:operation soapAction=""/>
  <input>
    <wsp:PolicyReference URI="#request-policy"/>
    <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
    <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
    <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
    <soap:body parts="parameters" use="literal"/>
  </input>
```

```
<output>
  <soap:body use="literal"/>
</output>
<fault name="FaultException">
  <soap:fault name="FaultException" use="literal"/>
</fault>
</operation>
<operation name="download">
  <soap:operation soapAction=""/>
  <input>
    <wsp:PolicyReference URI="#request-policy"/>
    <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
    <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
    <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
    <soap:body parts="parameters" use="literal"/>
  </input>
  <output>
    <soap:body use="literal"/>
  </output>
  <fault name="FaultException">
    <soap:fault name="FaultException" use="literal"/>
  </fault>
</operation>
<operation name="delete">
  <soap:operation soapAction=""/>
  <input>
```

```
        <wsp:PolicyReference URI="#request-policy"/>
        <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
        <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
        <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
        <soap:body parts="parameters" use="literal"/>
    </input>
    <output>
        <soap:body use="literal"/>
    </output>
    <fault name="FaultException">
        <soap:fault name="FaultException" use="literal"/>
    </fault>
</operation>
<operation name="getTypeList">
    <soap:operation soapAction=""/>
    <input>
        <wsp:PolicyReference URI="#request-policy"/>
        <wsdlsoap:header message="edt:EBSHeader" part="ebsrequest_header" use="literal"/>
        <wsdlsoap:header message="edt:MSAHeader" part="msarequest_header" use="literal"/>
        <wsdlsoap:header message="edt:IDPHeader" part="idprequest_header" use="literal"/>
        <soap:body parts="parameters" use="literal"/>
    </input>
    <output>
        <soap:body use="literal"/>
    </output>
    <fault name="FaultException">
```



```
        <soap:fault name="FaultException" use="literal"/>
      </fault>
    </operation>
  </binding>
  <service name="EDTService">
    <port binding="edt:EDTPortBinding" name="EDTPort">
      <soap:address location="https://ws.ebs.health.gov.on.ca:1441/EDTService/EDTService"/>
    </port>
  </service>
</definitions>
```

APPENDIX C: Message Schema

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema targetNamespace="http://edt.health.ontario.ca/" version="1.0"
  xmlns:tns="http://edt.health.ontario.ca/"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">

  <xs:element name="delete" type="tns:delete"/>

  <xs:element name="deleteResponse" type="tns:deleteResponse"/>

  <xs:element name="download" type="tns:download"/>

  <xs:element name="downloadResponse" type="tns:downloadResponse"/>

  <xs:element name="getTypeList" type="tns:getTypeList"/>

  <xs:element name="getTypeListResponse" type="tns:getTypeListResponse"/>

  <xs:element name="info" type="tns:info"/>

  <xs:element name="infoResponse" type="tns:infoResponse"/>

  <xs:element name="list" type="tns:list"/>
```

```
<xs:element name="listResponse" type="tns:listResponse"/>

<xs:element name="submit" type="tns:submit"/>

<xs:element name="submitResponse" type="tns:submitResponse"/>

<xs:element name="update" type="tns:update"/>

<xs:element name="updateResponse" type="tns:updateResponse"/>

<xs:element name="upload" type="tns:upload"/>

<xs:element name="uploadResponse" type="tns:uploadResponse"/>

<xs:simpleType name="audit">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9A-F]{8}-[0-9A-F]{4}-4[0-9A-F]{3}-[89AB][0-9A-F]{3}-[0-9A-F]{12}"/>
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="upload">
  <xs:sequence>
    <xs:element maxOccurs="5" minOccurs="1" name="upload" type="tns:uploadData"/>
  </xs:sequence>
</xs:complexType>
```

```
<xs:complexType name="uploadData">
  <xs:sequence>
    <xs:element minOccurs="1" name="content" type="xs:base64Binary"/>
    <xs:element minOccurs="0" name="description" type="xs:string"/>
    <xs:element minOccurs="1" name="resourceType" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="uploadResponse">
  <xs:sequence>
    <xs:element minOccurs="1" name="return" type="tns:resourceResult"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="resourceResult">
  <xs:sequence>
    <xs:element minOccurs="1" name="auditID" type="tns:audit"/>
    <xs:element maxOccurs="unbounded" minOccurs="1" name="response" type="tns:responseResult"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="responseResult">
  <xs:sequence>
    <xs:element minOccurs="0" name="description" type="xs:string"/>
    <xs:element minOccurs="1" name="resourceID" type="xs:integer"/>
    <xs:element minOccurs="1" name="result" type="tns:commonResult"/>
  </xs:sequence>
</xs:complexType>
```

```
        <xs:element minOccurs="1" name="status" type="tns:resourceStatus"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="commonResult">
    <xs:sequence>
        <xs:element minOccurs="1" name="code" type="xs:string"/>
        <xs:element minOccurs="1" name="msg" type="xs:string"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="getTypeList">
    <xs:sequence/>
</xs:complexType>

<xs:complexType name="getTypeListResponse">
    <xs:sequence>
        <xs:element minOccurs="1" name="return" type="tns:typeListResult"/>
    </xs:sequence>
</xs:complexType>

<xs:complexType name="typeListResult">
    <xs:sequence>
        <xs:element minOccurs="1" name="auditID" type="tns:audit"/>
        <xs:element maxOccurs="unbounded" minOccurs="1" name="data" type="tns:typeListData"/>
    </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="csnData">
```

```
  <xs:sequence>
```

```
    <xs:element minOccurs="0" name="soloCsn" type="xs:string"/>
```

```
    <xs:element minOccurs="0" name="groupCsn" type="xs:string"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="typeListData">
```

```
  <xs:sequence>
```

```
    <xs:element minOccurs="1" name="access" type="tns:resourceAccess"/>
```

```
    <xs:element minOccurs="1" name="descriptionEn" type="xs:string"/>
```

```
    <xs:element minOccurs="1" name="descriptionFr" type="xs:string"/>
```

```
    <xs:element minOccurs="1" name="groupRequired" type="xs:boolean"/>
```

```
    <xs:element minOccurs="1" name="resourceType" type="xs:string"/>
```

```
    <xs:element minOccurs="1" name="result" type="tns:commonResult"/>
```

```
    <xs:element maxOccurs="unbounded" minOccurs="0" name="csns" type="tns:csnData"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="info">
```

```
  <xs:sequence>
```

```
    <xs:element maxOccurs="100" minOccurs="1" name="resourceIDs" type="xs:integer"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="infoResponse">
  <xs:sequence>
    <xs:element minOccurs="1" name="return" type="tns:detail"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="detail">
  <xs:sequence>
    <xs:element minOccurs="1" name="auditID" type="tns:audit"/>
    <xs:element maxOccurs="50" minOccurs="0" name="data" type="tns:detailData"/>
    <xs:element minOccurs="1" name="resultSize" type="xs:integer"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="detailData">
  <xs:sequence>
    <xs:element minOccurs="1" name="createTimestamp" type="xs:dateTime"/>
    <xs:element minOccurs="0" name="description" type="xs:string"/>
    <xs:element minOccurs="0" name="resourceType" type="xs:string"/>
    <xs:element minOccurs="0" name="modifyTimestamp" type="xs:dateTime"/>
    <xs:element minOccurs="1" name="resourceID" type="xs:integer"/>
    <xs:element minOccurs="1" name="result" type="tns:commonResult"/>
    <xs:element minOccurs="1" name="status" type="tns:resourceStatus"/>
  </xs:sequence>
</xs:complexType>
```

```
<xs:complexType name="list">
  <xs:sequence>
    <xs:element minOccurs="0" name="resourceType" type="xs:string"/>
    <xs:element minOccurs="0" name="status" type="tns:resourceStatus"/>
    <xs:element minOccurs="0" name="pageNo" type="xs:integer"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="listResponse">
  <xs:sequence>
    <xs:element minOccurs="1" name="return" type="tns:detail"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="update">
  <xs:sequence>
    <xs:element maxOccurs="5" minOccurs="1" name="updates" type="tns:updateRequest"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="updateRequest">
  <xs:sequence>
    <xs:element minOccurs="1" name="content" type="xs:base64Binary"/>
    <xs:element minOccurs="1" name="resourceID" type="xs:integer"/>
  </xs:sequence>
</xs:complexType>
```



```
</xs:complexType>
```

```
<xs:complexType name="updateResponse">
```

```
  <xs:sequence>
```

```
    <xs:element minOccurs="1" name="return" type="tns:resourceResult"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="download">
```

```
  <xs:sequence>
```

```
    <xs:element maxOccurs="5" minOccurs="1" name="resourceIDs" type="xs:integer"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="downloadResponse">
```

```
  <xs:sequence>
```

```
    <xs:element minOccurs="1" name="return" type="tns:downloadResult"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="downloadResult">
```

```
  <xs:sequence>
```

```
    <xs:element minOccurs="1" name="auditID" type="tns:audit"/>
```

```
    <xs:element maxOccurs="5" minOccurs="0" name="data" type="tns:downloadData"/>
```

```
  </xs:sequence>
```

```
</xs:complexType>
```

```
<xs:complexType name="downloadData">
  <xs:sequence>
    <xs:element minOccurs="1" name="content" type="xs:base64Binary"/>
    <xs:element minOccurs="1" name="resourceID" type="xs:integer"/>
    <xs:element minOccurs="1" name="resourceType" type="xs:string"/>
    <xs:element minOccurs="1" name="description" type="xs:string"/>
    <xs:element minOccurs="1" name="result" type="tns:commonResult"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="submit">
  <xs:sequence>
    <xs:element maxOccurs="100" minOccurs="1" name="resourceIDs" type="xs:integer"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="submitResponse">
  <xs:sequence>
    <xs:element minOccurs="1" name="return" type="tns:resourceResult"/>
  </xs:sequence>
</xs:complexType>

<xs:complexType name="delete">
  <xs:sequence>
    <xs:element maxOccurs="100" minOccurs="1" name="resourceIDs" type="xs:integer"/>
  </xs:sequence>
</xs:complexType>
```

```
</xs:sequence>
</xs:complexType>

<xs:complexType name="deleteResponse">
  <xs:sequence>
    <xs:element minOccurs="1" name="return" type="tns:resourceResult"/>
  </xs:sequence>
</xs:complexType>

<xs:simpleType name="resourceStatus">
  <xs:restriction base="xs:string">
    <xs:enumeration value="UPLOADED"/>
    <xs:enumeration value="SUBMITTED"/>
    <xs:enumeration value="WIP"/>
    <xs:enumeration value="DOWNLOADABLE"/>
    <xs:enumeration value="DELETED"/>
    <xs:enumeration value="APPROVED"/>
    <xs:enumeration value="DENIED"/>
  </xs:restriction>
</xs:simpleType>

<xs:simpleType name="resourceAccess">
  <xs:restriction base="xs:string">
    <xs:enumeration value="UPLOAD"/>
    <xs:enumeration value="DOWNLOAD"/>
    <xs:enumeration value="BOTH"/>
  </xs:restriction>
</xs:simpleType>
```

```
    </xs:restriction>  
  </xs:simpleType>  
</xs:schema>
```

APPENDIX D: MSA Model Message Example

```
<soapenv:Envelope
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:msa="http://msa.ebs.health.ontario.ca/"
xmlns:idp="http://idp.ebs.health.ontario.ca/"
xmlns:edt="http://edt.health.ontario.ca/"
xmlns:ebs=http://ebs.health.ontario.ca/>

  <soapenv:Header>
    <ns2:EBS wsu:Id="id-1" xmlns:ns2="http://ebs.health.ontario.ca/" >
      <SoftwareConformanceKey>444561ee-277f-77b2-c664-7a9923jfgh1b</SoftwareConformanceKey>
      <AuditId>f68e6ff9-74f7-4022-8618-ec2cf0ee4b6a</AuditId>
    </ns2:EBS>
    <ns2:MSA wsu:Id="id-2" xmlns:ns2="http://msa.ebs.health.ontario.ca/" >
      <ServiceUserMUID>4523394</ServiceUserMUID>
      <UserID>johndoe</UserID>
    </ns2:MSA>
    <wsse:Security SOAP-ENV:mustUnderstand="1">
      <wsu:Timestamp wsu:Id="id-3">
        <wsu:Created>2012-06-26T16:18:15.185Z</wsu:Created>
        <wsu:Expires>2012-06-26T16:18:45.185Z</wsu:Expires>
      </wsu:Timestamp>
      <wsse:UsernameToken wsu:Id="id-4">
        <wsse:Username>72214255</wsse:Username>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <body>
    <ns1:MSA wsu:Id="id-5" xmlns:ns1="http://msa.ebs.health.ontario.ca/" >
      <ServiceUserMUID>4523394</ServiceUserMUID>
      <UserID>johndoe</UserID>
    </ns1:MSA>
  </body>
</soapenv:Envelope>
```

```

</wsse:UsernameToken>
<wsse:BinarySecurityToken
  EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary"
  ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#X509v3"
  wsu:Id="X509-0EE1C2718CEDCA9FC213407274954261">

    MIICMzCCAZygAwIBAgIET1e+dDANBgkqhkiG9w0BAQUFADBBeMQswCQYDVQQGEwJDQTEQMA4GA1UECBMT250YXJpbzENMA5GA1UEChMET0hJUD
    EVMBMGA1UECxMMUmVnaXN0cmF0aW9uMRcwFQYDVQQDEw4xNDIuMTQ1LjcwLjE3NzAeFw0xMjAzMDcyMDAwNTJaFw0xMzAzMDcyMDAwNTJaMF4x
    CzAJBgNVBAYTAkNBMRAdDgYDVQQIEwdPbnRhcmlvMQ0wCwYDVQQKEwRPSElQMRUwEwYDVQLEwxSZWdpY3RyYXRpb24xZzAVBgNVBAMTDjE0Mi
    4xNDUuNzAuMTc3MIGfMA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCs/JIP6CE5IkfTnD/c56K+QAYqETdLvW1xXJ6ipkVhjjC2ASKuuH4fVhby
    xo2B4VugsL9r4E5jHEKoi+GDK0LlLZRfSy0cB8IcpXonAuGqMzhCoEQ1CdxNb9etMyvQGRKEBgnIKKxTvpTyZdpYDi92up5E+FYl3jEejhp+1i
    DFJQIDAQABMA0GCSqGSIb3DQEBBQUAA4GBAHn8VZS169BJMa4E6SNLnY7u80zSh90mbrTUWjM1dEicv3jQMmsrWHfoCt+nRSqfNLUTLc8U0Lqi
    B3jnnNJgJt1T7Sp8eUZPdH0gY3i83ZXA8HDFKMZF3qL8I8ncu8FPcZGYBNhYrGjXXsuqXimiTIjxgm06ErRa/51szOFFxWrB

  </wsse:BinarySecurityToken>
  <ds:Signature Id="SIG-6" xmlns:ds="http://www.w3.org/2000/09/xmldsig#" >
    <ds:SignedInfo>
      <ds:CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
        <ec:InclusiveNamespaces PrefixList="SOAP-ENV ebs soap-sec soapenv sp tns wsdL wsp wsse wsu xs xsi"
          xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
      </ds:CanonicalizationMethod>
      <ds:SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
      <ds:Reference URI="#id-1">
        <ds:Transforms>
          <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
            <ec:InclusiveNamespaces
              PrefixList="SOAP-ENV ebs soap-sec soapenv sp tns wsdL wsp wsse wsu xs xsi"
              xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
          </ds:Transform>
        </ds:Transforms>
      </ds:Reference>
    </ds:SignedInfo>
  </ds:Signature>

```

```
</ds:Transforms>
<ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
<ds:DigestValue>FkhA37C0GmsKeEH50LAGhKntvRpD0+x0GsGzXAV210k=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-2">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces
        PrefixList="SOAP-ENV ebs soap-sec soapenv sp tns wsdL wsp wsse wsu xs xsi"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
  <ds:DigestValue>RA101voUNdV9+hi6IzNNxkTHfEdu2pu6fpPiwN23JGI=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-3">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces PrefixList="SOAP-ENV ebs soap-sec soapenv sp tns wsdL wsp wsse xs xsi"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
  <ds:DigestValue>3vVj2VEbLKEvGy4yt7k8i2BeWU0aCygnFMduT7EyP3A=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-4">
```

```
<ds:Transforms>
  <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
    <ec:InclusiveNamespaces PrefixList="SOAP-ENV ebs soap-sec soapenv sp tns wsdL wsp wsu xs xsi"
      xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
  </ds:Transform>
</ds:Transforms>
<ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
<ds:DigestValue>yF0mFgMDHMB00wIEsB3azib2EX7fR+Ich03J19kFMVE=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-5">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces PrefixList="SOAP-ENV ebs soap-sec sp tns wsdL wsp wsse wsu xs xsi"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
  <ds:DigestValue>zoxMcAQ2WLBiir333Njk52r4axwznflX+KxMQTPFvfQ=</ds:DigestValue>
</ds:Reference>
</ds:SignedInfo>
<ds:SignatureValue>

Hm0iZS4gZbxv07+sLjyi7Vfg3Rfpvr3IVnaHfRp4aKvg5yBFLLocPIYwhUhmCCs1LXrJxR0hsbe0K2sz3ML5hH+PDEGetLPKSN9R1x9K95w7V
1JQcTUULiVgNGLCfxgFV2HNY1iNvltC7C0S+7w4xSgsY4KlVgrBw0T1srhHpUA=
</ds:SignatureValue>
<ds:KeyInfo Id="KI-0EE1C2718CEDCA9FC213407274954662">
  <wsse:SecurityTokenReference wsu:Id="STR-0EE1C2718CEDCA9FC213407274954663">
```



```
<wsse:Reference URI="#X509-0EE1C2718CEDCA9FC213407274954261"
  ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-1.0#X509v3" />
</wsse:SecurityTokenReference>
</ds:KeyInfo>
</ds:Signature>
</wsse:Security>
</soapenv:Header>
<soapenv:Body wsu:Id="id-5"
  xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <edt:upload>
    <upload>
      <content>
        <inc:Include href=cid:2341682853256 xmlns:inc="http://www.w3.org/2004/08/xop/include" />
      </content>
      <description>00123</description>
      <resourceType>CL</resourceType>
    </upload>
  </edt:upload>
</soapenv:Body>
</soapenv:Envelope>
```

APPENDIX E: IDP Model Message Example

```
<soapenv:Envelope
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:msa="http://msa.ebs.health.ontario.ca/"
xmlns:idp="http://idp.ebs.health.ontario.ca/"
xmlns:edt="http://edt.health.ontario.ca/"
xmlns:ebs="http://ebs.health.ontario.ca/">

  <soapenv:Header>
    <ebs:EBS wsu:Id="id-4"
      xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <SoftwareConformanceKey>444361ee-277f-7732-c684-7a9923jfgh1b</SoftwareConformanceKey>
      <AuditId>124355467675</AuditId>
    </ebs:EBS>
    <idp:IDP wsu:Id="id-3"
      xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
      <ServiceUserMUID>1111222</ServiceUserMUID>
    </idp:IDP>
    <wsse:Security soapenv:mustUnderstand="1"
      xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
      xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
      <wsse:BinarySecurityToken
        EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary"
```

[illegible]

<ds:Transforms>

```
<ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
  <ec:InclusiveNamespaces PrefixList="ebs edt idp msa soapenv"
    xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
</ds:Transform>
</ds:Transforms>
<ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
<ds:DigestValue>peTHpiEd5ujPqxNuKGN0k4p7up8c0dFPuRXbpQ+eMwI=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#TS-1">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces PrefixList="wsse ebs edt idp msa soapenv"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
  <ds:DigestValue>DqLqNQVHwzHRx7amwoYxEMwxN2g0/rND2I13WPP1Vhw=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-3">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces PrefixList="ebs edt msa soapenv"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmlenc#sha256" />
```

```
<ds:DigestValue>K4IrndAA4zBmkumIfgKcIuiKA8dmzWGdKo5aq45LHg=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-4">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces PrefixList="edt idp msa soapenv"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmenc#sha256" />
  <ds:DigestValue>o92xRJQNwGz0Hv7DX87vSYUScX0qHL/bFGE3GmtUzQg=</ds:DigestValue>
</ds:Reference>
<ds:Reference URI="#id-5">
  <ds:Transforms>
    <ds:Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#">
      <ec:InclusiveNamespaces PrefixList="ebs edt idp msa"
        xmlns:ec="http://www.w3.org/2001/10/xml-exc-c14n#" />
    </ds:Transform>
  </ds:Transforms>
  <ds:DigestMethod Algorithm="http://www.w3.org/2001/04/xmenc#sha256" />
  <ds:DigestValue>svNyvvP+MrjIYLZFsg+bgw//8IPNVvI09px3vYUfW3I=</ds:DigestValue>
</ds:Reference>
</ds:SignedInfo>
<ds:SignatureValue>
  qDSZlgY/aTF0zzo1C4tx+1E8ertrbmBySRxEK6sJ1Jct/77TLV5PBGnAme9Ttdmzf6h7/qb4rBGL
  76LM0PaCQ9xm3DTsSQ0z/So82G+/kX8M9TPY9D44+dv1B+cXm9rPn2BLMSVwtJf0kwI22SmRzMTR
  6a6jfNYkGga6ZwZC9NLF65/KTvsyZ39vOd03T5GYc15RSjHKVBggowmKm7x5PHrhU+3gClEbthp8
```

```
+Fgmmd9PJ0tl9WunzR7NpY79xRNGxmDmL8hLvE4+uIc//b6TvrbbGB2t8IWb5e5Wdz+ssHgMm0802
wFwGXlVxvSHpEJroHz50vRgh7PKGlUSZP9fWkg==
</ds:SignatureValue>
<ds:KeyInfo Id="KI-04FD51796CB607011413612828892812">
  <wsse:SecurityTokenReference wsu:Id="STR-04FD51796CB607011413612828892813">
    <wsse:Reference
      URI="#X509-04FD51796CB607011413612828891871"
      ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-
token-profile-1.0#X509v3" />
    </wsse:SecurityTokenReference>
  </ds:KeyInfo>
</ds:Signature>
<wsse:UsernameToken wsu:Id="UsernameToken-2">
  <wsse:Username>johndoe@examplemail.com</wsse:Username>
  <wsse:Password
    Type="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-
1.0#PasswordText">*****</wsse:Password>
  </wsse:UsernameToken>
  <wsu:Timestamp wsu:Id="TS-1">
    <wsu:Created>2013-02-19T14:08:08Z</wsu:Created>
    <wsu:Expires>2013-02-19T14:08:38Z</wsu:Expires>
  </wsu:Timestamp>
</wsse:Security>
</soapenv:Header>
<soapenv:Body wsu:Id="id-5"
  xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">
  <edt:upload>
```

```
<upload>
  <content>
    <inc:Include href=cid:2341682853256 xmlns:inc="http://www.w3.org/2004/08/xop/include" />
  </content>
  <description>00123</description>
  <resourceType>CL</resourceType>
</upload>
</edt:upload>
</soapenv:Body>
</soapenv:Envelope>
```

MCEDT Currently Supported File/Resource Types Addendum

Inbound

File Type	Description
CL	Claims
OB	OBEC
SDC	Stale Dated Claims
RHB	Reciprocal Hospital Billing

Outbound

File Type	Description
OO	OBEC Response
ER	Error Reports
ES	Error Report Extract
RA	Remittance Advice
RS	Remittance Advice Extract
BE	Batch Edit

AH	Academic Health Governance Report
CO	EC Outside Use report
CS	EC Summary report
NS	Northern Specialist APP Governance
MR	Claims Mail File Reject Message
MO	OBEC Mail File Reject Message
GCM	General Ministry Communications

Claim File Upload Error Codes Addendum

Returned Error Code	Description
ECLAM0002	Mal Formed Header
ECLAM0003	No CSN specified
ECLAM0004	Invalid Health Number
ECLAM0005	Mal Formed Trailer. Claim Header – 1 header count does not match number of Claim Header – 1 headers in batch
ECLAM0006	Mal Formed Trailer. Claim Header – 2 header count does not match number of Claim Header – 2 headers in batch
ECLAM0007	Mal Formed Trailer. Item Record count does not match number of Item Records in batch
ECLAM0008	Records are not the correct width must be 79 bytes.

OBEC File Upload Error Codes Addendum

Returned Error Code	Description
EOBEC0001	OBEC File is empty
EOBEC0002	File is an invalid length
EOBEC0003	Mal Formed Header. The 'OBE' in the transaction code field is invalid.
EOBEC0004	Invalid Health Number length
EOBEC0005	Health Number is not numeric

Stale Dated Claims File Upload Error Codes Addendum

Returned Error Code	Description
ESDCL0002	Mal Formed Header
ESDCL0003	No CSN specified
ESDCL0004	Invalid Health Number
ESDCL0005	Mal Formed Trailer. Claim Header – 1 header count does not match number of Claim Header – 1 headers in batch
ESDCL0006	Mal Formed Trailer. Claim Header – 2 header count does not match number of Claim Header – 2 headers in batch
ESDCL0007	Mal Formed Trailer. Item Record count does not match number of Item Records in batch

