

# TMS, DMS and CMS Usage Guide for Falcon BMS 4.38.1

Carlos “Metal” Nader

Version 0.3.2.0+20260120 | Progress: Chapters 2/7 | Tables 0 | January 2026

## Contents

0.1	DMS Left/Right: Multifunction Display Format Cycling . . . . .	1
0.1.1	Concept and Orthogonality: Format Cycling vs. SOI Selection . . . . .	1
0.1.2	MFD Configuration . . . . .	1
0.1.2.1	Display Format Configuration (DTC) . . . . .	1
0.1.2.2	Primary, Secondary, and Tertiary format pages . . . . .	3
0.1.2.3	Format Cycling Mechanism: The Wrap-Around Sequence . . . . .	4
0.1.3	Cycling Constraints and Edge Cases . . . . .	4
0.1.3.1	BLANK Format Skipping . . . . .	4
0.1.3.2	Non-SOI-Candidate Formats (Edge Case) . . . . .	5
0.1.3.3	Format Persistence Across Master Mode Change . . . . .	5
0.1.4	DMS Left vs. DMS Right: Independent MFD Control . . . . .	5
0.1.5	DMS Left/Right Usage Table . . . . .	6

## 0.1 DMS Left/Right: Multifunction Display Format Cycling

### 0.1.1 Concept and Orthogonality: Format Cycling vs. SOI Selection

The DMS Left and DMS Right commands are fundamentally orthogonal to the DMS Up and DMS Down controls described in Sections ?? and ??. Whereas DMS Up and DMS Down select *which display* (HUD, Left MFD or Right MFD) becomes the Sensor of Interest (SOI), DMS Left and DMS Right cycle through different *format pages* displayed on *each MFD*, independently of which display is currently designated as SOI — **even if the HUD is the actual SOI, DMS Left/Right will actuate on each MFD.**

**Definition of Format Cycling:** Each MFD can display up to three different format pages, pre-configured during mission planning via the Data Transfer Cartridge (DTC) or directly by the pilot, in-flight. These three format pages are designated as PRIMARY, SECONDARY, and TERTIARY. DMS Left and DMS Right allow the pilot to cycle through these slots, advancing to the next format page with each button press. This operation does *not* change which display is SOI; it changes only what is currently shown on the screen.

It's important to understand that DMS Left *only* changes format pages on the Left MFD and DMS Right *only* changes format pages on the right MFD, on a continuous cycle that will be better detailed further down in this Section.

**Orthogonality Principle:** The critical distinction is this: DMS Up/Down operates on the **display selection axis** (designation of which display is SOI), whereas DMS Left/Right operates on the **format pages axis** (which page is shown on an MFD). A pilot can simultaneously manage both axes:

- Press DMS Down to transfer SOI from the Left MFD to the Right MFD (changes which display receives HOTAS commands).
- Press DMS Right to cycle the Right MFD to a different format page (changes what is displayed, independent of SOI).

This orthogonality is operationally powerful: the pilot can organize the MFD for increased situational awareness while simultaneously managing which display receives hands-on input (SOI). The two mechanisms do not interfere with each other and DMS Right/Left is not restricted by the current Master Mode.

### 0.1.2 MFD Configuration

#### 0.1.2.1 Display Format Configuration (DTC)

Each Master Mode (A-A, A-G, NAV) and also DGFT, MSL OVRD and Jettison has its own independent three-slot configuration, as preset in the DTC. When the pilot switches Master Modes in-flight, the avionics automatically load the format configuration for that mode and display the chosen format.

The formats can also be reconfigured by the pilot in flight, by pressing again the OSB corresponding to the actual format being displayed. See Dash-34 § 2.1.6.2 for a comprehensive explanation.

Below is a list of every possible display pages currently present in Falcon BMS that could be configured as an MFD format, either through the DTC or by the pilot in-flight. Note that not all of them can be SOI. When selecting, in any MFD, a format that can't be designated SOI, the *SOI is automatically transferred to the other MFD*.

Table 1: Falcon BMS Possible MFD Formats

Acronym	Full Name	Definition	Can be SOI
FCR	Fire Control Radar	Provides air-to-air and air-to-ground radar detection, tracking, and targeting data with multiple search and track modes for weapons employment	YES
HSD	Horizontal Situation Display	Presents tactical navigation, situational awareness, and positioning information on a moving map display for mission planning	YES
TGP	Targeting Pod	Displays targeting pod imagery for target acquisition, tracking, identification, and laser designation of air-to-ground targets	YES
WPN	Weapon/Stores Management	Shows weapons status, aircraft ordnance configuration, and munitions management for air-to-air and air-to-ground missions	YES
HAD	HARM Attack Display	Provides detection and targeting information from air defense radar sources for anti-radiation warfare missions	NO
FLIR	Forward Looking Infrared Navigation Pod	Displays thermal imaging data for navigation, target detection, and low-level flight operations in degraded visibility	NO
TFR	Terrain Following Radar Navigation Pod	Presents terrain elevation and clearance data for automated low-level navigation and terrain avoidance	NO
SMS	Stores Management System	Displays current weapons configuration, loadout, and stores management parameters and status information	NO
TCN	TACAN Format	Shows TACAN navigation aid position and bearing information for tactical air navigation and station keeping	NO
DTE	Data Transfer Equipment	Provides interface and status for external data link communications with ground stations and other aircraft	NO
FLCS	Digital Flight Control System	Displays flight control system parameters, status, and diagnostics for aircraft control system monitoring	NO

*Continues on next page*

Acronym	Full Name	Definition	Can be SOI
TEST	Test Format	Provides system test and diagnostic pages for built-in test (BIT) functions and aircraft system verification	NO
BLANK	Blank Format	Displays an empty/blank page with no symbology or information for display configuration flexibility	NO

### 0.1.2.2 Primary, Secondary, and Tertiary format pages

The PRIMARY, SECONDARY, and TERTIARY format pages configured by the pilot are accessed by pressing the corresponding button on the bottom row of each MFD. Each format page corresponds to one of the three central buttons in the lower OSB row of each MFD:

- **OSB 14 (left button):** PRIMARY slot
- **OSB 13 (center button):** SECONDARY slot
- **OSB 12 (right button):** TERTIARY slot

The diagram below illustrates the OSB layout in the F-16 MFD:

INSERIR IMAGEM MFD DE INTERNET

The three-slot architecture provides mission planning flexibility. During mission planning in the BMS Briefing, the pilot pre-configures which format pages are most useful for a given Master Mode. For instance, in air-to-air mode, the pilot might configure:

- PRIMARY (OSB 14) = FCR (Fire Control Radar page)
- SECONDARY (OSB 13) = HSD (Horizontal Situation Display)
- TERTIARY (OSB 12) = TGP (Targeting Pod page, for auxiliary visual cues)

With three slots, the pilot can quickly access the most relevant pages via DMS Left/Right presses. This is especially important in time-critical engagements.

**DTC Customization in Falcon BMS:** During mission planning in the BMS Briefing (MODES tab of the DTC page), the pilot can assign any valid format to any slot of any mode. For example, in air-to-air mode, the pilot might customize to:

- Left MFD: FCR | HSD | TGP (instead of FCR | BLANK | BLANK)

Or in air-to-ground mode:

- Left MFD: FCR | TGP | WPN
- Right MFD: SMS | HAD | HSD

These customizations are stored in the DTC and loaded automatically when the pilot takes off. They persist for the duration of the flight.

**Auto-Switch Behavior:** When the pilot presses the Master Mode button to transition from one mode to another (e.g., from A-A to A-G), the avionics automatically:

1. Load the three-slot configuration for the new Master Mode.
2. Display the PRIMARY format of the new mode.
3. Keep SOI on the same MFD (e.g., if SOI was Left MFD in A-A, it remains Left MFD in A-G; only the format changes).

**Critical implication:** Cycling via DMS Left/Right now uses the new mode's three slots, not the old mode's slots. If the pilot customizes A-A as FCR/HSD/TGP and A-G as FCR/TGP/WPN, then DMS Left cycling in A-A will advance through FCR→HSD→TGP, but DMS Left cycling in A-G will advance through FCR→TGP→WPN. The slots are mode-specific, not global.

—

### 0.1.2.3 Format Cycling Mechanism: The Wrap-Around Sequence

**Cycling Direction:** DMS Left and DMS Right advance through format slots in an anti-clockwise direction relative to the OSB button layout. For the Left MFD:

- DMS Left press 1: PRIMARY (OSB 14) → SECONDARY (OSB 13)
- DMS Left press 2: SECONDARY (OSB 13) → TERTIARY (OSB 12)
- DMS Left press 3: TERTIARY (OSB 12) → PRIMARY (OSB 14) [wrap-around]
- DMS Left press 4: PRIMARY → SECONDARY again [cycle repeats]

The same cyclic sequence applies to DMS Right for the Right MFD. The direction is consistent and predictable, allowing pilots to develop muscle memory.

**Wrap-Around Behavior:** After cycling through TERTIARY, the next DMS press returns to PRIMARY, creating an infinite loop. There is no “off” state or “hold” position. The cycling is continuous and wrap-around is instantaneous. If a slot is configured as BLANK (unused), cycling skips it automatically and advances to the next occupied slot (see Section 0.1.3.1).

**Press Type: Short Press (Tap Only):** DMS Left/Right respond to **short press only** (tap). There is no long-press or continuous-hold variant. A single tap advances to the next format; holding the button does *not* cycle continuously. This behavior is consistent across all Master Modes and all configurations. If the pilot needs to cycle through multiple slots, separate taps are required.

**Example Scenario:** A pilot in air-to-air mode has customized the Left MFD as FCR/HSD/TGP. Initially, the Left MFD displays FCR (PRIMARY). The pilot wants to check the tactical picture on HSD. The pilot presses DMS Left once. The Left MFD now displays HSD (SECONDARY). The pilot presses DMS Left again. The Left MFD now displays TGP (TERTIARY). The pilot decides to return to FCR. The pilot presses DMS Left once more. The Left MFD displays FCR again (wrap-around from TERTIARY back to PRIMARY). The SOI designation, if Left MFD was SOI, remains unchanged throughout these cycling operations.

—

## 0.1.3 Cycling Constraints and Edge Cases

### 0.1.3.1 BLANK Format Skipping

If one or more format slots are configured as BLANK (meaning no format is assigned to that slot, either by choice or by default), cycling automatically skips over BLANK slots and advances to the next non-BLANK slot.

**Example:** Configuration: PRIMARY = FCR, SECONDARY = BLANK, TERTIARY = HSD.

Cycling sequence:

- Press DMS Left (once): FCR → [skips BLANK] → HSD
- Press DMS Left (again): HSD → [skips BLANK] → FCR [wrap-around]
- Result: Only two visible formats cycle; BLANK is transparent.

This automatic skipping means that BLANK slots do *not* create “pauses” or “dead stops” in cycling. The pilot never sees a BLANK page; cycling flows smoothly from one occupied slot to the next.

---

### 0.1.3.2 Non-SOI-Candidate Formats (Edge Case)

In certain Master Modes, some format pages are *not valid* candidates for SOI designation. For example, SMS (Stores Management System) is not a valid SOI candidate in air-to-air mode. If a pilot customizes the air-to-air configuration to include SMS in one of the three slots, cycling can advance to SMS. The MFD will display SMS, but the page will show “NOT SOI” text, indicating that HOTAS commands routed to this MFD will not affect the SMS page.

**Operational Implication:** This is an edge case that arises from unusual customizations. For normal operations, pilots should configure the three slots with formats that are valid SOI candidates in the intended Master Mode (e.g., in A-A: FCR, HSD, TGP; in A-G: FCR, TGP, WPN). If a non-candidate format is encountered, the pilot simply cycles to another slot; the behavior is well-defined, and no malfunction occurs.

*Note:* This section flags the edge case for completeness. Detailed behavior (e.g., whether SOI is automatically removed, whether HOTAS inputs are blocked) is beyond the scope of this guide and depends on implementation details documented in Dash-34 § 2.1.1.2.3.

---

### 0.1.3.3 Format Persistence Across Master Mode Change

When the pilot changes Master Mode, the displayed format resets to the PRIMARY slot of the new mode. There is *no carryover* of the previously viewed slot.

**Example:** Pilot is in A-A mode, Left MFD is cycling through FCR/HSD/TGP, and the pilot has advanced to TERTIARY (TGP). The pilot then presses the A-G button to switch to air-to-ground mode. Immediately, the Left MFD resets to PRIMARY of the A-G configuration (let’s say it’s FCR or SMS, depending on customization). The fact that the pilot was viewing TERTIARY in A-A is not remembered in A-G.

**Why This Design:** Each Master Mode has a distinct operational context and a distinct three-slot configuration. Automatically resetting to PRIMARY ensures the pilot starts from a known, predictable state in the new mode. This prevents confusion and aligns with the principle that Master Mode transitions should reset the pilot’s display focus to the primary sensor of that mode.

---

## 0.1.4 DMS Left vs. DMS Right: Independent MFD Control

**This section addresses one of the most frequently misunderstood aspects of DMS operation.**

DMS Left and DMS Right are **completely independent**. DMS Left controls the Left MFD only; DMS Right controls the Right MFD only. Pressing one does not affect the other.

**Left MFD Independence:** DMS Left cycles through the three-slot configuration of the *Left MFD only*. If the Left MFD is displaying FCR (PRIMARY), pressing DMS Left advances it to whatever format is in the SECONDARY slot of the Left MFD configuration. The Right MFD is unaffected.

**Right MFD Independence:** DMS Right cycles through the three-slot configuration of the *Right MFD only*. The Left MFD is unaffected.

**Independence from SOI:** Additionally, format cycling via DMS Left/Right is independent of which MFD is designated as SOI. The pilot can have:

- Left MFD = SOI (receives HOTAS commands)
- Right MFD = not SOI

And still cycle both displays independently. Pressing DMS Right changes the Right MFD format even though it is not SOI. Pressing DMS Left changes the Left MFD format, and because Left MFD is SOI, it also receives any HOTAS input the pilot subsequently gives.

**Practical Scenario: A-A Engagement:** A typical air-to-air configuration might be:

- Left MFD: FCR (radar page, customized with FCR/HSD/TGP slots)
- Right MFD: SMS (stores page, customized with SMS/HAD/BLANK slots)
- SOI = Left MFD (pilot is managing radar tracks with HOTAS cursor and TMS)

During the engagement, the pilot might want to:

- Use DMS Left to cycle Left MFD between FCR and HSD (changes radar view).
- Use DMS Right to cycle Right MFD between SMS and HAD (checks stores status).
- Meanwhile, SOI remains on Left MFD; HOTAS TMS and cursor commands continue to affect the radar page.

Both MFDs cycle independently, and neither DMS Left/Right press affects the SOI designation.

**Why This Matters Tactically:** This independence allows the pilot to organize a visual workspace suited to the mission:

- Left MFD = Primary tactical sensor (under SOI control for hands-on management).
- Right MFD = Supplemental information (updated via DMS Right, providing situational awareness without consuming SOI).

The pilot never has to “choose” which display to look at or which to control; both are available simultaneously via independent mechanisms.

—

### 0.1.5 DMS Left/Right Usage Table

The table below summarizes DMS Left and DMS Right behavior across all Master Modes. Because format cycling is *identical* in all modes, the table shows a single row for each DMS direction, applicable to every Master Mode: A-A, A-G and NAV.



Table 2: DMS Left/Right Format Cycling Across All Master Modes

State	Dir	Act	Function	Effect / Nuance	Dash34	Train
A-A, A-G, NAV	Left	Short	Cycle Left MFD format	DMS Left cycles the Left MFD through its configured 3-slot sequence: PRIMARY → SECONDARY → TERTIARY → PRIMARY (wrap-around). If BLANK slots are present, they are skipped automatically. Each press advances one step; no continuous cycling on hold. SOI designation to any MFD is unaffected.	2.1.1.2.1, 2.1.6.3	—
A-A, A-G, NAV	Right	Short	Cycle Right MFD format	DMS Right cycles the Right MFD through its configured 3-slot sequence: PRIMARY → SECONDARY → TERTIARY → PRIMARY (wrap-around). If BLANK slots are present, they are skipped automatically. Each press advances one step; no continuous cycling on hold. Cycling Right does not affect Left MFD or SOI.	2.1.1.2.1, 2.1.6.3	—

**How to Use This Table:**

1. Identify the Master Mode you are operating in (A-A, A-G, etc.). *All modes use the same cycling rules.*
2. Determine which MFD you want to cycle: Left or Right.
3. Press DMS in the appropriate direction (Left or Right) for as many steps as needed to reach the desired format.
4. Check which format is now displayed. Refer to Section ?? to understand valid SOI candidates if you need to manage hands-on control.

**Special Notes:**

- **Short Press Only:** DMS Left/Right do not support long-press or hold variants. Each tap advances one slot.
- **Training Column Empty:** The Training (Train) column is left blank as per author guidance; training mission references will be populated in a future update.
- **Consistency Across Modes:** Unlike DMS Up/Down (Sections ?? and ??), DMS Left/Right behavior is *identical* in all Master Modes. Format cycling is a simple, mode-agnostic operation. Customization via DTC is the only variable.