

TMS, DMS and CMS Usage Guide for Falcon BMS 4.38.1

Carlos “Metal” Nader

Version 0.4.2.0-alpha.3+20260320 | Progress: Chapters 2/6 | Tables Chapter 5 | January 2026

Contents

List of HOTAS Tables	ii
1 HOTAS Fundamentals	1
1.1 Sensor of Interest (SOI) — Concept and Architecture	1

List of HOTAS Tables

Chapter 1

HOTAS Fundamentals

The F-16's HOTAS (Hands On Throttle And Stick) controls enable the pilot to execute critical flight, sensor, and weapon functions without removing hands from the throttle and side-stick controller. Within this architecture, three switches — the Display Management Switch (DMS), Target Management Switch (TMS), and Countermeasures Management Switch (CMS) — control display selection, sensor management, and defensive systems.

For the complete HOTAS control reference, see *TO 1F-16CMAM-34-1-1*, Dash-34, sections 2.1.1.1.4 and 2.1.5.

Two foundational concepts govern HOTAS switch behavior:

- **Sensor of Interest (SOI):** determines which display receives HOTAS inputs.
- **Master Modes (NAV, A-A, A-G):** define the available weapon systems and sensor configurations.

1.1 Sensor of Interest (SOI) — Concept and Architecture

The Sensor of Interest (SOI) is a designation that identifies which of the three F-16 cockpit displays currently receives HOTAS inputs.