

TMS, DMS and CMS Usage Guide for Falcon BMS 4.38.1

Carlos “Metal” Nader

Version 0.4.2.0.alpha.3+20260325 | Progress: Chapters 1/6 | Tables N/A | January 2026

Contents

List of HOTAS Tables	ii
1 HOTAS Fundamentals	1
1.1 Sensor of Interest (SOI)	1
1.1.1 SOI Fundamentals	1
1.1.2 SOI Symbology	1
1.1.3 SOI-Capable Displays	2
1.2 Master Modes	2
1.2.1 Primary and Override Master Modes	2
1.3 DMS, TMS, and CMS	3
1.3.1 Display Management Switch (DMS)	3
1.3.2 Target Management Switch (TMS)	3
1.3.3 Countermeasures Management Switch (CMS)	3

List of HOTAS Tables

Chapter 1

HOTAS Fundamentals

The F-16's HOTAS (Hands On Throttle And Stick) controls enable the pilot to execute flight, sensor, and weapon functions without removing hands from the throttle and side-stick controller. Within this architecture, three switches — the Display Management Switch (DMS), Target Management Switch (TMS), and Countermeasures Management Switch (CMS) — control display selection, sensor management, and defensive systems.

Two foundational concepts govern HOTAS switch behavior:

- **Sensor of Interest (SOI):** determines which display receives HOTAS inputs.
- **Master Modes (NAV, A-A, A-G):** define the available weapon systems and sensor configurations.

For the complete HOTAS control reference, see *TO 1F-16CMAM-34-1-1*, Dash-34, sections 2.1.1.1.4 and 2.1.5.

1.1 Sensor of Interest (SOI)

The F-16 cockpit contains three displays: the Head-Up Display (HUD) and two Multifunction Displays (MFD). The Sensor of Interest (SOI) determines which of these displays currently receives HOTAS inputs. At any moment, *only one* display can hold SOI designation. The active format on the display determines how the input is interpreted.

1.1.1 SOI Fundamentals

The SOI mechanism manages *where* HOTAS inputs are directed, not *what* those inputs do. The specific function of a HOTAS input — for example, whether TMS Up designates a target, breaks a track, or cycles through a mode — depends on delivery modes, current Master Mode, and active sensor format.

1.1.2 SOI Symbolology

SOI designation is indicated by a distinct visual marker on each display:

- **HUD as SOI:** An asterisk symbol (*) appears in the upper left corner of the HUD, above the airspeed scale.
- **MFD as SOI:** A border outline is drawn around the edges of the MFD display, forming a box that distinguishes the SOI display from the non-SOI display.

- **NOT SOI indication:** The text NOT SOI appears in the center of any SOI-capable MFD format that is not currently designated as SOI. This indicator does not appear on MFD formats that cannot be designated as SOI.

1.1.3 SOI-Capable Displays

The availability of SOI designation varies by Master Mode and MFD format.

Master Mode determines HUD eligibility for SOI designation. MFD formats can be designated as SOI in *all Master Modes*. The HUD, however, can be designated as SOI *only in NAV and A-G Master Modes*.

MFD format determines SOI eligibility *within* the MFD. Sensor formats that accept targeting and cursor control inputs — such as FCR, TGP, and WPN — can be designated as SOI. Informational and configuration formats, however — such as DTE, TCN, and FLCS — cannot be designated as SOI.

For SOI availability by Master Mode and MFD format, see Section ??.

1.2 Master Modes

Master Mode is the highest-level configuration state of the F-16 avionics suite. It configures cockpit displays, sensor modes, and weapon options, and determines SOI availability and switch functions.

1.2.1 Primary and Override Master Modes

Three primary Master Modes (NAV, A-A, and A-G) and two override modes (DGFT and MSL OVRD) are available in the F-16:

- **Navigation (NAV):** The default Master Mode, active when no other mode is selected. Both air-to-air and air-to-ground sensor modes are available in NAV. Navigation symbology is displayed on the HUD.
- **Air-to-Air (A-A):** Selected via the A-A button on the ICP. Only air-to-air sensor modes are available in A-A. Air-to-air weapon selection and engagement symbology are displayed on the HUD.
- **Air-to-Ground (A-G):** Selected via the A-G button on the ICP. Both air-to-air and air-to-ground sensor modes are available in A-G. Air-to-ground weapon delivery symbology is displayed on the HUD.
- **Dogfight (DGFT) and Missile Override (MSL OVRD):** Selected via the Dogfight/Missile Override switch on the throttle — DGFT outboard, MSL OVRD inboard. Only air-to-air sensor modes are available in both modes. DGFT and MSL OVRD take precedence over all other Master Modes except Emergency Jettison.

HOTAS switch inputs are interpreted within the active master mode configuration. That configuration can be programmed via the Data Transfer Cartridge (DTC) or adjusted manually in-flight (see Section ??). For complete Master Mode details, see Dash-34 § 2.1.1.2.1.

1.3 DMS, TMS, and CMS

Full coverage of DMS, TMS, and CMS — including all HOTAS tables — is in Chapter ??, Chapter ??, and Chapter ??, respectively.

1.3.1 Display Management Switch (DMS)

The Display Management Switch (DMS) is a four-way, momentary hat switch on the side-stick controller. Its primary functions are SOI designation and MFD format cycling (see Dash-34 § 2.1.5). The DMS selects *which display or sensor* receives HOTAS inputs. It does not designate targets or execute sensor-specific commands.

1.3.2 Target Management Switch (TMS)

The Target Management Switch (TMS) is a four-way, momentary hat switch on the side-stick controller. Its primary functions are target designation, sensor management, and markpoint creation (see Dash-34 § 2.1.5). The function of each TMS direction depends on the master mode, the active sensor mode, and the current SOI display.

1.3.3 Countermeasures Management Switch (CMS)

The Countermeasures Management Switch (CMS) is a four-way, momentary hat switch on the side-stick controller. Its primary functions are countermeasures dispensing and ECM control (see Dash-34 § 2.1.5). CMS actuation is independent of both SOI designation and master mode.