

Ultra Low Noise, Medium Current E-PHEMT

0.45-6GHz

Product Features

- Low Noise Figure, 0.5 dB
- Gain, 17 dB at 2 GHz
- High Output IP3, +33 dBm
- Output Power at 1dB comp., +20 dBm
- High Current, 60mA
- Wide bandwidth
- External biasing and matching required
- May be used as replacement ^{a,b} for Avago ATF-54143



SAV-541+

CASE STYLE: MMM1362
PRICE: \$1.39 ea. QTY. (20)

Typical Applications

- Cellular
- ISM
- GSM
- WCDMA
- WiMax
- WLAN
- UNII and HIPERLAN



+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

General Description

SAV-541+ is an ultra-low noise, high IP3 transistor device, manufactured using E-PHEMT* technology enabling it to work with a single positive supply voltage. It has outstanding Noise Figure, particularly below 2.5 GHz, and when combining this noise figure with high IP3 performance in a single device it makes it an ideal amplifier for demanding base station applications. We offer these units assembled into a complete module, 50Ω in/out, noise matched and fully specified. For more information please see our TAMP family of models on our web site.

simplified schematic and pin description



| Function | Pin Number | Description |
|----------|------------|---|
| Source | 2 & 4 | Source terminal, normally connected to ground |
| Gate | 3 | Gate used for RF input |
| Drain | 1 | Drain used for RF output |

* Enhancement mode Pseudomorphic High Electron Mobility Transistor.

a. Suitability for model replacement within a particular system must be determined by and is solely the responsibility of the customer based on, among other things, electrical performance criteria, stimulus conditions, application, compatibility with other components and environmental conditions and stresses.

b. The Avago ATF-54143 part number is used for identification and comparison purposes only.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. C
M123887
ED-13377
SAV-541+
150319
Page 1 of 13

Electrical Specifications at $T_{AMB}=25^{\circ}\text{C}$, Frequency 0.45 to 6 GHz

| Symbol | Parameter | Condition | Min. | Typ. | Max. | Units |
|--|----------------------------------|--|--|---|--------------------------------------|---------------|
| DC Specifications | | | | | | |
| V_{GS} | Operational Gate Voltage | $V_{DS}=3\text{V}$, $I_{DS}=60\text{ mA}$ | 0.37 | 0.48 | 0.69 | V |
| V_{TH} | Threshold Voltage | $V_{DS}=3\text{V}$, $I_{DS}=4\text{ mA}$ | 0.18 | 0.26 | 0.38 | V |
| I_{DSS} | Saturated Drain Current | $V_{DS}=3\text{V}$, $V_{GS}=0\text{ V}$ | | 1.0 | 5.0 | μA |
| G_M | Transconductance | $V_{DS}=3\text{V}$, $G_m=\Delta I_{DS}/\Delta V_{GS}$ $\Delta V_{GS}=V_{GS1}-V_{GS2}$ $V_{GS1}=V_{GS}$ at $I_{DS}=60\text{ mA}$ $V_{GS2}=V_{GS1}+0.05\text{V}$ | — 230 — — | — 392 — — | — 560 — — | mS |
| I_{GSS} | Gate leakage Current | $V_{GD}=V_{GS}=-3\text{V}$ | | | 200 | μA |
| RF Specifications, $Z_0=50\text{ Ohms}$ (Figure 1) | | | | | | |
| $NF^{(1)}$ | Noise Figure | $V_{DS}=3\text{V}$, $I_{DS}=60\text{ mA}$ $V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$ $V_{DS}=3\text{V}$, $I_{DS}=60\text{ mA}$ $V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$ | $f=0.9\text{ GHz}$ $f=2.0\text{ GHz}$ $f=3.9\text{ GHz}$ $f=5.8\text{ GHz}$ $f=2.0\text{ GHz}$ | 0.4 0.5 1.0 1.9 0.5 | — 0.9 — — — | dB |
| Gain | Gain | $V_{DS}=3\text{V}$, $I_{DS}=60\text{ mA}$ $V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$ | $f=0.9\text{ GHz}$ $f=2.0\text{ GHz}$ $f=3.9\text{ GHz}$ $f=5.8\text{ GHz}$ $f=2.0\text{ GHz}$ | — 15.0 — — — | 23.2 17.6 12.5 8.7 17.4 | dB |
| OIP3 | Output IP3 | $V_{DS}=3\text{V}$, $I_{DS}=60\text{ mA}$ $V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$ | $f=0.9\text{ GHz}$ $f=2.0\text{ GHz}$ $f=3.9\text{ GHz}$ $f=5.8\text{ GHz}$ $f=2.0\text{ GHz}$ | — 30.0 — — — | 32.6 33.1 33.0 31.0 35.1 | dBm |
| $P_{1dB}^{(2)}$ | Power output at 1 dB Compression | $V_{DS}=3\text{V}$, $I_{DS}=60\text{ mA}$ $V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$ | $f=0.9\text{ GHz}$ $f=2.0\text{ GHz}$ $f=3.9\text{ GHz}$ $f=5.8\text{ GHz}$ $f=2.0\text{ GHz}$ | — 19.1 19.2 19.0 18.2 21.5 | — — — — — | dBm |

Absolute Maximum Ratings⁽³⁾

| Symbol | Parameter | Max. | Units |
|----------------|------------------------|------------|----------------------|
| $V_{DS}^{(4)}$ | Drain-Source Voltage | 5 | V |
| $V_{GS}^{(4)}$ | Gate-Source Voltage | -5 to 0.7 | V |
| $V_{GD}^{(4)}$ | Gate-Drain Voltage | -5 to 0.7 | V |
| $I_{DS}^{(4)}$ | Drain Current | 120 | mA |
| I_{GS} | Gate Current | 2 | mA |
| P_{DISS} | Total Dissipated Power | 360 | mW |
| $P_{IN}^{(5)}$ | RF Input Power | 17 | dBm |
| T_{CH} | Channel Temperature | 150 | $^{\circ}\text{C}$ |
| T_{OP} | Operating Temperature | -40 to 85 | $^{\circ}\text{C}$ |
| T_{STD} | Storage Temperature | -65 to 150 | $^{\circ}\text{C}$ |
| Θ_{JC} | Thermal Resistance | 160 | $^{\circ}\text{C/W}$ |

Notes:

- (1) Includes test board loss (tested on Mini-Circuits TB-471+ test board)
 (2) Drain current was allowed to increase during compression measurements.
 (3) Operation of this device above any one of these parameters may cause permanent damage.
 (4) Assumes DC quiescent conditions.
 (5) I_{GS} is limited to 2 mA during test.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Characterization Test Circuit




Fig 1. Block Diagram of Test Circuit used for characterization. (DUT soldered on Mini-Circuits Test Board TB-471+)

Gain, Output power at 1dB compression (P_1 dB) and output IP_3 (OIP3) are measured using R&S Network Analyzer ZVA-24. Noise Figure measured using Agilent Noise Figure meter N8975A and Noise Source N4000A.

Conditions:

1. Drain voltage (with reference to source, V_{DS}) = 3 or 4V as shown.
2. Gate Voltage (with reference to source, V_{GS}) is set to obtain desired Drain-Source current (I_{DS}) as shown in graphs or specification table.
3. Gain: $P_{in} = -25$ dBm
4. Output IP_3 (OIP3): Two tones, spaced 1 MHz apart, 0 dBm/tone at output.
5. No external matching components used.










Fig 2. Test Board used for characterization, Mini-Circuits P/N TB-471+ (Material: Rogers 4350, Thickness: 0.02")

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical Performance Curves









- (1) Includes test board loss, set-up and conditions per Figure 1.
 (2) Measured using HP4155B semiconductor parameter analyzer.
 (3) F Min is minimum Noise Figure.
 (4) Drain Current was allowed to increase during compression measurement.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp






- (1) Includes test board loss, set-up and conditions per Figure 1.
 (2) Measured using HP4155B semiconductor parameter analyzer.
 (3) F Min is minimum Noise Figure.
 (4) Drain Current was allowed to increase during compression measurement.

Notes


- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp




GAIN vs FREQUENCY & TEMPERATURE (1)
@ VDS=3V, IDS=60mA




OIP3 vs FREQUENCY & TEMPERATURE (1)
@ VDS=3V, IDS=60mA




P1dB vs FREQUENCY & TEMPERATURE (1,4)
@ VDS=3V, IDS=60mA




NF vs FREQUENCY & TEMPERATURE (1)
@ VDS=4V, IDS=60mA



GAIN vs FREQUENCY & TEMPERATURE (1)
@ VDS=4V, IDS=60mA



OIP3 vs FREQUENCY & TEMPERATURE (1)
@ VDS=4V, IDS=60mA





- (1) Includes test board loss, set-up and conditions per Figure 1.
 (2) Measured using HP4155B semiconductor parameter analyzer.
 (3) F Min is minimum Noise Figure.
 (4) Drain Current was allowed to increase during compression measurement.

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp





- (1) Includes test board loss, set-up and conditions per Figure 1.
- (2) Measured using HP4155B semiconductor parameter analyzer.
- (3) F Min is minimum Noise Figure.
- (4) Drain Current was allowed to increase during compression measurement.

Reference Plane Location for S and Noise Parameters *(see data in pages 8-11)*

(Refer to Application Note AN-60-040)




Fig 3. Reference Plane Location

Notes:

Noise parameters were measured over 0.5 to 6 GHz by Modelithics® using a solid state tuner-based noise parameter (NP) test system available from Maury Microwave. F Min, optimum source reflection coefficient and noise resistance values are calculated values based on a set of measurements made at approximately 16 different impedances. Some data smoothing was applied to arrive at the presented data set.

S-parameters were measured by Modelithics® on an Anritsu Lightning vector network analyzer over 0.1 to 18GHz using 350um pitch RF probes from GGB industries combined with customized thru-reflect-line (TRL) calibration standards. The reference plane is at the device package leads, as shown in the picture.


Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical S-parameters, $V_{DS}=3V$ and $I_{DS}=40\text{ mA}$ (Fig. 3)

| Freq. (GHz) | S11 | | S21 | | | S12 | | S22 | | MSG/MAG (dB) |
|----------------|------|--------|------|-------------|--------|-------|--------|------|--------|-----------------|
| | Mag. | Ang. | Mag. | Mag (dB) | Ang. | Mag. | Ang. | Mag. | Ang. | |
| 0.1 | 0.99 | -16.6 | 25.3 | 28.1 | 169.5 | 0.008 | 89.1 | 0.55 | -14.7 | 34.8 |
| 0.5 | 0.86 | -74.6 | 19.6 | 25.8 | 132.2 | 0.035 | 54.4 | 0.43 | -55.3 | 27.5 |
| 0.9 | 0.75 | -112.6 | 14.2 | 23.0 | 109.0 | 0.047 | 40.5 | 0.32 | -83.3 | 24.8 |
| 1.0 | 0.74 | -120.4 | 13.2 | 22.4 | 104.6 | 0.049 | 38.4 | 0.30 | -89.5 | 24.3 |
| 1.5 | 0.68 | -149.6 | 9.5 | 19.6 | 86.7 | 0.057 | 31.3 | 0.23 | -114.1 | 22.3 |
| 1.9 | 0.66 | -166.7 | 7.7 | 17.8 | 75.4 | 0.062 | 27.5 | 0.19 | -131.2 | 21.0 |
| 2.0 | 0.66 | -170.5 | 7.4 | 17.4 | 72.9 | 0.063 | 26.6 | 0.19 | -135.2 | 20.7 |
| 2.5 | 0.65 | 172.8 | 6.0 | 15.6 | 61.0 | 0.07 | 22.9 | 0.17 | -153.9 | 19.3 |
| 3.0 | 0.65 | 158.7 | 5.0 | 14.1 | 50.2 | 0.077 | 19.5 | 0.16 | -171.3 | 18.2 |
| 4.0 | 0.66 | 134.4 | 3.8 | 11.6 | 30.0 | 0.091 | 11.9 | 0.16 | 156.7 | 15.8 |
| 5.0 | 0.68 | 113.5 | 3.0 | 9.7 | 11.1 | 0.104 | 2.7 | 0.18 | 130.5 | 13.3 |
| 6.0 | 0.71 | 94.7 | 2.5 | 8.0 | -7.1 | 0.118 | -7.5 | 0.22 | 109.1 | 11.7 |
| 7.0 | 0.75 | 77.8 | 2.1 | 6.4 | -24.7 | 0.13 | -18.3 | 0.28 | 90.7 | 10.5 |
| 8.0 | 0.78 | 62.4 | 1.8 | 5.0 | -41.5 | 0.14 | -29.4 | 0.33 | 74.8 | 9.6 |
| 9.0 | 0.82 | 47.8 | 1.5 | 3.6 | -57.8 | 0.146 | -41.0 | 0.40 | 60.0 | 9.0 |
| 10.0 | 0.85 | 33.7 | 1.3 | 2.3 | -73.9 | 0.15 | -52.7 | 0.46 | 46.1 | 8.8 |
| 11.0 | 0.88 | 20.6 | 1.1 | 1.0 | -89.3 | 0.152 | -64.4 | 0.53 | 33.2 | 8.7 |
| 12.0 | 0.90 | 8.4 | 1.0 | -0.2 | -104.0 | 0.153 | -75.8 | 0.58 | 21.2 | 8.0 |
| 13.0 | 0.91 | -3.5 | 0.9 | -1.3 | -118.3 | 0.154 | -87.1 | 0.62 | 10.3 | 7.5 |
| 14.0 | 0.92 | -14.4 | 0.8 | -2.3 | -131.9 | 0.154 | -97.9 | 0.66 | 0.0 | 7.0 |
| 15.0 | 0.94 | -23.0 | 0.7 | -3.6 | -143.0 | 0.148 | -106.3 | 0.70 | -8.7 | 6.5 |
| 16.0 | 0.95 | -30.4 | 0.6 | -4.9 | -153.0 | 0.139 | -114.2 | 0.75 | -16.6 | 6.1 |
| 17.0 | 0.95 | -39.0 | 0.5 | -6.0 | -164.0 | 0.134 | -122.6 | 0.77 | -25.2 | 5.7 |
| 18.0 | 0.94 | -48.3 | 0.5 | -6.9 | -175.7 | 0.131 | -131.4 | 0.79 | -33.9 | 5.4 |

MAXIMUM STABLE GAIN (MSG)/MAXIMUM AVAILABLE
GAIN (MAG) vs. FREQUENCYTypical Noise Parameters, $V_{DS}=3V$ and $I_{DS}=40\text{ mA}$ (Fig. 3)

| Freq. (GHz) | F Min. (dB) | Γ^{Opt} (Magnitude) | Γ^{Opt} (Angle) | Rn/50 | Ga Associated Gain (dB) |
|----------------|----------------|-------------------------------|---------------------------|-------|-------------------------------|
| 0.5 | 0.071 | 0.34 | 27.00 | 0.05 | 27.9 |
| 0.7 | 0.101 | 0.35 | 37.65 | 0.05 | 25.7 |
| 0.9 | 0.131 | 0.35 | 48.14 | 0.04 | 23.9 |
| 1.0 | 0.146 | 0.36 | 53.32 | 0.04 | 23.2 |
| 1.9 | 0.281 | 0.39 | 98.07 | 0.03 | 18.3 |
| 2.0 | 0.296 | 0.39 | 102.83 | 0.03 | 17.9 |
| 2.4 | 0.356 | 0.40 | 121.48 | 0.03 | 16.6 |
| 3.0 | 0.446 | 0.42 | 148.20 | 0.03 | 15.0 |
| 3.9 | 0.581 | 0.45 | -174.52 | 0.05 | 13.4 |
| 5.0 | 0.747 | 0.48 | -133.51 | 0.10 | 11.9 |
| 5.8 | 0.867 | 0.50 | -106.84 | 0.14 | 10.9 |
| 6.0 | 0.897 | 0.50 | -100.59 | 0.15 | 10.6 |

Notes:
 F Min.: Minimum Noise Figure
 Γ^{Opt} : Optimum Source Reflection Coefficient
 Rn: Equivalent noise resistance


Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical S-parameters, $V_{DS}=3V$ and $I_{DS}=60\text{ mA}$ (Fig. 3)

| Freq. (GHz) | S11 | | S21 | | | S12 | | S22 | | MSG/MAG (dB) |
|----------------|------|--------|------|-------------|--------|-------|--------|------|--------|-----------------|
| | Mag. | Ang. | Mag. | Mag (dB) | Ang. | Mag. | Ang. | Mag. | Ang. | |
| 0.1 | 0.99 | -18.2 | 27.8 | 28.9 | 168.7 | 0.009 | 78.4 | 0.50 | -14.8 | 35.0 |
| 0.5 | 0.85 | -78.1 | 21.0 | 26.5 | 130.2 | 0.032 | 53.5 | 0.39 | -60.2 | 28.1 |
| 0.9 | 0.74 | -116.2 | 14.9 | 23.5 | 107.3 | 0.044 | 41.8 | 0.29 | -90.1 | 25.3 |
| 1.0 | 0.72 | -123.9 | 13.8 | 22.8 | 102.9 | 0.045 | 39.7 | 0.27 | -96.8 | 24.9 |
| 1.5 | 0.67 | -152.5 | 9.9 | 19.9 | 85.5 | 0.053 | 33.6 | 0.21 | -122.9 | 22.7 |
| 1.9 | 0.65 | -169.2 | 8.0 | 18.1 | 74.5 | 0.059 | 30.3 | 0.18 | -140.6 | 21.4 |
| 2.0 | 0.65 | -172.8 | 7.7 | 17.7 | 72.0 | 0.06 | 29.8 | 0.18 | -144.8 | 21.0 |
| 2.5 | 0.65 | 170.9 | 6.2 | 15.9 | 60.5 | 0.068 | 26.6 | 0.17 | -163.6 | 19.6 |
| 3.0 | 0.64 | 157.0 | 5.2 | 14.3 | 49.9 | 0.075 | 22.8 | 0.16 | 179.6 | 18.4 |
| 4.0 | 0.66 | 133.3 | 3.9 | 11.9 | 29.9 | 0.091 | 14.6 | 0.17 | 149.8 | 15.7 |
| 5.0 | 0.68 | 112.7 | 3.1 | 9.9 | 11.2 | 0.105 | 4.8 | 0.20 | 125.6 | 13.3 |
| 6.0 | 0.71 | 94.1 | 2.6 | 8.2 | -6.8 | 0.12 | -5.7 | 0.24 | 105.4 | 11.8 |
| 7.0 | 0.74 | 77.4 | 2.2 | 6.7 | -24.1 | 0.132 | -17.3 | 0.29 | 87.9 | 10.6 |
| 8.0 | 0.78 | 62.1 | 1.8 | 5.3 | -40.8 | 0.142 | -28.5 | 0.35 | 72.6 | 9.8 |
| 9.0 | 0.81 | 47.7 | 1.6 | 3.9 | -56.9 | 0.149 | -40.4 | 0.41 | 58.1 | 9.1 |
| 10.0 | 0.85 | 33.6 | 1.3 | 2.5 | -72.8 | 0.152 | -52.4 | 0.48 | 44.4 | 8.8 |
| 11.0 | 0.88 | 20.5 | 1.2 | 1.2 | -88.0 | 0.154 | -64.1 | 0.54 | 31.6 | 8.7 |
| 12.0 | 0.90 | 8.3 | 1.0 | 0.0 | -102.6 | 0.154 | -75.7 | 0.59 | 19.8 | 8.1 |
| 13.0 | 0.91 | -3.5 | 0.9 | -1.0 | -116.9 | 0.155 | -87.1 | 0.63 | 8.9 | 7.6 |
| 14.0 | 0.92 | -14.4 | 0.8 | -2.0 | -130.4 | 0.155 | -97.8 | 0.66 | -1.3 | 7.1 |
| 15.0 | 0.93 | -23.0 | 0.7 | -3.2 | -141.3 | 0.149 | -106.3 | 0.71 | -9.9 | 6.7 |
| 16.0 | 0.95 | -30.5 | 0.6 | -4.6 | -151.3 | 0.14 | -114.0 | 0.75 | -17.6 | 6.3 |
| 17.0 | 0.95 | -39.1 | 0.5 | -5.6 | -162.3 | 0.134 | -122.4 | 0.77 | -26.1 | 5.9 |
| 18.0 | 0.94 | -48.4 | 0.5 | -6.4 | -174.0 | 0.132 | -131.7 | 0.79 | -34.7 | 5.6 |

MAXIMUM STABLE GAIN (MSG)/MAXIMUM AVAILABLE
GAIN (MAG) vs. FREQUENCYTypical Noise Parameters, $V_{DS}=3V$ and $I_{DS}=60\text{ mA}$ (Fig. 3)

| Freq. (GHz) | F Min. (dB) | Γ^{Opt} (Magnitude) | Γ^{Opt} (Angle) | Rn/50 | Ga Associated Gain (dB) |
|----------------|----------------|-------------------------------|---------------------------|-------|-------------------------------|
| 0.5 | 0.076 | 0.31 | 26.60 | 0.05 | 28.1 |
| 0.7 | 0.109 | 0.32 | 38.07 | 0.05 | 26.0 |
| 0.9 | 0.141 | 0.32 | 49.32 | 0.04 | 24.3 |
| 1.0 | 0.158 | 0.32 | 54.87 | 0.04 | 23.5 |
| 1.9 | 0.304 | 0.34 | 102.31 | 0.03 | 18.7 |
| 2.0 | 0.320 | 0.35 | 107.31 | 0.03 | 18.3 |
| 2.4 | 0.385 | 0.36 | 126.75 | 0.03 | 17.0 |
| 3.0 | 0.482 | 0.38 | 154.28 | 0.04 | 15.5 |
| 3.9 | 0.629 | 0.42 | -168.12 | 0.06 | 13.8 |
| 5.0 | 0.807 | 0.47 | -128.17 | 0.11 | 12.2 |
| 5.8 | 0.937 | 0.52 | -103.27 | 0.16 | 11.2 |
| 6.0 | 0.970 | 0.53 | -97.59 | 0.18 | 11.0 |

Notes:
 F Min: Minimum Noise Figure
 Γ^{Opt} : Optimum Source Reflection Coefficient
 Rn: Equivalent noise resistance


Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical S-parameters, $V_{DS}=3V$ and $I_{DS}=80\text{ mA}$ (Fig. 3)

| Freq. (GHz) | S11 | | S21 | | | S12 | | S22 | | MSG/MAG (dB) |
|----------------|------|--------|------|-------------|--------|-------|--------|------|--------|-----------------|
| | Mag. | Ang. | Mag. | Mag (dB) | Ang. | Mag. | Ang. | Mag. | Ang. | |
| 0.1 | 0.99 | -18.3 | 29.4 | 29.4 | 168.4 | 0.008 | 84.4 | 0.48 | -16.4 | 35.6 |
| 0.5 | 0.84 | -79.6 | 21.8 | 26.8 | 129.4 | 0.031 | 54.8 | 0.36 | -62.3 | 28.4 |
| 0.9 | 0.73 | -117.7 | 15.4 | 23.7 | 106.5 | 0.041 | 42.7 | 0.27 | -93.1 | 25.7 |
| 1.0 | 0.71 | -125.3 | 14.2 | 23.1 | 102.2 | 0.043 | 40.4 | 0.25 | -99.8 | 25.2 |
| 1.5 | 0.66 | -153.7 | 10.2 | 20.2 | 85.0 | 0.051 | 35.2 | 0.20 | -126.4 | 23.0 |
| 1.9 | 0.65 | -170.2 | 8.2 | 18.3 | 74.1 | 0.057 | 32.5 | 0.18 | -144.2 | 21.6 |
| 2.0 | 0.65 | -173.8 | 7.8 | 17.9 | 71.7 | 0.059 | 31.6 | 0.18 | -148.3 | 21.3 |
| 2.5 | 0.64 | 170.2 | 6.3 | 16.1 | 60.2 | 0.066 | 28.2 | 0.16 | -167.0 | 19.8 |
| 3.0 | 0.64 | 156.4 | 5.3 | 14.5 | 49.8 | 0.074 | 24.7 | 0.16 | 176.5 | 18.6 |
| 4.0 | 0.65 | 132.9 | 4.0 | 12.1 | 30.0 | 0.09 | 16.1 | 0.17 | 147.5 | 15.7 |
| 5.0 | 0.67 | 112.4 | 3.2 | 10.1 | 11.4 | 0.106 | 6.1 | 0.20 | 124.0 | 13.4 |
| 6.0 | 0.70 | 94.0 | 2.6 | 8.4 | -6.5 | 0.12 | -5.0 | 0.24 | 104.4 | 11.9 |
| 7.0 | 0.74 | 77.4 | 2.2 | 6.9 | -23.8 | 0.133 | -16.3 | 0.29 | 87.2 | 10.8 |
| 8.0 | 0.77 | 62.1 | 1.9 | 5.4 | -40.4 | 0.142 | -27.9 | 0.35 | 71.9 | 9.9 |
| 9.0 | 0.81 | 47.7 | 1.6 | 4.0 | -56.4 | 0.15 | -39.9 | 0.42 | 57.5 | 9.3 |
| 10.0 | 0.85 | 33.6 | 1.4 | 2.7 | -72.3 | 0.153 | -52.0 | 0.48 | 43.8 | 8.9 |
| 11.0 | 0.87 | 20.5 | 1.2 | 1.4 | -87.4 | 0.155 | -63.9 | 0.54 | 31.2 | 8.8 |
| 12.0 | 0.90 | 8.3 | 1.0 | 0.2 | -102.0 | 0.155 | -75.4 | 0.59 | 19.4 | 8.2 |
| 13.0 | 0.91 | -3.5 | 0.9 | -0.8 | -116.2 | 0.156 | -86.8 | 0.63 | 8.6 | 7.6 |
| 14.0 | 0.92 | -14.4 | 0.8 | -1.8 | -129.6 | 0.156 | -97.7 | 0.66 | -1.6 | 7.2 |
| 15.0 | 0.93 | -23.0 | 0.7 | -3.0 | -140.7 | 0.15 | -106.2 | 0.71 | -10.2 | 6.7 |
| 16.0 | 0.95 | -30.5 | 0.6 | -4.4 | -150.6 | 0.14 | -113.9 | 0.75 | -17.9 | 6.4 |
| 17.0 | 0.95 | -39.1 | 0.5 | -5.4 | -161.5 | 0.135 | -122.3 | 0.77 | -26.4 | 6.0 |
| 18.0 | 0.94 | -48.5 | 0.5 | -6.2 | -173.4 | 0.133 | -131.2 | 0.78 | -35.0 | 5.7 |

MAXIMUM STABLE GAIN (MSG)/MAXIMUM AVAILABLE
GAIN (MAG) vs. FREQUENCYTypical Noise Parameters, $V_{DS}=3V$ and $I_{DS}=80\text{ mA}$ (Fig. 3)

| Freq. (GHz) | F Min. (dB) | Γ Opt (Magnitude) | Γ Opt (Angle) | Rn/50 | Ga Associated Gain (dB) |
|----------------|----------------|-----------------------------|-------------------------|-------|-------------------------------|
| 0.5 | 0.086 | 0.31 | 27.68 | 0.05 | 28.4 |
| 0.7 | 0.123 | 0.31 | 39.97 | 0.05 | 26.3 |
| 0.9 | 0.159 | 0.32 | 51.98 | 0.04 | 24.6 |
| 1.0 | 0.178 | 0.32 | 57.88 | 0.04 | 23.8 |
| 1.9 | 0.342 | 0.35 | 107.88 | 0.03 | 19.1 |
| 2.0 | 0.360 | 0.35 | 113.08 | 0.03 | 18.7 |
| 2.4 | 0.433 | 0.36 | 133.22 | 0.03 | 17.4 |
| 3.0 | 0.543 | 0.39 | 161.34 | 0.04 | 15.9 |
| 3.9 | 0.707 | 0.43 | -161.16 | 0.07 | 14.1 |
| 5.0 | 0.908 | 0.49 | -122.96 | 0.13 | 12.5 |
| 5.8 | 1.055 | 0.54 | -100.45 | 0.20 | 11.4 |
| 6.0 | 1.091 | 0.56 | -95.52 | 0.22 | 11.2 |

Notes:
 F Min: Minimum Noise Figure
 Γ_{Opt} : Optimum Source Reflection Coefficient
 Rn: Equivalent noise resistance


Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Typical S-parameters, $V_{DS}=4V$ and $I_{DS}=60\text{ mA}$ (Fig. 3)

| Freq. (GHz) | S11 | | S21 | | | S12 | | S22 | | MSG/MAG (dB) |
|----------------|------|--------|------|------|--------|-------|--------|------|--------|-----------------|
| | Mag. | Avg. | Mag. | Avg. | dB | Mag. | Ang. | Mag. | Ang. | |
| 0.1 | 0.99 | -17.9 | 27.9 | 28.9 | 168.5 | 0.008 | 83.7 | 0.53 | -14.7 | 35.2 |
| 0.5 | 0.85 | -77.9 | 21.0 | 26.5 | 130.2 | 0.032 | 54.0 | 0.40 | -57.1 | 28.2 |
| 0.9 | 0.74 | -116.0 | 15.0 | 23.5 | 107.3 | 0.043 | 41.4 | 0.29 | -84.8 | 25.5 |
| 1.0 | 0.72 | -123.7 | 13.9 | 22.8 | 102.9 | 0.044 | 39.3 | 0.27 | -90.9 | 25.0 |
| 1.5 | 0.67 | -152.3 | 10.0 | 20.0 | 85.5 | 0.052 | 33.5 | 0.21 | -115.1 | 22.8 |
| 1.9 | 0.65 | -169.0 | 8.1 | 18.1 | 74.5 | 0.058 | 30.2 | 0.18 | -131.8 | 21.5 |
| 2.0 | 0.65 | -172.6 | 7.7 | 17.7 | 72.0 | 0.059 | 29.6 | 0.17 | -135.9 | 21.1 |
| 2.5 | 0.64 | 171.1 | 6.2 | 15.9 | 60.4 | 0.066 | 26.5 | 0.15 | -154.5 | 19.7 |
| 3.0 | 0.64 | 157.3 | 5.2 | 14.4 | 49.8 | 0.073 | 22.9 | 0.14 | -171.8 | 18.5 |
| 4.0 | 0.66 | 133.5 | 3.9 | 11.9 | 29.9 | 0.088 | 15.0 | 0.15 | 156.0 | 15.7 |
| 5.0 | 0.68 | 112.9 | 3.1 | 10.0 | 11.1 | 0.103 | 5.6 | 0.17 | 129.9 | 13.4 |
| 6.0 | 0.71 | 94.4 | 2.6 | 8.3 | -6.9 | 0.117 | -4.9 | 0.21 | 108.6 | 11.9 |
| 7.0 | 0.74 | 77.7 | 2.2 | 6.8 | -24.3 | 0.13 | -16.2 | 0.26 | 90.7 | 10.8 |
| 8.0 | 0.78 | 62.3 | 1.9 | 5.3 | -41.1 | 0.14 | -27.3 | 0.32 | 74.9 | 9.9 |
| 9.0 | 0.81 | 47.9 | 1.6 | 4.0 | -57.4 | 0.147 | -39.2 | 0.39 | 60.2 | 9.3 |
| 10.0 | 0.85 | 33.8 | 1.4 | 2.6 | -73.5 | 0.151 | -51.1 | 0.46 | 46.3 | 9.5 |
| 11.0 | 0.88 | 20.6 | 1.2 | 1.3 | -88.9 | 0.154 | -62.9 | 0.52 | 33.4 | 8.8 |
| 12.0 | 0.90 | 8.5 | 1.0 | 0.1 | -103.6 | 0.154 | -74.4 | 0.57 | 21.5 | 8.2 |
| 13.0 | 0.91 | -3.4 | 0.9 | -1.0 | -118.0 | 0.156 | -85.9 | 0.61 | 10.6 | 7.6 |
| 14.0 | 0.92 | -14.3 | 0.8 | -2.0 | -131.6 | 0.156 | -96.8 | 0.65 | 0.3 | 7.1 |
| 15.0 | 0.94 | -22.9 | 0.7 | -3.2 | -142.8 | 0.149 | -105.4 | 0.70 | -8.5 | 6.7 |
| 16.0 | 0.95 | -30.4 | 0.6 | -4.6 | -152.9 | 0.14 | -113.3 | 0.74 | -16.4 | 6.3 |
| 17.0 | 0.95 | -39.0 | 0.5 | -5.6 | -164.0 | 0.135 | -121.7 | 0.77 | -25.0 | 5.9 |
| 18.0 | 0.95 | -48.3 | 0.5 | -6.5 | -175.7 | 0.133 | -131.0 | 0.78 | -33.7 | 5.5 |

MAXIMUM STABLE GAIN (MSG)/MAXIMUM AVAILABLE
GAIN (MAG) vs. FREQUENCYTypical Noise Parameters, $V_{DS}=4V$ and $I_{DS}=60\text{ mA}$ (Fig. 3)

| Freq. (GHz) | F Min. (dB) | Γ Opt (Magnitude) | Γ Opt (Angle) | Rn/50 | Ga Associated Gain (dB) |
|----------------|----------------|-----------------------------|-------------------------|-------|-------------------------------|
| 0.5 | 0.086 | 0.34 | 26.43 | 0.06 | 28.1 |
| 0.7 | 0.121 | 0.34 | 37.91 | 0.05 | 26.0 |
| 0.9 | 0.156 | 0.34 | 49.17 | 0.05 | 24.2 |
| 1.0 | 0.173 | 0.34 | 54.72 | 0.04 | 23.4 |
| 1.9 | 0.331 | 0.35 | 102.19 | 0.03 | 18.7 |
| 2.0 | 0.349 | 0.35 | 107.19 | 0.03 | 18.3 |
| 2.4 | 0.419 | 0.36 | 126.64 | 0.03 | 17.0 |
| 3.0 | 0.524 | 0.37 | 154.19 | 0.04 | 15.4 |
| 3.9 | 0.682 | 0.41 | -168.19 | 0.06 | 13.7 |
| 5.0 | 0.875 | 0.47 | -128.23 | 0.12 | 12.2 |
| 5.8 | 1.016 | 0.52 | -103.33 | 0.17 | 11.2 |
| 6.0 | 1.051 | 0.54 | -97.65 | 0.18 | 11.0 |


Notes:
 F Min: Minimum Noise Figure
 Γ_{Opt} : Optimum Source Reflection Coefficient
 Rn: Equivalent noise resistance

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Product Marking



Additional Detailed Technical Information

Additional information is available on our web site www.minicircuits.com. To access this information enter the model number on our web site home page.

Performance data, graphs, s-parameter data set (.zip file)

Case Style: MMM1362

Plastic molded SOT-343 (SC-70) style package, lead finish: matte tin

Suggested Layout for PCB Design: PL-300

Tape & Reel: F90

Standard quantities available on reel: 7" reels with 20, 50, 100, 200, 500, 1K, 2K, or 3K devices.

Characterization Test Board: TB-471+

Environmental Ratings: ENV08T2

ESD Rating


Human Body Model (HBM): Class 1A (250 V to < 500 V) in accordance with ANSI/ESD STM 5.1 - 2001

Machine Model (MM): Class M1 (40 V) in accordance with ANSI/ESD STM 5.2 - 1999

MSL Rating

Moisture Sensitivity: MSL1 in accordance with IPC/JEDECJ-STD-020D

MSL Test Flow Chart




Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Recommended Application Circuit



| VDS, V (nom) | 3 | 4 |
|---------------|-----------|-----------|
| IDS, mA (nom) | 60mA | 60mA |
| R1 | 4320Ω | 4320Ω |
| R2 | 4320Ω | 4320Ω |
| R3 | 3570Ω | 1210Ω |
| R4 | 33.2Ω | 16.7Ω |
| Q1 | MMBT3906* | MMBT3906* |
| Q2 | MMBT3906* | MMBT3906* |
| C1 | 0.01μF | 0.01μF |
| C2 | 0.01μF | 0.01μF |
| L1** | 840nH | 840nH |
| L2** | 840nH | 840nH |

* Fairchild Semiconductor™ part number

** Piconics™ part number CC45T47K240G5

Optimized Amplifier Circuits

For band specific, drop-in modules, and as an alternative to designing circuits, please refer to Mini-Circuits TAMP and RAMP series models which are based upon SAV/TAV E-PHEMT's and include all DC blocking, bias, matching and stabilization circuitry, without need for any external components.

Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

