

FORMAL LANGUAGES

WITH RESPECT TO THE
CHOMSKY-SCHÜTZENBERGER-HIERARCHY

Eric Kunze

TU Dresden, January 27, 2020

CONTENTS

- 1 Introduction**
- 2 Formal Grammar**
- 3 Chomsky-Schützenberger Hierarchy**
- 4 Applications**

CONTENTS

- 1 Introduction**
- 2 Formal Grammar
- 3 Chomsky-Schützenberger Hierarchy
- 4 Applications

SYNTAX VS. SEMANTIC

“Colorless green ideas sleep furiously.”

“Colorless green ideas sleep furiously.”




Figure 1: Tree representation of the sentence structure [4]

“Colorless green ideas sleep furiously.”




Figure 1: Tree representation of the sentence structure [4]

NOAM CHOMSKY (* December 7, 1928)

“father of modern linguistics”

i s o m o r p h i s m

i s o m o r p h i s m

► **alphabet** Σ — set of symbols

i s o m o r p h i s m

- ▶ **alphabet** Σ — set of symbols
- ▶ **word** w over Σ — finite sequence of symbols

| i s o m o r p h i s m | = 11

- ▶ **alphabet** Σ — set of symbols
- ▶ **word** w over Σ — finite sequence of symbols
- ▶ **length** $|w|$ — number of symbols of w

i s o m o r p h i s m $\in \Sigma_{\text{lat}}^*$

- ▶ **alphabet** Σ — set of symbols
- ▶ **word** w over Σ — finite sequence of symbols
- ▶ **length** $|w|$ — number of symbols of w
- ▶ **Kleene-Star** Σ^* — set of all words over Σ

i s o m o r p h i s m $\in L_{\text{eng}} \subset \Sigma_{\text{lat}}^*$

- ▶ **alphabet** Σ — set of symbols
- ▶ **word** w over Σ — finite sequence of symbols
- ▶ **length** $|w|$ — number of symbols of w
- ▶ **Kleene-Star** Σ^* — set of all words over Σ
- ▶ **(formal) language** $L \subseteq \Sigma^*$ — set of (selected) words over Σ

- ▶ $\mathbb{N}_0 = \{\epsilon, 1, 11, 111, \dots\}$ over $\Sigma = \{1\}$

SIMPLE EXAMPLES

- ▶ $\mathbb{N}_0 = \{\varepsilon, 1, 11, 111, \dots\}$ over $\Sigma = \{1\}$
- ▶ $\text{count}_2 = \{a^n b^n : n \in \mathbb{N}\}$ over $\Sigma = \{a, b\}$

SIMPLE EXAMPLES

- ▶ $\mathbb{N}_0 = \{\varepsilon, 1, 11, 111, \dots\}$ over $\Sigma = \{1\}$
- ▶ $\text{count}_2 = \{a^n b^n : n \in \mathbb{N}\}$ over $\Sigma = \{a, b\}$
- ▶ $\text{count}_3 = \{a^n b^n c^n : n \in \mathbb{N}\}$ over $\Sigma = \{a, b, c\}$

SIMPLE EXAMPLES

- ▶ $\mathbb{N}_0 = \{\varepsilon, 1, 11, 111, \dots\}$ over $\Sigma = \{1\}$
- ▶ $\text{count}_2 = \{a^n b^n : n \in \mathbb{N}\}$ over $\Sigma = \{a, b\}$
- ▶ $\text{count}_3 = \{a^n b^n c^n : n \in \mathbb{N}\}$ over $\Sigma = \{a, b, c\}$
- ▶ programming language C
 - ▷ alphabet: valid keywords and symbols
 - ▷ words: valid programs

CONTENTS

1 Introduction

2 Formal Grammar

3 Chomsky-Schützenberger Hierarchy

4 Applications

How to form strings over a given alphabet Σ ?

How to form strings over a given alphabet Σ ?

- ▶ accept words — automata theory
- ▶ generate words — theory of grammar

How to form strings over a given alphabet Σ ?

- ▶ accept words — automata theory
- ▶ generate words — theory of grammar

Definition: Grammar

A (formal) grammar G is a 4-tuple (N, Σ, P, S) where

- ▶ N and Σ are finite, disjoint sets of symbols (alphabets)
- ▶ elements of N are called non-terminal symbols, elements of Σ are called terminal symbols
- ▶ P is a set of productions $(N \cup \Sigma)^* N (N \cup \Sigma)^* \rightarrow (N \cup \Sigma)^*$
- ▶ $S \in N$ is the start symbol

Example

$G = (N, \Sigma, P, S)$ where $N = \{S\}$, $\Sigma = \{a, b\}$ and
 $P = \{S \rightarrow aSb, S \rightarrow ab\}$.

Example

$G = (N, \Sigma, P, S)$ where $N = \{S\}$, $\Sigma = \{a, b\}$ and $P = \{S \rightarrow aSb, S \rightarrow ab\}$.

Produced words over Σ :

$\{ab, aabb, aaabbb, \dots\} = \text{count}_2$

CONTENTS

1 Introduction

2 Formal Grammar

3 Chomsky-Schützenberger Hierarchy

4 Applications

CHOMSKY-HIERARCHY [1]

Let $G = (N, \Sigma, P, S)$ be a formal grammar. Then G is a **type-0-grammar**.

CHOMSKY-HIERARCHY [1]

Let $G = (N, \Sigma, P, S)$ be a formal grammar. Then G is a **type-0-grammar**. G is called a

- ▶ **type-1-grammar** (*context-sensitive*) if every production has the form
 - ▷ $u_1Au_2 \rightarrow u_1wu_2$ where $A \in N$, $u_1, u_2, w \in (N \cup \Sigma)^*$ and $|w| \geq 1$ or
 - ▷ $S \rightarrow \varepsilon$
- Is $(S \rightarrow \varepsilon) \in P$, so S never appears on a production's right side.

CHOMSKY-HIERARCHY [1]

Let $G = (N, \Sigma, P, S)$ be a formal grammar. Then G is a **type-0-grammar**. G is called a

- ▶ **type-1-grammar** (*context-sensitive*) if every production has the form
 - ▷ $u_1 A u_2 \rightarrow u_1 w u_2$ where $A \in N$, $u_1, u_2, w \in (N \cup \Sigma)^*$ and $|w| \geq 1$ or
 - ▷ $S \rightarrow \varepsilon$
- Is $(S \rightarrow \varepsilon) \in P$, so S never appears on a production's right side.

Example: $L(G) = \text{count}_3$

Let $N = \{S, A, B\}$, $\Sigma = \{a, b, c\}$ and P consist of the following rules:

- ▶ (1) $S \rightarrow abc$
- ▶ (2) $S \rightarrow aSBc$
- ▶ (3) $cB \rightarrow Bc$
- ▶ (4) $bB \rightarrow bb$

Let $G = (N, \Sigma, P, S)$ be a formal grammar. G is called a

- **type-2-grammar** (*context-free*) if every production has the form $A \rightarrow w$ where $A \in N$ and $w \in (N \cup \Sigma)^*$

Let $G = (N, \Sigma, P, S)$ be a formal grammar. G is called a

- **type-2-grammar** (*context-free*) if every production has the form $A \rightarrow w$ where $A \in N$ and $w \in (N \cup \Sigma)^*$

Example: $L(G) = \text{count}_2$

Let $N = \{S\}$, $\Sigma = \{a, b\}$ and

$$P = \{S \rightarrow aSb, S \rightarrow ab\}$$

Let $G = (N, \Sigma, P, S)$ be a formal grammar. G is called a

- **type-3-grammar** (*regular*) if every production has the form $A \rightarrow uB$ oder $A \rightarrow u$ where $A, B \in N$ and $u \in \Sigma^*$

Example: $L(G) = \mathbb{N}_0$

Let $N = \{S\}$, $\Sigma = \{1\}$,

$$P = \{S \rightarrow \varepsilon, S \rightarrow 1S\}$$

CONTENTS

- 1 Introduction
- 2 Formal Grammar
- 3 Chomsky-Schützenberger Hierarchy
- 4 Applications**

- **syntax of programming languages**

e.g. if-condition in C

$$ifStat \rightarrow \text{if } (BoolExp) Stat$$
$$ifStat \rightarrow \text{if } (BoolExp) Stat \text{ else } Stat$$

- ▶ **syntax of programming languages**

e.g. if-condition in C

$$ifStat \rightarrow \text{if } (BoolExp) Stat$$
$$ifStat \rightarrow \text{if } (BoolExp) Stat \text{ else } Stat$$

- ▶ **mathematical logic**

- ▷ (propositional) logic as formal language L_{\log} over alphabet $\Sigma = \{p_1, p_2, \dots\} \cup \{\neg, \wedge, \vee, (,)\}$

- ▷ words: valid formulae — e.g. $(\neg(p_1 \vee p_2) \wedge p_3) \in L_{\log}$

- ▶ **syntax of programming languages**

e.g. if-condition in C

$$ifStat \rightarrow \text{if } (BoolExp) Stat$$
$$ifStat \rightarrow \text{if } (BoolExp) Stat \text{ else } Stat$$

- ▶ **mathematical logic**

- ▷ (propositional) logic as formal language L_{\log} over alphabet $\Sigma = \{p_1, p_2, \dots\} \cup \{\neg, \wedge, \vee, (,)\}$

- ▷ words: valid formulae — e.g. $(\neg(p_1 \vee p_2) \wedge p_3) \in L_{\log}$

- ▶ **Computability Theory**

- ▷ Which problem is computable with which machine?

REFERENCES



F. Baader.

Formale Systeme – Automatentheorie und Formale Sprachen.

Lecture notes, TU Dresden, Institut für theoretische Informatik, Dresden, Germany, 2016.



E. Börger.

Computability, complexity, logic.

North Holland, Amsterdam, 1989.



N. Chomsky.

Three models for the description of language.

IRE Transactions on Information Theory, 2(3):113–124, Sep. 1956.



N. Chomsky.

Syntactic structures.

Mouton, The Hague [u.a.], 11. pr. edition, 1975.



J. E. Hopcroft, R. Motwani, and J. D. Ullman.

Introduction to Automata Theory, Languages, and Computation (3rd Edition).

Addison-Wesley Longman Publishing Co., Inc., USA, 2006.



H. Rogers.

Theory of recursive functions and effective computability.

MIT Press, Cambridge, Mass. [u.a.], 3. print. edition, 1992.

FORMAL LANGUAGE

- ▶ **alphabet** Σ — set of symbols
 - ▷ latin alphabet $\Sigma_{\text{lat}} = \{a, b, \dots, z\}$
 - ▷ binary alphabet $\Sigma_{\text{bin}} = \{0, 1\}$

FORMAL LANGUAGE

- ▶ **alphabet** Σ — set of symbols
 - ▷ latin alphabet $\Sigma_{\text{lat}} = \{a, b, \dots, z\}$
 - ▷ binary alphabet $\Sigma_{\text{bin}} = \{0, 1\}$
- ▶ **word** w over Σ — finite sequence of symbols
 - ▷ *english* and *sdlfkhui* are words over Σ_{lat}
 - ▷ 01101 is a word over Σ_{bin} , but not over Σ_{lat}

FORMAL LANGUAGE

- ▶ **alphabet** Σ — set of symbols
 - ▷ latin alphabet $\Sigma_{\text{lat}} = \{a, b, \dots, z\}$
 - ▷ binary alphabet $\Sigma_{\text{bin}} = \{0, 1\}$
- ▶ **word** w over Σ — finite sequence of symbols
 - ▷ *english* and *sdlfkhui* are words over Σ_{lat}
 - ▷ 01101 is a word over Σ_{bin} , but not over Σ_{lat}
- ▶ **length** $|w|$ — number of symbols of w
 - ▷ word with length zero: ϵ
 - ▷ $|\text{english}| = 7$

FORMAL LANGUAGE

- ▶ **alphabet** Σ — set of symbols
 - ▷ latin alphabet $\Sigma_{\text{lat}} = \{a, b, \dots, z\}$
 - ▷ binary alphabet $\Sigma_{\text{bin}} = \{0, 1\}$
- ▶ **word** w over Σ — finite sequence of symbols
 - ▷ *english* and *sdlfkhui* are words over Σ_{lat}
 - ▷ 01101 is a word over Σ_{bin} , but not over Σ_{lat}
- ▶ **length** $|w|$ — number of symbols of w
 - ▷ word with length zero: ϵ
 - ▷ $|\text{english}| = 7$
- ▶ **Kleene-Star** Σ^* — set of all words over Σ

FORMAL LANGUAGE

- ▶ **alphabet** Σ — set of symbols
 - ▷ latin alphabet $\Sigma_{\text{lat}} = \{a, b, \dots, z\}$
 - ▷ binary alphabet $\Sigma_{\text{bin}} = \{0, 1\}$
- ▶ **word** w over Σ — finite sequence of symbols
 - ▷ *english* and *sdlfkhui* are words over Σ_{lat}
 - ▷ 01101 is a word over Σ_{bin} , but not over Σ_{lat}
- ▶ **length** $|w|$ — number of symbols of w
 - ▷ word with length zero: ϵ
 - ▷ $|\text{english}| = 7$
- ▶ **Kleene-Star** Σ^* — set of all words over Σ
- ▶ **(formal) language** $L \subseteq \Sigma^*$ — set of (selected) words over Σ

EXAMPLE — count_2

Theorem

Let $G = (N, \Sigma, P, S)$ where $N = \{S\}$, $\Sigma = \{a, b\}$ and

$$P = \left\{ \underbrace{S \rightarrow aSb}_{(1)}, \underbrace{S \rightarrow ab}_{(2)} \right\}$$

Then $L(G) = \{a^n b^n : n \in \mathbb{N}\} = \text{count}_2$.

Proof. We just prove that $\text{count}_2 \subseteq L(G)$, i.e. $a^n b^n \in L(G)$ for all $n \in \mathbb{N}$.

► consideration:

$$\begin{aligned} \triangleright S &\vdash_{(1)} aSb \quad \vdash_{(2)} aabb = a^2 b^2 \\ \triangleright S &\vdash_{(1)}^2 a^2 S b^2 \quad \vdash_{(2)} a^2 a b b^2 = a^3 b^3 \quad \dots \end{aligned}$$

► in general:

$$S \vdash_{(1)}^{n-1} a^{n-1} S b^{n-1} \vdash_{(2)} a^{n-1} a b b^{n-1} = a^n b^n$$

EXAMPLE — count_3

Is there a grammar G with $L(G) = \text{count}_3 = \{a^n b^n c^n : n \in \mathbb{N}\}$?

Theorem

Let $G = (N, \Sigma, P, S)$ be a formal grammar with $N = \{S, A, B\}$, $\Sigma = \{a, b, c\}$ and P consists of the following rules:

- ▶ (1) $S \rightarrow abc$
- ▶ (2) $S \rightarrow aSBc$
- ▶ (3) $cB \rightarrow Bc$
- ▶ (4) $bB \rightarrow bb$

Then $L(G) = \text{count}_3$.

Example: $a^3 b^3 c^3 \in L(G)$?

$$\begin{array}{ll} S & \vdash_{(2)}^2 aaSBcBc \quad \vdash_{(1)} aaabcBcBc \\ & \vdash_{(3)}^2 aaabBcBcc \quad \vdash_{(3)}^1 aaabBBccc \\ & \vdash_{(4)}^2 aaabbbccc \end{array}$$

MATHEMATICAL LOGIC

- ▶ (propositional) Logic as formal language L_{\log}
- ▶ alphabet: $\Sigma = \{p_1, p_2, \dots\} \cup \{\neg, \wedge, \vee, (,)\}$
- ▶ words:
 - ▷ $p_1, p_2, \dots \in L_{\log}$
 - ▷ $\neg f \in L_{\log}$ if $f \in L_{\log}$
 - ▷ $(f_1 \wedge f_2) \in L_{\log}$ if $f_1, f_2 \in L_{\log}$
 - ▷ $(f_1 \vee f_2) \in L_{\log}$ if $f_1, f_2 \in L_{\log}$
- ▶ examples:
 - ▷ $(p_1 \wedge p_2) \in L_{\log}$
 - ▷ $((\neg(p_1 \vee p_2) \wedge p_3) \vee \neg p_1) \in L_{\log}$

Question: Which problem is computable with which machine?

CHURCH-TURING thesis

Any real-world computation can be translated into an equivalent computation involving a Turing machine.

Halting Problem: Decide whether a given (arbitrary) program will finish running or continue to run forever