

Hybrid Logics

Undecidability and infinite models

Carlos Areces
carlos.areces@gmailcom

Spring Term 2018
Stanford

What we cover in this lecture

- ▶ Today we will see some examples of modal logics which are **undecidable**.
- ▶ We will show some techniques used to prove undecidability, and other related properties.

The logic $\mathcal{HL}(\downarrow)$

- ▶ We already discussed it would be interesting to have **dynamic naming**, or “variables” in addition to nominals.
- ▶ Suppose we can create names “**on the fly**”. Introduce the $\downarrow x$, that names the current state x .
- ▶ $\downarrow x$ names the current evaluation point, and let us refer to it in the rest of the formula. E.g., $\downarrow x. \Diamond x$ characterizes reflexive points.

The logic $\mathcal{HL}(\downarrow)$

- ▶ We already discussed it would be interesting to have **dynamic naming**, or “variables” in addition to nominals.
- ▶ Suppose we can create names “**on the fly**”. Introduce the $\downarrow x$, that names the current state x .
- ▶ $\downarrow x$ names the current evaluation point, and let us refer to it in the rest of the formula. E.g., $\downarrow x.\Diamond x$ characterizes reflexive points.

To the signature of the basic modal logic add an infinite enumerable set of variables VAR.

Syntax of $\mathcal{HL}(\downarrow)$

$$\varphi ::= x \mid p \mid \neg\varphi \mid \varphi \wedge \psi \mid \langle r \rangle \varphi \mid \downarrow x.\varphi$$

where $p \in \text{PROP}$, $r \in \text{REL}$, $x \in \text{VAR}$.

The logic $\mathcal{HL}(\downarrow)$

The semantics of this logic is defined over usual Kripke models $\mathcal{M} = \langle W, \{R_i\}, V \rangle$ plus a **assignment function** $g : \text{VAR} \rightarrow W$ which assigns variables to elements in the domain.

The logic $\mathcal{HL}(\downarrow)$

The semantics of this logic is defined over usual Kripke models $\mathcal{M} = \langle W, \{R_i\}, V \rangle$ plus a **assignment function** $g : \text{VAR} \rightarrow W$ which assigns variables to elements in the domain.

- Given a model $\mathcal{M} = \langle W, \{R_i\}, V \rangle$ and an assignment g define:

$\mathcal{HL}(\downarrow)$ Semantics:

$$\begin{aligned} \mathcal{M}, g, w \models x & \text{ iff } g(x) = w \\ \mathcal{M}, g, w \models \downarrow x. \varphi & \text{ iff } \mathcal{M}, g_w^x, w \models \varphi \text{ where } g_w^x \text{ is identical to } g \\ & \text{ except } g_w^x(x) = w. \end{aligned}$$

Infinite model

- ▶ We saw that the basic modal logic (and other extensions) have the finite model property
- ▶ This is useful for proving decidability (knowing also a bound for the model size)
- ▶ We will see that $\mathcal{HL}(\downarrow)$ is able to **force** an infinite model
- ▶ By itself, this does not prove undecidability, but it paves the way

Infinite model

- ▶ Write a formula which says that there is a non empty set B whose elements constitute a strict partial order. That is:
 - ▶ Irreflexive
 - ▶ Transitive
- ▶ And where every element has a successor

This implies that B is infinite.

Infinite model

- ▶ Write a formula which says that there is a non empty set B whose elements constitute a strict partial order. That is:
 - ▶ Irreflexive
 - ▶ Transitive
- ▶ And where every element has a successor

This implies that B is infinite.


- ▶ How can we speak about a set of points with a modal formula that is evaluated in a **single point**? **Spy Point!**

Infinite model

- ▶ Write a formula which says that there is a non empty set B whose elements constitute a strict partial order. That is:
 - ▶ Irreflexive
 - ▶ Transitive
- ▶ And where every element has a successor

This implies that B is infinite.

- ▶ How can we speak about a set of points with a modal formula that is evaluated in a **single** point? **Spy Point!**



Forcing and infinite model

Each s -successor has an edge towards s

$$(\textit{Back}) \quad \downarrow s. ([r] \neg s \wedge \langle r \rangle \top \wedge [r] \langle r \rangle s)$$

Forcing and infinite model

Each s -successor has an edge towards s

$$(\textit{Back}) \quad \downarrow s. ([r] \neg s \wedge \langle r \rangle \top \wedge [r] \langle r \rangle s)$$

The s -successors in two steps are s -successors in one step

$$(\textit{Spy}) \quad \downarrow s. ([r][r](\neg s \rightarrow (\downarrow x. \langle r \rangle (s \wedge \langle r \rangle x))))$$

Forcing and infinite model

Each s -successor has an edge towards s

$$(Back) \quad \downarrow s.([r]\neg s \wedge \langle r \rangle \top \wedge [r]\langle r \rangle s)$$

The s -successors in two steps are s -successors in one step

$$(Spy) \quad \downarrow s.([r][r](\neg s \rightarrow (\downarrow x.\langle r \rangle(s \wedge \langle r \rangle x))))$$

The relation over the s -successors is irreflexive

$$(Irr) \quad [r]\neg(\downarrow x.\langle r \rangle x)$$

Forcing and infinite model

Each s -successor has an edge towards s

$$(\textit{Back}) \quad \downarrow s. ([r] \neg s \wedge \langle r \rangle \top \wedge [r] \langle r \rangle s)$$

The s -successors in two steps are s -successors in one step

$$(\textit{Spy}) \quad \downarrow s. ([r][r](\neg s \rightarrow (\downarrow x. \langle r \rangle (s \wedge \langle r \rangle x))))$$

The relation over the s -successors is irreflexive

$$(\textit{Irr}) \quad [r] \neg (\downarrow x. \langle r \rangle x)$$

Every s -successors has a successor which is not s

$$(\textit{Succ}) \quad \downarrow s. ([r] \langle r \rangle \neg s)$$

Forcing and infinite model

Each s -successor has an edge towards s

$$(\textit{Back}) \quad \downarrow s. ([r] \neg s \wedge \langle r \rangle \top \wedge [r] \langle r \rangle s)$$

The s -successors in two steps are s -successors in one step

$$(\textit{Spy}) \quad \downarrow s. ([r][r](\neg s \rightarrow (\downarrow x. \langle r \rangle (s \wedge \langle r \rangle x))))$$

The relation over the s -successors is irreflexive

$$(\textit{Irr}) \quad [r] \neg (\downarrow x. \langle r \rangle x)$$

Every s -successors has a successor which is not s

$$(\textit{Succ}) \quad \downarrow s. ([r] \langle r \rangle \neg s)$$

The relation over the s -successors is transitive

$$(\textit{Tran}) \quad \downarrow s. [r] \downarrow x. [r] (\neg s \rightarrow [r] (\neg s \rightarrow \downarrow z. \langle r \rangle (s \wedge \langle r \rangle (x \wedge \langle r \rangle z))))$$

Forcing and infinite model

Each s -successor has an edge towards s

$$(\textit{Back}) \quad \downarrow s. ([r] \neg s \wedge \langle r \rangle \top \wedge [r] \langle r \rangle s)$$

The s -successors in two steps are s -successors in one step

$$(\textit{Spy}) \quad \downarrow s. ([r][r](\neg s \rightarrow (\downarrow x. \langle r \rangle (s \wedge \langle r \rangle x))))$$

The relation over the s -successors is irreflexive

$$(\textit{Irr}) \quad [r] \neg (\downarrow x. \langle r \rangle x)$$

Every s -successors has a successor which is not s

$$(\textit{Succ}) \quad \downarrow s. ([r] \langle r \rangle \neg s)$$

The relation over the s -successors is transitive

$$(\textit{Tran}) \quad \downarrow s. [r] \downarrow x. [r] (\neg s \rightarrow [r] (\neg s \rightarrow \downarrow z. \langle r \rangle (s \wedge \langle r \rangle (x \wedge \langle r \rangle z))))$$

Let φ be the formula $\textit{Back} \wedge \textit{Spy} \wedge \textit{Irr} \wedge \textit{Succ} \wedge \textit{Tran}$

Forcing an infinite model

Theorem

If $\mathcal{M}, g, w \models \varphi$ then \mathcal{M} is infinite

Proof. By construction of φ .

Forcing an infinite model

Theorem

If $\mathcal{M}, g, w \models \varphi$ then \mathcal{M} is infinite

Proof. By construction of φ .

We have to check also that φ does have models.

Theorem

There exists \mathcal{M}, g, w s.t. $\mathcal{M}, g, w \models \varphi$.

Proof. Let B be an infinite set of elements and w an element such that $w \notin B$. Let R be the smallest relation such that

- ▶ R defines an strict partial order over B
- ▶ wRb and bRw for every element $b \in B$

$\mathcal{M} = \langle B \cup \{w\}, R, V \rangle$ verifies $\mathcal{M}, g, w \models \varphi$ (for any V and g).

Undecidability

- ▶ How do we prove that a logic is undecidable?
- ▶ If we want to prove it in a direct way, we must write a formula that codifies arbitrary executions in a Turing machine
- ▶ The **tiling** problem, which has been proved to be undecidable, will be useful for the modal case

The tiling problem

- ▶ Given a finite set of **types of tiles** \mathcal{T}




The tiling problem

- ▶ Given a finite set of **types of tiles** \mathcal{T}



The **tiling problem**: Is it possible to put tiles of type \mathcal{T} in $\mathbb{N} \times \mathbb{N}$ such that each pair of adjacent tiles has the same color?




The tiling problem

- ▶ Given a finite set of **types of tiles** \mathcal{T}



The **tiling problem**: Is it possible to put tiles of type \mathcal{T} in $\mathbb{N} \times \mathbb{N}$ such that each pair of adjacent tiles has the same color?




- ▶ The tiling problem in $\mathbb{N} \times \mathbb{N}$ is known to be undecidable

The tiling problem

- ▶ Given a finite set of **types of tiles** \mathcal{T}




The **tiling problem**: Is it possible to put tiles of type \mathcal{T} in $\mathbb{N} \times \mathbb{N}$ such that each pair of adjacent tiles has the same color?



- ▶ The tiling problem in $\mathbb{N} \times \mathbb{N}$ is known to be undecidable
- ▶ Given a set of types of tiles \mathcal{T} , we want to write a formula $\varphi_{\mathcal{T}}$ such that $\varphi_{\mathcal{T}}$ is satisfiable iff there exists a tiling for \mathcal{T}

The tiling problem for $\mathcal{HL}(\downarrow)$

- We will use again a **spy point**




- (Notice, codifying the tiling problem does not imply forcing an infinite model, why?)

The tiling problem for $\mathcal{HL}(\downarrow)$

- Let $T = \{T_1, \dots, T_n\}$ be a set of types of tiles


The tiling problem for $\mathcal{HL}(\downarrow)$

- ▶ Let $T = \{T_1, \dots, T_n\}$ be a set of types of tiles
- ▶ Given a type of tile T_i , $u(T_i)$, $r(T_i)$, $d(T_i)$, $l(T_i)$ represent the colors of T_i corresponding to their sides.




The tiling problem for $\mathcal{HL}(\downarrow)$

- ▶ Let $T = \{T_1, \dots, T_n\}$ be a set of types of tiles
- ▶ Given a type of tile T_i , $u(T_i)$, $r(T_i)$, $d(T_i)$, $l(T_i)$ represent the colors of T_i corresponding to their sides.



- ▶ Suppose that we also have a modality $\langle o \rangle$ that we use to move from the spy point into every tile
- ▶ And we have as well modalities $\langle u \rangle$ and $\langle r \rangle$ in order to move up from a tile and to the right of a tile respectively.



The tiling problem for $\mathcal{HL}(\downarrow)$

First we codify the grid:

Each s -successor has an edge towards s

$$(\textit{Back}) \quad [o] \neg s \wedge \langle o \rangle \top \wedge [o] \langle o \rangle s$$

The tiling problem for $\mathcal{HL}(\downarrow)$

First we codify the grid:

Each s -successor has an edge towards s

$$(\textit{Back}) \quad [o] \neg s \wedge \langle o \rangle \top \wedge [o] \langle o \rangle s$$

The successor of a tile is an s -successor

$$(\textit{Spy}) \quad [o][\dagger](\downarrow x. \langle o \rangle (s \wedge \langle o \rangle x)) \quad \dagger \in \{r, u\}$$

The tiling problem for $\mathcal{HL}(\downarrow)$

First we codify the grid:

Each s -successor has an edge towards s

$$(\textit{Back}) \quad [o] \neg s \wedge \langle o \rangle \top \wedge [o] \langle o \rangle s$$

The successor of a tile is an s -successor

$$(\textit{Spy}) \quad [o][\dagger](\downarrow x. \langle o \rangle (s \wedge \langle o \rangle x)) \quad \dagger \in \{r, u\}$$

From a tile, s cannot be reached using r and u

$$(\textit{Empty}) \quad [o][\dagger] \neg s \quad \dagger \in \{r, u\}$$

The tiling problem for $\mathcal{HL}(\downarrow)$

First we codify the grid:

Each s -successor has an edge towards s

$$(\textit{Back}) \quad [o] \neg s \wedge \langle o \rangle \top \wedge [o] \langle o \rangle s$$

The successor of a tile is an s -successor

$$(\textit{Spy}) \quad [o][\dagger](\downarrow x. \langle o \rangle (s \wedge \langle o \rangle x)) \quad \dagger \in \{r, u\}$$

From a tile, s cannot be reached using r and u

$$(\textit{Empty}) \quad [o][\dagger] \neg s \quad \dagger \in \{r, u\}$$

Every tiles has a tile above and to the right

$$(\textit{Grid}) \quad [o] \langle \dagger \rangle \top \quad \dagger \in \{r, u\}$$

The tiling problem for $\mathcal{HL}(\downarrow)$

First we codify the grid:

Each s -successor has an edge towards s

$$(\textit{Back}) \quad [o] \neg s \wedge \langle o \rangle \top \wedge [o] \langle o \rangle s$$

The successor of a tile is an s -successor

$$(\textit{Spy}) \quad [o][\dagger](\downarrow x. \langle o \rangle (s \wedge \langle o \rangle x)) \quad \dagger \in \{r, u\}$$

From a tile, s cannot be reached using r and u

$$(\textit{Empty}) \quad [o][\dagger] \neg s \quad \dagger \in \{r, u\}$$

Every tiles has a tile above and to the right

$$(\textit{Grid}) \quad [o] \langle \dagger \rangle \top \quad \dagger \in \{r, u\}$$

Each tile has only one tile above and only one tile to the right

$$(\textit{Func}) \quad [o] \downarrow x. ([\dagger] \downarrow y. (\langle o \rangle \langle o \rangle (x \wedge [\dagger] y))) \quad \dagger \in \{r, u\}$$

The tiling problem for $\mathcal{HL}(\downarrow)$

First we codify the grid:

Each s -successor has an edge towards s

$$(\textit{Back}) \quad [o] \neg s \wedge \langle o \rangle \top \wedge [o] \langle o \rangle s$$

The successor of a tile is an s -successor

$$(\textit{Spy}) \quad [o][\dagger](\downarrow x. \langle o \rangle (s \wedge \langle o \rangle x)) \quad \dagger \in \{r, u\}$$

From a tile, s cannot be reached using r and u

$$(\textit{Empty}) \quad [o][\dagger] \neg s \quad \dagger \in \{r, u\}$$

Every tiles has a tile above and to the right

$$(\textit{Grid}) \quad [o] \langle \dagger \rangle \top \quad \dagger \in \{r, u\}$$

Each tile has only one tile above and only one tile to the right

$$(\textit{Func}) \quad [o] \downarrow x. ([\dagger] \downarrow y. (\langle o \rangle \langle o \rangle (x \wedge [\dagger] y))) \quad \dagger \in \{r, u\}$$

There is confluence between up-right and right-up

$$(\textit{Conf}) \quad [o] \downarrow x. (\langle u \rangle \langle r \rangle \downarrow y. (\langle o \rangle \langle o \rangle (x \wedge \langle r \rangle \langle u \rangle y)))$$

The tiling problem for $\mathcal{HL}(\downarrow)$

Finally, there is a tile in each point of the grid and all the colors coincide:

Each point has a single type of tile

$$(\textit{Unique}) \quad [o] \left(\bigvee_{1 \leq i \leq n} t_i \wedge \bigwedge_{1 \leq i < j \leq n} (t_i \rightarrow \neg t_j) \right)$$

The tiling problem for $\mathcal{HL}(\downarrow)$

Finally, there is a tile in each point of the grid and all the colors coincide:

Each point has a single type of tile

$$(\textit{Unique}) \quad [o] \left(\bigvee_{1 \leq i \leq n} t_i \wedge \bigwedge_{1 \leq i < j \leq n} (t_i \rightarrow \neg t_j) \right)$$

Each tile has an adjacent tile above which is appropriately colored

$$(\textit{Vert}) \quad [o] \bigwedge_{1 \leq i \leq n} \left(t_i \rightarrow \langle u \rangle \bigvee_{1 \leq j \leq n, u(T_i)=d(T_j)} t_j \right)$$

The tiling problem for $\mathcal{HL}(\downarrow)$

Finally, there is a tile in each point of the grid and all the colors coincide:

Each point has a single type of tile

$$(\textit{Unique}) \quad [o] \left(\bigvee_{1 \leq i \leq n} t_i \wedge \bigwedge_{1 \leq i < j \leq n} (t_i \rightarrow \neg t_j) \right)$$

Each tile has an adjacent tile above which is appropriately colored

$$(\textit{Vert}) \quad [o] \bigwedge_{1 \leq i \leq n} \left(t_i \rightarrow \langle u \rangle \bigvee_{1 \leq j \leq n, u(T_i)=d(T_j)} t_j \right)$$

Each tile has an adjacent tile to the right which is appropriately colored

$$(\textit{Horiz}) \quad [o] \bigwedge_{1 \leq i \leq n} \left(t_i \rightarrow \langle r \rangle \bigvee_{1 \leq j \leq n, r(T_i)=l(T_j)} t_j \right)$$

The tiling problem for $\mathcal{HL}(\downarrow)$

Finally, there is a tile in each point of the grid and all the colors coincide:

Each point has a single type of tile

$$(\textit{Unique}) \quad [o] \left(\bigvee_{1 \leq i \leq n} t_i \wedge \bigwedge_{1 \leq i < j \leq n} (t_i \rightarrow \neg t_j) \right)$$

Each tile has an adjacent tile above which is appropriately colored

$$(\textit{Vert}) \quad [o] \bigwedge_{1 \leq i \leq n} \left(t_i \rightarrow \langle u \rangle \bigvee_{1 \leq j \leq n, u(T_i)=d(T_j)} t_j \right)$$

Each tile has an adjacent tile to the right which is appropriately colored

$$(\textit{Horiz}) \quad [o] \bigwedge_{1 \leq i \leq n} \left(t_i \rightarrow \langle r \rangle \bigvee_{1 \leq j \leq n, r(T_i)=l(T_j)} t_j \right)$$

Let

$$\varphi_T = \downarrow s. (\textit{Back} \wedge \textit{Empty} \wedge \textit{Spy} \wedge \textit{Grid} \wedge \textit{Func} \wedge \textit{Conf} \wedge \textit{Unique} \wedge \textit{Vert} \wedge \textit{Horiz})$$

The tiling problem for $\mathcal{HL}(\downarrow)$

Theorem

Let T be a set of tile types. Then φ_T is satisfiable iff there is a T -tiling of $\mathbb{N} \times \mathbb{N}$.

The tiling problem for $\mathcal{HL}(\downarrow)$

Theorem

Let T be a set of tile types. Then φ_T is satisfiable iff there is a T -tiling of $\mathbb{N} \times \mathbb{N}$.

Proof:

(\Rightarrow) Suppose that $\mathcal{M}, w \models \varphi_T$. By construction, \mathcal{M} represents a tiling in $\mathbb{N} \times \mathbb{N}$.

The tiling problem for $\mathcal{HL}(\downarrow)$

Theorem

Let T be a set of tile types. Then φ_T is satisfiable iff there is a T -tiling of $\mathbb{N} \times \mathbb{N}$.

Proof:

- (\Rightarrow) Suppose that $\mathcal{M}, w \models \varphi_T$. By construction, \mathcal{M} represents a tiling in $\mathbb{N} \times \mathbb{N}$.
- (\Leftarrow) Suppose that $f : \mathbb{N} \times \mathbb{N} \rightarrow T$ is a tiling in $\mathbb{N} \times \mathbb{N}$. We define the model $\mathcal{M} = \langle W, \{R_o, R_u, R_r\}, V \rangle$:
 - ▶ $W = \mathbb{N} \times \mathbb{N} \cup \{w\}$
 - ▶ $R_o = \{(w, v), (v, w) \mid v \in \mathbb{N} \times \mathbb{N}\}$
 - ▶ $R_u = \{(x, y), (x, y + 1) \mid x, y \in \mathbb{N}\}$
 - ▶ $R_r = \{(x, y), (x + 1, y) \mid x, y \in \mathbb{N}\}$
 - ▶ $V(t_i) = \{x \mid x \in \mathbb{N} \times \mathbb{N}, f(x) = T_i\}$

It is not hard to see that $\mathcal{M}, w \models \varphi_T$

A tiling for every need

- ▶ Tiling problem are not only useful for proving undecidability

A tiling for every need

- ▶ Tiling problem are not only useful for proving undecidability
- ▶ Tiling problems are also useful for proving complexity bounds and other degrees of undecidability. For example:

A tiling for every need

- ▶ Tiling problems are not only useful for proving undecidability
- ▶ Tiling problems are also useful for proving complexity bounds and other degrees of undecidability. For example:
 - ▶ The tiling problem we just saw is Π_1^0 -complete.

A tiling for every need

- ▶ Tiling problem are not only useful for proving undecidability
- ▶ Tiling problems are also useful for proving complexity bounds and other degrees of undecidability. For example:
 - ▶ The tiling problem we just saw is Π_1^0 -complete.
 - ▶ If we distinguish T_1 , a particular type of tile, the tiling problem in $\mathbb{N} \times \mathbb{N}$ where T_1 occurs infinitely often in the first row is Σ_1^1 -complete.

A tiling for every need

- ▶ Tiling problem are not only useful for proving undecidability
- ▶ Tiling problems are also useful for proving complexity bounds and other degrees of undecidability. For example:
 - ▶ The tiling problem we just saw is Π_1^0 -complete.
 - ▶ If we distinguish T_1 , a particular type of tile, the tiling problem in $\mathbb{N} \times \mathbb{N}$ where T_1 occurs infinitely often in the first row is Σ_1^1 -complete.
 - ▶ The “two person corridor tiling” is EXPTIME-complete

Two person corridor tiling

- ▶ This tiling has 3 players: Spoiler, Duplicator and a referee.

Two person corridor tiling


- ▶ This tiling has 3 players: Spoiler, Duplicator and a referee.
- ▶ From the finite set of types of tiles $T = \{t_0, t_1, \dots, t_{s+1}\}$ we will distinguish t_0 y t_{s+1}

Two person corridor tiling

- ▶ This tiling has 3 players: Spoiler, Duplicator and a referee.
- ▶ From the finite set of types of tiles $T = \{t_0, t_1, \dots, t_{s+1}\}$ we will distinguish t_0 y t_{s+1}
- ▶ As an input parameter we also get a $n \in \mathbb{N}$, which defines the width of the corridor

Two person corridor tiling

- ▶ This tiling has 3 players: Spoiler, Duplicator and a referee.
- ▶ From the finite set of types of tiles $T = \{t_0, t_1, \dots, t_{s+1}\}$ we will distinguish t_0 y t_{s+1}
- ▶ As an input parameter we also get a $n \in \mathbb{N}$, which defines the width of the corridor
- ▶ The game starts with the referee putting tiles as follows



Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile
- ▶ The rules about color coincidence are the usual ones (and they include the “borders” of the corridor)

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile
- ▶ The rules about color coincidence are the usual ones (and they include the “borders” of the corridor)
- ▶ The players play alternatively, and Spoiler plays first.

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile
- ▶ The rules about color coincidence are the usual ones (and they include the “borders” of the corridor)
- ▶ The players play alternatively, and Spoiler plays first.
- ▶ When do the players win or lose?

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile
- ▶ The rules about color coincidence are the usual ones (and they include the “borders” of the corridor)
- ▶ The players play alternatively, and Spoiler plays first.
- ▶ When do the players win or lose?
 - ▶ If after a finite number of rounds a tile of type t_{s+1} is put in the first column, Spoiler wins

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile
- ▶ The rules about color coincidence are the usual ones (and they include the “borders” of the corridor)
- ▶ The players play alternatively, and Spoiler plays first.
- ▶ When do the players win or lose?
 - ▶ If after a finite number of rounds a tile of type t_{s+1} is put in the first column, Spoiler wins
 - ▶ Otherwise (if no player can make a valid move, t_{s+1} is not in the column 1, or the game goes on infinitely) Duplicator wins

Two person corridor tiling

- ▶ The rules for completing the corridor are strict: from down to up and from left to right
- ▶ I.e., the players cannot choose **where** to put a tile, they can only choose the **type** of tile
- ▶ The rules about color coincidence are the usual ones (and they include the “borders” of the corridor)
- ▶ The players play alternatively, and Spoiler plays first.
- ▶ When do the players win or lose?
 - ▶ If after a finite number of rounds a tile of type t_{s+1} is put in the first column, Spoiler wins
 - ▶ Otherwise (if no player can make a valid move, t_{s+1} is not in the column 1, or the game goes on infinitely) Duplicator wins
- ▶ The problem of detecting if Spoiler has a winning strategy is known to be EXPTIME-complete.

Two person corridor tiling

- ▶ Using the “two person corridor tiling” one can prove that PDL is EXPTIME-hard, codifying the tree of possible moves between Spoiler y Duplicator.
- ▶ Also, it can be used to prove that $K + A$ is EXPTIME-hard.