Statistical Language Modeling for Information Access Theory IV: Between IR and IE

Maarten de Rijke Edgar Meij Krisztian Balog

University of Amsterdam Norwegian University of Science and Technology

August 1-4, 2011

Outline

1 Expertise Retrieval

Setting the scence Models for expertise retrieval Let's evaluate

2 Retrieving Questions from Question and Answer Archives

3 Wrap Up and Look Ahead

What Is Expertise Retrieval About?

- One line summary: finding and profiling people within an organizational setting
- Background, models for expertise retrieval, experimental setup and evaluation, recent developments
- Presentation mostly based on Krisztian Balog, People Search in the Enterprise, PhD thesis, U. Amsterdam, July 2008
 - http://krisztianbalog.com/phd-thesis/

From Documents to Things to People


- Increasingly, search engines become aware of entities and entity like classes: CDs, books, people, locations, answers, ...
- This lecture: people and answers
- · Why interesting
 - From a modeling point of view: entities are directly represented (yet)—you need to get to them by collecting evidence and associating it to them, somehow
 - Mixes information retrieval and information extraction, providing a level of focus not offered by document retrieval
 - People love to search for people


















- >> SEARCH All Public Records >> SEARCH Phone Numbers
- >> SEARCH Addresses
- >> SEARCH Neighbors >> SEARCH Relatives
- >> SEARCH Potential Dates >> SEARCH Aquaintances
- >> SEARCH Neighbors
- >> SEARCH Correctional Files
- >> SEARCH Criminal Files >> SEARCH Family History
- >> SEARCH Classmates
- >> SEARCH Arrest Records
- >> SEARCH Felony Records
- >> SEARCH Birth Records >> SEARCH Phone Directories
- >> SEARCH Obituaries
- >> SEARCH Death Records
- >> SEARCH Last Names
- >> SEARCH Inmate Records >> SEARCH Business Information
- >> SEARCH Vital records
- >> SEARCH Ancestry Archives
- >> SEARCH Arrest Records
- >> SEARCH Phone Books
- >> SEARCH Birth Records
- >> SEARCH Correctional Files
- >> SEARCH Courthouses
- >> SEARCH Lost people
- >> SEARCH Incarceration Arrests
- >> SEARCH Judgment Files
- >> SEARCH Old Marriage Records
- >> SEARCH Military records
- >> SEARCH Missing people
- >> SEARCH Naturalization Records
- >> SEARCH Sentencing Files
- >> SEARCH Sex Offenders
- >> SEARCH Missing Children
- >> SEARCH Most Wanted
- >> SEARCH Captured Criminals
- >> SEARCH Cemetery Records
- >> SEARCH Fugitives
- >> SEARCH Family Tree
- >> SEARCH Conviction Files
- >> SEARCH Crime Records



4 Phttp://recordsfinder.net

RECORDSFINDER.net

108) * News (608) *

In addition, RecordsFinder.net also gives you immediate

- Investigate a suspicious person or strange neighbor
- · Find out if a sex offender lives near you Find Death Records and Obituaries
- Get sources for Social Security Records in any state
- Search Our Criminal Record Database
- Search Missing People and Children
- Lookup Civil and Census Records
- Lookup Phone Numbers & Addresses


Welcome to RecordsFinder.net

Flavors of People Search

- Locating classmates and old friends
- Finding dates, partners
- White/yellow pages (name, addres, phone, ...)
- Background check (recordsfinder.com: "investigate a susicious person or strange neighbor")
- Interest in this lecture: professional or work-related people search applications
 - A personnel officer wants to find information about a person who applied for a specific position
 - A company requires the state-of-the-art in some field, therefore they want to contact with someone from a knowledge institute
 - An enterprise needs to set up a task force to accomplish some objective

Two Main Tasks

- Expert finding
 - Identifying a list of people who are knowledgeable about a given topic Who are the experts on topic X?
- Expert profiling
 - Returning a list of topics that a person is knowledgeable about
 - What topics does person Y know about?
- Concretely:



Two Main Tasks

• Concretely: http://www.uvt.nl/webwijs/

expert finding





expert profiling



Phone +31 13 466 3117 Fax +31 13 466 2892 E-mail: Antal.vdnBosch@uvt.nl

Present



stancon V

Expertise

My research is positioned in the intersection between artificial intelligence and linguistics. I am specialized in machine learning and language lechnology / computational linguistics. As for applications, I have professional oxperience with speech synthesis, the automatic syntectic and sementic analysis of text, lext mining, dialous systems, and spelling correction.

Subjects artificial intelligence

computer linguistics language technology speech technology syntax talking computer


Additional Tasks

- Mining contact details
 - Essential for an operational system
- Finding similar experts
 - Counterpart of "find similar pages" feature of Web search engines
- Enterprise document search
 - Not just names, but documents relevant to the topic

Language Modeling Framework

- Expert finding: p(ca|q) the probability of a candidate being an expert given the query topic q?
- Expert profiling: p(q|ca) the probability of a knowledge area (topic) being part of the candidate's profile?
- Use Bayes to reduce to p(q|ca)

Main Building Blocks



p(ca|q) — expert finding

p(q|ca) — expert profiling

Quickly: Two Models for Expertise Retrieval

- Estimating p(q|ca)... how do we find experts? how do **you** find experts?
- An association finding problem
 - candidate-based: create a textual model candidates' knowledge according to the document with which they associated
 - document-based: identify the docs that best describe the topic, then find out who is most strongly associated with them

Model 1: Candidate Model

- Collect all term information from all documents associated with given candidate
- Smooth it with a background model
- Use this to represent candidate
- In a few steps

•
$$p(t|M_{ca}) = (1 - \lambda) \cdot p(t|ca) + \lambda \cdot p(t)$$

•
$$p(t|ca) = \sum_{d} p(t|d) \cdot p(d|ca)$$

•
$$p(q|M_{ca}) = \prod_{t \in a} p(t|M_{ca})^{n(t,q)}$$

• Putting it altogether:

$$p(q|M_{ca}) = \prod_{t \in q} \left\{ (1 - \lambda) \cdot \left(\sum_{d} p(t|d) \cdot p(d|ca) \right) + \lambda \cdot p(t) \right\}^{n(t,q)}$$



Model 2: Document Model

- Find docs relevant to query and determine who's most strongly associated with the relevant docs
- Step by step:
 - $p(q|ca) = \sum_{d} p(q|d)p(d|ca)$
 - $p(q|M_d) = \prod_{t \in a} p(t|M_d)^{n(t,q)}$
 - $p(t|M_d) = (1 \lambda) \cdot p(t|d) + \lambda \cdot p(t)$
- All in one:

All in one:
$$p(q|ca) = \sum_{d} \left\{ ((1 - \lambda) \cdot p(t|d) + \lambda \cdot p(t))^{n(t,q)} \right\} \cdot p(d|ca)$$
 query
$$p(q|d) \qquad \text{occument} \qquad p(d|ca)$$
 candidate

Document-Candidate Associations

- *Need*: estimate the probability that a doc is associated with a candidate p(d|ca)
- Assume: extraction component produces n(d, ca), the number of times person ca appears in doc d

$$p(d|ca) = \frac{p(ca|d) \cdot p(d)}{p(ca)}$$

- Multiple choices
 - Boolean: associations are binary; p(ca|d) = 1 if n(ca, d) > 0, 0 otherwise
 - TF.IDF like features
 - KL divergence (see below)
 - ...

Smoothing

- JM
- Dirichlet $\lambda = \frac{\beta}{\beta + n(x)}$ where n(x) is
 - Model 1: sum of lengths of all docs assocated with a given candidate (x = ca)
 - Model 2: document length (x = d)

and β is the avg representation length

- Model 1: of a candidate representation
- Model 2: of a doc

TREC enterprise track

Tasks at the enterprise track

| | TREC | | | | |
|--------------------------|------|------|------|--|--|
| Task | 2005 | 2006 | 2007 | | |
| Expert search | х | x | х | | |
| E-mail known item search | x | | | | |
| E-mail discussion search | x | x | | | |
| Document search | | | x | | |

- Standard metrics: MAP, MRR, both for expert finding and for expert profiling
- Multiple collections, with their own characteristics...
 - W3C (TREC 2006, 2006): w3c.org
 - CSIRO (TREC 2007, 2008): csiro.au
 - UvT Epert Collection: uvt.nl/webwijs

Expert Finding: Model 1 vs Model 2

| Model | TREC 2005 | | TREC 2006 | | TREC 2007 | |
|-------|-----------|---------------|----------------------|---------------|---------------|-------|
| | MAP | MRR | MAP | MRR | MAP | MRR |
| 1 | .1883 | .4692 | .3206 | .7264 | .3700 | .5303 |
| 2 | .2053 | $.6088^{(2)}$ | .4660 ⁽³⁾ | $.9354^{(3)}$ | $.4137^{(1)}$ | .5666 |

Table 5.1: Model 1 vs. Model 2 on the expert finding task, using the TREC 2005–2007 test collections. Best scores for each year are in boldface.




Figure 6.2: Topic-level differences in scores, Model 1 (baseline) vs Model 2. (Top): AP; (Bottom): RR. From left to right: TREC 2005, 2006, 2007.

Expert Profiling

| | | Uv | UvT ALL | | | U√T MAIN | | | |
|----------|-------|-------|----------|----------------------|-------|----------|----------|----------------------|--|
| Language | Mod | lel 1 | Mod | lel 2 | Mod | del 1 | Mod | .el 2 | |
| | MAP | MRR | MAP | MRR | MAP | MRR | MAP | MRR | |
| English | .2023 | .3913 | | .4968 ⁽³⁾ | | .4375 | .3549(3) | | |
| Dutch | .2081 | .4130 | .2503(3) | .4963 ⁽³⁾ | .2782 | .4155 | .3102(3) | .4854 ⁽³⁾ | |

Table 5.5: Model 1 vs. Model 2 on ALL vs. MAIN topics of the UvT collection. Best scores for each language are in boldface.




Figure 6.5: Topic-level differences in scores, Model 1 (baseline) vs Model 2. (Top): AP; (Bottom): RR. From left to right: English ALL, Dutch ALL, English MAIN, and Dutch MAIN.

Variations and Improvements

- Better estimates of candidate-document associations
- Bring in organisational structure
 - Smooth with documents from colleagues in the same group
- Proximity-based models
 - Passage/window based (M1B, M2B)
- Weigh candidate's weight in doc using KL-divergence between candidate's LM and doc LM
- Boosting underlying doc retrieval (BFB, query expansion using expert profiles, doc priors, ...)
- Careful combination leads to MAP scores of 0.5267 on TREC 2007 data (M1B; SIGIR 2009)
- Up to **0.5405** with some "secret" ingredients (M1B; SIGIR 2009)
- Up to **0.5747** without secret sauce but with rich query model based on example documents (M1B; CIKM 2008)

Something Else

- Finding Similar Experts task
 - Balog and De Rijke, SIGIR 2007
- Complement topic-centric models with contextual factors
 - Media experience, "up-to-date-ness", organizational structure, reliability, proximity, position, . . .
 - Model as priors
- Experiment with Tilburg University science communicators
 - If the expert you'd normally recommend is not available, whom would you recommend?
- Contextual factors significantly improve early precision (MRR): $0.54 \rightarrow 0.59$
 - Hofmann et all, JASIST 2010

Expertise Retrieval Upshot

- Going beyond documents
 - After all, document search has become a commodity (on the web, at least)
- Language models offer a flexible setting for modeling ER, accommodating priors, mixtures, etc.
- Very competitive performance on a range of ER tasks
- Lots of modeling work left to be done, lots of work on the interface of IR/IE left to be done
 - Be creative

Hang on

If You Have A Hammer...

- Apply the underlying type-topic associations elsewhere
 - Stakeholders in the news
 - Influential authors on a given topic (digital library setting)
 - Intelligence
 - · Blog distillation
 - Spotting moods associated with a given topic
 - Getting to know your politician
 - Automatic composition of committees, PCs, ...
 - ...
- What's next
 - Web-based ER
 - Result presentation
 - New evaluation/application settings

Question Answering vs Question Retrieval

- QA has been around since the early 1960s
- Initially as a front end to (structured database)
 - Early fame for systems provided access to baseball data, data on rocks collected by NASA during its moon missions, ...
- Since late 1990s lot of attention for *corpus-based* QA: given a text corpus and a question, a system has to identify and return "the answer" (in the corpus)
- Recent rise in interest in *community-based QA*: retrieving questions that are similar to a given input query
 - FAQs (Jijkoun and de Rijke, CIKM 2005)
 - Yahoo! Answers (Agichtein et al, WSDOM 2008)
 - wondir.com (Xue et al, SIGIR 2008)

Combining a Translation-Based LM with a QL Model

- Given a question, find a good answer in the repository
 - Unlike standard doc retrieval, can use both answer part and question part (of items in repository)
- Xue et al combine a translation-based language model for the question part with a query likelihood approach for the answer part
- Word mismatch problem ("the vocabulary gap") potentially worse than with doc retrieval
 - short bits of text, little redundancy

The Models

- Setting: query ("the user's question"): q, archive consisting of (q, a) pairs
- $p(\mathbf{q}|(q,a)) = \prod_{w \in \mathbf{q}} p(w|(q,a))$
- $p(w|(q,a)) = \frac{|(q,a)|}{|(q,a)|+\lambda} p_{mx}(w|(q,a)) + \frac{\lambda}{|(q,a)|+\lambda} p_{ml}(w|GE)$
- $p_{mx}(w|(q, a)) = \alpha p_{ml}(w|q) + \beta \sum_{t \in q} p(w|t) p_{ml}(t|q) + \gamma p_{ml}(w|a)$
- Huh?
 - Generation probability of the question:

$$\alpha p_{ml}(w|q) + \beta \sum_{t \in q} p(w|t) p_{ml}(t|q)$$

• Generation probility of the answer:

$$\gamma p_{ml}(w|a)$$

Evaluation

- Use IBM Model 1 to estimate translation probabilities $p(w_i|w_j)$, using (q, a) and (a, q) pairs as parallel corpus
 - Briefly: EM plus maximum likelihood estimates
- Compare: standard mixture LM ($\beta = 0$), translation model ($\gamma = 0$), everything together ($\alpha \cdot \beta \cdot \gamma > 0$)
- Evaluation: using 50 TREC QA questions, against a 1M (q, a) collection

| Model | MAP | P@10 |
|--------------|--------|--------|
| $\beta = 0$ | 0.3791 | 0.2368 |
| $\gamma = 0$ | 0.4238 | 0.2868 |
| full | 0.4885 | 0.3053 |

What's Next Here?

- Parameter estimation
- Bringing in additional factors
 - Social features (number of stars)
 - Question class specific features

• ...

Wrap Up and Look Ahead

- Summary
 - Getting started with expertise retrieval
 - A bit on retrieving questions and answers
- What else?
 - Learning to rank
 - Discriminative vs generative models
 - So many ranking criteria
 - Learning to rank (offline, online)
 - Semantic search
 - Query modeling
 - Evaluation methodology
 - ...
- So many things you can work on!