

Mathematics for Informatics

Carlos Areces and Patrick Blackburn

`areces@loria.fr`

`blackbur@loria.fr`

`http://www.loria.fr/~areces`

`http://www.loria.fr/~blackbur`

INRIA Lorraine
Nancy, France

2007/2008

The Course

The Programing Language *S*

- ▶ imperative style, very simple

The Programming Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y
 - ▶ temporal variables: Z_1, Z_2, \dots
 - ▶ you don't need to declare them
 - ▶ they are all initialized to the value 0

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y
 - ▶ temporal variables: Z_1, Z_2, \dots
 - ▶ you don't need to declare them
 - ▶ they are all initialized to the value 0
- ▶ The only data type: the natural numbers (including 0)
 - ▶ there are no constants

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y
 - ▶ temporal variables: Z_1, Z_2, \dots
 - ▶ you don't need to declare them
 - ▶ they are all initialized to the value 0
- ▶ The only data type: the natural numbers (including 0)
 - ▶ there are no constants
- ▶ increment in one: $X_1 \leftarrow X_1 + 1$

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y
 - ▶ temporal variables: Z_1, Z_2, \dots
 - ▶ you don't need to declare them
 - ▶ they are all initialized to the value 0
- ▶ The only data type: the natural numbers (including 0)
 - ▶ there are no constants
- ▶ increment in one: $X_1 \leftarrow X_1 + 1$
- ▶ decrement in one:
 - ▶ $X_1 \leftarrow X_1 - 1$
 - ▶ if X_1 is 0 then it won't be modified

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y
 - ▶ temporal variables: Z_1, Z_2, \dots
 - ▶ you don't need to declare them
 - ▶ they are all initialized to the value 0
- ▶ The only data type: the natural numbers (including 0)
 - ▶ there are no constants
- ▶ increment in one: $X_1 \leftarrow X_1 + 1$
- ▶ decrement in one:
 - ▶ $X_1 \leftarrow X_1 - 1$
 - ▶ if X_1 is 0 then it won't be modified
- ▶ a primitive IF GOTO construction
 - ▶ IF $X_1 \neq 0$ GOTO A
 - ▶ A is a label that marks another instruction in the program

The Programing Language \mathcal{I}

- ▶ imperative style, very simple
 - ▶ input variables: X_1, X_2, \dots
 - ▶ output variable (only one): Y
 - ▶ temporal variables: Z_1, Z_2, \dots
 - ▶ you don't need to declare them
 - ▶ they are all initialized to the value 0
- ▶ The only data type: the natural numbers (including 0)
 - ▶ there are no constants
- ▶ increment in one: $X_1 \leftarrow X_1 + 1$
- ▶ decrement in one:
 - ▶ $X_1 \leftarrow X_1 - 1$
 - ▶ if X_1 is 0 then it won't be modified
- ▶ a primitive IF GOTO construction
 - ▶ IF $X_1 \neq 0$ GOTO A
 - ▶ A is a label that marks another instruction in the program
- ▶ you can't call subroutines.

Example 1

[A] $X \leftarrow X - 1$
 $Y \leftarrow Y + 1$
 IF $X \neq 0$ GOTO A

- ▶ We write X for X_1 ; Z for Z_1
- ▶ when $X = 0$ the program stops as there is no next instruction
- ▶ it computes the function $f : \mathbb{N} \rightarrow \mathbb{N}$,

$$f(x) = \begin{cases} x & \text{if } x \neq 0 \\ 1 & \text{otherwise} \end{cases}$$

- ▶ it always leaves the variable X in 0

Example 2

```
[A]   IF  $X \neq 0$  GOTO  $B$   
       $Z \leftarrow Z + 1$   
      IF  $Z \neq 0$  GOTO  $E$   
[B]    $X \leftarrow X - 1$   
       $Y \leftarrow Y + 1$   
       $Z \leftarrow Z + 1$   
      IF  $Z \neq 0$  GOTO  $A$ 
```

- it computes the function $f : \mathbb{N} \rightarrow \mathbb{N}, f(x) = x$

Example 2

```
[A]   IF  $X \neq 0$  GOTO  $B$   
       $Z \leftarrow Z + 1$   
      IF  $Z \neq 0$  GOTO  $E$   
[B]    $X \leftarrow X - 1$   
       $Y \leftarrow Y + 1$   
       $Z \leftarrow Z + 1$   
      IF  $Z \neq 0$  GOTO  $A$ 
```

- ▶ it computes the function $f : \mathbb{N} \rightarrow \mathbb{N}, f(x) = x$
- ▶ when it tries to go to E , it finishes

Example 2

```
[A]   IF  $X \neq 0$  GOTO  $B$   
       $Z \leftarrow Z + 1$   
      IF  $Z \neq 0$  GOTO  $E$   
[B]    $X \leftarrow X - 1$   
       $Y \leftarrow Y + 1$   
       $Z \leftarrow Z + 1$   
      IF  $Z \neq 0$  GOTO  $A$ 
```

- ▶ it computes the function $f : \mathbb{N} \rightarrow \mathbb{N}$, $f(x) = x$
- ▶ when it tries to go to E , it finishes
- ▶ In the example, Z is used only to force an unconditional jump.
In general GOTO L is equivalent to

```
 $V \leftarrow V + 1$   
IF  $V \neq 0$  GOTO  $L$ 
```

where V is a new variable.

Macros

- ▶ \mathcal{S} does not have unconditional jump
- ▶ but we can simulate it with GOTO L

Macros

- ▶ \mathcal{S} does not have unconditional jump
- ▶ but we can simulate it with GOTO L
- ▶ we use it as if it were part of the language, but
 - ▶ each time that we see

GOTO L

in a program P , we replace it with

$V \leftarrow V + 1$

IF $V \neq 0$ GOTO L

where V is a variable that does not appears in P .

Macros

- ▶ \mathcal{S} does not have unconditional jump
- ▶ but we can simulate it with GOTO L
- ▶ we use it as if it were part of the language, but
 - ▶ each time that we see

GOTO L

in a program P , we replace it with

$V \leftarrow V + 1$

IF $V \neq 0$ GOTO L

where V is a variable that does not appear in P .

We will see that we can simulate many other operations.

Once we know that we can write them down in \mathcal{S} , we will use them as if they were part of the language (they are called **pseudoinstructions**)

- ▶ the abbreviated form it's called a **macro**
- ▶ the program that the macro stands for it's called **macro expansion**

Macro for variable assignment: $V \leftarrow V'$

[A] IF $X \neq 0$ GOTO B

GOTO C

[B] $X \leftarrow X - 1$

$Y \leftarrow Y + 1$

$Z \leftarrow Z + 1$

GOTO A

[C] IF $Z \neq 0$ GOTO D

GOTO E

[D] $Z \leftarrow Z - 1$

$X \leftarrow X + 1$

GOTO C

Macro for variable assignment: $V \leftarrow V'$

- the first cycle copies the value from X into Y and Z

[A] IF $X \neq 0$ GOTO B

GOTO C

[B] $X \leftarrow X - 1$

$Y \leftarrow Y + 1$

$Z \leftarrow Z + 1$

GOTO A

[C] IF $Z \neq 0$ GOTO D

GOTO E

[D] $Z \leftarrow Z - 1$

$X \leftarrow X + 1$

GOTO C

Macro for variable assignment: $V \leftarrow V'$

[A] IF $X \neq 0$ GOTO B

GOTO C

[B] $X \leftarrow X - 1$

$Y \leftarrow Y + 1$

$Z \leftarrow Z + 1$

GOTO A

[C] IF $Z \neq 0$ GOTO D

GOTO E

[D] $Z \leftarrow Z - 1$

$X \leftarrow X + 1$

GOTO C

- ▶ the first cycle copies the value from X into Y and Z
- ▶ the second cycle puts in X the original value and leaves Z in zero.

Macro for variable assignment: $V \leftarrow V'$

[A] IF $X \neq 0$ GOTO B

GOTO C

[B] $X \leftarrow X - 1$

$Y \leftarrow Y + 1$

$Z \leftarrow Z + 1$

GOTO A

[C] IF $Z \neq 0$ GOTO D

GOTO E

[D] $Z \leftarrow Z - 1$

$X \leftarrow X + 1$

GOTO C

- ▶ the first cycle copies the value from X into Y and Z
- ▶ the second cycle puts in X the original value and leaves Z in zero.
- ▶ we use the macro GOTO A
 - ▶ it should not be expanded as

$Z \leftarrow Z + 1$

IF $Z \neq 0$ GOTO A

but as

$Z_2 \leftarrow Z_2 + 1$

IF $Z_2 \neq 0$ GOTO A

Macro for variable assignment: $V \leftarrow V'$

```
[A]    IF  $X \neq 0$  GOTO  $B$ 
        GOTO  $C$ 
[B]     $X \leftarrow X - 1$ 
         $Y \leftarrow Y + 1$ 
         $Z \leftarrow Z + 1$ 
        GOTO  $A$ 
[C]    IF  $Z \neq 0$  GOTO  $D$ 
        GOTO  $E$ 
[D]     $Z \leftarrow Z - 1$ 
         $X \leftarrow X + 1$ 
        GOTO  $C$ 
```

- ▶ it can be used to assign to variable V the content of variable V' and leave V' without changes within an arbitrary program P : $V \leftarrow V'$.
 - ▶ change Y by V
 - ▶ change X by V'
 - ▶ change Z for a temporal variable that does not appears in P

Macro for variable assignment: $V \leftarrow V'$

```
[A]   IF  $X \neq 0$  GOTO  $B$ 
      GOTO  $C$ 
[B]    $X \leftarrow X - 1$ 
       $Y \leftarrow Y + 1$ 
       $Z \leftarrow Z + 1$ 
      GOTO  $A$ 
[C]   IF  $Z \neq 0$  GOTO  $D$ 
      GOTO  $E$ 
[D]    $Z \leftarrow Z - 1$ 
       $X \leftarrow X + 1$ 
      GOTO  $C$ 
```

- ▶ it can be used to assign to variable V the content of variable V' and leave V' without changes within an arbitrary program P : $V \leftarrow V'$.
 - ▶ change Y by V
 - ▶ change X by V'
 - ▶ change Z for a temporal variable that does not appears in P
- ▶ but it works properly only when $V = 0$ and $Z = 0$

Macro for variable assignment: $V \leftarrow V'$

$Y \leftarrow 0$

[A] IF $X \neq 0$ GOTO B

GOTO C

[B] $X \leftarrow X - 1$

$Y \leftarrow Y + 1$

$Z \leftarrow Z + 1$

GOTO A

[C] IF $Z \neq 0$ GOTO D

GOTO E

[D] $Z \leftarrow Z - 1$

$X \leftarrow X + 1$

GOTO C

- ▶ it can be used to assign to variable V the content of variable V' and leave V' without changes within an arbitrary program P : $V \leftarrow V'$.
 - ▶ change Y by V
 - ▶ change X by V'
 - ▶ change Z for a temporal variable that does not appears in P
- ▶ but it works properly only when $V = 0$ and $Z = 0$
- ▶ we fix this by using $Y \leftarrow 0$ as first pseudoinstruction
 - ▶ we don't need to make $Z \leftarrow 0$

Macro for the assignment of zero: $V \leftarrow 0$

In a program P , the
pseudoinstruction $V \leftarrow 0$ is
expanded as

```
[L]     $V \leftarrow V - 1$   
      IF  $V \neq 0$  GOTO  $L$ 
```

where L is a label that does
not appear in P

Macro for the assignment of zero: $V \leftarrow 0$

Then the program for $V \leftarrow V'$ is:

In a program P , the pseudoinstruction $V \leftarrow 0$ is expanded as

[L] $V \leftarrow V - 1$
 IF $V \neq 0$ GOTO L

where L is a label that does not appear in P

$V \leftarrow 0$

[A] IF $V \neq 0$ GOTO B
 GOTO C

[B] $V \leftarrow V - 1$
 $V' \leftarrow V' + 1$
 $Z \leftarrow Z + 1$
 GOTO A

[C] IF $Z \neq 0$ GOTO D
 GOTO E

[D] $Z \leftarrow Z - 1$
 $V \leftarrow V + 1$
 GOTO C

Macro for the assignment of zero: $V \leftarrow 0$

In a program P , the
pseudoinstruction $V \leftarrow 0$ is
expanded as

[L] $V \leftarrow V - 1$
 IF $V \neq 0$ GOTO L

where L is a label that does
not appear in P

Then the program for $V \leftarrow V'$ is:

[H] $V \leftarrow V - 1$
 IF $V \neq 0$ GOTO H
[A] IF $V \neq 0$ GOTO B
 GOTO C
[B] $V \leftarrow V - 1$
 $V' \leftarrow V' + 1$
 $Z \leftarrow Z + 1$
 GOTO A
[C] IF $Z \neq 0$ GOTO D
 GOTO E
[D] $Z \leftarrow Z - 1$
 $V \leftarrow V + 1$
 GOTO C

```
Y ← X1  
Z ← X2  
[B] IF Z ≠ 0 GOTO A  
GOTO E  
[A] Z ← Z - 1  
Y ← Y + 1  
GOTO B
```

Addition of two variables

```
       $Y \leftarrow X_1$   
       $Z \leftarrow X_2$   
[B]   IF  $Z \neq 0$  GOTO A  
      GOTO E  
[A]    $Z \leftarrow Z - 1$   
       $Y \leftarrow Y + 1$   
      GOTO B
```

computes the function $f : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$

$$f(x_1, x_2) = x_1 + x_2$$

$Y \leftarrow X_1$

$Z \leftarrow X_2$

[C] IF $Z \neq 0$ GOTO A
GOTO E

[A] IF $Y \neq 0$ GOTO B
GOTO A

[B] $Y \leftarrow Y - 1$
 $Z \leftarrow Z - 1$
GOTO C

Subtraction of two variables

```
     $Y \leftarrow X_1$   
     $Z \leftarrow X_2$   
[C]  IF  $Z \neq 0$  GOTO A  
      GOTO E  
[A]  IF  $Y \neq 0$  GOTO B  
      GOTO A  
[B]   $Y \leftarrow Y - 1$   
       $Z \leftarrow Z - 1$   
      GOTO C
```

computes the function

$$f : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$$

$$g(x_1, x_2) = \begin{cases} x_1 - x_2 & \text{if } x_1 \geq x_2 \\ \uparrow & \text{otherwise} \end{cases}$$

Subtraction of two variables

```
      Y ← X1
      Z ← X2
[C]   IF Z ≠ 0 GOTO A
      GOTO E
[A]   IF Y ≠ 0 GOTO B
      GOTO A
[B]   Y ← Y - 1
      Z ← Z - 1
      GOTO C
```

computes the function

$$f : \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{N}$$

$$g(x_1, x_2) = \begin{cases} x_1 - x_2 & \text{if } x_1 \geq x_2 \\ \uparrow & \text{otherwise} \end{cases}$$

- ▶ g is a **partial** function
- ▶ we mark indefinision as \uparrow (in the metalanguage)
- ▶ the cause of indefinision is **no termination**
 - ▶ there is no other cause of indefinision

States

A **state** in a program P is a list of equations of the form $V = m$ (where V is a variable and m is a number) such that

- ▶ there is exactly one equation for each variable that appears in P

States

A **state** in a program P is a list of equations of the form $V = m$ (where V is a variable and m is a number) such that

- ▶ there is exactly one equation for each variable that appears in P

For example, for P :

```
[A]   X ← X - 1
      Y ← Y + 1
      IF X ≠ 0 GOTO A
```

- ▶ the following are possible states of P :

- ▶ $X = 3, Y = 1$
- ▶ $X = 3, Y = 1, Z = 0$
- ▶ $X = 3, Y = 1, Z = 8$
 - ▶ it is not necessary that the state is reachable

States

A **state** in a program P is a list of equations of the form $V = m$ (where V is a variable and m is a number) such that

- ▶ there is exactly one equation for each variable that appears in P

For example, for P :

```
[A]   X ← X - 1
      Y ← Y + 1
      IF X ≠ 0 GOTO A
```

- ▶ the following are possible states of P :

- ▶ $X = 3, Y = 1$
- ▶ $X = 3, Y = 1, Z = 0$
- ▶ $X = 3, Y = 1, Z = 8$
 - ▶ it is not necessary that the state is reachable

- ▶ the following are not states of P :

- ▶ $X = 3$
- ▶ $X = 3, Z = 0$
- ▶ $X = 3, Y = 1, X = 0$

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$
2. if the i -th instruction of P is $V \leftarrow V - 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = \max\{m - 1, 0\}$

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$
2. if the i -th instruction of P is $V \leftarrow V - 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = \max\{m - 1, 0\}$
3. if the i -th instruction of P is IF $V \neq 0$ GOTO L
 - ▶ τ is identical to σ

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$
 2. if the i -th instruction of P is $V \leftarrow V - 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = \max\{m - 1, 0\}$
 3. if the i -th instruction of P is IF $V \neq 0$ GOTO L
 - ▶ τ is identical to σ
- 3.1 if σ has $V = 0$ then $j = i + 1$

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$
2. if the i -th instruction of P is $V \leftarrow V - 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = \max\{m - 1, 0\}$
3. if the i -th instruction of P is IF $V \neq 0$ GOTO L
 - ▶ τ is identical to σ
 - 3.1 if σ has $V = 0$ then $j = i + 1$
 - 3.2 if σ has $V = m$ for $m \neq 0$ then

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$
2. if the i -th instruction of P is $V \leftarrow V - 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = \max\{m - 1, 0\}$
3. if the i -th instruction of P is IF $V \neq 0$ GOTO L
 - ▶ τ is identical to σ
 - 3.1 if σ has $V = 0$ then $j = i + 1$
 - 3.2 if σ has $V = m$ for $m \neq 0$ then
 - ▶ if there is an instruction in P with label L then
 $j = \min\{k : k\text{-th instruction in } P \text{ with label } L\}$

Instant Description

Let's assume that the program P has length n .

For a state σ of P and $i \in \{1, \dots, n+1\}$,

- ▶ the pair (i, σ) is an **instant description** of P .
- ▶ (i, σ) is called **terminal** if $i = n+1$.

For (i, σ) non terminal, we can define the **successor** state (j, τ) as:

1. if the i -th instruction of P is $V \leftarrow V + 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = m + 1$
 2. if the i -th instruction of P is $V \leftarrow V - 1$.
 - ▶ $j = i + 1$
 - ▶ τ is σ , except that $V = m$ is replaced by $V = \max\{m - 1, 0\}$
 3. if the i -th instruction of P is IF $V \neq 0$ GOTO L
 - ▶ τ is identical to σ
- 3.1 if σ has $V = 0$ then $j = i + 1$
 - 3.2 if σ has $V = m$ for $m \neq 0$ then
 - ▶ if there is an instruction in P with label L then
 $j = \min\{k : k\text{-th instruction in } P \text{ with label } L\}$
 - ▶ otherwise $j = n + 1$

Computations

A **computation** of a program P from an instant description d_1 is a list

$$d_1, d_2, \dots, d_k$$

of instant descriptions of P such that

- ▶ d_{i+1} is the successor of d_i for $i \in \{1, 2, \dots, k-1\}$
- ▶ d_k is terminal

States and Instant Descriptions

Given a program P and let r_1, \dots, r_m be numbers.

- ▶ The **initial state** of P for r_1, \dots, r_m is the state σ_1 , that has

$$X_1 = r_1 \quad , \quad X_2 = r_2 \quad , \quad \dots \quad , \quad X_m = r_m \quad , \quad Y = 0$$

together with

$$V = 0$$

for each variable V that appears in P which is different from X_1, \dots, X_m, Y

- ▶ the **initial description** of P for r_1, \dots, r_m is

$$(1, \sigma_1)$$

Computation from the initial state

Let P be a program and let

- ▶ r_1, \dots, r_m be numbers
- ▶ σ_1 the initial state (the P and r_1, \dots, r_m)

Computation from the initial state

Let P be a program and let

- ▶ r_1, \dots, r_m be numbers
- ▶ σ_1 the initial state (the P and r_1, \dots, r_m)

There are two cases

- ▶ there is a computation of P

$$d_1, \dots, d_k$$

such that $d_1 = (1, \sigma_1)$

We note as $\Psi_P^{(m)}(r_1, \dots, r_m)$ the value of Y in the instant configuration d_k .

Computation from the initial state

Let P be a program and let

- ▶ r_1, \dots, r_m be numbers
- ▶ σ_1 the initial state (the P and r_1, \dots, r_m)

There are two cases

- ▶ there is a computation of P

$$d_1, \dots, d_k$$

such that $d_1 = (1, \sigma_1)$

We note as $\Psi_P^{(m)}(r_1, \dots, r_m)$ the value of Y in the instant configuration d_k .

- ▶ there is no computation, i.e. there is an infinite sequence

$$d_1, d_2, d_3, \dots$$

where

- ▶ $d_1 = (1, \sigma_1)$.
- ▶ d_{i+1} is the successor of d_i

We say that $\Psi_P^{(m)}(r_1, \dots, r_m)$ is undefined (we note $\Psi_P^{(m)}(r_1, \dots, r_m) \uparrow$)

Computable Functions

A (partial) function $f : \mathbb{N}^m \rightarrow \mathbb{N}$ is **partially computable** if there is a program P such that

$$f(r_1, \dots, r_m) = \psi_P^{(m)}(r_1, \dots, r_m)$$

for each $(r_1, \dots, r_m) \in \mathbb{N}^m$.

Computable Functions

A (partial) function $f : \mathbb{N}^m \rightarrow \mathbb{N}$ is **partially computable** if there is a program P such that

$$f(r_1, \dots, r_m) = \psi_P^{(m)}(r_1, \dots, r_m)$$

for each $(r_1, \dots, r_m) \in \mathbb{N}^m$.

The equality (in the meta-language) is true iff

- ▶ both sides are defined and they have the same value, or
- ▶ both sides are undefined

Computable Functions

A (partial) function $f : \mathbb{N}^m \rightarrow \mathbb{N}$ is **partially computable** if there is a program P such that

$$f(r_1, \dots, r_m) = \Psi_P^{(m)}(r_1, \dots, r_m)$$

for each $(r_1, \dots, r_m) \in \mathbb{N}^m$.

The equality (in the meta-language) is true iff

- ▶ both sides are defined and they have the same value, or
- ▶ both sides are undefined

A function f is **computable** if it is partially computable and total.

Computable Functions

A (partial) function $f : \mathbb{N}^m \rightarrow \mathbb{N}$ is **partially computable** if there is a program P such that

$$f(r_1, \dots, r_m) = \Psi_P^{(m)}(r_1, \dots, r_m)$$

for each $(r_1, \dots, r_m) \in \mathbb{N}^m$.

The equality (in the meta-language) is true iff

- ▶ both sides are defined and they have the same value, or
- ▶ both sides are undefined

A function f is **computable** if it is partially computable and total.

Note that the same program P can be used to compute functions with 1 variable, 2 variables, etc. Suppose that in P we have occurrences of X_n but not of X_i for $i > n$.

- ▶ if we only specify $m < n$ input variables, X_{m+1}, \dots, X_n take the value 0
- ▶ if we specify $m > n$ input variables, P will ignore X_{n+1}, \dots, X_m