

# Workshop Red Hat Decision Manager

Lab Integrando Red Hat Code Ready Studio y Red Hat Decision Manager

## Objetivo

Mostrar al participante el procedimiento para integrar Red Hat Code Ready Studio con el middleware Red Hat Decision Manager para la creación de proyectos de reglas de negocio.

## Procedimiento

### Installing Red Hat Developer Studio

1. In a terminal window, navigate to the directory where you downloaded the installer JAR file and enter the following command:

```
java -jar devstudio-12.9.0.GA-installer-standalone.jar
```

2. Follow the instructions in the installer to complete the installation.

### Installing Red Hat Developer Studio plug-ins

3. To start Red Hat Developer Studio, select Red Hat Developer Studio from the **Start** menu.
4. Click **Help** → **Install New Software**.
5. Click **Add** to display the **Add Repository** window.
6. Enter a name in the **Name** field, for example, `devstudio-12.0.0.GA`.
7. Click **Archive**, navigate to the `devstudio-integration-stack-12.0.0.GA-updatesite.zip` file, select the file, and then click **OK**.
8. Click **Add**.
9. In the **Install** window, select **JBoss Business Process and Rule Development** from the **Available Software** list, click **Next**, and click **Next** again.
10. Read the license agreements, click **I accept the terms of the license agreements** to accept the license agreements, and then click **Finish**.
11. After the installation process has been completed, click **Restart Now** in the **Software Updates** window to restart Red Hat Developer Studio.

### Configuring the Red Hat Decision Manager server

1. Start Red Hat Developer Studio.

2. Click **Window** → **Show View** → **Other**, select **Server** → **Servers**, and then click **Open** to add the server view.
3. Right-click in the **Servers** pane and select **New** → **Server** to open the server menu.
4. Click **Red Hat JBoss Middleware** → **JBoss Enterprise Application Platform 7.x** and then click **Next** to define the server.
5. In the **Create a new Server Adapter** window, select **Create new runtime (next page)** from the list, and then click **Next**.
6. To set the home directory in the **JBoss Runtime** window, click the **Browse** button under **Home Directory** and navigate to the Red Hat JBoss EAP directory where Red Hat Decision Manager is installed.
7. Enter a name for the server in the **Name** field, ensure that the configuration file is set, and then click **Finish**.

## Creating a Red Hat Decision Manager project

1. In Red Hat Developer Studio, from the main menu, click **File** → **New** → **Project**.
2. In the search field, enter **Drools Project**, select **Drools Project**, and then click **Next**.
3. Select the second option to create a project with a Red Hat Decision Manager example, and then click **Next**.
4. In the **Project name** field, enter a name for the project.
5. Click **Finish**.
6. Complete the following steps to test the project:
  - i. Navigate to the **src/main/java** directory and expand the **com.sample** package.
  - ii. Right click a Java class and select **Run As** → **Java Application**.

The output is displayed on the console tab.