

Workshop Red Hat Decision Manager

Lab Instalación de Red Hat PAM

Objetivo

- Mostrar al participante el procedimiento para la instalación de Red Hat Process Automation Manager en ambiente de desarrollo.

Requisitos

- Contar con el sistema operativo Linux/Windows
- Tener instalado JDK 11.x
- Git

Procedimiento

1. Clone el repositorio git de la demostración de instalación de Red Hat Process Automation Manager 7:

\$ git clone <https://github.com/jbossdemocentral/rhpam7-install-demo.git>

2. Copie los cuatro archivos zip que acaba de descargar en el directorio de instalación del directorio rhpam7-install-demo.

Red Hat JBoss EAP 7.3

<https://developers.redhat.com/download-manager/file/jboss-eap-7.3.0.zip>

RHPAM: Business Central, zip desplegable

<https://developers.redhat.com/download-manager/file/rhpam-7.11.0-business-central-eap7-deployable.zip>

RHPAM - Servidor KIE, zip desplegable

<https://developers.redhat.com/download-manager/file/rhpam-7.11.0-kie-server-ee8.zip>

Complementos RHPAM

<https://developers.redhat.com/download-manager/file/rhpam-7.11.0-add-ons.zip>

3. Ejecute el archivo 'init.sh' o 'init.bat'. NOTA: 'init.bat' debe ejecutarse con privilegios administrativos.

4. Una vez que finalice la instalación, debería ver un mensaje de éxito en su terminal junto con la información del entorno.

```
Red Hat Process Automation Manager 7.11.0 setup complete. =
=
= Start Red Hat Process Automation Manager with: =
=
= ./target/jboss-eap-7.3/bin/standalone.sh =
=
= Log in to Red Hat Process Automation Manager to start =
= developing rules projects: =
=
= http://localhost:8080/business-central =
=
= Log in: [ u:pamAdmin / p:redhatpam1! ] =
=
= http://localhost:8080/rhpam-case-mgmt-showcase =
=
= Others: =
= [ u:kieserver / p:kieserver1! ] =
= [ u:caseUser / p:redhatpam1! ] =
= [ u:caseManager / p:redhatpam1! ] =
= [ u:caseSupplier / p:redhatpam1! ] =
=
=====
```