



Hot dip galvanised price extras list

ArcelorMittal

for Automotive Europe

This price list can be accessed at our website: automotive.arcelormittal.com > Product offer > Price lists for Europe or requested through our agencies.

Valid as from 01/01/2016 – version 02/02/2016 (EUR/tonne)

1. User guidelines

1.1 Price calculation

The following document only lists extras.

The price as invoiced includes:

The basis price

+ Transportation extra

+ Transportation tax (depending on the country)

+ Any extras from the list below

+ Warehousing fee

+ Specific logistic extras

1.2 Product availability

Not all combinations of specifications are available at each production facility.

2. Extras

2.1 Steel grades

Galvanised: Z

Galfan: ZA

Galvannealed: ZF

ZnMgAl: ZM

.1 Steels for cold forming and deep drawing applications

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
DX52D +Z/+ZF	CR1	ArcelorMittal 52 +Z/+ZA/+ZF/+ZM	25
DX53D +Z/+ZF	CR2	ArcelorMittal 53 +Z/+ZA/+ZF/+ZM	52
DX54D +Z/+ZF	CR3	ArcelorMittal 54 +Z/+ZA/+ZF/+ZM	90
DX56D +Z/+ZF	CR4	ArcelorMittal 56 +Z/+ZA/+ZF/+ZM	110
DX57D +Z/+ZF	CR5	ArcelorMittal 57 +Z/+ZA/+ZF/+ZM	141

.2 High Strength Low Alloy steels

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HX260LAD +Z/+ZA/+ZF	CR240LA	HSLA260 +Z/+ZA/+ZF/+ZM	35
HX300LAD +Z/+ZA/+ZF	CR270LA	HSLA300 +Z/+ZA/+ZF/+ZM	45
HX340LAD +Z/+ZA/+ZF	CR300LA	HSLA340 +Z/+ZA/+ZF/+ZM	55
HX380LAD +Z/+ZA/+ZF	CR340LA	HSLA380 +Z/+ZA/+ZF/+ZM	70
HX420LAD +Z/+ZA/+ZF	CR420LA	HSLA420 +Z/+ZA/+ZF/+ZM	75

.3 Bake Hardening steels

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HX180BD +Z/+ZF	CR180BH	180 BH +Z/+ZF/+ZM	70
HX220BD +Z/+ZF	CR210BH	220 BH +Z/+ZF/+ZM	60
HX260BD +Z/+ZF	CR240BH	260 BH +Z/+ZF/+ZM	85
HX300BD +Z/+ZF	CR270BH	300 BH +Z/+ZF/+ZM	90

.4 Interstitial-Free High Strength steels

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HX180YD +Z/+ZF	CR180IF	IF 180 +Z/+ZF/+ZM	87
HX220YD +Z/+ZF+ZA	CR210IF	IF 220 +Z/+ZF/+ZA/+ZM	92
HX260YD +Z/+ZF+ZA	CR240IF	IF 260 +Z/+ZF/+ZA/+ZM	97
HX300YD +Z/+ZF		IF 300 +Z/+ZF	102

.5 TRIP steels

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HCT690T +Z	CR400Y690T-TR	TRIP 690 +Z	250
HCT780T +Z/+ZF	CR450Y780T-TR	TRIP 780 +ZF	280

.6 Dual Phase steels

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HCT450X +Z/+ZF		DP 450 +Z/+ZF	120
	CR290Y490T-DP	FF 280DP +Z	130
HCT500X +Z/+ZF	CR290Y490T-DP	DP 500 +Z/+ZF	130
HCT600X +Z/+ZF	CR330Y590T-DP	DP 600 +Z/+ZF	150
HCT780X +Z	CR440Y780T-DP	DP 780Y450 +Z/+ZF	180
		DP 780Y500 +Z	180
HCT980X +Z/+ZF	CR590Y980T-DP	DP 980LCEY600 +Z/+ZF	280
		DP 980LCEY660 +Z	280
HCT980XG +Z/+ZF	CR700Y980T-DP	DP 980LCEY700 +Z	280

>>

.7 Complex phase steels

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HDT750C +Z		Complex phase 750 HR +Z(4)	205
HCT780C +Z	CR570Y780T-CP	Complex phase 800 Y600 +Z	190
HDT760C +Z		Complex phase 780 HR +Z(4)	280
HDT950C		Complex phase 1000 HR +Z(4)	280
HCT980C +Z	CR780Y980T-CP	Complex phase 1000 Y800 +Z	280

(4) Only hot rolled substrate

.8 Ferrite Bainite - only on hot rolled substrate

EN 10346:2015	VDA 239-100	ArcelorMittal specific offer	
HDT450F +Z	HR300Y450T-FB	FB 450 +Z	70
		FB 540 +Z	85
		FB 560 +Z	95
HDT580F +Z	HR300Y450T-FB	FB 590 +Z	115

.9 Carbon-manganese steel

CMN440 +ZF	90
------------	----

.10 Hot dip galvanised on hot rolled substrate

Rebate	-15
--------	-----

2.2 Extra for galfan, Galvannealed, Ultragal®

Galfan galvanised steels with alloyed coating (Zn - Al)	ZA	15
Galvannealed galvanised steels with alloyed coating (Zn - Fe)	ZF	15
Ultragal®		15

2.3 Dimensions

Extras for thickness / width

Thickness (mm)	Width (mm)								
	600 699	700 799	800 899	900 1099	1100 1299	1300 1850	1851 1925	1926 2000	2001 2070
0.50 - 0.54	186	172	145	123	112	112	-	-	-
0.55 - 0.59	170	152	128	111	98	97	-	-	-
0.60 - 0.69	153	137	109	97	87	86	195	-	-
0.70 - 0.79	127	121	94	81	71	71	180	210	-
0.80 - 0.99	109	106	79	66	56	56	165	195	240
1.00 - 1.24	96	95	66	56	48	48	110	150	198
1.25 - 1.49	87	86	59	46	39	39	90	120	148
1.50 - 1.99	79	74	51	38	31	31	95	125	155
2.00 - 2.99	66	63	38	28	20	20	85	-	-
≥ 3.00	66	60	28	20	17	15	-	-	-

The thickness must be either the midpoint of the tolerance range specified in the order, or the target thickness ordered, whichever value is the lowest.

2.4 Special tolerances according to EN 10143:2006

Tolerances on dimensions

EN 10143:2006		
Thickness	Full EN	0
	Special	8
Width	Special	15

2.5 Coating

.1

Two-sided Zinc (according to EN 10346:2015) with a normal zinc coating thickness of:

- Galvanised 100 g/m² two-sided triple spot measurement
- Galfan 200 g/m² two-sided
- Galvannealed

Galvanised	≤ Z100	≤ Z140	≤ Z200 ⁽²⁾
Galfan	≤ ZA95	≤ ZA130	≤ ZA185
Galvannealed	≤ ZF90	≤ ZF110	(2)

Nominal thickness (mm)

0.50 - 0.54	0	17	40
0.55 - 0.59	0	15	36
0.60 - 0.69	0	13	32
0.70 - 0.79	0	11	28
0.80 - 0.99	0	9	23
1.00 - 1.24	0	7	17
1.25 - 1.49	0	5	15
1.50 - 1.99	0	5	12
2.00 - 2.99	0	4	9
3.00 - 3.99	0	3	7
≥ 4.00	0	2	5

(2) Not accepted
Zinc extras will be applied in case the zinc prices deviate from the long term historical average value.

.2

Zn-Mg-Al (Zagnelis™)	ZM70	ZM90	ZM120
	5/5 μ	7/7 μ	10/10 μ
Nominal thickness (mm)			
0.60 - 0.69	5	8	20
0.70 - 0.79	4	6	17
0.80 - 0.99	2	5	14
1.00 - 1.24	2	4	12
1.25 - 1.99	0	4	10

>>

2.6 Surface aspect

		Finish	
		Improved B	Superior C
Minimised spangle	M	20	70

2.7 Surface treatment

NIT	10
NIT Plus	10
L-treatment	20
Dry Lub	30
Easyfilm®	30

2.8 Coil weight

Width (mm)	Weight (t)		
	3 - 4.999	5 - 9.999	≥ 10
600 - 999	20	0	0
1000 - 1499	25	15	0
≥ 1500	(2)	20	0

(2) Not accepted

Permitted deviation for the weight specified per coil

Our factories are not bound to supply the exact coil weight specified. Coil weight may be between 75 and 100% of the weight specified. 20% of the tonnage of the sample ordered as coils may be supplied as lightweight coils, i.e. coils weighing between 25 and 75% of the specified weight.

2.9 Welds

Welds not accepted (before or after cold rolling)	10
Only welds after cold rolling not accepted	5
Welds after cold rolling accepted but before cold rolling refused	0
All welds accepted	-3

When an order for coils specifies no welds, the weight per coil cannot be specified but must be arranged by prior agreement. The weight of coils without welds may be between 50 and 100% of the weight specified.

2.10 Order quantities: extras per item

.1 Item definition

An item is defined as a quantity of material specified in one order form for which the steel grade, dimensions, coating, delivery time and the destination are the same.

.2 Extras

Tonnage per item (t) (spot business)

5 - 9.999	25
10 - 14.999	15
15 - 19.999	10
≥ 20	0

Note: the weight of the order item should be expressed as a multiple of the weight of a single coil.

Unit weight / quantities per order unit should be agreed with the factory.

For orders in scheduled business, the minimum monthly tonnage is 20 t. Extra of 50 EUR/t for orders < 20 t/month.

.3 Tolerances on quantities (spot business)

Item tonnage (t)	Tolerances (%)
≤ 100	± 20
> 100	± 10

2.11 Packaging

Coils are charged gross for net, wooden pallet included.

Standard ArcelorMittal packaging

no paper	0
paper	5
seaworthy	10

For all other packaging requirements:

After prior agreement, with a minimum of	10
--	----

2.12 Certificates - Inspection

EN 10204:2004	Standard indication	
Certificate of compliance with the order	2.1	0
Test report	2.2	0
Inspection certificate ⁽³⁾	3.1	5
Inspection certificate	3.2	10

(3) Electronic version: 2 EUR/t

Supplementary test, not mentioned in a standard	5
---	---