

Cold rolled price extras list

for Industry Europe



ArcelorMittal

Versions in Dutch, French, German, Italian, Spanish, Polish, Czech, Romanian and Turkish can be accessed at our website: industry.arcelormittal.com > Products & Solutions > [Price extras lists](#) or requested through our agencies. For more detailed information, please consult our online product catalogue on industry.arcelormittal.com > Products & Solutions > [Product catalogue](#) or click on the hyperlinks in this document.

Valid as from 01/10/2014 – version 30/06/2014 (EUR/tonne)

1. User guidelines

1.1 Price calculation

The following document only lists extras.

The price as invoiced includes:

The basis price

+ Transportation extra (for Solfer®: transportation from Florange)

+ Transportation tax (depending on the country)

+ Any extras from the list below

1.2 Product availability

Not all combinations of specifications are available at each production facility.

2. Extras

2.1 Steel grades

.1 Steels for cold forming (data sheet B10)

EN 10130:2006	ArcelorMittal specific offer	
DC01		0
	DC02 AM FCE	5
DC03	DC03 AM FCE	10
DC04	DC04 AM FCE	16
DC05		40
DC06		80
DC07		120

.2 Structural steels (data sheet B30)

ArcelorMittal specific offer	
HC180 AM FCE	0
HC200 AM FCE	2
HC220 AM FCE	8

.3 High Strength Low Alloy steels (data sheet B20)

EN 10268:2006+A1:2013	ArcelorMittal specific offer	
HC260LA	HC260LA AM FCE	25
HC300LA	HC300LA AM FCE	35
HC340LA	HC340LA AM FCE	50
HC380LA	HC380LA AM FCE	70
HC420LA	HC420LA AM FCE	75
HC460LA	HC460LA AM FCE	80
HC500LA	HC500LA AM FCE	(1)

(1) After prior agreement

.4 Steels with guaranteed mechanical properties (data sheet B40)

ArcelorMittal specific offer	
HC180CA AM FCE	3
HC220CA AM FCE	11
HC260CA AM FCE	15

.5 Indaten® atmospheric corrosion resistant steels (data sheet B34)

ArcelorMittal specific offer	
Indaten® HC315WP	125

.6 Blued steels (data sheet B15)

ArcelorMittal specific offer	
DC01BS AM FCE	75
DC03BS AM FCE	85
DC04BS AM FCE	91

>>

.7 Steels for enamelling

Steels for conventional enamelling (*data sheet C10*)

EN 10209:2013

ArcelorMittal specific offer

DC01EK		20
	DC03EK AM FCE	26
DC04EK		32
DC05EK		50
DC06EK		80
	DC07EK AM FCE	(1)

(1) After prior agreement

Decarburised cold rolled steel for white and colour enamelling processes:

Solfer® range (*data sheet C20*)

EN 10209:2013

ArcelorMittal specific offer

	Solfer® CA	40
DC03ED	Solfer®	60
DC04ED	Solfer®+	60

Structural cold rolled steel for enamelling with guaranteed minimum yield strength after enamel firing (*data sheet C30*)

ArcelorMittal specific offer

HC300EK	50
---------	----

.8 High strength steel for lightweight gas containers (*data sheet B64*)

PrEN 10338:2009

ArcelorMittal specific offer

HCT600X	DP600 AM FCE	150
---------	--------------	-----

2.2 Dimensions

.1 Extras for thickness / width

Thickness (mm)	Width (mm)									
	600 - 699	700 - 799	800 - 899	900 - 1099	1100 - 1299	1300 - 1699	1700 - 1849	1850 - 1925	1926 - 2000	≥ 2001
0.20 - 0.29	(1)	(1)	(1)	(1)	(1)	(1)	-	-	-	-
0.30 - 0.39	135	115	110	100	110	120	-	-	-	-
0.40 - 0.49	125	100	85	75	65	70	-	-	-	-
0.50 - 0.59	105	85	60	50	40	40	50	50	-	-
0.60 - 0.69	100	74	50	40	30	30	31	76	161	-
0.70 - 0.79	80	59	45	35	25	25	26	66	144	195
0.80 - 0.89	70	54	40	31	21	19	19	56	122	165
0.90 - 1.24	60	49	35	21	16	16	16	46	97	135
1.25 - 1.49	55	44	30	16	11	11	11	36	79	110
1.50 - 1.99	50	39	25	11	6	6	6	36	74	115
2.00 - 2.99	50	39	20	11	6	6	6	56	87	120
3.00 - 4.00	45	39	20	11	6	6	6	71	102	135

(1) After prior agreement

The thickness is the aimed thickness either specified in the order or the midpoint of the tolerance range.

.2 Supplementary extras for sheets

Thickness (mm)	Width (mm)	
	600 - 899	≥ 900
0.40 - 0.49	125	105
0.50 - 0.59	95	75
0.60 - 0.99	70	55
1.00 - 1.49	55	45
1.50 - 4.00	50	40

Length* < 1250 mm or length > 4000 mm

supplementary extra

15

* Length is measured in rolling direction.

2.3 Special tolerances according to EN 10131:2006

.1 Tolerances on dimensions

EN 10131:2006

Thickness	Special	5
	1/2 EN	10
Width (reduced tolerance and/or edge trimming)		15
Length (only for sheets)		7

.2 Special flatness (only for sheets)

EN 10131:2006

Thickness (mm)		
	≤ 0.69	20
	0.70 - 1.19	15
	≥ 1.2	10

Very tight tolerances (all thicknesses)

36

2.4 Surface aspect

EN 10130:2006

Exposed (aspect B one-sided)	40
------------------------------	----

2.5 Surface finish

EN 10130:2006

Roughness (µm)			
≤ 0.40	Bright	b	25
≤ 0.90	Semi-bright	g	10
0.61 - 1.90	Normal	m	0
1.60 - 3.00	Rough	r1	10
≥ 3	Very rough	r2	(1)

(1) After prior agreement

2.6 Unannealed, untempered coils

Unannealed, untempered coils

-30

>>

2.7 Surface treatment

Rust protecting oil	0
Uncoiled (paper/plastic packaging mandatory)	2
Totally free of oil stains (paper/plastic packaging mandatory)	5
Ready-to-Enamel (C80)	(1)

(1) After prior agreement

2.8 Coil and bundle weight

.1 Coil weight (maxi coil weight calculated)*

Width (mm)	Weight (t)		
	3 - 4.999	5 - 9.999	≥ 10
600 - 999	20	15	0
1000 - 1499	25	15	0
≥ 1500	(2)	20	0

(2) Not accepted

* The maxi coil weight is calculated taking into account the maxi coil weight ordered and the maxi outside diameter.

Permitted deviation for the weight specified per coil

Our factories are not bound to supply the exact coil weight specified. Coil weight may be between 75 and 100% of the weight specified. 20% of the tonnage of the sample ordered as coils may be supplied as lightweight coils, i.e. coils weighing between 25 and 75% of the specified weight.

.2 Bundle weight

Weight (t)	
1 - 1.999	25
2 - 2.999	10
3 - 4.999	5
≥ 5	0

2.9 Welds (only applicable for coils)

No welds accepted (pickled and after cold rolling)	5
Other cases	0
All welds accepted (pickled and after cold rolling)	-3

When an order for coils specifies no welds, the weight per coil cannot be specified but must be arranged by prior agreement.

2.10 Order quantities: extras per item

.1 Item definition

An item is defined as a quantity of material specified in one order form for which the steel grade, thickness, width, coating, delivery time and the destination are the same.

.2 Extras

Tonnage per item (t)	
< 5	(1)
5 - 9.999	15
10 - 14.999	12
15 - 19.999	10
≥ 20	0

(1) After prior agreement

Note: the weight of the order item should be expressed as a multiple of the weight of a single coil.

Unit weight / quantities per order unit should be agreed with the factory.

.3 Tolerances on quantities

Item tonnage (t)	Tolerances (%)
≤ 100	± 20
> 100	± 10

2.11 Packaging

Coils and sheets are charged gross for net, wooden pallet included.

.1 Coils and sheets

Standard ArcelorMittal packaging	
no paper	0
paper or plastic*	5
seaworthy	5

* Mandatory for uncoiled or totally free of oil stains material

For all other packaging requirements:

After prior agreement, with a minimum of	10
--	----

.2 Special packaging⁽¹⁾

Internal diameter (mm)	Thickness (mm)	
	< 0.38	≥ 0.38
610	(1)	0
508	0	3

(1) After prior agreement

>>

2.12 Certificates – Inspection

Inspection takes place at the supplier's premises. Coils and sheets from which the test pieces are taken, continue to be part of delivery.

EN 10204:2004	Standard indication	
Certificate of compliance with the order	2.1	0
Test report	2.2	0
Inspection certificate	3.1*	5
Inspection certificate	3.2	10
Supplementary test, not mentioned or optional in a standard		5
* More than one certificate (except for AM FCE qualities)		7

2.13 Shipments

All shipments are specified "librex" (shipped when ready). Any restriction on shipment made by the client must be agreed in advance by the plant and will be charged as follows:

4 weeks' storage maximum	supplementary extra	15
More than 4 weeks		not accepted

The storage period must be specified when the order is placed. If the agreed deadline is exceeded, ArcelorMittal will proceed in accordance with the General Conditions of Sale.

