



Hot dip galvanised price extras list

ArcelorMittal

for Industry Europe

Versions in Dutch, French, German, Italian, Spanish, Polish, Czech, Romanian and Turkish can be accessed at our website: industry.arcelormittal.com > Products & Solutions > [Price extras lists](#) or requested through our agencies. For more detailed information, please consult our online product catalogue on industry.arcelormittal.com > Products & Solutions > [Product catalogue](#) or click on the hyperlinks in this document.

Valid as from 01/10/2014 – version 30/06/2014 (EUR/tonne)

1. User guidelines

1.1 Price calculation

The following document only lists extras.

The price as invoiced includes:

The basis price

+ Transportation extra (galfan: transportation from Liège)

+ Transportation tax (depending on the country)

+ Any extras from the list below

1.2 Product availability

Not all combinations of specifications are available at each production facility.

2. Extras

2.1 Steel grades

Galvanised: Z ([data sheet E20](#))

Galfan: ZA ([data sheet E30](#))

.1 Steels for cold forming and deep drawing applications ([data sheet E20 / E30](#))

PrEN 10346:2014

DX51D +Z	DX51D +ZA	0
DX52D +Z	DX52D +ZA	25
DX53D +Z	DX53D +ZA	52
DX54D +Z	DX54D +ZA	90
DX56D +Z	DX56D +ZA	110
DX57D +Z	DX57D +ZA	(1)

(1) After prior agreement

.2 Structural steels ([data sheet E20 / E30](#))

PrEN 10346:2014

ETA-13/0257

S220GD +Z	S220GD +ZA	0
S250GD +Z	S250GD +ZA	5
S280GD +Z	S280GD +ZA	15
S320GD +Z	S320GD +ZA	23
S350GD +Z	S350GD +ZA	40
S390GD +Z	S390GD +Z	50
S420GD +Z		(1)
S450GD +Z		(1)
S550GD +Z	S550GD +ZA	53

(1) After prior agreement

.3 High Strength Low Alloy steels ([data sheet E20](#))

PrEN 10346:2014

HX260LAD +Z	30
HX300LAD +Z	40
HX340LAD +Z	50
HX380LAD +Z	70
HX420LAD +Z	75
HX460LAD +Z	80
HX500LAD +Z	90

2.2 Extra for galfan ([data sheet E30](#))

Galfan galvanised steels with alloyed coating (Zn - Al)	15
---	----

>>

2.3 Dimensions

.1 Extras for thickness / width

Thickness (mm)	Width (mm)					
	600 699	700 799	800 899	900 1099	1100 1299	1300 1850
0.19 - 0.20	-	-	277	255	255	-
0.21 - 0.22	-	-	244	222	222	-
0.23 - 0.24	-	-	233	213	213	-
0.25 - 0.29	-	-	216	194	194	-
0.30 - 0.34	-	-	186	165	165	-
0.35 - 0.39	194	172	152	133	130	-
0.40 - 0.44	171	152	132	113	102	-
0.45 - 0.49	163	143	123	106	99	99
0.50 - 0.54	150	135	109	89	81	81
0.55 - 0.59	147	128	103	88	78	78
0.60 - 0.69	132	111	87	76	68	68
0.70 - 0.79	119	102	81	72	61	61
0.80 - 0.89	105	87	75	66	56	56
0.90 - 0.99	102	85	70	60	51	51
1.00 - 1.24	93	78	63	53	48	48
1.25 - 1.49	85	72	57	45	40	40
1.50 - 1.99	79	66	51	38	34	34
2.00 - 2.49	65	52	38	28	22	22
2.50 - 2.99	64	52	38	27	22	22
3.00 - 3.99	62	51	37	24	19	18
≥ 4.00	60	50	35	22	18	16

The thickness is the aimed thickness either specified in the order or the midpoint of the tolerance range.

.2 Extras for cut to length - surface type A

Thickness (mm)	Width (mm)	
	600 - 899	≥ 900
≤ 0.49	125	105
0.50 - 0.59	95	75
0.60 - 0.99	70	55
1.00 - 1.49	55	45
≥ 1.50	50	40

.3 Supplementary extras for cut to length

Length < 1250 mm or length > 4000 mm	15
Surface type B	6
Surface type C	15

2.4 Special tolerances according to EN 10143:2006

.1 Tolerances on dimensions

EN 10143:2006

Thickness	Special	5
	1/2 EN	10
Width (reduced tolerance and/or edge trimming)		15
Length (for sheets)		7

.2 Special flatness (only for sheets)

EN 10143:2006

Thickness (mm)		
	≤ 0.69	20
	0.70 - 1.19	15
	≥ 1.20	10

2.5 Coating

Two-sided Zinc (according to PrEN 10346:2014) with a normal zinc coating thickness of:

- Galvanised: 100 g/m² two-sided
- Galfan: 95 g/m² two-sided

Galvanised	Z100	≤ Z140	≤ Z200	≤ Z225	≤ Z275	≤ Z350	≤ Z450	≤ Z600	≤ Z725	> Z725
	7/7 μ	10/10 μ	14/14 μ	16/16 μ	20/20 μ	25/25 μ	32/32 μ	42/42 μ	51/51 μ	
Galfan										
ZA95 ZA130 ZA185 ZA200 ZA255 ZA300										
7/7 μ 10/10 μ 14/14 μ 15/15 μ 20/20 μ 23/23 μ										
Thickness (mm)										
0.19 - 0.20	0	38	97	120	-	-	-	-	-	-
0.21 - 0.22	0	35	87	109	-	-	-	-	-	-
0.23 - 0.24	0	31	79	100	125	-	-	-	-	-
0.25 - 0.29	0	28	73	91	116	-	-	-	-	-
0.30 - 0.34	0	24	62	76	96	137	-	-	-	-
0.35 - 0.39	0	22	53	65	82	117	-	-	-	-
0.40 - 0.44	0	19	47	57	73	103	-	-	-	-
0.45 - 0.49	0	17	41	51	64	93	-	-	-	-
0.50 - 0.54	0	15	37	47	57	82	-	-	-	-
0.55 - 0.59	0	14	34	40	51	76	-	-	-	-
0.60 - 0.69	0	13	30	37	46	68	96	-	-	-
0.70 - 0.79	0	10	25	31	42	58	82	116	-	-
0.80 - 0.89	0	9	23	29	37	52	73	104	-	-
0.90 - 0.99	0	8	21	25	32	45	63	93	-	-
1.00 - 1.24	0	7	19	22	27	42	59	82	-	-
1.25 - 1.49	0	6	15	19	23	33	47	65	-	-
1.50 - 1.99	0	6	13	16	20	27	39	56	76	89
2.00 - 2.49	0	4	9	11	15	20	27	42	57	67
2.50 - 2.99	0	3	8	9	12	18	23	34	47	53
3.00 - 3.99	0	3	6	6	9	14	20	27	37	45
≥ 4.00	0	2	4	6	8	10	15	21	29	33

The thickness is the aimed thickness either specified in the order or the midpoint of the tolerance range.

>>

2.6 Coating finish

Only for General Industry applications

.1 For hot dip galvanised

Products are delivered with minimised spangle (normal spangle is an exception).

Finish Aspect	Normal A	Improved B	Superior C
Standard appearance	0	20	70
Shiny appearance*	15	35	75 (U2S)

* The technical description is defined in the catalogue.

.2 For galfan

Finish	Normal A	Improved B	Superior C
	0	20	70

2.7 Surface treatment

		Thickness of metallic coated steels (mm)		
		0.19 - 0.29	0.30 - 0.39	≥ 0.40
E	E-Passivation® (E70)	0	0	0
O	Oiling	2	2	2
EO	E-Passivation® + Oiling	2	2	2
S	Thin organic coating:			
	Easyfilm® E (E80)	60	30	20

2.8 Coil and bundle weight

.1 Coil weight (maxi coil weight calculated)*

Width (mm)	Weight (t)		
	3 - 4.999	5 - 9.999	≥ 10
600 - 999	20	0	0
1000 - 1499	25	15	0
≥ 1500	(2)	20	0

(2) Not accepted

* The maxi coil weight is calculated taking into account the maxi coil weight ordered and the maxi outside diameter.

Permitted deviation for the weight specified per coil

Our factories are not bound to supply the exact coil weight specified. Coil weight may be between 75 and 100% of the weight specified. 20% of the tonnage of the sample ordered as coils may be supplied as lightweight coils, i.e. coils weighing between 25 and 75% of the specified weight.

.2 Bundle weight

Weight (t)	
< 1	(2)
1 - 1.999	25
2 - 2.499	10
2.500 - 4.999	5
≥ 5	0

(2) Not accepted

2.9 Welds (only applicable for coils)

No welds accepted (pickled and after cold rolling)	5
Other cases	0
All welds accepted (pickled and after cold rolling)	-3

When an order for coils specifies no welds, the weight per coil cannot be specified but must be arranged by prior agreement.

2.10 Order quantities: extras per item

.1 Item definition

An item is defined as a quantity of material specified in one order form for which the steel grade, thickness, width, coating, delivery time and the destination are the same.

.2 Extras

Tonnage per item (t)	
5 - 9.999	15
10 - 14.999	12
15 - 19.999	10
≥ 20	0

Note: the weight of the order item should be expressed as a multiple of the weight of a single coil.

Unit weight / quantities per order unit should be agreed with the factory.

.3 Tolerances on quantities

Item tonnage (t)	Tolerances (%)
≤ 100	± 20
> 100	± 10

2.11 Packaging

Coils and sheets are charged gross for net, wooden pallet included.

Standard ArcelorMittal packaging

no paper	0
paper or plastic*	5
seaworthy	5

* In case of E-Passivation® and if a paper or plastic packaging is requested by the client, then the packaging is free of charge.

For all other packaging requirements:

After prior agreement, with a minimum of	10
--	----

>>

2.12 Certificates – Inspection

EN 10204:2004	Standard indication	
Certificate of compliance with the order	2.1	0
Test report	2.2	0
Inspection certificate	3.1*	5
Inspection certificate	3.2	10

Supplementary test, not mentioned or optional in a standard		5
* More than one certificate (except for AM FCE qualities)		7

2.13 Shipments

All shipments are specified “librex” (shipped when ready). Any restriction on shipment made by the client must be agreed in advance by the plant and will be charged as follows:

4 weeks' storage maximum	supplementary extra	15
More than 4 weeks		not accepted

The storage period must be specified when the order is placed. If the agreed deadline is exceeded, ArcelorMittal will proceed in accordance with the General Conditions of Sale.

