



Hot rolled price extras list

for Industry Europe

ArcelorMittal

Versions in Dutch, French, German, Italian, Spanish, Polish, Czech, Romanian and Turkish can be accessed at our website: industry.arcelormittal.com > Products & Solutions > [Price extras lists](#) or requested through our agencies. For more detailed information, please consult our online product catalogue on industry.arcelormittal.com > Products & Solutions > [Product catalogue](#) or click on the hyperlinks in this document.

Valid as from 01/10/2014 – version 30/06/2014 (EUR/tonne)

1. User guidelines

1.1 Price calculation

The following document only lists extras.

The price as invoiced includes:

The basis price

+ Transportation extra

+ Transportation tax (depending on the country)

+ Any extras from the list below

1.2 Product availability

Not all combinations of specifications are available at each production facility.

2. Extras

2.1 Steel grades

.1 Steels for cold forming and deep drawing applications (data sheet A10)

EN 10111:2008	ArcelorMittal specific offer	
DD11	DD11 AM FCE	0
	DD11-CL1 AM FCE	(1)
DD12	DD12 AM FCE	10
DD13	DD13 AM FCE	15
DD14	DD14 AM FCE	25
	DD15 AM FCE	30

(1) After prior agreement

.2 Structural steels (data sheet A30)

EN 10025-2:2004	ArcelorMittal specific offer	
S185*		0
S235JR*		5
	S235JR-CL1 AM FCE	(1)
S235J0	S235J0 AM FCE	15
S235J2+N	S235J2+N AM FCE	20
S235J2	S235J2 AM FCE	15
S275JR*	S275JR AM FCE*	15
S275J0	S275J0 AM FCE	30
S275J2+N	S275J2+N AM FCE	35
S275J2	S275J2 AM FCE	30
S355JR*	S355JR AM FCE*	35
S355J0	S355J0 AM FCE	40
S355J2+N*	S355J2+N AM FCE*	50
S355J2	S355J2 AM FCE	45
S355K2+N*	S355K2+N AM FCE*	55
S355K2*		52
E295		35
E335		45

* Suitability for galvanising: Class 1 supplementary extra (1)

Other grades: suitability for galvanising is included

(1) After prior agreement

Normalised rolled structural steels are only offered with J2 and K2 requirements.

.3 Structural forming grades (data sheet A14)

ArcelorMittal specific offer	
S200 AM FCE	0
S200D AM FCE	33
S240D AM FCE	10

>>

.4 High Strength Low Alloy steels (data sheet A20)

EN 10149-2:2013		Amstrong™ offer
	Amstrong™ 240MC	20
	Amstrong™ 280MC	35
S315MC	Amstrong™ 315MC	40
S355MC	Amstrong™ 355MC	45
	Amstrong™ 390MC	65
S420MC	Amstrong™ 420MC	65
S460MC	Amstrong™ 460MC	75
S500MC	Amstrong™ 500MC	80
S550MC	Amstrong™ 550MC	100
S600MC	Amstrong™ 600MC	110

.5 Ultra High Strength Low Alloy steels (data sheet A22)

EN 10149-2:2013		Amstrong™ offer
S650MC	Amstrong™ 650MC	160
S700MC	Amstrong™ 700MC	200

.6 Quenchable boron steels (data sheet A54)

EN 10083-3:2006		ArcelorMittal specific offer
20MnB5	22MnB5 AM FCE	120
30MnB5	30MnB5 AM FCE	125
38MnB5	38MnB5 AM FCE	130

.7 Atmospheric corrosion resistant steels Indaten® (data sheet A34) and steels with copper addition

EN 10025-5:2004		ArcelorMittal specific offer
S235J0W		(1)
S235J2W		(1)
S355J0W		(1)
S355J0WP	Indaten® 355A	125
S355J2W	Indaten® 355D	160
S355J2WP		125

(1) After prior agreement

Steels with copper addition

Cu content (%)	
0.20 - 0.35	(1)
0.36 - 0.50	(1)

(1) After prior agreement

.8 Steels for laser cutting (data sheet A40)

ArcelorMittal specific offer	
S200 Laser AM FCE	15
S240 Laser AM FCE	20
S275 Laser AM FCE	45
S355 Laser AM FCE	55
S320MC Laser AM FCE	45
S360MC Laser AM FCE	65
S420MC Laser AM FCE	85

Extra for laser cutting ability according to § 2.8 is included

Other qualities (1)

(1) After prior agreement

For coils use reference quality extra and add extra for laser cutting ability according to § 2.8

For sheets, add extra "cut to length" § 2.2.2 + special flatness Laser Classic or Laser Premium § 2.3.4 to the laser quality coil extra.

.9 Hot rolled steels for one side enamelling (data sheet C50)

ArcelorMittal specific offer	
S240EK AM FCE	30
S300EK AM FCE	36

.10 High carbon steels (data sheet A52)

EN 10083-2:2006	EN 10132-4:2000	ArcelorMittal specific offer	
C22E			35
C35E		C35E AM FCE	40
C40E		C40E AM FCE	45
C45E		C45E AM FCE	50
C50E		C50E AM FCE	55
C55E			60
C60E		C60E AM FCE	65
	C67S	C67S AM FCE	70
	C75S	C75S AM FCE	75
	C100S	C100S AM FCE	95

.11 Steels for re-rolling (data sheet A12)

ArcelorMittal specific offer	
DC01RB AM FCE	0
DC03RB AM FCE	10
DC04RB AM FCE	15
DC05RB AM FCE	20
DC06RB AM FCE	40
DC01RC AM FCE	0
DC03RC AM FCE	15
DC04RC AM FCE	20
DC05RC AM FCE	35
DC06RC AM FCE	40

>>

.12 Steels for pipes (data sheet A60)

A prior technical agreement is requested.

EN 10208-2:2009	API-5L:2008	
L245MB	Grade B	30
L290MB	X42	40
	X46	50
L360MB	X52	60
	X56	75
L415MB	X60	75
L450MB	X65	80
L485MB	X70	90
L555MB	X80	(1)

(1) After prior agreement

Specific supplementary extras for low sulphur contents due to other analytical characteristics of steels for pipes

To be added to steels for pipes extras

Sulphur content	
S ≤ 0.005%	5
S ≤ 0.003%	10
S ≤ 0.002%	40

.13 Steels for pressure vessels and boilers (data sheet A62)*

* in case of multi-certification, the steel grade extra of the highest grade has to be charged

Steels with properties at specified elevated temperatures

EN 10028-2:2009	
P235GH+N	50
P265GH+N	60
P295GH+N	65
P355GH+N	80
16Mo3	150

Steels for simple pressure vessels

EN 10207:2005	
P235S	45
P265S	55
P275SL	60

Weldable fine grain steels, normalised

EN 10028-3:2009	
P275NH+N	70
P275NL1+N	75
P275NL2+N	80
P355N+N	85
P355NH+N	90
P355NL1+N	95
P355NL2+N	100

Weldable fine grain steels, thermomechanically rolled

EN 10028-5:2009	
P420M	95
P420ML1	100

.14 Steels for gas containers (data sheet A64)

EN 10120:2008

P245NB	32
P265NB	40
P310NB	50
P355NB	60

2.2 Dimensions

.1 Extras for thickness / width

Thickness (mm)	Width (mm)								
	600 - 799	800 - 899	900 - 1099	1100 - 1499	1500 - 1549	1550 - 1599	1600 - 1849	1850 - 2049	≥ 2050
1.50 - 1.59	107	54	49	40	40	40	40	-	-
1.60 - 1.69	97	44	43	37	37	37	37	-	-
1.70 - 1.79	80	44	39	35	35	32	32	-	-
1.80 - 1.99	72	39	35	30	30	32	32	-	-
2.00 - 2.49	61	34	28	24	24	28	28	35	(1)
2.50 - 2.99	59	29	25	21	21	21	21	30	38
3.00 - 3.99	53	29	23	19	19	21	21	28	36
4.00 - 6.99	53	24	20	17	17	19	19	28	36
7.00 - 9.99	55	29	25	21	20	21	22	28	38
10.00 - 11.99	57	34	28	23	23	24	25	28	38
12.00 - 14.99	59	34	28	25	25	25	25	30	38
15.00 - 19.99	61	38	40	30	30	25	25	35	40
20.00 - 25.00	64	48	50	40	40	35	35	45	45

(1) After prior agreement

The thickness is the aimed thickness either specified in the order or the midpoint of the tolerance range.

.2 Supplementary extras for sheets

Thickness (mm)	Length (mm)					
	< 1000	1000 - 1999	2000 - 6000	6001 - 8999	9000 - 11999	12000 - 16000
1.50 - 1.99	(1)	67	50	60	60	(2)
2.00 - 2.99	(1)	62	41	46	49	(2)
3.00 - 9.99	(1)	52	34	39	41	55
10.00 - 11.99	(1)	52	34	39	41	55
12.00 - 16.00	(1)	47	33	35	37	50
16.01 - 25.00	(1)	(2)	(1)	(1)	(1)	(1)

(1) After prior agreement

(2) Not accepted

Or, if standard dimensions, for thicknesses ≥ 2.0 mm

1000*2000	27
1250*2500	27
1500*3000	27
1500*6000	27

Supplementary extras for sheets if width ≥ 2000

8

>>

2.3 Special tolerances according to EN 10051:2010

.1 Tolerances on thicknesses in accordance with the specifications of the catalogue

3/4 EN 10051:2010	0
1/2 EN 10051:2010	5
1/3 EN 10051:2010	15

.2 Tolerances on width

Without edge trimming	0
With edge trimming	apply extras 2.5 Edge trimming

.3 Tolerances on length

Normal tolerances EN 10051:2010	0
Tighter tolerances after agreement	10

.4 Special flatness (only for sheets)

Flatness Laser Classic* or Special Flatness (according to EN)	10
Flatness Laser Premium*	25
Additional extra for tensile strength ≥ 480 MPa**	15

* Flatness Laser Classic or Premium: only available on qualities for laser cutting
 ** The minimum value of the tensile strength range may be higher than 480 MPa.

2.4 Pickling (with mill edges)

	Thickness (mm)							
	1.00 1.19	1.20 1.24	1.25 1.49	1.50 1.99	2.00 6.34	6.35 7.99	8.00 13.00	> 13.00 15.00
Width (mm)								
600 – 999	(1)	65	55	43	30	40	45	(1)
≥ 1000	(1)	60	50	43	30	40	45	(1)
For tensile strength ≥ 480 MPa*				supplementary extra				5
For tensile strength ≥ 700 MPa*				supplementary extra				9
Easyfilm® HPE (A80)	th ≤ 8 mm		supplementary extra				5	
	th > 8 mm		supplementary extra				(1)	
Unpickled				supplementary extra				2
Totally free of oil stains				supplementary extra				(1)

(1) After prior agreement

* The minimum value of the tensile strength range may be higher than 480 or 700 MPa.

2.5 Edge trimming

Edge trimmed coils

	< 6	6 - 8	> 8
Thickness (mm)			
Unpickled	18	18	20
Pickled	10	18	40
High carbon	40	40	40
Sheets	10	10	10

2.6 Improved surface

.1 Aspect

Visible parts (minor surface defects visible after coating are not acceptable)

Thickness > 5 mm	20
Thickness 2 - 5 mm	10
Thickness < 2 mm	30

.2 Skin-pass (for unpickled material only upon request by customers)

Skin-pass	20
-----------	----

2.7 Sulphur content

$S \leq 0.002\%$	23
$0.002\% < S_{\max} \leq 0.005\%$	15
$0.005\% < S_{\max} \leq 0.010\%$	8

2.8 Special suitability

Steels for laser cutting (data sheet A40) - use only if quality not in the list § 2.1.8	15
Suitable for flanging or roll forming - Options 11 and 12 for quality C conform to EN 10025-2:2004	15
HIC requirements for tubes	(1)

(1) After prior agreement

2.9 Floor plates – diamond or teardrop pattern (data sheet A90)

To be added to other price supplements for extras for smooth coils and sheets

Floor plates	30
--------------	----

2.10 Stamping (only for sheets)

Ink stamping	3
Embossed stamping	6

>>

2.11 Coil and bundle weight

.1 Coil weight (maxi coil weight calculated)*

Width (mm)	Weight (t)			
	< 5	5 9.999	10 14.999	≥ 15
600 – 1099	(2)	5	0	0
≥ 1100	(2)	5	5	0

(2) Not accepted

* The maxi coil weight is calculated taking into account the maxi coil weight ordered and the maxi outside diameter.

Permitted deviation for the weight specified per coil

Our factories are not bound to supply the exact coil weight specified.

Coil weight may be between 75 and 100% of the weight specified.

20% of the tonnage of the sample ordered as coils may be supplied as lightweight coils, i.e. coils weighing between 25 and 75% of the specified weight.

.2 Bundle weight

< 2 t	5
-------	---

2.12 Order quantities: extras per item

.1 Item definition

An item is defined as a quantity of material specified in one order form for which the steel grade, thickness, width, coating, delivery time and the destination are the same.

.2 Extras

	Coils	Sheets
Weight (t)		
< 5	(2)	(1)
5 – 9.999	(2)	(1)
10 – 19.999	15	0
20 – 49.999	0	0
≥ 50	0	0

(1) After prior agreement

(2) Not accepted

Note: the weight of the order item should be expressed as a multiple of the weight of a single coil.

Unit weight / quantities per order unit should be agreed with the factory.

.3 Tolerances on quantities

Item tonnage (t)	Tolerances (%)
< 30	± 20
30 < 40	± 15
40 ≤ 100	± 10
> 100	± 5

2.13 Internal diameter (only for unpickled material and after prior agreement)

Internal diameter (mm)

610	15
-----	----

2.14 Packaging

Coils and sheets are charged gross for net, wooden pallet and spacers included.

Standard ArcelorMittal packaging

Unpickled	no paper	0
Pickled	no paper	0
	paper or plastic	5
	seaworthy	5

For all other packaging requirements:

After prior agreement, with a minimum of	10
--	----

2.15 Certificates - Inspection

EN 10204:2004

Standard indication

Certificate of compliance with the order	2.1	0
Test report	2.2	0
Inspection certificate	3.1*	5
Inspection certificate	3.2	10

Supplementary test, not mentioned or optional in a standard

5

* More than one certificate (except for AM FCE qualities)

7

2.16 Impact test (KV)

Temperature test when not included or optional in the standard

-20°C	5
-40°C	10
-50°C	20

2.17 Shipments

All shipments are specified "librex" (shipped when ready). Any restriction on shipment made by the client must be agreed in advance by the plant and will be charged as follows:

4 weeks' storage maximum	supplementary extra	15
More than 4 weeks		not accepted

The storage period must be specified when the order is placed. If the agreed deadline is exceeded, ArcelorMittal will proceed in accordance with the General Conditions of Sale.