

Hot dip galvanised strip products

Price extras in Euros

Effective 1 April 2015

General

This document shows price extras only.

The invoiced price comprises these extras plus basis price, distribution and tax.

Material is charged on gross weight. Lengths and widths should be specified in whole millimetres.

Unless otherwise agreed with Tata Steel, sales are FCA Tata Steel IJmuiden loading quay (ship), FCA Tata Steel IJmuiden loading dock (truck) or FCA Tata Steel IJmuiden railway yard (rail).

All prices in this list are in EUR/tonne and do not include value-added tax or any other tax relating to the sale and delivery of the goods. If delivery is within the European Union, the purchaser will bear all taxes and will reimburse Tata Steel for any taxes charged to Tata Steel in respect of the sale or delivery of the goods.

All transactions are subject to Tata Steel IJmuiden BV General Conditions of Sale.

Specifications are subject to mill acceptance and not all combinations of extras are necessarily available. For specific information about products and their availability, please check www.tatasteeleurope.com or consult Tata Steel.

1. Quality

1.1 Steel for drawing and cold forming

Tata Steel	EN 10346 : 2009	€/tonne
n.a.	DX51D+Z/ZF	0
	DX52D+Z/ZF	25
	DX53D+Z/ZF	52
	DX54D+Z/ZF	88
	DX56D+Z/ZF	110
	DX57D+Z	141

1.2 Structural steel

Tata Steel	EN 10346 : 2009	€/tonne
	S220GD+Z	0
	S250GD+Z	5
	S280GD+Z	15
	S320GD+Z	23
	S350GD+Z	40
S390GD+Z		50
S420GD+Z		60
S450GD+Z		60
	S550GD+Z	70

1.3 High-strength steel

Tata Steel	EN 10346 : 2009	€/tonne
Re-phosphorised		
HX220PD+Z/ZF		85
HX260PD+Z/ZF		75
HX300PD+Z/ZF		80
Interstitial free		
	HX180YD+Z	87
	HX220YD+Z/ZF	92
	HX260YD+Z/ZF	97
Bake hardening		
	HX180BD+Z/ZF	75
	HX220BD+Z/ZF	70
	HX260BD+Z/ZF	85
	HX300BD+Z/ZF	90
Low alloy (micro-alloying)		
HX220LAD+Z/ZF		25
	HX260LAD+Z/ZF	30
	HX300LAD+Z/ZF	40
	HX340LAD+Z/ZF	50
	HX380LAD+Z/ZF	65
	HX420LAD+Z	80
	HX460LAD	90
	HX500LAD+Z	105

1.4 Advanced high-strength steel

Tata Steel	EN 10346 : 2009	€/tonne
Dual phase		
DP600	HCT600X+Z/ZF	150
DP800	HCT780X+Z	180
DP800 HyperForm®		200
DP1000HY		280
Complex phase		
CP800	HCT780C+Z	200

2. Zinc coating

2.1 Coating thickness (Z/ZF)

Thickness (mm)		Coating mass (g/m²)							
		>100 ≤ 100*	>140 ≤140	>200 ≤200	>225 ≤225	>275 ≤275	>350 ≤350	>450 ≤450	>600 ≤600
≥	<	€/tonne							
0,35	0,40	-13	0	29	39	55	85	-	-
0,40	0,45	-11	0	25	35	49	77	-	-
0,45	0,50	-11	0	22	31	44	71	-	-
0,50	0,55	-10	0	20	28	40	63	103	-
0,55	0,60	-10	0	18	25	37	57	94	-
0,60	0,70	-9	0	16	22	34	52	86	-
0,70	0,80	-9	0	14	20	31	47	77	115
0,80	0,90	-8	0	12	18	28	42	69	105
0,90	1,00	-7	0	11	16	25	37	57	95
1,00	1,25	-7	0	10	14	21	33	54	85
1,25	1,50	-6	0	8	12	17	27	45	63
1,50	2,00	-5	0	7	10	15	23	37	51
2,00	2,50	-4	0	6	8	12	18	29	38
2,50	3,00	-3	0	5	7	10	15	23	30
3,00	≤4,00	-3	0	4	6	8	12	19	23

* For surface qualities A and B, surcharges of €/t 20 will be applied when zinc coating < 100 g/m²

Notes:

Other thickness / coating weight combinations available on request.

2.2 Coating type

	€/tonne
Extra for galvannealed (ZF)	30

3. Surface

3.1 Surface quality

EN 10346: 2009 (Z/ZF)	Description	€/tonne
MA/A	standard	0
MB/B	improved	20
MC	best quality	70

3.2 Surface treatment

	€/tonne
Passivation (Cr free)	0
Oiling	3

4. Dimensions

4.1 Thickness and width: coils

Thickness (mm)		Width (mm)								
		≥900 <1000	≥1000 <1100	≥1100 <1200	≥1200 <1300	≥1300 <1500	≥1500 <1700	≥1700 ≤1830	>1830 ≤1950	>1950
≥	<	€/tonne								
0,35	0,40	178	174	168	166	149	-	-	-	-
0,40	0,45	151	147	135	133	131	131	-	-	-
0,45	0,50	140	136	130	128	128	128	-	-	-
0,50	0,55	119	115	105	103	101	101	-	-	-
0,55	0,60	114	110	98	96	96	96	-	-	-
0,60	0,70	95	91	83	81	80	80	80	186	-
0,70	0,80	88	84	75	73	71	71	71	169	204
0,80	0,90	80	76	67	65	63	63	63	152	187
0,90	1,00	74	70	61	59	57	57	57	155	190
1,00	1,25	65	61	54	52	50	50	50	101	146
1,25	1,50	56	52	46	44	42	42	42	79	114
1,50	2,00	50	46	41	38	36	36	36	87	122
2,00	2,50	39	35	30	27	26	25	25	-	-
2,50	3,00	36	32	28	25	24	23	-	-	-
3,00	≤4,00	34	29	25	23	22	21	-	-	-

Notes:

- Where dimensions are specified as a range, a maximum (with all tolerances under) or a minimum (with all tolerances over), the extras applicable are those for the mean of the range as specified or implied.
- Other dimensions available on request.

5. Dimensions tolerances

5.1 Thickness tolerances

EN 10143 : 2006	€/tonne
Normal	0
Special	5
Tighter than special - 1/2 Normal	10
<1/2 EN	20

5.2 Width tolerances and side trimming

EN 10143 : 2006	€/tonne
Normal	0
Special / Outside EN 10143 : 2006 (Side Trimmed Last)	15

5.3 Special flatness

EN 10143 : 2006	€/tonne
Thickness (mm)	
≥	<
	0,7
0,7	1,2
1,2	
	20
	15
	10

6. Quantity

6.1 Coil weights

Max. coil weight		Width (mm)				
		≥900	≥1100	≥1300	≥1500	≥ 1700
		<1100	<1300	<1500	<1700	
≥	<	€/tonne				
5	10	30	30	30	35	35
10	15	0	0	0	0	0
15		0	0	0	0	0

Notes:

1. Coil weight price extras apply unless the specified coil weight is the result of technical limitations at Tata Steel.
2. The minimum specifiable coil weight is 5 tonnes.
3. Specified coil weights must be in balance with the ordered quantity.

6.2 Order quantity per order item

Quantity (tonnes)		Tata Steel tolerance	€/tonne
≥	<		
100		±10%	0
40	100	±20%	0
20	40	±20%	10

Notes:

1. An order item is a quantity of material specified in one order of which the specification (grade, dimension, etc) delivery time and destination is the same.
2. The minimum order quantity is 20 tonnes.
3. Material should be ordered in quantities that are multiples of whole coils.
4. Tata Steel will seek to supply the nearest number of whole coils to meet the ordered quantity or a quantity that is within the tolerances shown.
5. Where quantity is specified as a range, a maximum (with all tolerances under) or a minimum (with all tolerances over), the extras applicable are those for the mean of the range as specified or implied.

6.3 Welds

	€/tonne
If recoiling welds are not accepted	3

7 Testing and inspection

7.1 Test certificates

	€/tonne
to EN 10204 : 2004	
Declaration of compliance with order - type 2.1	0
Test report (cast analysis only) - type 2.2	0
Test report (cast analysis and mechanical properties) - type 2.2	3
Inspection certificate (cast analysis and mechanical properties based on specific testing) - type 3.1	5
Other, non-mandatory tests	on request

Notes:

At purchaser's choice only one certificate to EN 10204 will be issued, to be agreed on ordering.

8 Packaging

8.1

	€/tonne
Steel strapping	0
Paper/film and steel strapping	3
Steel/board box, paper/film and steel strapping	5

Notes:

1. For weighing and invoicing gross equals net.
2. The wood if used in packing is included in the weight.
3. Packaging materials are to be regarded as non-returnable.



www.tatasteeleurope.com

Tata Steel

PO Box 10.000

1970 CA IJmuiden

The Netherlands

T: +31 (0) 251 496126

E: strip.enquiries@tatasteel.com

IS:04/2015

Care has been taken to ensure that this information is accurate, but Tata Steel, including its subsidiaries, does not accept responsibility or liability for errors or information which is found to be misleading.

Tata Steel reserves the right to change this information at any time without prior notice. The online version will take precedence over the printed version at any moment in time.

Copyright 2015
Tata Steel Europe Limited