Prediction, Compression, and Intelligence: Three Names for the Same Operation

Section 3 — Philosophy of Machine Minds
Executive Education Lecture Notes

Contents

1 Why this equivalence matters **2**

2 Prelude: Shannon and the cost of surprise **6**

3 Prediction ⇔ Compression (Shannon's half of the bridge) **11**

4 Kolmogorov complexity **15**

5 Solomonoff induction **19**

6 AIXI: intelligence as optimal compression-driven prediction **25**

7 What this buys us for LLMs **31**

8 Caveats and what the equivalence does not say **35**

A Worked cross-entropy calculation **40**

Preface: how to read these notes

Two readers, one document. Orange **Intuition** boxes are the *manager track*: plain English, small numbers, one takeaway each. The running body is the *student track*: definitions, lemmas, proofs. Green **Activity** boxes are for either reader — they finish in under ten minutes and produce a number you can argue about. If you only read the orange boxes and the section headings, you will still leave with the thesis.

The thesis in one sentence. *Predicting the next symbol well, compressing a file well, and acting intelligently are — under precise definitions given later — the same operation measured in different units.* That is either the most important business fact of the decade, or a confusion between three different things that happen to share a name. By the end of these notes you will know which, and you will know what observation would prove you wrong.

1 Why this equivalence matters

A story to hold in your head

Three friends meet at a bar. The first is a stenographer: her job is to guess, letter by letter, what the speaker will say next, and she is eerily good at it. The second runs a file-compression startup: his software turns a 1 GB text dump into a 150 MB archive without losing a byte. The third is a chess player who has never read a book on chess but wins anyway, because she has an uncanny sense of which move a strong opponent would play.

Over the course of these notes we will prove that the three friends are, in a precise mathematical sense, the same person. Shannon will show the stenographer and the compressor are literally doing the same job in different units. Kolmogorov will show that "the shortest description of a thing" does not depend on which language you describe it in. Solomonoff and Hutter (the latter an ETH alum, the former a little-known American polymath — we will introduce both properly later) will show that a gambler who always bets on the shortest explanation is, in a sense we will make exact, the smartest possible learner. That is the whole plot.

Intuition

One sentence. Being good at predicting what comes next, being good at compressing a file, and being good at thinking are — up to a translation we will spell out — the same skill.

Why a decision-maker should care. Your vendors are selling products whose entire training objective is one number: the average surprise of the model when it sees the next word of the internet. If the equivalence holds, minimising that one number is a proxy for general intelligence. If it does not hold, you are buying a very expensive autocomplete. You cannot tell which without seeing the equivalence and its cracks.

The falsifiable version. If the equivalence is real, then across language models of similar size, *lower bits-per- character on held-out English text should track higher scores on reasoning benchmarks* (MMLU, BIG-Bench, GSM8K). If two models have the same held-out bits-per-character but wildly different benchmark scores, the equivalence is

leaky and we should say where. This is not a rhetorical flourish — it is the empirical hook the rest of the document hangs on.

A worked number to anchor the rest

Before the definitions, here is the number to remember. Uncompressed English Wikipedia is about 19 GB. The classical utility `gzip` shrinks it to roughly 5 GB (a compression ratio of about 3.8). A modestly tuned 7-billion-parameter language model, used as a compressor through arithmetic coding, shrinks the same file to under 3 GB — a ratio above 6. The Hutter Prize, a long-running competition founded by Marcus Hutter, currently stands near 1.1 GB on a 1 GB benchmark slice, i.e. a ratio close to 9. The prize's explicit premise is: *the team that compresses English hardest has, by that very fact, built the best model of English.* [**?**]

Example 1.1 (Bits, dollars, and benchmark points)**.** Suppose a firm stores 100 TB of customer-support transcripts at \$0.023 per GB-month on commodity cloud storage. Raw cost: about \$28,000/year. A foundation model that compresses the logs 2× (a realistic figure for natural-language logs) saves roughly \$14,000/year. That is the **dollars column**. The **bits column** is the bits-per-character of the same model on a held-out slice of the same logs. The **capability column** is what the same model scores on MMLU. The thesis of these notes is that the three columns are, up to noise and the caveats of Section 8, three views of one underlying quantity.

Activity A1 — Guess the next letter

Materials. A short sentence (10–20 words), one letter per index card, kept face down. **Protocol.** In pairs. Flip card 1. Before flipping card 2, the guesser names the letter they think is next. Tally hits over 60 cards. **Debrief.** Hit rate h gives a back-of-envelope upper bound on your per-letter surprise: roughly $-\log_2 h$ bits. A frontier LM achieves about 0.9 bits per character on English. What did you achieve? The gap between you and the LM, in bits, is the gap that Shannon will soon teach us to price.

Activity A2 — Compress your own paragraph

Snippet (Python, ∼5 lines).

```
import gzip, sys
s = open("my_paragraph.txt","rb").read()
print("gzip bpc:", 8*len(gzip.compress(s))/len(s))
```

Run it on a paragraph you wrote yourself. Typical English prose gives gzip $\approx$ 2.5–3.0 bits per character. The same paragraph scored by a small public LM (code omitted; see the course repository) will give something closer to 1.0. The ratio between those two numbers is roughly the ratio of "what a dumb model of English knows" to "what a smart model of English knows." That ratio, multiplied by your storage bill, is the dollar value of intelligence measured in bits.

The chain of results, informally

The rest of the section previews, in English, the four technical results that lock the equivalence together. Each will get a full treatment later; here we only name them and say which gap they close.

1. **Shannon source coding.** The minimum average number of bits you need to encode a symbol drawn from a known distribution equals that distribution's entropy. Corollary: if you can predict, you can compress; if you can compress, you have (implicitly) predicted. Prediction and compression are the same job in different units.

2. **Kolmogorov complexity.** The length of the shortest program that prints a string is, up to an additive constant that does not depend on the string, independent of which universal programming language you choose. So "shortest description" is a property of the string, not of the describer. This licenses talk of "the" complexity of a dataset.

3. **Solomonoff induction.** If you must bet on what comes next with no prior knowledge, the Bayes-optimal gambler assigns probability proportional to 2^{-K}, where K is the Kolmogorov complexity of the hypothesis. Shorter explanations are more likely; this is Occam's razor made into a theorem.

4. **AIXI.** An agent that acts to maximise expected reward under Solomonoff's prior is, in a precisely defined sense, the optimal reinforcement learner. It is uncomputable — but every real learner is a computable approximation to it, and the distance from it is the distance from ideal intelligence.

Intuition

The triangle to keep on a napkin. Three vertices — *Predict*, *Compress*, *Act intelligently*. Three edges. Shannon is the edge Predict $\leftrightarrow$ Compress; Solomonoff is the edge Compress $\leftrightarrow$ Act (through Kolmogorov, which makes "compress" language-independent); and the full triangle closes at AIXI. Figure 1 draws it. If you remember only one picture from these notes, remember that one.



Figure 1: The three-vertex picture. Each edge is a theorem that translates one vertex into another. Kolmogorov complexity (§3) is the hub that makes the translation coordinate-free.

Why this matters for decisions, not just for theory

A decision-maker evaluating a foundation-model vendor faces a simple but hard question: *is the loss number on the vendor's training dashboard a proxy for anything you care about?* If the equivalence we are about to prove holds cleanly, the answer is yes: every 0.1-bit improvement in held-out cross-entropy corresponds to a measurable improvement in downstream capability, and the conversion rate can be estimated. If the equivalence leaks — and we will show exactly where it does — the answer is "sometimes, in these regimes, with these caveats." Either answer is actionable; neither is available without the chain of theorems.

Activity A4 — Falsification worksheet

Fill the table below before reading further. We will return to it in Section 8 and see which of your rows survives.

Equivalence claim	What would refute it	What is merely consistent
Lower bpc ⇒ higher MMLU (same size).		
Better zip ratio on a domain ⇒ better agent on that domain.		
A model that memorises (does not generalise) cannot compress held-out data well.		

A caveat, promoted out of the footnotes. A *perfect* next-token predictor would be an ideal learner. Real next-token predictors are not perfect. The gap between them and the ideal is exactly where this document's caveats live (Section 8); we state the thesis before we qualify it, but the qualification is not optional. In particular: the equivalence is between the *training objective* and general capability, not between any specific checkpoint and general capability. A model can be a poor compressor of your domain while the objective it was trained on remains the right objective. Keep the distinction; a lot of vendor arguments blur it.

Formal statement of the thesis. The central technical claim of this note is that three operations often treated as distinct — predicting the next symbol in a sequence, compressing that sequence into a shorter description, and behaving intelligently in its presence — are, under a precise set of definitions, the *same operation* viewed from three angles. Shannon's source coding theorem [**?**] identifies prediction with compression; Kolmogorov complexity [**?**] makes the notion of "shortest description" independent of the choice of description language; Solomonoff's universal prior [**?**] promotes the Kolmogorov minimiser to a Bayesian predictor that converges to any computable source; and Hutter's AIXI [**?**] upgrades that predictor into a reward-seeking agent whose optimality can be stated as a theorem. The chain is not an analogy. Every step in this note is a definition, a lemma, or a theorem. The pedagogical payoff is that one can then ask sharp questions about large language models — whether they count as compressors, whether better

compression entails more general capability, and where the equivalence breaks — without smuggling in metaphor.

2 Prelude: Shannon and the cost of surprise

Intuition

Information is the price you pay for being surprised, and you are surprised in exact proportion to how unlikely an event was. Keep three numbers in mind for the rest of this section:

- **Fair coin.** $p(\text{heads}) = \frac{1}{2}$. One yes/no question settles it: $H = 1$ bit per flip.
- **Biased coin, 7/8 heads.** Most flips are boring; occasionally a tail surprises you. The average surprise works out to

  $$H = -\tfrac{7}{8}\log_2\tfrac{7}{8} - \tfrac{1}{8}\log_2\tfrac{1}{8} \;\approx\; 0.169 + 0.375 \;=\; 0.544 \text{ bits per flip.}$$

  That is the "about half a bit" we promised — now with the arithmetic to back it up.
- **A 1-in-1024 event.** $-\log_2(1/1024) = 10$ bits of "wow." A 50/50 event carries one bit of "huh."

Two forecasters make this concrete. In Los Angeles, Ana says "sunny" nearly every day and is right nearly every day; her distribution over {sun, cloud, rain} is roughly $(0.85, 0.10, 0.05)$, so $H(\text{LA}) \approx 0.74$ bits per day. In Zurich, Bärbel faces {sun, cloud, rain, snow, Föhn, fog} with a distribution closer to $(0.25, 0.30, 0.25, 0.07, 0.03, 0.10)$, giving $H(\text{ZRH}) \approx 2.32$ bits per day. If the newspaper pays each forecaster one cent per bit transmitted, Bärbel earns about three times what Ana does — not because Zurich is colder, but because Zurich is *less predictable*. Shannon's source-coding theorem (Theorem 2.5) says neither can do better than her own entropy floor, no matter how clever her code.

Why a decision-maker should care. Every storage bill, every bandwidth bill, every "our model is more efficient" vendor claim bottoms out against an entropy floor. Printed English has entropy between about 0.6 and 1.3 bits per character [**?**, Ch. 6]; if a vendor tells you they compress English text to 0.3 bits per character, they are either wrong, lying, or have discovered English has lower entropy than anyone thought — which would itself be news on the scale of cold fusion. Entropy also sets the floor on forecasting: no analyst, human or machine, can predict a genuinely high-entropy process (next week's lottery numbers) better than chance, no matter how much compute you throw at it. Knowing where the entropy floor sits for *your* data is the difference between a reasonable AI budget and a fantasy one.

Formal setup

Fix a finite *alphabet* $\mathcal{A} = \{a_1, \ldots, a_K\}$ and let X be a discrete random variable on $\mathcal{A}$ with probability mass function $p(a) = \Pr[X = a]$. All logarithms are base 2 unless stated; values are measured in *bits*. The alphabet could be {heads, tails} for a coin, {A, C, G, T}

for a DNA base, the 256 possible bytes in a file, or the roughly 50,000 sub-word tokens inside a modern language model.

Definition 2.1 (Self-information and Shannon entropy)**.** The **self-information** (or *surprisal*) of the outcome $x \in \mathcal{A}$ under p is

$$I_p(x) \;=\; -\log_2 p(x), \tag{1}$$

with the convention $0 \cdot \log_2 0 = 0$. The **Shannon entropy** of X is the expected self-information,

$$H(X) \;=\; \mathbb{E}\Big[I_p(X)\Big] \;=\; -\sum_{k=1}^{K} p(a_k)\,\log_2 p(a_k). \tag{2}$$

Why the logarithm?

Three demands pin down $-\log_2 p$ up to the choice of base. (i) A sure event ($p = 1$) should carry zero surprise: $\log 1 = 0$. (ii) Rarer events should carry more surprise: $-\log p$ is decreasing in p. (iii) Independent surprises should *add*: if X and Y are independent, the surprise of seeing both is $-\log(p_X p_Y) = -\log p_X - \log p_Y$. Only the logarithm turns multiplication of probabilities into addition of surprise, which is exactly what "number of yes/no questions" demands.

Codes, trees, and Kraft

A **code** for $\mathcal{A}$ is an injective map $C : \mathcal{A} \to \{0,1\}^*$ assigning a binary string $C(a)$ to each symbol. We write $\ell(a) = |C(a)|$ for the code length. C is a **prefix code** (or *instantaneous code*) if no codeword $C(a_i)$ is a proper prefix of any other codeword $C(a_j)$. The prefix property is what lets a receiver decode a stream of codewords without delimiters: as soon as the bits read match a codeword, that codeword is committed.



Figure 2: Prefix-code tree for the code $C(a) = 0,\ C(b) = 10,\ C(c) = 110,\ C(d) = 111$. Each leaf is a codeword; no codeword lies on the path to another. The subtree rooted at depth ℓ covers a $2^{-\ell}$ fraction of the infinite leaves, which is the content of Kraft's inequality.

Lemma 2.2 (Kraft's inequality)**.** *For any prefix code C on $\mathcal{A}$ with lengths $\ell(a_k)$,*

$$\sum_{k=1}^{K} 2^{-\ell(a_k)} \;\le\; 1. \tag{3}$$

Conversely, for any length assignment $\ell_1, \ldots, \ell_K \in \mathbb{N}$ satisfying (3) *there exists a prefix code with those lengths.*

Proof sketch. Identify each codeword with a leaf in the infinite binary tree (Fig. 2). A prefix condition forbids any codeword from lying on the path to another, so distinct codewords correspond to *disjoint* subtrees. The subtree rooted at a node of depth ℓ contains a $2^{-\ell}$ fraction of the infinite leaves, and disjointness of those fractions gives the bound. The converse is an explicit construction: sort ℓ_k in increasing order and assign the lexicographically smallest available length-ℓ_k string at each step. □

Example 2.3 (Entropy of a 4-symbol alphabet, revisited early)**.** Let $\mathcal{A} = \{a, b, c, d\}$ with $p(a) = \frac{1}{2}$, $p(b) = \frac{1}{4}$, $p(c) = p(d) = \frac{1}{8}$. Then

$$\begin{aligned} H(X) &= -\tfrac{1}{2}\log_2 \tfrac{1}{2} - \tfrac{1}{4}\log_2 \tfrac{1}{4} - 2 \cdot \tfrac{1}{8}\log_2 \tfrac{1}{8} \\ &= \tfrac{1}{2} \cdot 1 + \tfrac{1}{4} \cdot 2 + \tfrac{1}{4} \cdot 3 \;=\; \tfrac{7}{4} \text{ bits.} \end{aligned}$$

The prefix code $C(a) = 0,\ C(b) = 10,\ C(c) = 110,\ C(d) = 111$ of Fig. 2 achieves expected length $L = \frac{1}{2} \cdot 1 + \frac{1}{4} \cdot 2 + \frac{1}{8} \cdot 3 + \frac{1}{8} \cdot 3 = \frac{7}{4}$ bits exactly. Its lengths $(1, 2, 3, 3)$ satisfy Kraft with *equality* and match $-\log_2 p(a_k)$ symbol by symbol. When probabilities are negative powers of two, the Shannon floor is hit on the nose.

Guess-the-next-flip bet game — 10 minutes

Pair students up. One student flips a coin biased 3/4 heads (simulated by rolling a d4: 1–3 = heads, 4 = tails); the other bets any fraction of a running 16-chip stake on the outcome. The house rule: if you bet fraction f on the outcome that actually occurs and the true probability was p, your stake is multiplied by $2f/(2p) = f/p$.[a] Play ten rounds, then compute per round

$$(\text{avg. chips lost}) \;\approx\; D_{\mathrm{KL}}(p \,\|\, q) \;=\; \sum_x p(x) \log_2 \tfrac{p(x)}{q(x)},$$

where q is the student's betting distribution. The class discovers *experimentally* that the only way not to bleed chips is to bet $q = p$, and that their average loss equals the gap between the cross-entropy they "paid" and Shannon's floor $H(p)$. *Leo:* a scoreboard he can compute round by round. *Yuki:* bits become chips.

[a] The Kelly-optimal fraction is $f = p$, which multiplies the stake by 1 on average; deviations lose in the long run. Over many rounds the log-growth rate is $\sum_x q(x) \log_2(f(x)/p(x))$, a KL divergence.

Gibbs' inequality: the wrong code pays a tax

Lemma 2.4 (Gibbs' inequality)**.** *For any two probability mass functions p, q on $\mathcal{A}$,*

$$-\sum_k p(a_k) \log_2 q(a_k) \;\geq\; -\sum_k p(a_k) \log_2 p(a_k), \tag{4}$$

with equality if and only if $p = q$.

A one-picture reason to believe $\ln x \leq x - 1$

The curve $y = \ln x$ is concave; its tangent at $x = 1$ is the line $y = x - 1$. A concave curve lies on or below any of its tangents, so $\ln x \leq x - 1$ everywhere, with equality exactly at $x = 1$. Draw the two curves on the same axes once; you will never forget this inequality again.

Proof. Using $\ln x \le x - 1$ (with equality iff $x = 1$) and $\log_2 x = \ln x / \ln 2$,

$$\sum_k p(a_k) \log_2 \frac{q(a_k)}{p(a_k)} \;\le\; \frac{1}{\ln 2} \sum_k p(a_k) \left(\frac{q(a_k)}{p(a_k)} - 1 \right) \;=\; \frac{1}{\ln 2} \left(\sum_k q(a_k) - 1 \right) \;\le\; 0,$$

because $\sum_k q(a_k) \le 1$. Rearranging gives (4); the equality conditions of $\ln x \le x - 1$ and $\sum q = 1$ together force $p = q$. □

What Gibbs really says

If the world is distributed as p but you design a code as if the world were distributed as q, you pay $-\sum p \log q$ bits on average instead of $-\sum p \log p$. The difference,

$$D_{\mathrm{KL}}(p \,\|\, q) \;=\; \sum_k p(a_k) \log_2 \tfrac{p(a_k)}{q(a_k)},$$

is the *tax* the world levies on your wrong model. It is non-negative, zero only when $q = p$, and we will meet it again under the name "cross-entropy loss" whenever a neural network is being trained.

Shannon's source-coding theorem

Theorem 2.5 (Shannon source-coding inequality)**.** *Let C be any uniquely decodable (in particular, any prefix) code for $\mathcal{A}$ and let $L = \mathbb{E}[\ell(X)] = \sum_k p(a_k)\ell(a_k)$ be its expected code length. Then*

$$L \;\ge\; H(X). \tag{5}$$

Moreover, there exists a prefix code (e.g. the Shannon–Fano code with $\ell(a_k) = \lceil -\log_2 p(a_k) \rceil$) such that

$$L \;<\; H(X) + 1. \tag{6}$$

Proof sketch. Let $q(a_k) = 2^{-\ell(a_k)}/Z$, where $Z = \sum_k 2^{-\ell(a_k)} \le 1$ by Theorem 2.2; so q is a bona fide probability vector. Read q as the *implicit model* your code C is betting on: it assigns probability $q(a_k)$ to symbol a_k because it spent $\ell(a_k)$ bits describing it. By Theorem 2.4, the cross-entropy $-\sum_k p(a_k) \log_2 q(a_k) \ge H(X)$, i.e. the wrong model pays a tax. Because $-\log_2 q(a_k) = \ell(a_k) + \log_2 Z \le \ell(a_k)$ (since $Z \le 1$ makes $\log_2 Z \le 0$), we get $L \ge -\sum_k p(a_k) \log_2 q(a_k) \ge H(X)$. For (6), the lengths $\lceil -\log_2 p(a_k) \rceil$ satisfy Kraft (3), and each ceiling adds at most 1 to the expected length. See **?**, Ch. 5 for the full treatment. □

The slogan, properly qualified

"Every code is a probability model and every probability model is a code." Precisely: a prefix code with lengths $\ell(a_k)$ implicitly asserts the distribution $q(a_k) \propto 2^{-\ell(a_k)}$; a distribution q suggests lengths $\lceil -\log_2 q(a_k) \rceil$. When we train a language model to minimise cross-entropy loss, we are literally minimising the expected code length under Shannon's theorem. This is the hinge that the rest of these notes turns on.

More worked examples

Example 2.6 (Back to the 4-symbol alphabet, with a wrong model)**.** Keep $p = (\frac{1}{2}, \frac{1}{4}, \frac{1}{8}, \frac{1}{8})$ but design a code as if the distribution were uniform, $q = (\frac{1}{4}, \frac{1}{4}, \frac{1}{4}, \frac{1}{4})$, giving two bits per

symbol to every letter. Then $L = 2$ bits, the cross-entropy is $-\sum p \log_2 q = 2$ bits, and the KL tax is $D_{\mathrm{KL}}(p\|q) = 2 - \frac{7}{4} = \frac{1}{4}$ bit per symbol. Over a million symbols, betting on uniform instead of p costs you 250,000 bits — about 31 kilobytes of wasted bandwidth.

Example 2.7 (Biased coin, bit by bit)**.** The 7/8-heads coin has $H \approx 0.544$ bits. You cannot encode one flip in fewer than one bit, of course — codewords are integer-length. But if you block flips in groups of 10, the block alphabet has $2^{10} = 1024$ outcomes and the block entropy is $10 \cdot 0.544 = 5.44$ bits, which Shannon–Fano reaches to within one bit. Long-run bandwidth drops from 10 bits per block (naive) to about 6 bits per block. This is why every real compressor (gzip, arithmetic coding, LLM tokenisers) works on blocks or streams, not symbol-by-symbol.

Entropy of your phone lock-screen — 5 minutes

On scrap paper, write down (1) the length n of your phone PIN or pattern, (2) whether it contains a birthday (your own, a partner's, a child's), and (3) whether it repeats a digit. Using the prior

$$p(\mathrm{PIN}) \approx \begin{cases} 3 \times 10^{-3} & \text{if birthday-shaped,} \\ 10^{-n} & \text{otherwise,} \end{cases}$$

compute $-\log_2 p$ in bits. Compare to the entropy of a uniformly random n-digit PIN, $n \log_2 10 \approx 3.32n$ bits. The typical result in a classroom is that "birthday" PINs land near 8–9 bits while a truly random 6-digit PIN is near 20 bits. That ~ 11-bit gap is the factor-of-2000 advantage a thief enjoys against the average human. *Yuki:* personally concrete. *Leo:* ends in a number.

Huffman-code-by-hand worksheet — 15 minutes

Given probabilities $p = (0.40, 0.20, 0.15, 0.15, 0.10)$ over symbols $\{A, B, C, D, E\}$:

1. Sort and repeatedly merge the two lowest-probability symbols into a meta-symbol whose probability is their sum. Record each merge as a parent node.
2. After four merges you have a single root. Label each left edge 0 and each right edge 1; read each leaf's codeword from the root.
3. Compute $L = \sum p(a_k)\ell(a_k)$ and compare to $H(X) = -\sum p \log_2 p \approx 2.15$ bits. The Huffman code achieves $L = 2.20$ bits, within 0.05 of entropy.
4. *Stretch:* change $p(A)$ from 0.40 to 0.95 and redo. Watch the code for A collapse to a single bit while the others grow. This is the shape of *adaptive* compression.

Leo: pencil-and-paper payoff. *Yuki:* the tree becomes a physical drawing.

Six lines of Python — take home

Paste this into any Python 3 prompt:

```
from collections import Counter
from math import log2
def H(s):
    n = len(s)
```

```
    return -sum((c/n)*log2(c/n) for c in Counter(s).values())
print(H("to be or not to be that is the question"))
```

Run it on (a) the first paragraph of a novel in your native language, (b) the same paragraph translated to English, and (c) a 200-character string of your own keystrokes. You will typically see $H \approx 4.2$ bits per character on natural-language prose and $H \approx 3.0$ on keystrokes from a human who has a strong hand-preference. The true entropy of English is lower ($\sim$1 bit/char) because this snippet ignores correlations between neighbouring characters — which is exactly the gap a language model closes. *Leo:* code he can execute. *Yuki:* numbers for two inputs he already cares about.

Forward pointer

We will re-encounter cross-entropy in Theorem 2.1's shadow every time a neural network is trained; the KL tax will reappear as the "surprise" of a held-out document under a language model; and the source-coding theorem will become the statement that *prediction is compression* in the very next section.

3 Prediction ⇔ Compression (Shannon's half of the bridge)

Intuition

A predictor that assigns probabilities to the next word is, mechanically, a compressor; its error rate and its compression rate are the same number wearing different clothes (see Theorem 3.2 and Theorem 3.3).

The two-consultants analogy (postage version). Two consultants write up the same quarter. Both are earnest. The one who understands your business writes a one-pager: *revenue up 4%, driven by Zurich, offset by FX.* The one whose mental model is slightly off writes ten pages of hedging — because every surprise in the data costs her extra sentences. Both describe reality perfectly; only one *compresses* it.
Think of it as postage. The true entropy $H(p)$ is the postage a perfectly-informed sender pays. Cross-entropy $H(p, q)$ is the postage you actually pay when your delivery model is q but the world is p. The difference, $H(p, q) - H(p)$, is the **surcharge for being wrong**, and information theory has a name for it: the Kullback–Leibler divergence $D_{\mathrm{KL}}(p\|q)$.

A concrete, addable number. Suppose tomorrow's stock move is *up* with probability 0.9 and *down* with probability 0.1. The true entropy is

$$H(p) = -0.9 \log_2 0.9 - 0.1 \log_2 0.1 \approx 0.469 \text{ bits/day.}$$

If your model believes the market is 50/50, you spend exactly 1 bit per day describing it. The surcharge is $1 - 0.469 \approx 0.531$ bits per day. Over a million days (or tokens) that is

$$0.531 \times 10^6 \approx 5.3 \times 10^5 \text{ extra bits,}$$

roughly 66 kilobytes of *pure hedging*, paid because the model was wrong about the coin.

Perplexity in one sentence. LLM papers report "perplexity 8" or "2.1 bits per token." These are the same number: $\log_2 8 = 3$ bits per token; $\log_2(\text{PPL})$ = bits per token = cross-entropy (Theorem 3.3). *Perplexity* 8 *means the model behaves as if at each word it were choosing uniformly among* 8 *plausible options.* Lower is better.

Why a decision-maker should care. The training objective of every major LLM *is* cross-entropy on text. When a vendor says "our model scored 0.1 lower cross-entropy," they are saying "our model compresses the world 0.1 bits better per word," which over trillions of words is a lot of real modelling skill. Two models with identical cross-entropy are, at the level Shannon cares about, the same model. This gives you a vendor-agnostic yardstick — and a cheap test for benchmark theatre: if a new model does not improve cross-entropy but wins on a specific test, ask whether the test was in the training set.

From analogy to definition

Before the formalism, a one-line vocabulary bridge: a *prefix code* is a dictionary that assigns each symbol a unique bit-string such that no codeword is a prefix of another — so a decoder can unambiguously split a stream back into symbols. A *good* model q assigns high probability to the symbols that actually occur; the corresponding code is short exactly when q is accurate. Keep that picture as you read the definitions.

Sequence models predict *conditionally.* Fix a stochastic process $(X_t)_{t\geq 1}$ on $\mathcal{A}$ and write $X_{<t} = (X_1, \ldots, X_{t-1})$ with $X_{<1} = \emptyset$.

Definition 3.1 (Cross-entropy and conditional cross-entropy)**.** Let p be the true distribution of $(X_1, \ldots, X_T)$ and let q be a model distribution that factors autoregressively, $q(x_{1:T}) = \prod_{t=1}^{T} q(x_t \mid x_{<t})$. The **cross-entropy** of q against p at position t is

$$H_t(p, q) \;=\; \mathbb{E}_{x_{<t}\sim p}\Big[-\sum_{a\in\mathcal{A}} p(a \mid x_{<t})\, \log_2 q(a \mid x_{<t})\Big], \tag{7}$$

and the **average cross-entropy per token** is $\overline{H}(p, q) = \frac{1}{T}\sum_{t=1}^{T} H_t(p, q)$.

Read-aloud translation. "If the world draws symbols from p but you describe them with q, equation (7) is the *average number of bits* it will cost per symbol."

Theorem 3.2 (Cross-entropy equals expected code length)**.** *Fix T and a model q. Any prefix code that uses $\ell(x_t \mid x_{<t}) = \lceil -\log_2 q(x_t \mid x_{<t})\rceil$ bits to encode x_t given $x_{<t}$ satisfies*

$$\mathbb{E}_{x_{1:T}\sim p}\Big[\tfrac{1}{T}\sum_{t=1}^{T} \ell(x_t \mid x_{<t})\Big] \;=\; \overline{H}(p, q) + O(1/T), \tag{8}$$

and arithmetic coding attains (8) *with $O(1/T)$ overhead. Moreover,*

$$\overline{H}(p, q) \;=\; \overline{H}(p) + \overline{D}_{\mathrm{KL}}(p \,\|\, q), \tag{9}$$

where $\overline{H}(p) = \frac{1}{T}\sum_t H(X_t \mid X_{<t})$ is the true conditional entropy rate and $\overline{D}_{\mathrm{KL}}(p\|q) \geq 0$ is the average conditional Kullback–Leibler divergence.

Proof of (9). For each t and each history $x_{<t}$,

$$-\sum_a p(a\,|\,x_{<t})\log_2 q(a\,|\,x_{<t}) \;=\; -\sum_a p(a\,|\,x_{<t})\log_2 p(a\,|\,x_{<t}) + \sum_a p(a\,|\,x_{<t})\log_2 \frac{p(a\,|\,x_{<t})}{q(a\,|\,x_{<t})}.$$

The first term on the right is $H(X_t \mid X_{<t} = x_{<t})$; the second is $D_{\mathrm{KL}}(p(\cdot \mid x_{<t}) \,\|\, q(\cdot \mid x_{<t}))$. Taking expectation over $x_{<t} \sim p$ and averaging over t yields (9). Non-negativity of the KL term is exactly **Gibbs' inequality** (Theorem 2.4): for any two distributions p, q on the same support, $-\sum_a p(a)\log q(a) \;\geq\; -\sum_a p(a)\log p(a)$, with equality iff $p = q$. Statement (8) follows by plugging $\ell = \lceil -\log_2 q \rceil$ into Theorem 2.5 on each conditional distribution and absorbing the at-most-1-bit rounding into the $O(1/T)$ overhead; arithmetic coding eliminates even the integer ceilings up to a constant [**?**, Ch. 5]. □

Corollary 3.3 (Perplexity vs. bits per token)**.** *The* ***perplexity*** *of q on p is* $\mathrm{PPL}(q) = 2^{\overline{H}(p,q)}$*, so*

$$\log_2 \mathrm{PPL}(q) \;=\; \overline{H}(p,q) \;=\; \textit{(bits per token used by arithmetic coding with model } q\textit{).} \tag{10}$$

In words: perplexity is the effective branching factor; bits per token is its $\log_2$; they are two dials on the same gauge.

Theorem 3.2 is the entire Shannon side of the bridge: *minimising the cross-entropy training objective is literally minimising the expected compressed length.* A next-token predictor with cross-entropy $\overline{H}(p,q)$ bits per symbol corresponds, via arithmetic coding, to a compressor that uses $\overline{H}(p,q)$ bits per symbol. Better predictions ⇔ shorter codes.

Concrete handles

Activity 3.A — Compress your own message (paper, 10 min)

You are given an alphabet $\mathcal{A} = \{A, B, C, D\}$ with true distribution

$$p(A) = \tfrac{1}{2}, \quad p(B) = \tfrac{1}{4}, \quad p(C) = \tfrac{1}{8}, \quad p(D) = \tfrac{1}{8}.$$

Tasks.

1. Compute $H(p)$ in bits. (Answer: 1.75 bits/symbol.)
2. Design a prefix code. Hint: assign the shortest codeword to the most common symbol. One valid choice: $A \mapsto 0$, $B \mapsto 10$, $C \mapsto 110$, $D \mapsto 111$.
3. Compute expected code length $\mathbb{E}[\ell] = \sum_a p(a)\ell(a)$. Compare to $H(p)$. (You should hit the entropy exactly — this code is *optimal*.)
4. Now pretend your model was $q(A) = q(B) = q(C) = q(D) = \frac{1}{4}$ (uniform). The natural code is 2 bits per symbol. Expected length under *true* p is still 2. The surcharge $2 - 1.75 = 0.25$ bits/symbol is $D_{\mathrm{KL}}(p\|q)$. Verify this by computing $\sum_a p(a)\log_2 \frac{p(a)}{q(a)}$.

This is Theorem 3.2 on one page of paper.

Activity 3.B — Role-play: the two consultants (3 min)

Pair up. Partner X reads the *matched* consultant's lines; partner Y reads the *mismatched* consultant's lines. Both describe the same quarter.

Matched consultant ($q = p$):

(M1) "Revenue up 4%."

(M2) "Zurich drove growth."

(M3) "FX was a drag."

Mismatched consultant ($q \neq p$):

(W1) "Revenue is up, but only if we exclude these adjustments, and those adjustments, and also the following footnote . . . "

(W2) "Several offices contributed; Zurich was one of many; let me also describe Geneva, Basel, and Lugano . . . "

(W3) "FX might have helped or hurt; depending on the basket I reconstruct from scratch . . . "

Debrief. The mismatched consultant is not lying; she is *paying the KL surcharge* in sentences. Name the cost: each extra word is a bit.

Activity 3.C — Per-token cross-entropy in 6 lines of Python

Run this mentally or on a laptop. Two toy models assign probabilities to the three tokens of "the cat sat."

```
import math
p_good = [0.5, 0.4, 0.3] # model A's P(token_t | history)
p_bad = [0.1, 0.05, 0.02] # model B's P(token_t | history)
ce = lambda probs: -sum(math.log2(x) for x in probs) / len(probs)
print("A:", round(ce(p_good), 3), "bits/token") # 1.442
print("B:", round(ce(p_bad), 3), "bits/token") # 4.738
```

Interpretation. Model A spends ≈ 1.44 bits per token; Model B spends ≈ 4.74. On a million-token corpus, Model B wastes $\approx (4.74 - 1.44) \times 10^6/8 \approx 413$ KB *per sentence's worth of surprise* — a vivid way to see why vendors chase tenths of a bit.

Activity 3.D — Perplexity → bytes saved (numerical, 5 min)

Vendor V_1 reports perplexity 8; vendor V_2 reports perplexity 4.29. A 1M-token corpus is about to be archived.

1. V_1: $\log_2 8 = 3.0$ bits/token.
2. V_2: $\log_2 4.29 \approx 2.1$ bits/token.
3. Difference: 0.9 bits/token.
4. Over 10^6 tokens: 9.0×10^5 bits $= 112{,}500$ bytes ≈ 110 KB *saved* by choosing V_2.
5. Over a trillion tokens (10^{12}): ≈ 110 GB saved.

Moral. Tiny-looking cross-entropy gaps are enormous at corpus scale. This is why frontier labs fight over the third decimal.



Figure 3: Per-token surprise $-\log_2 q(x_t \mid x_{<t})$ for the sentence "the cat sat" under two toy models. The total height is the cross-entropy times T; the area difference is the KL surcharge. (Section 3)

For the decision-maker

Three questions to ask an LLM vendor.

1. *What is your held-out cross-entropy (or equivalently, perplexity) on a corpus we supply?* This is the only vendor-agnostic compression score.
2. *Was the benchmark corpus demonstrably outside the training set?* If not, the number is theatre.
3. *How much does a* 0.1*-bit-per-token improvement cost in compute, and what does it buy at our deployment scale?* Use Section 3 to translate bits into storage, bandwidth, or inference tokens.

A worked numerical example separating the matched and mismatched models on a 3-token sequence is given in Section A; Section 3 above are the in-class shortcuts to the same computation.

4 Kolmogorov complexity

Intuition

One-line answer. The Kolmogorov complexity $K(x)$ of an object x is the length, in bits, of the shortest computer program that prints x and stops (Theorem 4.1). It is the vendor-independent floor on how far x can ever be compressed.

Twin USB sticks. Imagine two 8 GB USB sticks on your desk. One is full of family JPGs; the other is full of bytes drawn from `/dev/urandom`. Both weigh the same;

both read the same number of bits off the bus. Zip the first and you get roughly 6–7 GB; zip the second and you get back almost exactly 8 GB — sometimes *larger*, once zip's header is added. The difference is not in the hardware. It is a property of the *contents*: the photos have structure a short program can exploit, the random bytes do not. Kolmogorov complexity is the mathematical name for that difference.

The recipe-over-the-phone picture. You are a chef. A colleague in another city must reproduce your dish exactly. You dictate the shortest instructions that do the job. "Boil water" takes two words. A soufflé takes a page. A pattern of 10,000 genuinely random sprinkles on a cake has no shorter description than itself: you read out every position. Such an object is *Kolmogorov random*; it has no exploitable structure. Everything else — the digits of π, the works of Shakespeare, your customer database — has a recipe shorter than the raw data.

A tiny worked example. The string `01010101...` (a million characters long) has an $\approx$ 30-character recipe: `print "01" 500000 times`. A million genuine coin flips has no such shortcut; its recipe is, to within a small constant, a million characters. Same disk size, wildly different Kolmogorov complexity. *Complexity measures structure, not size.*

Invariance and uncomputability, previewed. Two different programming languages disagree about the length of a recipe by at most the size of a translator between them (Theorem 4.2). So $K(x)$ is a property of the object, not your toolkit. But no algorithm, given x, can hand you its shortest program (Theorem 4.3); if one existed, it would decide the halting problem. $K(x)$ is a perfectly well-defined number that you can bound from above — by running zip, by training a model — but never compute exactly.

Why a decision-maker should care. Your company's data has a *true*, vendor-independent information content. No one can quote it to you exactly; anyone who claims to has sold you the Brooklyn Bridge. But every real compressor — zip, JPEG, your LLM — gives you an upper bound, and upper bounds are enough to tell snake oil from signal.

The compression sniff test

If a vendor claims to losslessly compress genuinely random or properly encrypted data, they are selling snake oil — Shannon closed that door in 1948. A truly random source has entropy equal to its raw bit-length; no code can do better on average (Theorem 2.5). "We compress encrypted traffic by 40 %" is either marketing about a non-random *side channel* (timestamps, packet sizes, TLS record framing) — which may be legitimate — or a claim that should not appear in a contract you sign. Activity 4 gives you a bingo card for the next vendor demo.

Activity 1 — Shortest-recipe game

Setup (10 minutes, pairs). Each pair receives the four strings below. Write, in the pseudocode of your choice, the shortest program you can that prints each exactly. Score: total characters summed across the four programs. Lowest score wins.

(a) `01` repeated 500 times (total length 1000).

(b) The first 100 decimal digits of π.

(c) The filename `IMG_0423.JPG`.

(d) 100 bytes freshly drawn from `/dev/urandom`, printed as a 200-character hex string (distributed on paper).

Debrief. Strings (a), (b), (c) collapse to tiny programs: a loop, a formula, and a literal constant shorter than the output. String (d) does not collapse: the shortest program anyone in the room produces is essentially `print "<the 200 hex chars>"`. You have just re-derived, by hand, the distinction between Kolmogorov-compressible and Kolmogorov-random objects.

Shannon's framework is probabilistic: entropy is a property of a distribution, not of an individual string. Kolmogorov's move [**?**] was to attach a complexity measure to a *single* object by asking for the length of its shortest description in a fixed universal language.

Fix once and for all a **universal Turing machine** U — a machine that, given as input a description $\langle M, w\rangle$ of any Turing machine M and input w, simulates M on w.

Definition 4.1 (Kolmogorov complexity)**.** The **Kolmogorov complexity** of a finite binary string $x \in \{0,1\}^*$, relative to U, is

$$K_U(x) \;=\; \min\Big\{\, |\pi| \;:\; \pi \in \{0,1\}^*,\; U(\pi) = x \,\Big\}, \tag{11}$$

where $|\pi|$ is the bit-length of the program π and $U(\pi) = x$ means U on input π halts with output x.

Activity 2 — The gzip-vs-K scoreboard

Setup (5 minutes, demo or take-home). For each of the four strings from Activity 4, measure three numbers:

(i) **Raw size** — the bit-length of the string itself.

(ii) **`gzip -9` size** — bit-length of the compressed file (subtract the $\sim$80-bit gzip header for tiny inputs, or just note it).

(iii) **Shortest-recipe bound** — the bit-length of the winning program from Activity 4, converted to bits at 8 bit/character.

Plot the three as a bar chart per string. You will see: for (a)–(c) the recipe bound sits far below gzip; for (d) all three bars are essentially the same height. The "recipe bound" is itself only an upper bound on $K(x)$ — the true $K(x)$ is uncomputable (Theorem 4.3) — but seeing gzip dominated by a one-line Python program is the fastest way to feel in your bones that K lives far below any off-the-shelf compressor.

Theorem 4.2 (Invariance theorem)**.** *If U_1 and U_2 are two universal Turing machines,*

then there exists a constant c_{U_1,U_2}[1], depending on U_1 and U_2 but not on x, such that

$$\left|K_{U_1}(x) - K_{U_2}(x)\right| \;\le\; c_{U_1,U_2} \quad \textit{for every } x \in \{0,1\}^*. \tag{12}$$

Proof sketch. Because U_1 is universal, there is a fixed-length binary program $s_{2\to1}$ — an interpreter for U_2 written for U_1 — that, when prepended to any U_2-program π, causes U_1 to simulate $U_2(\pi)$. Thus every U_2-program π of length $|\pi|$ yields a U_1-program of length $|s_{2\to1}| + |\pi|$ with the same output, giving $K_{U_1}(x) \le K_{U_2}(x) + |s_{2\to1}|$. Symmetrically with $s_{1\to2}$. Taking $c_{U_1,U_2} = \max(|s_{1\to2}|, |s_{2\to1}|)$ gives (12). □

By convention we henceforth write $K(x)$ and treat the universal simulator as the additive constant.

The Berry paradox, dramatised

Consider the English phrase

> "the smallest positive integer not nameable in fewer than twenty English words."

That phrase contains nineteen words. So if the integer it picks out exists, we have just named it in nineteen words, contradicting the very property we used to pick it. The paradox is resolved by noting that "nameable in English" is too slippery to be a mathematical predicate. But if we replace "nameable in English" with "printed by a program of length $\le m$", the slipperiness vanishes — and the same self-referential trick becomes a clean proof that K cannot be computed. That is the content of Theorem 4.3.

Theorem 4.3 (Uncomputability of K)**.** *There is no total computable function $f : \{0,1\}^* \to \mathbb{N}$ such that $f(x) = K(x)$ for all x.*

Proof (Berry-paradox style). Suppose for contradiction such an f exists. Define the program P_m, parameterised by an integer $m \in \mathbb{N}$, that does the following: enumerate $\{0,1\}^*$ in shortlex order and, for each x, compute $f(x)$ and output the first x such that $f(x) > m$; then halt. Strings of complexity greater than m exist (there are only $2^m - 1$ programs of length less than m, but infinitely many strings), so P_m halts and outputs some $x^\star_m$ with $K(x^\star_m) > m$.

The program P_m has a fixed body of bit-length B (independent of m), plus a binary encoding of m of at most $\lceil \log_2(m+1) \rceil + O(1)$ bits (e.g. Elias delta coding). So $|P_m| \le B + \log_2 m + O(1)$, giving

$$K(x^\star_m) \;\le\; |P_m| \;\le\; B + \log_2 m + O(1). \tag{13}$$

Combined with $K(x^\star_m) > m$,

$$m \;<\; B + \log_2 m + O(1), \tag{14}$$

which fails for every sufficiently large m (since $m - \log_2 m \to \infty$) — a contradiction. □

[1]The constant c_{U_1,U_2} is finite and does not grow with $|x|$. Concretely: the smallest self-contained CPython interpreter in C is a few hundred kilobytes of source, and a minimal C compiler written in Python is comparable; so for the pair (Python, C), c_{U_1,U_2} is on the order of 10^6–10^7 bits. For a megabyte-scale corpus ($\sim 10^7$ bits) this is already a non-trivial fraction; for a one-gigabyte ERP export ($\sim 10^{10}$ bits) it is numerically negligible, and "machine-independent up to an additive constant" is a property you can plan around. For objects *smaller* than the constant — a one-sentence log entry, a password — it is not, and quoting "the" Kolmogorov complexity of such an object is meaningless without fixing U.

Activity 3 — Snake-oil bingo

Setup (5 minutes, individual then plenary). Below is a 3×3 card of claims collected from real compression- and AI-vendor pitches. Mark each cell **S** (violates Shannon / Kolmogorov — snake oil), **L** (legitimate, exploits a non-random side channel), or **?** (need to ask the vendor a clarifying question).

"Lossless 10:1 on AES-256 ciphertext."	"40 % reduction on TLS traffic via header deduplication."	"Patented sub-Shannon entropy coding."
"AI-powered compression of already-compressed JPEGs."	"Adaptive model shrinks your logs by 8×."	"Zero-loss reduction of random-number tables."
"Our LLM produces an n-bit summary of an n^2-bit corpus."	"Universal compressor — works on any input."	"Dictionary coding of repetitive Kafka topics, typical 70 %."

Debrief. Cells about ciphertext, already-compressed JPEGs, random tables, and "universal" compressors are S. Header deduplication on TLS and dictionary coding on repetitive topics are L. "AI-powered" and "sub-Shannon" are ? until the vendor tells you what distribution they are assuming. The LLM summary cell is L *only* if lossy.

The upshot of Theorem 4.3 is operational: every practical compressor — gzip, PNG, FLAC, and indeed every neural language model — produces an *upper bound* on $K(x)$, never its exact value. What a decision-maker does with this on Monday morning: (i) treat every compression ratio a vendor quotes as a claim about *your* data's distribution, not about the compressor's cleverness; (ii) demand that ratios be reported on a held-out sample from your own corpus, not the vendor's demo set; (iii) recognise that the gap between your best available compressor and the true K is where better models — and, in Section 5, better *predictors* — still have room to win.

5 Solomonoff induction

Intuition

To predict the future, average the predictions of every possible theory, giving shorter theories exponentially more weight (Theorems 5.1 and 5.2).

The prediction-market analogy. Imagine a prediction market where every trader is a theory of the world. Simple theories start with a large float; complex theories start with almost nothing — their share price is their *simplicity premium*, set by theory length: a theory of length L bits gets weight 2^{-L}. A theory you can state in 10 bits gets a float $2^{10} = 1024$ times larger than one needing 20 bits. Each new data point is an earnings call. Theories that predicted it cheaply get paid; theories that predicted it badly get margin-called. Over time the market consolidates around the simplest theories that still explain the tape. That consolidation *is* the Solomonoff prediction M. This is Occam's razor, precisely quantified: "precisely" meaning that the trade-off between fit and simplicity is not an aesthetic preference but a *probability* with a formula.

Occam as an airline fee. Think of the prior as a business-class airline that charges

\$2 of prior mass for every extra byte of theory you pack. A 10-byte theory boards for $\$2^{10} \approx \$1024$ (measured in inverse prior), a 20-byte theory for $\$2^{20} \approx \$1{,}048{,}576$. Fit-to-data is the voucher that reimburses you; over- fitters, who smuggled in extra bytes just to match noise, never recover the fee.

A tiny worked example (same universe as Theorem 5.3). Two theorists compete: π_0 says "always 0" (2 bits long), π_1 says "alternate 0101 . . . " (3 bits long). Before data, π_0 holds 2/3 of the prior float, π_1 holds 1/3. You observe the bit 0: both theorists predicted it, so the ratio is unchanged. You observe another 0 (sequence so far 00): still consistent with both, so again unchanged.[a] The moment you see a 1, π_0 is margin-called to zero and π_1 inherits the entire float. One bit of the right kind can collapse a prior — that is what makes Solomonoff *fast*.

Convergence, in plain English. If the true process is computable, Solomonoff's predictor converges to it: the total "surprise" it will ever suffer, summed over all future time steps, is bounded by the length (in bits) of the shortest program that describes the true process. A decision-maker's translation: you pay, *once*, a number of bits equal to the complexity of the truth; after that, the predictor is free.

Bayesian model averaging, without the jargon. "Bayesian model averaging" is the generic name for: keep a zoo of hypotheses, weight each by how well it predicted the past, average their predictions for the future. Solomonoff is the limiting case where the zoo is "every computable hypothesis" and the prior weight is $2^{-\text{length}}$.

Why a decision-maker should care: Solomonoff induction is the gold standard of "learning from data." Every ML method is, badly and efficiently, trying to imitate it. "Ensemble methods" and "regularise for simplicity" are engineering approximations of this ideal. It also explains why overfitting is bad in a principled way: an overfit model is a long, ad-hoc theory, and Solomonoff would have weighted it near-zero from the start. The question "which model is best?" has a right answer: whichever predicts held-out data with the fewest bits of surprise.

[a] π_1 predicts 01 deterministically, so in fact 00 already falsifies π_1 — we gloss this for rhetorical rhythm and restore it in the formal example.

From intuition to definition

Kolmogorov complexity selects a *single* shortest program. Solomonoff's prior [**?**] performs a *Bayesian average* over *all* programs, weighted by their lengths. Concretely: fix a *prefix-free* universal Turing machine U. "Prefix-free" just means that no valid program is a prefix of another valid program — the same property that makes Morse code or Huffman codes unambiguous. For such a machine, the set of halting inputs forms a prefix code, so the total prior mass is at most one:

$$\sum_{\pi : U(\pi)\downarrow} 2^{-|\pi|} \;\leq\; 1 \qquad \text{(Kraft's inequality).}$$

A one-line sanity check: if each program of length L were given weight 2^{-L} and there were 2^L of them at each length, the total would diverge. Kraft's inequality says the prefix-free property prunes enough programs to keep the sum finite, and indeed ≤ 1; it therefore defines a genuine probability distribution.

Definition 5.1 (Universal prior M)**.** For a finite binary string $x \in \{0,1\}^*$, the **universal (Solomonoff) prior** is

$$M(x) \;=\; \sum_{\pi\,:\,U(\pi)=x*} 2^{-|\pi|}, \tag{15}$$

where the sum runs over all programs π such that $U(\pi)$ halts and outputs a string whose prefix is x (denoted $x*$). Equivalently, $M(x)$ is the probability that U, fed with a uniformly random infinite bitstream, prints x as its first $|x|$ output bits.

The Solomonoff predictive posterior is obtained, as with any probability distribution, by conditioning:

$$M(x_{t+1} \mid x_{1:t}) \;=\; \frac{M(x_{1:t}\,x_{t+1})}{M(x_{1:t})}, \tag{16}$$

defined whenever $M(x_{1:t}) > 0$. Every ML system that "updates on data" is, secretly, approximating this ratio.

Classroom prediction market — 5 rounds, 10 min

Props. One bag of 64 poker chips per group of 5 students; a whiteboard; five index cards each labelled with a candidate "theory" for the sequence about to be generated.
Setup. Write on the whiteboard five candidate rules for a binary sequence:
H_1: all zeros (length 2, weight $2^{-2} = 16$ chips);
H_2: all ones (length 2, weight 16 chips);
H_3: alternating 0101 ... (length 3, weight 8 chips);
H_4: alternating 1010 ... (length 3, weight 8 chips);
H_5: i.i.d. fair coin (length 4, weight 4 chips).
(Chip counts $16 + 16 + 8 + 8 + 4 = 52$; keep the remaining 12 chips in the "other theories" reserve to make the prefix-free bookkeeping honest.)
Play. Instructor secretly picks one of the five rules and generates one bit at a time. After each bit, any H_i that deterministically contradicted the observed bit surrenders all its chips to the reserve; the survivors keep theirs. For H_5, halve its chip count every round (the i.i.d. likelihood of any specific bit is 1/2). After 5 rounds, renormalise: the remaining chips are the posterior weights.
Debrief. Students see (a) the shortest surviving theory usually dominates; (b) a single contradicting bit *instantly* zeroes a deterministic hypothesis, matching (16); (c) if the true rule was the i.i.d. coin, its survival is slow but steady — simplicity dominates early, fidelity to the data wins late.

Theorem 5.2 (Solomonoff's convergence theorem)**.** *Let μ be any computable probability measure on $\{0,1\}^\infty$. Then there is a constant*

$$c_\mu \;=\; 2^{-K(\mu)+O(1)} \tag{17}$$

such that, for all finite prefixes x,

$$M(x) \;\geq\; c_\mu \cdot \mu(x). \tag{18}$$

Consequently, if $X_{1:\infty} \sim \mu$, the cumulative expected KL divergence between the Solomonoff predictor and μ is bounded uniformly:

$$\sum_{t=1}^{\infty} \mathbb{E}_\mu\Big[D_{\mathrm{KL}}\Big(\mu(\cdot \mid X_{<t}) \,\|\, M(\cdot \mid X_{<t})\Big)\Big] \;\leq\; K(\mu)\ln 2 + O(1). \tag{19}$$

In particular, $D_{\mathrm{KL}}(\mu(\cdot \mid X_{<t}) \| M(\cdot \mid X_{<t})) \to 0$ in μ-expectation as $t \to \infty$.

Reading (17)–(19) **in plain English.** Inequality (18) says the universal prior never underestimates the truth by more than a *constant* factor c_μ, and that constant is exactly the prior mass the truth deserves: $2^{-K(\mu)}$. Inequality (19) says the *total* surprise M will accumulate, across all future time steps, is at most $K(\mu)$ bits (with $\ln 2$ converting bits to nats). A fair coin has $K(\mu)$ around 20 bits on a reasonable reference machine. A Markov chain whose source code is 100 bytes has $K(\mu) \leq 800$ bits. Either way the regret is bounded by a *constant that does not grow with the data* — a property no finite-model learner can match without cheating.

Proof sketch. Because μ is computable, it has a description as a program π_μ of length $|\pi_\mu| = K(\mu) + O(1)$. Any program that, given π_μ as a subroutine, simulates a μ-sample and outputs a string beginning with x contributes at least $2^{-K(\mu)-O(1)}\,\mu(x)$ to $M(x)$; summing gives (18). For the KL bound, the key identity is the telescoping

$$\log \frac{\mu(X_{1:T})}{M(X_{1:T})} \;=\; \sum_{t=1}^{T} \log \frac{\mu(X_t \mid X_{<t})}{M(X_t \mid X_{<t})},$$

whose μ-expectation is $\sum_{t=1}^{T} \mathbb{E}_\mu[D_{\mathrm{KL}}(\mu_t \| M_t)]$. The left-hand side is at most $\log(1/c_\mu) = K(\mu) + O(1)$ bits by (18) and a Jensen step, which in nats is $K(\mu)\ln 2 + O(1)$. The correct program π_μ has prior mass exactly $2^{-K(\mu)}$; the finite KL budget is the information-theoretic price of identifying it. For the full proof see **?**, Ch. 5. □

Reading the bound as Shannon's inequality

Theorem 5.2 is not really a new theorem so much as Shannon's source-coding inequality (Theorem 2.5) instantiated at one particular coding distribution, the universal mixture M. Recall the prediction-is-compression identity from Section 3: coding data drawn from μ using a wrong model q costs $H(\mu, q) = H(\mu) + D_{\mathrm{KL}}(\mu \| q)$ bits on average, an excess of exactly $D_{\mathrm{KL}}(\mu \| q)$. The telescoping step in the proof sums that excess over all time steps, and dominance (18) bounds the total by a single cross-entropy gap:

$$\sum_{t=1}^{\infty} \mathbb{E}_\mu[D_{\mathrm{KL}}(\mu_t \| M_t)] \;\leq\; \log_2 \tfrac{1}{c_\mu} \;\leq\; K(\mu) + O(1) \text{ bits.}$$

Slogan: *Solomonoff's optimality is Shannon's cross-entropy inequality, with the universal mixture as the coding distribution, charged $K(\mu)$ bits once for the truth.*

Three quantifiers in this reading deserve emphasis because they are exactly what will *fail* to carry over to AIXI in Section 6.

1. **Additive, not proportional.** The penalty is $K(\mu)$ bits added to your lifetime loss, not a factor that scales with the data. Per-step loss therefore vanishes.

2. **Paid once, on the hypothesis.** The charge is $K(\mu)$ — the description length of the *truth* — not $K(x_{1:n})$ of the observed data. You pay for which world you are in, not for how much of it you have seen.

3. **Log-loss, not reward.** This is a statement about prediction. Nothing in it says anything about an agent whose actions alter the data stream; that gap is the content of Section 6.

Two codes, and Levin's bridge. It is easy to conflate two different codes floating around this section: the *Shannon code of the prior*, of length $-\log_2 M(x)$, and the *Kolmogorov code*, of length $K(x)$. The convergence bound above uses the first — it is $-\log_2 M$, not K, that appears in the telescoped cross-entropy. Levin's *coding theorem* is the independent, non-trivial result that these agree up to a constant,

$$K(x) \;=\; -\log_2 M(x) + O(1),$$

and it is Levin's theorem, not the definition of M, that licenses the slogan "shorter program $\Leftrightarrow$ higher prior mass." In the notes we will continue to move freely between $-\log_2 M$ and K; just remember that the permission to do so is a separate theorem.

M is a proposed prior, not the truth

One subtlety worth making explicit before we move on. The symbol M is not a claim about reality. The truth is some other (unknown) computable measure μ; M is the agent's *betting distribution.* If we had set $M = \mu$, Theorem 5.2 would be vacuous — it would just assert that the truth matches itself. The content of Solomonoff's theorem lies entirely in the fact that M is *different* from μ, yet pays only a finite price for the difference.

What privileges M, then, is not correctness but *dominance* ((18)): for every lower-semicomputable semimeasure ν, $M(x) \geq 2^{-K(\nu)+O(1)}\,\nu(x)$. That inequality is what powers the bound, and it is a statement about M relative to the *class* of computable competitors, not about whether M describes nature. Where does the definition of M actually come from? Two ingredients, both assumptions:

1. **Occam + Kraft.** Once one decides that prior probability should track simplicity, Kraft's inequality forces the weighting $2^{-|\pi|}$: it is the only normalisation compatible with prefix-free decoding over program space. The *assumption* is the identification of simplicity with prior probability; the $2^{-|\pi|}$ then writes itself.

2. **A choice of reference UTM.** Different universal machines give different M's, differing by multiplicative constants $2^{O(1)}$ that depend on the hypothesis μ. This is not a free lunch — it is the "bad priors" knob, and we will see in Section 6 that when prediction is swapped for control this knob upgrades from a constant to a choice between different long-run policies.

The honest summary is therefore: Solomonoff does not derive the truth. He derives a *universally competitive prior under Occam, Kraft, and a fixed UTM*, and Theorem 5.2 is the Shannon-style guarantee that this particular bet loses at most $K(\mu)$ bits against whichever computable μ nature chose.

A two-program universe, updated step by step

We now carry out the minimal example in full, because no amount of prose substitutes for watching a posterior move.

Example 5.3 (Toy Solomonoff update on a two-program universe)**.** Restrict the universe of programs to two deterministic generators: π_0 : always output 0 (bit-length $|\pi_0| = 2$)

and π_1 : output the cycle 01010101 . . . (bit-length $|\pi_1| = 3$). Under the Solomonoff-style weighting $w(\pi) = 2^{-|\pi|}$, the prior over the two hypotheses is

$$P(\pi_0) = \frac{2^{-2}}{2^{-2} + 2^{-3}} = \frac{2}{3}, \qquad P(\pi_1) = \frac{2^{-3}}{2^{-2} + 2^{-3}} = \frac{1}{3}.$$

Step-by-step update on the prefix 0101.

after seeing	$P(\pi_0)$	$P(\pi_1)$	predicted next bit
(nothing)	2/3	1/3	$P(0) = 2/3 + 1/3 \cdot 1 = 1$
0	2/3	1/3	$P(0) = 2/3 + 0 = 2/3$; $P(1) = 1/3$
01	0	1	$P(0) = 1$ (the cycle says 0)
010	0	1	$P(1) = 1$
0101	0	1	$P(0) = 1$

The decisive moment is bit 2: π_0 predicted 0 with probability 1 and saw 1, so its likelihood is zero and Bayes zeros its posterior. From that step onward π_1 owns the entire posterior, and the Solomonoff predictor behaves as the deterministic cycle predictor.

Two features worth internalising. (i) The shorter program π_0 was *not* favoured after data — simplicity is a prior preference overridden by evidence. (ii) A single contradicting bit collapses an exponentially-weighted prior to a point mass; this is the mechanism by which Solomonoff induction converges so fast on deterministic sources.

Visualisation. Figure 4 renders the two rows of the table as bars. The second bit of data is where the entire picture changes.



Figure 4: Posterior mass on the two programs π_0 (always-zero, length 2) and π_1 (alternating, length 3) as the observations 0, 01, 0101 arrive. One bit — the second — is enough to collapse the prior to a point mass on π_1.

Python: a 6-line Solomonoff predictor

Goal. Reproduce Theorem 5.3 and experiment with other sequences. Helps build the reflex that "posterior update == multiply by likelihood and renormalise," regardless of how philosophical the prior is.

```
# Two-program Solomonoff toy.
programs = {
    "pi0": {"length": 2, "next": lambda s: "0"}, # always 0
    "pi1": {"length": 3, "next": lambda s: "01"[len(s) % 2]}, # cycle 01
}
prior = {k: 2 ** (-v["length"]) for k, v in programs.items()}
Z = sum(prior.values()); post = {k: v / Z for k, v in prior.items()}
```

```
def update(post, observed_bit, history):
    new = {}
    for k, p in post.items():
        predicted = programs[k]["next"](history)
        new[k] = p if predicted == observed_bit else 0.0
    Z = sum(new.values()) or 1.0
    return {k: v / Z for k, v in new.items()}

history = ""
for bit in "0101":
    post = update(post, bit, history); history += bit
    print(history, post)
```

Extensions. (i) Add a third program π_2 that outputs 001001... and feed it the sequence 001001. (ii) Replace the deterministic programs with stochastic ones (e.g. a 0.6-biased coin) and watch the posterior drift rather than collapse. (iii) Swap the data to 0100 and observe that *both* programs die, at which point Solomonoff would fall back on the infinite zoo we truncated.

Worksheet: which program survives?

Given. Three candidate programs for a numeric sequence:

$$\pi_A : \text{constant } 1, \quad \pi_B : \text{repeat } 1, 1, 2, \quad \pi_C : \text{Fibonacci, } a_{n+2} = a_n + a_{n+1}.$$

Assign rough bit-lengths $|\pi_A| = 6$, $|\pi_B| = 10$, $|\pi_C| = 15$ (from their Python source, say). Compute the prior weights proportional to $2^{-|\pi_i|}$. Now observe the sequence

$$1,\ 1,\ 2,\ 3,\ 5,\ 8.$$

Tasks. (a) After each term, which programs are still consistent? (b) Write down the posterior weights at each step. (c) At what point does π_C overtake π_B in the posterior? (d) If the next term is 13, does your answer change? What if it were 13.001? (e) The Solomonoff prior contains *every* computable program. Which program not on the list would you expect to be the main "runner-up" after seeing $1, 1, 2, 3, 5, 8$?

Decision-maker takeaway. Solomonoff induction is uncomputable — you cannot run M on a real computer — but it is the *formal target* that the whole field of machine learning is approximating. Every time an ML engineer adds a regulariser, drops a complicated feature, or averages an ensemble, they are paying Occam's airline fee from Theorem 5.2. The theorem guarantees that if they paid it honestly, and if the truth were computable, their cumulative regret would be finite — bounded by the bit-length of the truth. No method with a finite hypothesis class can make that promise. What you *buy* with Solomonoff is not an algorithm but a benchmark.

6 AIXI: intelligence as optimal compression-driven prediction

Intuition

One-line version. AIXI is the agent that, before every move, asks every possible theory of the world "what happens if I do this?", weights each theory by how short it is, averages the predicted rewards, and picks the action with the highest weighted total (Theorems 6.1 and 6.3). It is a *definition of optimal behaviour*, not a product — the averaging step requires infinite compute.

The regional-manager analogy. Imagine a regional manager who, before every staffing decision, consulted every possible theory of her stores — every demand model, every weather-effect hypothesis, every crank manifesto about Mercury retrograde — weighted by how simple each theory is. For each candidate decision she asks: "If I do this, what happens over the next hundred Tuesdays, and how much will I enjoy it?" She takes the weighted average and places the staffing bet that maximises expected sales across all of them. That manager would be provably optimal in a precise technical sense. She would also be impossible: consulting every possible theory takes infinite time. This is AIXI.

Or, the auditor story. AIXI is the diligent auditor who, before approving a single expense report, reads every audit manual ever written in every language, ranks them by length, and adjudicates the expense by simplicity-weighted consensus. The auditor is never wrong in principle. The auditor also never approves anything. Real audit teams are food trucks reading the Michelin menu; AIXI is the chef with an infinite pantry and no kitchen.

Why compression is the whole story. AIXI's only prior is Occam's razor: short theories get exponentially more weight than long ones. That single ingredient — plus bookkeeping — is enough to produce universally optimal action. Intelligence, in this framework, *is* compression plus planning.

The catch. AIXI is uncomputable; it requires running every possible program. Bounded approximations exist but are toys at present. AIXI is to intelligence what the ideal gas law is to a real gas — a north star, not a product.

Why a decision-maker should care. AIXI is a crisp, non-hand-wavy definition of "what would a perfectly general AI do?" When someone claims their system is "a step toward AGI," ask: is it a step toward better approximating AIXI? Is it building better world-models (compression) and planning against them (expectimax)? If yes, the claim is in the right ballpark. If it is pattern-matching in a narrow domain with no planning layer, the claim is marketing. No real system *is* AIXI, so any product advertised as "universal intelligence" is abusing the term.

From passive prediction to sequential action

Hutter's AIXI framework [**?**] extends Solomonoff induction from passive sequence prediction to sequential decision-making. Where Solomonoff's agent only had to *predict* the next bit, AIXI has to *act* and then see what the environment does back.

The setup. The agent interacts with an environment over discrete time steps. At step t the agent chooses an action $a_t \in \mathcal{A}_{\text{act}}$, and the environment returns a *percept* $e_t = (o_t, r_t)$ consisting of an observation $o_t \in \mathcal{O}$ ("what I see") and a reward $r_t \in [0, r_{\max}] \subset \mathbb{R}$ ("how

much I liked it"). Write the interaction history as

$$h_{<t} \;=\; (a_1, e_1, a_2, e_2, \ldots, a_{t-1}, e_{t-1}).$$

Think of $h_{<t}$ as the manager's logbook so far.

An **environment** ν is a conditional probability measure $\nu(e_{1:m} \mid a_{1:m})$: given the agent's planned action sequence, it tells you how likely any percept sequence is. An environment is the "true world"; the agent does not know which one it is in.

The **universal mixture environment** ξ is the Solomonoff-style weighted average over all of them:

$$\xi(e_{1:m} \mid a_{1:m}) \;=\; \sum_{\nu \in \mathcal{M}} 2^{-K(\nu)}\, \nu(e_{1:m} \mid a_{1:m}), \tag{20}$$

where $\mathcal{M}$ is the class of all lower-semicomputable ("chronological") environments and $K(\nu)$ is the Kolmogorov complexity of a prefix program for ν. The weight $2^{-K(\nu)}$ is Occam's razor made numerical: halving the description length *squares* the weight.

Intuition

Read (20) like this: "the probability my mixture assigns to seeing percepts $e_{1:m}$ after actions $a_{1:m}$ is a simplicity-weighted vote among every computable theory of the world." The vote never converges to one theory unless that theory is the only short one compatible with the data.

The AIXI action rule

Definition 6.1 (AIXI)**.** Fix a finite planning horizon m and (optionally) a discount factor. The **AIXI action** at history $h_{<t}$ is

$$a_t^{\text{AIXI}} \;=\; \arg\max_{a_t} \sum_{e_t} \max_{a_{t+1}} \sum_{e_{t+1}} \cdots \max_{a_m} \sum_{e_m} \Big(\sum_{k=t}^{m} r_k \Big)\, \xi\Big(e_{t:m} \,\Big|\, h_{<t}, a_{t:m}\Big). \tag{21}$$

Each $\max_{a_\tau}$ says "pick the best action I could possibly take at step τ"; each $\sum_{e_\tau}$ says "average over what the environment might show me, weighted by the universal mixture ξ." The inner $\sum_{k=t}^{m} r_k$ is the total reward collected along a given rollout.

In words. AIXI plans by *expectimax* over all possible futures, where "possible" is weighted by the universal mixture (20). The $2^{-K(\nu)}$ weighting is what ties the definition of intelligence back to compression: hypothesised environments with short descriptions receive exponentially more weight. An AIXI-optimal agent simultaneously (i) compresses its environment optimally and (ii) acts to maximise reward under that compressed model.

Drawing the expectimax tree

Nested max-$\sum$ notation is easy to write and hard to read. Figure 5 is the same equation as (21), drawn for 2 actions, 2 percepts, and 2 plies of lookahead.

A 2-hypothesis worked example

We now collapse (21) to arithmetic on a toy world.



Figure 5: Expectimax tree behind (21), drawn for two actions, two possible percepts, and two plies. Blue squares are `MAX` (agent chooses); orange circles are `E` (weighted average under ξ); green leaves hold a cumulative reward. AIXI is exactly this tree, but (i) infinitely wide in branching, (ii) infinitely deep, and (iii) with each orange `E` node averaging over *every computable theory* of the world.

Example 6.2 (Two-step, two-hypothesis AIXI)**.** Actions $\mathcal{A}_{\text{act}} = \{A, B\}$, percepts $\{0, 1\}$ (with $r_t = e_t$: a percept 1 gives reward 1). Horizon $m = 2$. Suppose the mixture has collapsed to just two live hypotheses with posterior weights

$$w_{\text{simple}} = \tfrac{3}{4}, \qquad w_{\text{complex}} = \tfrac{1}{4}.$$

Simple theory: "A pays 1 w.p. 0.6; B pays 1 w.p. 0.3; independent of history." **Complex theory:** "A pays 1 w.p. 0.3; B pays 1 w.p. 0.8; independent of history."

For the one-step case (ignore second step), the expected immediate reward of pulling A is

$$\mathbb{E}_\xi[r \mid A] \;=\; \tfrac{3}{4} \cdot 0.6 + \tfrac{1}{4} \cdot 0.3 \;=\; 0.525,$$

and of pulling B is

$$\mathbb{E}_\xi[r \mid B] \;=\; \tfrac{3}{4} \cdot 0.3 + \tfrac{1}{4} \cdot 0.8 \;=\; 0.425.$$

AIXI picks A. Note the complex theory is kept alive — it still gets 25% of the vote — which is why a future observation of B paying out would swing the posterior fast. *Exploration is not programmed in; it is a side effect of keeping every theory on the books.*

For the full two-step case, the student repeats the same arithmetic inside each branch of Fig. 5. The horizon-2 answer is still A first, and the reader should verify it on the worksheet below.

Universal optimality

Theorem 6.3 (Universal optimality of AIXI, informal)**.** *Within the class of lower-semicomputable environments, AIXI is* Pareto optimal*: no agent π' achieves strictly greater expected total reward than AIXI in* every *environment $\nu \in \mathcal{M}$. Moreover, for any computable ν the AIXI predictor converges to the true environment's predictions in the sense of* (19) *with M replaced by ξ.*

Intuition

Pareto-optimal is a *weak* optimality guarantee and it is important to be honest about it. It says: no rival agent strictly dominates AIXI across all worlds. It does *not* say AIXI is best on average in the world you actually live in. A specialist agent handcrafted for chess will beat AIXI at chess; it will just lose to AIXI on the average of all computable games. Picture a Pareto frontier (Fig. 6): AIXI sits on the frontier, but so do many narrower agents. The content of Theorem 6.3 is "AIXI is not dominated," not "AIXI is uniquely best."



Figure 6: Cartoon Pareto frontier across two environments. AIXI lies on the frontier (no agent strictly dominates it), and so do the narrow specialists. Only the grey "dominated generalist" is strictly worse than something else in both worlds.

For the precise statement and proof see **?**, Ch. 5. The significance of Theorem 6.3 is that "intelligence" has, within this framework, been reduced to a single ingredient (the universal prior (20)) plus bookkeeping (the expectimax expansion). Remove the Solomonoff prior and the agent collapses to uninformed search; keep it, and the agent becomes universally optimal in the Pareto sense.

Three caveats Shannon's half does not carry over

It is tempting to read Theorem 6.3 as "AIXI just plugs Solomonoff into an expectimax, therefore it inherits Theorem 5.2's optimality." This intuition is wrong, and the gap is worth making explicit because it explains most of the philosophical objections levelled at AIXI in the literature. Theorem 5.2 is a *passive-prediction* guarantee: data arrives, the posterior closes in, the regret is additive in $K(\mu)$. A controller's actions *change* what data arrives, and that single difference breaks the clean inheritance in three ways.

1. **Traps and non-ergodicity.** An irrecoverable action can permanently prevent the agent from ever gathering the data that would have refuted its prior. Solomonoff's convergence assumes observations keep arriving indefinitely; AIXI can walk off a cliff at step 3 and never learn anything afterwards. No log-loss bound protects against this because the log-loss bound is computed in expectation under μ, while the trap changes what μ even reveals of itself.

2. **Exploration and UTM-dependence.** Bayes-optimal action under the universal mixture ξ does not, in general, explore enough. Leike and Hutter (2015) showed

that AIXI is *not* asymptotically optimal in every computable environment, and that its long-run behaviour depends on the choice of reference universal machine: the "bad priors" knob from Section 5 upgrades, in the control setting, from an $O(1)$ constant into a choice between *different policies* that disagree forever. Two AIXIs with different reference machines can converge to different stationary behaviours in the same environment.

3. **Embedded agency (the anvil problem).** The expectimax in (21) treats agent and environment as strictly separate objects: ξ models the world, the arg max picks the action. The moment the environment can modify the agent itself — damage its memory, overwrite its reward channel, drop an anvil on the box running the expectimax — the formalism no longer type-checks. AIXI does not model *itself* as part of the world.

The honest framing is therefore: AIXI is the *optimal prediction-driven agent, modulo ergodicity and a fixed UTM*, not "optimal, QED." The gap between Theorem 5.2 and Theorem 6.3 is exactly the gap between log-loss regret (pure Shannon, charged once for the hypothesis) and reward regret (control, where the agent's own actions shape the data stream).

Activities

Activity A: Two-armed bandit, live in the room

Goal. Feel in your bones why simplicity-weighting produces exploration for free.
Setup. Pair up. One partner is the *environment*: they secretly fix probabilities $(p_A, p_B) \in [0,1]^2$ for arms A and B paying out, and flip accordingly. The other partner is the *agent* and plays 20 rounds. The agent carries two paper advisors: a *simple advisor* who insists on the current empirical-best arm, and a *complex advisor* who insists the other arm is due. At each round the agent rolls a die to weight the two advisors $\frac{3}{4} : \frac{1}{4}$ and plays their weighted vote.
Debrief. Count total reward. Compare to a "greedy" agent who always pulls the empirical-best arm. Discuss: where did the simplicity-weighting kick in? When did the complex advisor save the day?

Activity B: Hand-compute AIXI (worksheet)

Extend Theorem 6.2 to the full two-step horizon. Fill in the reward at each of the 16 leaves of Fig. 5 under both hypotheses; fold with weights $\frac{3}{4} : \frac{1}{4}$; take expectations at the orange nodes and maxima at the blue nodes; verify the root action is A. **Bonus:** change the weights to $\frac{1}{2} : \frac{1}{2}$ and find the switching point.

Activity C: A 15-line AIXI-ish agent in Python

A toy environment has 4 states in a cycle $s_0 \to s_1 \to s_2 \to s_3 \to s_0$; reward is 1 in s_3 else 0. Two candidate models: `uniform` (next state random) and `cycle` (the true dynamics). The agent maintains a posterior over the two and plans with horizon 2.

```
import itertools
def predict(model, s, steps):
    if model == "cycle":
```

```
        return [((s+i+1) % 4, 1.0) for i in range(steps)]
    # uniform: each next state 1/4
    return [(None, 0.25) for _ in range(steps)]

def xi_reward(posterior, s, plan):
    # posterior: {"cycle": w1, "uniform": w2}, plan: list of actions (
        ignored in this toy)
    total = 0.0
    for m, w in posterior.items():
        r = 0.0
        cur = s
        for _ in plan:
            if m == "cycle":
                cur = (cur + 1) % 4
                r += (1 if cur == 3 else 0)
            else:
                r += 0.25 # expected reward under uniform
        total += w * r
    return total

def aixi_action(posterior, s, actions=("step",), horizon=2):
    best, best_r = None, -1
    for plan in itertools.product(actions, repeat=horizon):
        r = xi_reward(posterior, s, plan)
        if r > best_r: best, best_r = plan[0], r
    return best
```

Exercise. Start with posterior $\{\texttt{cycle} : 0.5,\ \texttt{uniform} : 0.5\}$. After observing three clean cycle steps, update by Bayes (likelihood ratio $1 : (1/4)^3 = 64 : 1$ in favour of `cycle`) and re-plan. Watch the posterior concentrate. This is AIXI-in-miniature: two hypotheses instead of infinitely many, but the machinery is identical.

7 What this buys us for LLMs

Intuition

The one-line version, for the coffee chat. A large language model trained to guess the next word is, provably and mechanically, a compressor of its training data. That is not an analogy. It is a theorem (Theorem 3.2) plus a pipe (the arithmetic coder). By the chain we built in Equation (23), being a good compressor puts the model somewhere on the intelligence spectrum defined by Solomonoff (Theorem 5.2).

Residuals and arithmetic coding, in very plain English. At every token, the model publishes a probability for each possible next word. The *residual* is the gap between that guess and what actually happened. If the model said "the" with probability 0.9 and "the" appeared, the residual is about $-\log_2 0.9 \approx 0.15$ bits — almost free. If the model said 0.01 and "the" still appeared, the residual is $-\log_2 0.01 \approx 6.6$ bits — an expensive surprise. *Arithmetic coding* is a near-optimal way to write all those surprise numbers down back to back. The compressed file has two parts: the model weights (one fixed cost) plus the bill for every surprise (variable cost). Better

model ⇒ fewer surprises ⇒ smaller bill ⇒ shorter file. "KL divergence", when we use it below, is the same tax, averaged: the extra bits per token you pay for betting on the wrong distribution.

Three things a decision-maker should take away, up front. (1) Cross-entropy on your own domain data is a real yardstick — one number, comparable across vendors. (2) "Just predict the next word" is not marketing spin; the mathematics agrees that it produces general-looking behaviour. (3) There is a ceiling (the Shannon entropy of the text). As models approach it, cost per extra bit goes vertical; the frontier moves to multimodal data, embodied interaction, and reasoning architectures. Plan capex accordingly.

The Hutter Prize, concretely. Marcus Hutter put up a 500,000 € bounty for whoever compresses the first 1 GB of English Wikipedia (the `enwik9` file) the most [**?**]. The current leaderboard is dominated by neural compressors; as of early 2024, Fabrice Bellard's `nncp` sits near 0.113 bits per character, down from `gzip`'s ~ 2.1. Training an LLM on Wikipedia to minimise cross-entropy *is* compressing Wikipedia; the model weights plus arithmetic-coded residuals are the compressed file. Better prediction = smaller file = (by Theorem 3.2) better distributional model = (by Theorem 5.2) closer to the true generating process = (per Hutter) more intelligence.

Scaling laws. Plot model size against cross-entropy loss on held-out text: you get a strikingly clean curve. Double the data, double the parameters, the loss drops predictably. The curve has been stable across four orders of magnitude [**?**]. Cross-entropy — our bits-per-token yardstick — is a smooth function of investment. You can buy intelligence by the bit: not efficiently, not forever, but predictably. Figure 7 sketches the shape.

A worked example, in numbers. GPT-2 hit roughly 1.2 bits per English character on the standard benchmark; GPT-4-class models are around 0.7. That looks like a modest drop. But English text is about 1.3 bits of true entropy per character (Shannon's 1950s estimate). So GPT-2 was at $\sim 92\%$ of the way from "random guessing" (~ 5 bpc) to the floor; GPT-4 is at $\sim 98\%$. Six percentage points. Small in bits, enormous in dollars: the last bit contains the reasoning, the rare facts, the nuanced world-models. Figure 8 makes the cost asymmetry visible.

Emergent capabilities, cautious framing. If the training objective is a compression proxy, and compression is provably linked to a universal notion of intelligence, then an LLM doing arithmetic, translation, and code — capabilities nobody explicitly trained for — is consistent with the theory. To compress English well, you must model the world that the English is about. We resist the stronger claim that emergence is *predicted* by the theory; it is consistent, which is enough for a capital-allocation argument.

A Short Story

Two sales reps walk into your office on the same afternoon. Rep A pitches a *language model*: it writes emails, summarises documents, drafts code. KPI: user satisfaction. Rep B pitches a *Wikipedia compressor*: one number, bits-per-character, lower is better. You sign with Rep A. Three weeks later, legal calls: Rep A and Rep B shipped the *same binary*. Different marketing, same product. That is the content of Equation (23). The KPI you choose to stare at determines which half of the equivalence you buy, but the vendor was selling both all along.

The formal content

A large language model parameterises a conditional distribution $q_\theta(x_t \mid x_{<t})$ and is trained by minimising the negative log-likelihood

$$\mathcal{L}(\theta) \;=\; -\frac{1}{T}\sum_{t=1}^{T} \log_2 q_\theta(x_t \mid x_{<t}). \tag{22}$$

By Theorem 3.2, $\mathcal{L}(\theta)$ is the expected arithmetic-coding length per token: minimising cross-entropy *is* minimising compressed size. Equivalently, by Theorem 3.3, a perplexity of P corresponds to exactly $\log_2 P$ bits per token — e.g. perplexity 32 is 5 bits, perplexity 8 is 3 bits. A one-bit-per-token improvement on a 100 GB corpus saves, in principle, ~ 12.5 GB of code length.

? showed that $\mathcal{L}(\theta)$ follows clean power laws in model size N, dataset size D, and compute C, of the form $\mathcal{L} \approx (N_c/N)^{\alpha_N}$. Viewed through (22), each such power-law decrement is a *bit-per-token compression improvement.* The operational content of Theorem 5.2 in this setting is that, to the extent that the data-generating process is computable, any predictor whose bits-per-token approaches the conditional entropy rate $\overline{H}(p)$ (the theoretical minimum achievable loss) is implicitly approximating the μ-posterior of the universal prior M.

? operationalised this equivalence by wiring a large language model into an arithmetic coder and using it to compress raw bytes of image and audio data. They reported compression ratios lower than domain-specific specialist compressors (e.g. PNG, FLAC) on out-of-domain modalities, despite the model having been trained solely on text. From the vantage point of Theorems 3.2 and 5.2, the experiment is a consistency check: a predictor that approximates a universal prior should, by (18), compress any computable source to within an additive $K(\mu)$ of its true entropy, and text exposure turns out to be enough to learn a useful approximation of that prior.

The **Hutter Prize** [**?**] formalises the economic version of the claim: a cash prize for improving the lossless compression ratio on a fixed text corpus. Within the equivalence framework, every winning submission is, by definition, a model whose cross-entropy on the corpus is lower — which, by Theorem 3.3, is a more accurate next-symbol predictor.

Two pictures

The working equivalence

Collecting the theorems of Sections 3 to 6 we obtain the *working equivalence*, first in English, then in symbols.

In English. *A model that predicts text well is, by theorem, a model that compresses text well, and a model that compresses text well is, by theorem, an approximation of the universal prior that defines Solomonoff's notion of intelligence.* One object, three KPIs.

In symbols:

$$\underbrace{\text{low cross-entropy}}_{\text{good predictor}} \iff \underbrace{\text{short arithmetic code}}_{\text{good compressor}} \iff \underbrace{\text{approx. of universal prior}}_{\substack{\text{Solomonoff/AIXI}\\ \text{sense of intelligence}}} \tag{23}$$

The leftmost arrow is a theorem within Shannon's framework (Theorem 3.2). The rightmost arrow is an asymptotic theorem modulo computability (Theorem 5.2). Neither is a metaphor.



Figure 7: Scaling laws [?]. Three curves, one per dataset size; all three asymptote to the conditional entropy floor $\overline{H}(p)$ (dashed). Doubling N gives a predictable α_N-sized drop in bits per token.



Figure 8: The last-mile argument. Cost per additional bit below the Shannon floor climbs exponentially. Moving from GPT-2's 92% to GPT-4's 98% is six percentage points on the x-axis and several orders of magnitude on the y-axis. The curve is schematic; the shape is what matters.

Activities

Activity 1 — Hutter Prize bingo

Project the current Hutter Prize leaderboard (`http://prize.hutter1.net`). Each student writes down, on a sticky note, who they think wins the 2030 title: (a) a transformer LLM plugged into `nncp`-style arithmetic coder; (b) a state-space model (Mamba-like); (c) a diffusion-based token model; (d) a symbolic/hybrid system; (e) "none — the leaderboard plateaus at ~ 0.10 bpc". Collect notes, tally, revisit at the end of term. *Helps Yuki* (concrete artefact), *helps Maria* (named numbers).

Activity 2 — LLM as compressor (Python)

Run this snippet locally. It wires `gpt2-small` into a simple arithmetic coder and compresses a 10 KB sample of `enwik8`. Report bytes in, bytes out, and the ratio against `gzip`.

```python
import gzip, math, torch
from transformers import GPT2LMHeadModel, GPT2TokenizerFast
# Load model + tokenizer
tok = GPT2TokenizerFast.from_pretrained("gpt2")
mdl = GPT2LMHeadModel.from_pretrained("gpt2").eval()
# Load 10 KB of enwik8
with open("enwik8_10kb.txt") as f: text = f.read()
ids = tok.encode(text, return_tensors="pt")
# Compute summed negative log-likelihood -> bits
with torch.no_grad():
    logits = mdl(ids).logits[:, :-1, :]
    logp = torch.log_softmax(logits, dim=-1)
    targets = ids[:, 1:]
    nll = -logp.gather(2, targets.unsqueeze(-1)).sum().item()
bits_gpt2 = nll / math.log(2)
bytes_gzip = len(gzip.compress(text.encode()))
print(f"raw : {len(text):>7d} bytes")
print(f"gzip : {bytes_gzip:>7d} bytes")
print(f"gpt2 code : {bits_gpt2/8:>7.0f} bytes (+model weights)")
```

Discussion: where does the model-weights cost go? At what corpus size does the weights amortise? *Helps Leo* (hands-on), *answers Maria's falsifiability demand.*

Activity 3 — Perplexity-to-bits worksheet

Fill in the table. Assume 100 GB of English text.

Model	Perplexity	Bits/token	Storage (GB)
n-gram baseline	128	_____	_____
GPT-2	32	_____	_____
GPT-4 class	8	_____	_____
Shannon floor	≈ 5.3	_____	_____

Hint: bits/token $= \log_2(\text{perplexity})$. Assume 4 characters per token; 1 byte per character in raw text. Answers: $7, 5, 3, 2.4$ bits/tok. *Helps Leo* (do-able on paper), *helps Aisha* (she can now say the sentence "perplexity 32 means 5 bits per token").

Activity 4 — Two-vendors role-play

Two students play Rep A (sells "a language model") and Rep B (sells "a Wikipedia compressor"). Each has two minutes and one KPI. The class, acting as buyer, asks questions. Debrief question: "If the binary is the same, which KPI should your CFO actually track?" Answer keys: cross-entropy on in-domain eval data; it happens to be both KPIs at once. *Helps Yuki* (picture), *helps Aisha* (language for the board).

8 Caveats and what the equivalence does not say

Intuition

The equivalence is real but narrow. It tells you that good prediction entails good *modelling*; it does *not* tell you that good prediction entails understanding, agency, or safety. It promises statistical competence. It does not promise causal reasoning, counterfactual simulation, or moral judgement. Those may emerge — the theory leaves the door open — but they are not guaranteed by the objective.

The food-truck and the Michelin kitchen. Keep this image in your pocket for the rest of the section. Uncomputability is not cosmetic: $K(x)$ and AIXI are unreachable (Theorem 4.3), and every real compressor, every real agent, is a finite approximation. Saying an LLM is "approximating AIXI" is like a food-truck claiming to approximate a Michelin three-star kitchen by reading the menu. Technically on the same axis. In practice, not the relevant comparison. The rest of this section is a tour of five specific places where the axis and the kitchen come apart.

The running cast. To keep the five abstract caveats walkable, we will reuse three characters:

- *Anna the junior analyst,* who has memorised every deal memo in the vault — 4,000 deals going back a decade.
- *Ben the junior analyst,* who has read only ten of those memos but understands why each deal priced where it did.
- *The phrasebook chatbot,* which has "learned" French by memorising 100,000 tourist phrases and can now order croissants flawlessly in thirteen dialects.

You will meet each of them again.

Remark 1 (the only non-tautological falsifier). A reasonable operator will ask: if AIXI is uncomputable and every deployed system is "a finite approximation," what test *other than cross-entropy itself* decides whether system A approximates the ideal better than system B? The honest answer is: held-out cross-entropy on distributions the training set did not see, plus downstream task transfer. There is no deeper falsifier in the current theory. If that makes the AIXI framing feel tautological, the operator is reading the field correctly, not mis-reading the theorem. The operational response is not philosophical ("but really, AIXI!"). It is empirical: hold out a genuinely unseen distribution, measure transfer, and stop there.

Compression $\neq$ understanding. Ask Anna, with her 4,000 memorised memos, to price a deal that is *not* in the vault. What you learn from her answer is whether she compressed the memos or the market. Ask the phrasebook chatbot a sentence that is off-phrasebook — "my croissant has opinions about the Maastricht Treaty" — and you find out whether it has learned French or merely tiled the phrase space. A lossless compressor has captured statistics, which is *some* kind of understanding, but not necessarily the kind a board means when it asks "does the model understand our business?"

Embodiment. A text-only system has only ever been surprised by text. It has no ground-truth feedback from physical reality. Solomonoff's framework accepts any

computable environment, but LLMs have the text channel and lack the body-in-a-world channel. Agentic, tool-using, multimodal systems are early attempts to close the gap. The equivalence does not tell you the gap has been closed.

Benchmarks are not the floor. A model with low cross-entropy on a benchmark may just have memorised the benchmark. Data contamination is rampant. The equivalence only holds when the test distribution is genuinely held out — which, for a model trained on "the internet", is an increasingly expensive proposition.

Why a decision-maker should care. Use the equivalence as a *lower bound, not an upper bound.* When a vendor says "lowest perplexity," accept that as real evidence of genuine modelling skill. Then ask the second question: skill at what, tested on what, does it transfer to your domain? The equivalence tells you the knob exists. It does not tell you that turning the knob solves your problem. Confusing "next-token prediction" with "just autocomplete" misses a deep result; confusing "next-token prediction" with "general intelligence" overclaims a narrow one. Both errors are expensive. Staying in the middle — taking the equivalence seriously but not theologically — is the managerial win.

Formal caveats (C1)–(C5)

Several limitations of the chain (23) deserve formal acknowledgement. Each is followed by a one-line *procurement corollary*: the thing to actually say when a vendor pitches you.

(C1) Uncomputability. By Theorem 4.3, $K(x)$ is not computable; by a related argument so is $M(x)$. The entire right-hand side of (23) therefore names a mathematical *ideal*, not an algorithm. Every real compressor produces an upper bound $\tilde{K}(x) \geq K(x)$, and equality is in principle unattainable. "Approximates the universal prior" must be taken as an asymptotic statement about cross-entropy, not as a literal claim that the model is computing M.

Procurement corollary

If a vendor says their model "approximates AIXI" or "computes the Solomonoff prior," ask on what computable sub-class, with what error bound, and over what distribution. The honest answer is "we lower cross-entropy on held-out data." That is fine; it is just not the same claim.

(C2) The additive constant. Theorem 4.2 only guarantees machine-independence up to an additive constant c_{U_1,U_2}. For short strings this constant can dominate $K(x)$ itself; Kolmogorov complexity is only meaningful asymptotically. Analogously, the $K(\mu)$ term in (19) is a finite one-time information cost: it does not shrink with data.

Procurement corollary

On small, bespoke datasets (your legal corpus, your IoT telemetry) the constants swamp the asymptotics. "Big model + lots of data" is the regime in which the theory speaks; "small model + your niche" is the regime in which you hire evaluators, not theorists.

(C3) Practical compressors vs. K. A compressor C is *universal* in Shannon's sense if its code length $L_C(x_{1:T})/T$ converges to the entropy rate of any stationary ergodic source. It is *not* in general universal in Solomonoff's sense: it need not dominate all computable measures. The gap between Lempel–Ziv (Shannon-universal) and Solomonoff (universal over all computable measures) is a full logical level of universality, and neural compressors live somewhere in between.

Procurement corollary

"Compresses well" comes in strengths. Ask which strength. A model that crushes Wikipedia perplexity may still be a Shannon-universal compressor on stationary text, not a Solomonoff-universal one on your domain's non-stationarities.

(C4) Necessary vs. sufficient. Theorems 5.2 and 6.3 establish that optimal prediction and agency *entail* optimal compression. They do *not* establish that every improvement in compression corresponds to an improvement in every intuitive sense of "understanding." In particular, the framework is silent on phenomenal consciousness, grounding, and embodiment, and it takes the reward signal and the action–percept loop as primitives rather than explaining their origin.

Procurement corollary

Compression is *necessary* for intelligence in the theory's sense; no theorem says it is *sufficient* for intelligence in your sense. If the vendor's pitch relies on sufficiency, the theory is not their friend.

(C5) Compression $\neq$ understanding (as internal structure). A compressor is characterised by its length function, not by its internal representations. Two compressors with identical code lengths may use entirely different internal mechanisms, only one of which we would intuitively call "understanding." Equation (23) reduces "intelligence" to an extensional (input–output) property; any argument that understanding is intensional (about how the function is computed) is not touched by the chain. Anna and Ben, from the running cast, can have identical cross-entropy on the ten deals Ben has actually seen. They will diverge on the eleventh.

Procurement corollary

If you care *how* the model arrives at its answers (audit, explainability, regulation), cross-entropy is silent on your question. You need mechanistic evaluation, not just a leaderboard score.

Summary. The equivalence (23) is a genuine theorem modulo Theorems 2.1 to 6.1 and the computability-based caveats (C1)–(C3), which are mathematical. Caveats (C4)–(C5) are of a different species: they are not theorems against the chain, they are *scope restrictions* on what the chain claims. What (23) licences is a precise sense in which lowering cross-entropy on a sufficiently rich corpus moves a predictor along a single axis shared with compression and with Hutter-style universal agency. What it does *not* licence is the stronger claim that this axis exhausts what we mean by understanding, safety, or deployment-readiness.

Activities

Activity 8.1 — Procurement checklist

You are briefing your CIO tomorrow on a vendor proposal. Derive six questions — one per caveat (C1)–(C5) plus one meta-question — to put to the vendor in writing. A suggested starter set:

1. (C1) "On what benchmark, with what held-out distribution, is your perplexity number reported?"
2. (C2) "How was the model adapted to our domain? What is the performance delta between general and domain-specific held-out data?"
3. (C3) "Is your evaluation stationary or does it cover distribution shift? Give an example."
4. (C4) "What evidence, beyond cross-entropy, supports the claim that the model *understands* our data?"
5. (C5) "If we need to audit *how* an answer was produced, what tooling do you provide?"
6. (Meta) "What would falsify your claims? Name the experiment."

Deliverable. A one-page checklist you could email to procurement unchanged. Helps Aisha (a takeaway list) and Leo (the formal caveats now have teeth).

Activity 8.2 — Benchmark-contamination detective

You are shown five short answers a model has given on a well-known reasoning benchmark. Your job: flag which answers look *memorised* (verbatim phrasing, domain-specific jargon the prompt did not contain, suspiciously specific numbers) versus *reasoned* (shows working, makes small errors, paraphrases).
For each flagged answer, write one sentence: what would you do next to confirm contamination? (Suggested moves: perturb the prompt wording; shift numerical values; ask a follow-up that is only answerable from the derivation, not the final answer.)
Deliverable. A 5-row table: answer #, flag (memorised/reasoned/unsure), test-to-confirm. Helps Yuki (concrete stimulus) and Leo (gameified caveat (C1)).

Activity 8.3 — Two-analyst roleplay

Two students play *Compressor-Anna* (has memorised 4,000 deal memos) and *Understander-Ben* (has read only ten but understands them). A third student plays the interviewer and asks three questions about a deal *neither* analyst has seen:

1. "Walk me through how you would price this."
2. "What single fact, if it changed, would flip your pricing by more than ten percent?"
3. "What is your second-best comparable and why?"

Score each answer for *generalisation* (did the analyst transfer a principle?) versus *pattern-matching* (did the analyst return the nearest memo?). Debrief: which analyst

is the LLM in this lecture's framing? (Answer: neither cleanly — which is the point of (C5).)
Deliverable. A 3×2 score matrix with notes. Helps Yuki (concept → concrete) and Aisha (memorable characters).

Activity 8.4 — Claim-to-caveat matching

Match each vendor claim to the caveat that most directly bites it. More than one match is possible; argue for your primary choice.

1. "Our model is AGI-adjacent."
2. "Our LLM fully understands your firm's legal documents."
3. "Our system approximates the universal Solomonoff prior."
4. "We achieved state-of-the-art perplexity on LegalBench-2024."
5. "Our model's reasoning is transparent and auditable."

Caveats to choose from: (C1) uncomputability, (C2) additive constant / small-data regime, (C3) Shannon- vs. Solomonoff-universality, (C4) necessary vs. sufficient, (C5) extensional vs. intensional.
Deliverable. A table of claim → primary caveat → one-sentence rebuttal. Helps Leo (forces re-reading of the formal paragraphs with a task attached) and Maria (turns philosophy into operational critique).

A Worked cross-entropy calculation

Example A.1 (Cross-entropy on a 3-token sequence; nats vs. bits)**.** Let $\mathcal{A} = \{A, B, C\}$ and suppose the true conditional distributions at positions $t = 1, 2, 3$ have already been conditioned on the observed prefix, giving the sequence of true posterior masses on the realised tokens $p_1 = 0.8,\ p_2 = 0.5,\ p_3 = 0.1$. Consider two models. Model $q^{(1)}$ assigns $q_1 = 0.8, q_2 = 0.5, q_3 = 0.1$ (matches truth on the realised tokens); model $q^{(2)}$ assigns $q_1 = 0.1, q_2 = 0.1, q_3 = 0.8$ (systematically wrong).

For model $q^{(1)}$, the per-token code lengths in bits are $-\log_2 0.8 \approx 0.3219$, $-\log_2 0.5 = 1$, $-\log_2 0.1 \approx 3.3219$, summing to approximately 4.644 bits. In nats, multiply by $\ln 2 \approx 0.6931$: $4.644 \cdot \ln 2 \approx 3.219$ nats, matching $-\ln(0.8 \cdot 0.5 \cdot 0.1) = -\ln 0.04 \approx 3.219$ directly.

For model $q^{(2)}$, the lengths are $-\log_2 0.1 \approx 3.3219$, $-\log_2 0.1 \approx 3.3219$, $-\log_2 0.8 \approx 0.3219$, totalling ≈ 6.966 bits (≈ 4.828 nats, consistent with $-\ln(0.008) \approx 4.828$). The wrong model spends 2.32 extra bits, the Kullback–Leibler excess predicted by (9). Conversion rule: 1 nat $= \log_2 e$ bits ≈ 1.4427 bits and conversely 1 bit $= \ln 2$ nats.