

DS-2CE56H1T-ITM 5 MP Turret Camera

















Key Features

- 5 MP high-performance CMOS
- 2560 × 1944 resolution
- 2.8 mm, 3.6 mm, 6 mm fixed focal Lens
- EXIR 2.0, Smart IR, up to 20 m IR distance
- OSD menu, DNR, DWDR
- IP67
- Up the Coax (HIKVISION-C)





Specification


Camera	
Image Sensor	5 MP CMOS image sensor
Effective Pixels	2560 (H) × 1944 (V)
Min. illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	2.8 mm, 3.6 mm, 6 mm fixed focal Lens
Horizontal Field of View	89° (2.8 mm), 68.4° (3.6 mm), 46° (6 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°; Tilt:0° to 75°; Rotate: 0° to 360°
Synchronization	Internal synchronization
Frame Rate	2560 × 1944@20fps, 2560 × 1944@12.5fps 2560 × 1440@30fps, 2560 × 1440@25fps (default) 1920 × 1080@30fps, 1920 × 1080@25fps
Menu	
AGC	Support
D/N Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MWB
BLC	Support
DWDR (Digital Wide Dynamic Range)	Support
Language	English, Chinese
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
Interface	
Video Output	1 HD analog output
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25%
Power Consumption	Max. 5 W
Protection Level	IP67
Material	Metal
IR Range	Up to 20 m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	91 mm × 82.6 mm × 68.3 mm (3.58" × 3.25" × 2.69")
Weight	Approx. 350 g (0.77 lb)



Order Models

DS-2CE56H1T-ITM

Dimension



Φ 60 mm 3-Φ 4.5 mm (2.36")82.6 mm (3.25")91 mm (3.58")

Accessory



DS-1272ZJ-110-TRS Wall Mounting Bracket



Vertical Pole Mounting Bracket



DS-1H18 Video Balun



DS-1280ZJ-XS Junction Box



DS-1H18 Video Balun

Distributed by

HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA

T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Africa T +27 (10) 0351172 sale.africa@hikvision.com

Hikvision Europe T +31-23-55-42-770 info.eu@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Oceania T +61-2-8599-4233 salesau@hikvision.com

Hikvision Hong Kong T +852-2151-1761

Hikvision Middle East

T +971-4-8816086 salesme@hikvision.com

Hikvision Spain T +34-91-737-16-55

info.es@hikvision.com

Hikvision Canada

T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Russia

T +7-495-669-67-99 saleru@hikvision.com

Hikvision Poland

T +48-22-460-01-50 poland@hikvision.com

Hikvision Korea

T +82-31-731-8841 sales.korea@hikvision.com

Hikvision India

T +91-22-28469900 sales@pramahikvision.com

Hikvision UK T +01628-902140 support.uk@hikvision.com

Hikvision Brazil

T +55 11 3318-0050 Latam.support@hikvision.com