

HK-SFP-1.25G Series Transceiver

Features and Functions

Features

- a. Single Power Supply 3.3V
- b. Small Form Factor Pluggable (SFP) MSA Compatible
- c. Single Fiber Bi-Direction LC Connector
- d. Hot Pluggable Capability
- e. Compliant With ROHS Standard

Applications

- a. Fiber Channel
- b. Gigabit Ethernet
- c. Switch to Switch Interface

■ Absolute maximum ratings

Parameter	Symbol	Min.	Max.	Unit
Storage Temperature	Ts	-40	+85	$^{\circ}$
Supply Voltage	V _{CC}	-0.5	+3.6	V
Voltage at any Input Pin	V _{IN}	0	Vcc	V
Power supply current	Icc	-	300	mA

■ Recommended Operating Conditions

4	Parameter	Symbol	Min.	Тур	Max.	Unit
Operating Temperature	T _{op1}	0	=	+70	$^{\circ}$	
	T _{op2}	-40	-	+85		
	Supply Voltage	V _{CC}	3.1	3.3	3.5	٧
	Data Rate	-	-	1250	-	Mb/s

Ordering Information


Part No.	Wavelength (nm)	Temp. (°C)	TX Power (dBm)	RX Sens(Max) (dBm)	Distance (km)
HK-SFP-1.25G-20-1310	TX1310nm FP/RX1550nm	0 to 70	-6 to -1	-21	20
HK-SFP-1.25G-20-1550	TX1550nmDFB/RX1310nm	0 to 70	-9 to -1	-21	20






Mechanical(Units in mm)







Operating Conditions

Part No.	HK-SFP-1.25G-20-1310	HK-SFP-1.25G-20-1550	
Fiber			
Fiber type	SMF, Single fiber, 9/125um		
Connector	LC		
Connector quantity	1		
Distance	$0^{\sim}20\mathrm{km}$		
Wavelength	Tx1310nm/Rx1550nm	Tx1550nm/Rx1310nm	
TX Power	-9 [~] −1dBm		
RX Sens(Max.)	-21dBm		
Environment			
Operating temperature	0~70°C		
Storage temperature	-40∼85°C		
Relative humidity	30~80%		
Power			
Power supply voltage	DC 3.3V		

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com Hikvision Europe T +31-23-5542770 saleseuro@hikvision.com

Hikvision France T +33(0)1-85-330-444 info.fr@hikvision.com

Hikvision Oceania T +61-2-8599-4233 salesau@hikvision.com Hikvision Middle East T +971-4-8816086 salesme@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Hong Kong T +852-2151-1761 Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Poland T +48-22-460-01-50 poland@hikvision.com

Hikvision Canada T+1-909-895-0400 sales.usa@hikvision.com Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision UK T +44-1628-9021-4 support.uk@hikvision.com