# DS-KH9310-WTE1 Video Intercom Network Indoor Station





## **Key Feature**

- 7-inch colorful touch screen with resolution 1024 × 600
- UI V2.0: User friendly design
- Plug & play
- Standard PoE
- Receives video call and unlocks via the client software or the mobile client remotely
- Supports link to hikvision devices to bulid a management center

## **Approval**

CE-EMC	a. EN 55032:2015		
	b. EN 61000-3-2:2014		
	c. EN 61000-3-3:2013		
	d. EN 50130-4:2011 +A1:2014		
CE-LVD	EN 60950-1:2006 + A11:2009 + A1:2010 +		
	A12:2011 + A2:2013		
CE-RED	a. EN 201 489-1 V2.1.1, EN 301 489-17 V3.1.1		
	b. EN 300 328 V2.1.1, EN 62311:2008		
СВ	IEC 60950-1:2005 (Second Edition) + Am 1:2009		
	+ Am 2:2013		
FCC-SDOC	47 CFR Part 15, Subpart B		
FCC-ID	47 CFR Part 15, Subpart B		
C-	AS/NZS CISPR 32:2015		
TICK(EMC)			
C-TICK(RF)	AS/NZS 4268:2017		
UL	UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07,		
	Information Technology Equipment – Safety –		
	Part 1: General Requirements		
IC(EMC)	ICES-003:Issue 6		

IC(RF)	RSS-247 Issue 2, February 2017, RSS-Gen Issue 5, April 2018
ROHS	2011/65/EU
REACH	Regulation (EC) No 1907/2006
WEEE	2012/19/EU




# **Specification**

System paramete	rs				
Memory	1 GB				
Flash	4 GB Emmc				
Display parameters					
Display screen	7-inch colorful TFT touch screen				
Display resolution	1024 × 600				
Operation method	Capacitive touch screen				
Brightness	Adjustable				
Audio parameters	S				
Audio input	Built-in omnidirectional microphone				
Audio output	Built-in loudspeaker				
Audio compression standard	G.711 U, G.711 A				
Audio quality	Noise suppression and echo cancellation				
Network parameters					
Wired network	10/100 Mbps self-adaptive				
Wireless network	Wi-Fi 802.11 b/g/n				
Network protocol	TCP/IP, SIP, RTSP				
Interfaces					
Network port	RJ45				
RS-485	1				
Alarm in	8				
Button	1				
TAMPER	1				
Alarm out	2 relay				
Debugging port	1				
Micro USB	For debug only				
General					
Power supply	12 VDC & standard PoE, IEEE 802.3af				
Power consumption	≤8 W				
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)				
Working humidity	10% to 90%				
Dimensions	187 mm × 137 mm × 25.7 mm (7.36" × 5.39" × 1.01")				
Weight 419.3 g (without package) 694 g (with package)					


## **Available Model**

DS-KH9310-WTE1

# **Dimension**



# **Appearance and Interfaces**



No.	Description	No.	Description
1	Display Screen	6	RS-485/Relay
			Interface
2	Microphone	7	Debugging Port
3	Unlock Button	8	Micro USB Interface
4	Power Terminal	9	Loudspeaker
5	Alarm Terminal	10	TAMPER



Distributed by

## **HIKVISION**°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

#### Hikvision USA

T+1-909-895-0400 sales.usa@hikvision.com

#### Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900

#### sales@pramahikvision.com Hikvision Canada

T+1-866-200-6690 sales.canada@hikvision.com

#### Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com

Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

#### Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

#### Hikvision Turkey T +90 [216]521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

#### Hikvision South Africa Tel: +27 [10] 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

#### Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

#### Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

#### Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com