

# DS-2CE16D0T-EXIF 2MP Outdoor EXIR Fixed Mini Bullet Camera





## **Key Feature**

- High quality imaging with 2 MP, 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed lens
- Up to 20 m IR distance for bright night imaging
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP66)








# Specification

Specification			
Camera			
Image Sensor	2 MP CMOS		
Signal System	PAL/NTSC		
Resolution	1920 (H) × 1080 (V)		
Frame Rate	TVI: 1080p@25fps/30fps AHD: 1080p@25fps/30fps CVI: 1080p@25fps/30fps CVBS: PAL/NTSC		
Min. Illumination	0.02 Lux @ (F1.2, AGC ON), 0 Lux with IR		
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s		
Lens	2.8 mm, 3.6 mm Fixed Lens		
Field of View	2.8 mm, horizontal FOV: 102°, vertical FOV: 55°, diagonal FOV: 123° 3.6 mm, horizontal FOV: 81°, vertical FOV: 42°, diagonal FOV: 100°		
Lens Mount	M12		
Day & Night	ICR		
WDR (Wide Dynamic Range)	Digital WDR		
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°		
Menu			
Image Mode	STD/HIGH-SAT		
AGC	Yes		
Day/Night Mode	Auto/Color/BW (Black and White)		
White Balance	Auto		
AE (Auto Exposure) Mode	DWDR, BLC, Global		
Noise Reduction	2D DNR		
Language	English		
Function	Brightness, Mirror, Smart IR, Sharpness		
Interface			
Video Output	Switchable TVI/AHD/CVI/CVBS		
General			
Operating Conditions	-40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing)		
Power Supply	12 VDC ± 25%		
Consumption	Max. 3.3 W		
Protection Level	IP66		
Material	Metal		
IR Range	Up to 20 m		
Communication	HIKVISION-C		
Dimension	138.8 mm × 60.9 mm × 57.9 mm (5.465" × 2.389" 2.278")		
Weight	Approx. 260 g (0.57 lb.)		

# Dimension









### Accessory





DS-1280ZJ-XS

#### Available Model

DS-2CE16D0T-EXIF

Distributed by		
		1

## **HIKVISION**°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 [10] 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T+7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T+7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T+82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2019 | Data subject to change without notice |