

# DS-K1T671MF Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in Mifare card reading module
- Face recognition distance (without face mask): 0.3 m to 3 m, Duration < 0.2 s/User, Accuracy rate ≥ 99%</li>
- Max.6000 faces, Max.6000 cards and Max. 5000 fingerprints
- Two-way audio with client software, indoor station, and main station
- Supports TCP/IP
- Configuration via the web client
- Supports ISAPI and ISUP5.0 protocol
- IP65





# Specification

System					
Operation system	Linux				
Display					
Dimensions	7-inch				
Туре	LCD				
Operation method	Capacitive touch screen				
Video					
Pixel	2 MP				
Lens	2				
Audio					
Tone quality	Noise suppression and echo cancellation				
Network					
Wired network	10 M/100 M/1000 M self-adaptive				
nterface					
Network interface	1				
RS-485	1				
Wiegand	1				
Lock output	1				
Exit button	1				
Door contact input	1				
IO input	2				
IO output	1				
Power interface	2-pin				
TAMPER	1				
USB	2				
Capacity	apacity				
Card capacity	6000				
Face capacity	6000				
Fingerprint capacity	5000				
Event capacity	50,000				
Authentication					
Card type	Mifare 1 card				
Card reading frequency	13.56MHz				
Card reading distance	0 to 5 cm				
Face recognition accuracy rate	≥ 99%				
Face recognition distance	0.3 to 3 m (Without face mask)				
Fingerprint recognition duration	≤1s				
Function					
QR code recognition	Support				
Face anti-spoofing	Support				
Advertisement	Support				
Audio prompt	Support				
Time synchronization	Support				




General			
Power supply method	2-pin connecter		
Power supply	12 VDC/2 A		
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)		
Working humidity	10 to 90% (No condensing)		
Dimensions	290 mm × 116.5 mm × 33 mm (11.4" × 4.6" × 1.3")		
Protective level	IP65 Surface		
Installation			
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)		
Platform	Hik-ProConnect and HikCentral Professional		

# Available Model

DS-K1T671MF

## Dimension





## Accessory

### Optional

DS-KAB671-P1	DS-KAB671-S	DS-KAB671-S	DS-KAB671-B	DS-KAB671-B
	<b>Protective Shield</b>	<b>Protective Shield</b>	Stand Stick	Stand Stick
DS-K3H4411-120	DS-K3H4410-120			

Distributed by

**HIKVISION**°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com