

DS-2CE56D0T-IF 2 MP IR Turret Camera





Key Features

- 2 MP high performance CMOS
- 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed lens
- Up to 20 m IR distance
- OSD menu, DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66
- Up the coax (HIKVISION-C)





Specifications


| Camera | |
|--------------------------|--|
| Image Sensor | 2 MP CMOS image sensor |
| Signal System | PAL/NTSC |
| Frame Rate | PAL: 1080p@25fps NTSC: 1080p@30fps |
| Resolution | 1920 (H) × 1080 (V) |
| Min. illumination | 0.02 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s |
| Lens | 2.8 mm, 3.6 mm fixed lens |
| Horizontal Field of View | 103° (2.8 mm), 82.2° (3.6 mm) |
| Lens Mount | M12 |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360° |
| Synchronization | Internal synchronization |
| WDR (Wide Dynamic Range) | DWDR |
| Menu | |
| Image Mode | STD/HIGH-SAT |
| AGC | Support |
| Day/Night Mode | Smart/color/BW(Black and White) |
| Backlight Compensation | Support |
| DWDR | Support |
| Language | English |
| Functions | Brightness, Sharpness, DNR, Mirror |
| Interface | |
| Video Output | 1 HD analog output |
| Switch Button | TVI/AHD/CVI/CVBS |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC ±15% |
| Power Consumption | Max. 4 W |
| Ingress Protection | IP66 |
| Material | Enclosure: Plastic Main Body: Metal |
| IR Range | Up to 20 m |
| Dimension | Ø 89.9 mm × 70.1 mm (Ø 3.54" × 2.76") |
| Weight | Approx. 280 g (0.62 lb.) |


Order Model

DS-2CE56D0T-IF



Dimensions





Accessories



DS-1272ZJ-110-TRS Wall Mount



DS-1275ZJ-SUS Vertical Pole Mount



DS-1276ZJ-SUS Corner Mount



DS-1H18 Video Balun



DS-1280ZJ-XS Junction Box

Distributed by

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision Poland T +48-22-460-01-50 poland@hikvision.com Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision UK T +44-1628-9021-4 support.uk@hikvision.com Hikvision Europe T+31-23-5542770 saleseuro@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com Hikvision Middle East T +971-4-8816086 salesme@hikvision.com

Hikvision France T +33(0)1-85-330-444 info.fr@hikvision.com

Hikvision Oceania T +61-2-8599-4233 salesau@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Hong Kong T +852-2151-1761