

Usage Guide — transfer.firebee.com.br

File sharing service via curl

Firebee Development Team

May 2026

Contents

1 Usage Guide — transfer.firebee.com.br	1
1.1 Overview	1
1.2 Uploading Files	2
1.3 Downloading Files	2
1.4 Uploading via Pipe (stdin)	3
1.5 Shell Alias / Convenience Function	3
1.6 Sharing Files with Others	4
1.7 Service Limits	4
1.8 Troubleshooting	4
1.9 Service Configuration (Reference)	5

1 Usage Guide — transfer.firebee.com.br

1.1 Overview

transfer.sh is a lightweight, self-hosted file sharing service accessed entirely via the command line with `curl`. There is no web upload interface and no account to create — simply upload a file and share the generated URL.

The Firebee instance is available at:

`http://transfer.firebee.com.br:3210`

Important: port `:3210` is required in all URLs. The service does not respond on the default port `80/443`.

1.2 Uploading Files

1.2.1 Basic syntax

```
curl --upload-file <file-path> http://transfer.firebee.com.br:3210
```

The server returns a unique URL for the file. Real example:

```
$ curl --upload-file ./teste.txt http://transfer.firebee.com.br:3210  
http://transfer.firebee.com.br:3210/G2k6d6aMSl/teste.txt
```

The generated URL contains a random identifier (G2k6d6aMSl) followed by the original filename.

1.2.2 Examples by file type

Text file:

```
curl --upload-file ./report.txt http://transfer.firebee.com.br:3210
```

Compressed archive:

```
curl --upload-file ./backup.tar.gz http://transfer.firebee.com.br:3210
```

Image:

```
curl --upload-file ./screenshot.png http://transfer.firebee.com.br:3210
```

Any extension works — the filename in the URL preserves the original extension.

1.3 Downloading Files

To download, use the URL returned on upload directly in a browser or via curl:

```
curl http://transfer.firebee.com.br:3210/G2k6d6aMSl/teste.txt -o teste.txt
```

Or save with the original filename automatically:

```
curl -O http://transfer.firebee.com.br:3210/G2k6d6aMSl/teste.txt
```

1.4 Uploading via Pipe (stdin)

You can send data directly from a pipe without creating an intermediate file:

```
cat file.txt | curl -X PUT --upload-file "-" http://transfer.firebee.com.br:3210/
```

Pipe use cases:

Compress and send in a single command:

```
tar czf - ./folder/ | curl -X PUT --upload-file "-" http://transfer.firebee.com.br:3210/
```

Send command output:

```
ps aux | curl -X PUT --upload-file "-" http://transfer.firebee.com.br:3210/processes
```

Database dump directly to the service:

```
mongodump --archive | curl -X PUT --upload-file "-" http://transfer.firebee.com.br:3210/
```

1.5 Shell Alias / Convenience Function

Add to ~/.bashrc or ~/.zshrc to simplify usage:

```
transfer() {  
  if [ -z "$1" ]; then  
    echo "Usage: transfer <file>"  
    return 1  
  fi  
  curl --upload-file "$1" "http://transfer.firebee.com.br:3210/${basename "$1"}"  
  echo # newline after the URL  
}
```

After reloading the shell (source ~/.bashrc), usage becomes simple:

```
transfer report.pdf  
transfer backup.tar.gz
```

1.6 Sharing Files with Others

The URL returned by the upload can be shared with anyone who has access to the network where the service is exposed. Just send the URL — no authentication is required to download.

```
http://transfer.firebee.com.br:3210/G2k6d6aMSl/teste.txt
```

^^^^^^
Randomly generated unique ID

Security note: the URL is the only “secret” for the file. Anyone with the URL can download it. Do not share URLs of sensitive files in public channels.

1.7 Service Limits

Parameter	Value
Maximum file size	5 GB
Retention period	14 days (files are deleted automatically)
Rate limit	10 requests per time window
Storage provider	Local (VPS server disk)

Files are automatically deleted after 14 days. If you need longer persistence, re-upload before expiry.

1.8 Troubleshooting

1.8.1 The URL does not open in the browser

Make sure the :3210 port is included in the URL. The service does not respond at `http://transfer.firebee.com.br` without the port.

1.8.2 Rate limit error

If you receive an HTTP 429 error, wait a moment and try again. The limit is 10 requests per window.

1.8.3 Slow or interrupted upload

For large files, use the `--limit-rate` flag to control speed and avoid timeouts:

```
curl --upload-file ./large-file.tar.gz --limit-rate 10M http://transfer.firebee.c
```

1.8.4 Check upload progress

```
curl --upload-file ./file.tar.gz http://transfer.firebee.com.br:3210 --progress-b
```

1.9 Service Configuration (Reference)

The service runs via Docker Compose on the VPS:

```
image: dutchcoders/transfer.sh:latest  
port: 3210 → 8080 (internal)  
storage: local volume /data  
max upload: 5 GB  
purge: 14 days
```

Configuration repository: `transfer-sh-firebee/docker-compose.yaml`