

A dark blue vertical bar is positioned on the left side of the slide. A blue arrow-shaped banner extends from this bar to the right, containing the date. Below the banner, several thin, curved lines in dark blue and light grey sweep upwards from the bottom left corner.

26-8-2022

# Database Programming with SQL 2 / 2

JUAN CARLOS HERRERA HERNANDEZ  
UNIVERSIDAD POLITECNICA DE AGUASCALIENTES

## Contenido

Section 11 – Ensuring Quality Queries Part I .....	2
11-1 Ensuring Quality Query Results .....	2
Section 12 – DML .....	2
12-1 INSERT Statements .....	2
12-2 Updating Column Values and Deleting Rows .....	3
12-3 DEFAULT Values, MERGE, and Multi-Table Inserts.....	4
Section 13 – DDL .....	6
13-1 Creating Tables .....	6
13-2 Using Data Types.....	7
13-3 Modifying a Table .....	8
Section 14 – Constraints .....	9
14-1 Intro to Constraints; NOT NULL and UNIQUE Constraints.....	9
14-2 PRIMARY KEY, FOREIGN KEY, and CHECK Constraints .....	9
14-3 Managing Constraints .....	9
Section 15 – Views .....	9
15-1 Creating Views .....	9
15-2 DML Operations and Views .....	9
15-3 Managing Views.....	9

## Section 11 – Ensuring Quality Queries Part I

### 11-1 Ensuring Quality Query Results

Solve a series of problems:

- Solve a series of problems Create a query to produce specified data
- Modify a query to produce specified data

Select * from user_tables	PURGE RECYCLEBIN;
select * from tab;	

## Section 12 – DML

### 12-1 INSERT Statements

<b>USER</b>	Someone doing “real work” with the computer, using it as a means rather than an end
<b>Transaction</b>	Consists of a collection of DML statements that form a logical unit of work.
<b>Explicit</b>	Fully and clearly expressed; leaving nothing implied
<b>INSERT INTO</b>	Adds a new row to a table

The table copies will not inherit the associated primary-to-foreign-key integrity rules (relationship constraints) of the original tables.

Copy structure and data	Copy only structure
CREATE TABLE copy_departments as SELECT * FROM departments;	CREATE TABLE copy_departments as (SELECT * FROM departments where 1=2);

Describe employees	SALARY NUMBER(6,2) Precision 6, Scale 2 [-9999.99, 9999.99]
user	select user from dual;
sysdate	select sysdate from dual; -- default DD-Mon-YYYY
	select to_char(sysdate, 'Month fmdd, yyyy') from dual;

select columns	all columns
INSERT INTO copy_departments (department_id, department_name, location_id) VALUES (200,'Human Resources', 1500);	INSERT INTO copy_departments VALUES (210,'Estate Management', 102, 1700);

INSERT INTO copy_employees (employee_id, first_name, last_name, email, hire_date, salary) VALUES (302,'Grigorz','Polanski', 'GPolanski', TO_DATE('2017-07-20', 'yyyy-mm-dd'), 4200);
---

Insert multiple records at the same time
INSERT INTO sales_reps(id, name, salary, commission_pct) SELECT employee_id, last_name, salary, commission_pct FROM employees WHERE job_id LIKE '%REP%';

## 12-2 Updating Column Values and Deleting Rows

<b>UPDATE</b>	Modifies existing rows in a table
<b>Correlated subquery UPDATE</b>	retrieves information from one table & uses the information to update another table
<b>Integrity Constraint</b>	Ensures that the data adheres to a predefined set of rules
<b>Correlated subquery DELETE</b>	deletes information on a linked table based on what was deleted on the other table
<b>Delete</b>	Removes existing rows from a table

Not Correlated	Correlated
<pre>UPDATE copy_employees SET hire_date = sysdate WHERE employee_id = 206;</pre>	<pre>UPDATE copy_employees SET hire_date = sysdate,     salary = (SELECT salary FROM copy_employees               WHERE employee_id= 205),     job_id = (SELECT job_id FROM copy_employees               WHERE employee_id= 205) WHERE employee_id = 206;</pre>

Correlated
<pre>ALTER TABLE copy_employees ADD (department_name varchar2(30));  select e.department_id, d.department_id, d.department_name from employees e, departments d where e.department_id = d.department_id;  UPDATE copy_employees e SET e.department_name= (SELECT d.department_name                        FROM departments d                        WHERE e.department_id= d.department_id);</pre>

Not Correlated	Correlated
<pre>DELETE FROM departments WHERE department_id = 50;  DELETE FROM copy_employees WHERE department_id = 50;</pre>	<pre>DELETE FROM copy_employees WHERE department_id =     (SELECT department_id FROM departments      WHERE department_name= 'Shipping');</pre>

Be carefully	
<pre>SELECT * FROM copy_employees e WHERE e.manager_id IN     (SELECT d.manager_id      FROM employees d      GROUP BY d.manager_id      HAVING count(d.department_id) &lt; 2);</pre>	<pre>DELETE FROM copy_employees e WHERE e.manager_id IN     (SELECT d.manager_id      FROM employees d      GROUP BY d.manager_id      HAVING count(d.department_id) &lt; 2);</pre>

row-level locks, until you issue a COMMIT or ROLLBACK
<pre> SELECT e.employee_id, e.salary, d.department_name FROM employees e JOIN departments d USING (department_id) WHERE location_id = 1500 AND job_id= 'ST_CLERK' FOR UPDATE ORDER BY e.employee_id;  GRANT update, select ON employees TO schemas  User: SCHEMAS update ESQUEMAS.employees e set salary = salary where e.employee_id = 141; </pre>

### 12-3 DEFAULT Values, MERGE, and Multi-Table Inserts

A **data warehouse** is a collection of data designed to support business-management decision making. Data warehouses contain a wide variety of data, such as sales data, customer data, payroll, accounting, and personnel data, which presents a coherent picture of business conditions at a single point in time.

<pre> CREATE TABLE my_employees ( hire_date DATE DEFAULT SYSDATE, first_name VARCHAR2(15), last_name VARCHAR2(15)); </pre>	<pre> -- Explicit INSERT INTO my_employees (hire_date, first_name, last_name) VALUES (DEFAULT, 'Angelina', 'Wright'); </pre>	<pre> -- Implicit INSERT INTO my_employees (first_name, last_name) VALUES('Angelina', 'Wright'); </pre>
--	--	---

<pre> UPDATE my_employees SET hire_date = DEFAULT WHERE last_name = 'Wright'; </pre>	<pre> UPDATE my_employees SET hire_date = '21-SEP-89' WHERE last_name = 'Wright'; </pre>	<pre> UPDATE copy_employees SET hire_date = to_date('1989-09-21', 'yyyy-mm-dd') WHERE employee_id = 100; </pre>
--	--	---

<pre> MERGE will INSERT and UPDATE simultaneously.  MERGE INTO destination-table USING source-table ON matching-condition WHEN MATCHED THEN UPDATE SET ..... WHEN NOT MATCHED THEN INSERT VALUES (.....); </pre>	<pre> MERGE INTO copy_emp c USING employees e ON (c.employee_id = e.employee_id) WHEN MATCHED THEN UPDATE SET     c.last_name = e.last_name,     c.department_id = e.department_id WHEN NOT MATCHED THEN INSERT VALUES (e.employee_id, e.last_name, e.department_id); </pre>
--	--

## ALL , FIRST

## MERGE Example

EMPLOYEES (source table)	EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
	100	King	90
	103	Hunold	60
	142	Davies	50

COPY\_EMP before the MERGE is executed

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	Smith	40
103	Chang	30

COPY\_EMP after the MERGE has executed

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	King	90
103	Hunold	60
142	Davies	50

## Multi-Table Inserts Conditional

```
INSERT ALL
  WHEN call_format IN ('tlk','txt','pic') THEN
    INTO all_calls
      VALUES (caller_id, call_timestamp, call_duration, call_format)
  WHEN call_format IN ('tlk','txt') THEN
    INTO police_record_calls
      VALUES (caller_id, call_timestamp, recipient_caller)
  WHEN call_duration < 50 AND call_type = 'tlk' THEN
    INTO short_calls
      VALUES (caller_id, call_timestamp, call_duration)
  WHEN call_duration >= 50 AND call_type = 'tlk' THEN
    INTO long_calls
      VALUES (caller_id, call_timestamp, call_duration)
SELECT caller_id, call_timestamp, call_duration, call_format,
       recipient_caller
FROM calls
WHERE TRUNC(call_timestamp) = TRUNC(SYSDATE);
```

## Section 13 – DDL

### 13-1 Creating Tables

<b>Data dictionary</b>	Created and maintained by the Oracle Server and contains information about the database
<b>Schema</b>	A collection of objects that are the logical structures that directly refer to the data in the database
<b>DEFAULT</b>	Specifies a preset value if a value is omitted in the INSERT statement
<b>Table</b>	Stores data; basic unit of storage composed of rows and columns
<b>CREATE TABLE</b>	Command used to make a new table

Table names are not case sensitive.

Table names should be plural, for example STUDENTS, not student

The main database object types are:

Table	Index	Constraint	View	Sequence	Synonym
-------	-------	------------	------	----------	---------

```
CREATE TABLE my_cd_collection (  
  cd_number NUMBER(3),  
  title VARCHAR2(20) not null,  
  artist VARCHAR2(20) check(regex_like(artist, '[a-zA-Z .]')),  
  purchase DATE DEFAULT SYSDATE);
```

-- External Tables Example

```
CREATE TABLE emp_load (  
  employee_number CHAR(5),  
  employee_dob CHAR(20),  
  employee_last_name CHAR(20),  
  employee_first_name CHAR(15),  
  employee_middle_name CHAR(15),  
  employee_hire_date DATE )  
ORGANIZATION EXTERNAL (  
  TYPE ORACLE_LOADER  
  DEFAULT DIRECTORY def_dir1  
  ACCESS PARAMETERS  
    (RECORDS DELIMITED BY NEWLINE  
    FIELDS (employee_number CHAR(2),  
           employee_dob CHAR(20),  
           employee_last_name CHAR(18),  
           employee_first_name CHAR(11),  
           employee_middle_name CHAR(11),  
           employee_hire_date CHAR(10) date_format DATE mask "mm/dd/yyyy"))  
  LOCATION ('info.dat') );
```

User tables:	Data Dictionary tables (Only Select):
Employees Departments	SELECT * FROM DICTIONARY; SELECT * FROM USER_TABLES; SELECT * FROM USER_INDEXES; SELECT * FROM user_objects WHERE object_type= 'SEQUENCE'; SELECT * FROM USER_SEGMENTS; SELECT * FROM ALL_TABLES;

## 13-2 Using Data Types

<b>BLOB</b>	Binary large object data up to 4 gigabytes
<b>CLOB</b>	Character data up to 4 gigabytes
<b>INTERVAL YEAR TO MONTH</b>	Allows time to be stored as an interval of years and months
<b>INTERVAL DAY TO SECOND</b>	Allows time to be stored as an interval of days to hours, minutes, and seconds
<b>TIMESTAMP</b>	Allows the time to be stored as a date with fractional seconds
<b>TIMESTAMP WITH TIMEZONE</b>	stores a time zone value as a displacement from Universal Coordinated Time or UCT
<b>TIMESTAMP WITH LOCAL TIMEZONE</b>	when a column is selected in a SQL statement the time is automatically converted to the user's timezone

- CHAR (fixed size, maximum 2000 characters)
- VARCHAR2 (variable size, maximum 4000 characters)
- NUMBER (variable size, maximum precision 38 digits)
- DATE range yyyy-mm-dd hh24:mi:ss
- TIMESTAMP range yyyy-mm-dd hh12:mi:ss and fractions of a second
- INTERVAL DAY [(day\_precision)] TO SECOND The default precision value is 2

select current\_timestamp, SYSTIMESTAMP from dual

current_timestamp	03-OCT-22 05.22.33.598000000 PM AMERICA/MEXICO_CITY
SYSTIMESTAMP UCT	03-OCT-22 05.22.33.598000000 PM -05:00

MySQL Date yyyy-mm-dd	ORACLE Date yyyy-mm-dd hh:mi:ss
create table tmp_Formatos( Fecha date, FechaTiempo datetime, TiempoMarca timestamp);	create table tmp_Formatos( Fecha date, TiempoMarca timestamp);
select now(), sysdate(), current_timestamp();	select sysdate, current_date, current_timestamp, SYSTIMESTAMP from dual;
insert into tmp_Formatos values(sysdate(), sysdate(), sysdate());	insert into tmp_Formatos values(sysdate, sysdate);
Select * from tmp_formatos;	select * from tmp_formatos;
select second(fechaTiempo), extract(second from TiempoMarca) from tmp_formatos;	select to_char(fecha, 'ss'), extract(second from TiempoMarca) from tmp_formatos;

create table tmp_Horarios ( Fecha date, TS TIMESTAMP, TS_TZ TIMESTAMP WITH TIME ZONE, TS_LTZ TIMESTAMP WITH LOCAL TIME ZONE);	create table tmp_Intervalos ( loan1 INTERVAL YEAR TO MONTH, loan2 INTERVAL YEAR TO MONTH);
insert into tmp_horarios values (sysdate, sysdate, SYSTIMESTAMP, sysdate);	INSERT INTO tmp_Intervalos (loan1, loan2) VALUES (INTERVAL '121' MONTH(3), INTERVAL '3-6' YEAR TO MONTH);
	select sysdate+loan1 from tmp_intervalos;



### 13-3 Modifying a Table

You can add or modify a column in a table, but you cannot specify where the column appears

```
ALTER TABLE tablename
ADD (column_name data_type [DEFAULT expression],
     column_name data_type [DEFAULT expression], ...);
```

```
ALTER TABLE mod_emp
MODIFY (salary NUMBER(8,2) DEFAULT 50);
```

```
ALTER TABLE tablename
DROP COLUMN columnname;
```

```
-- Dropping a column from a large table can take a long time
ALTER TABLE tablename SET UNUSED (column_name);
```

```
-- when you want to reclaim the extra disk space
ALTER TABLE copy_employees
DROP UNUSED COLUMNS;
```

```
ALTER SESSION SET RECYCLEBIN = ON;
DROP TABLE table_name;
```

FLASHBACK TABLE table_name TO BEFORE DROP;	select * from USER_RECYCLEBIN;
DROP TABLE Table_Name PURGE;	RENAME old_name to new_name;

it does not release storage space	Free up storage space
Delete from Table_Name;	Truncate Table Table_Name;

```
COMMENT ON TABLE Employees is 'Tabla de empleados';
comment on column Employees.last_name is 'Apellido Paterno';
```

```
select * from user_tab_comments;
SELECT * FROM USER_COL_COMMENTS;
```

	Review the changes made (UNDO tablespace) SCN (System Change Number)
UPDATE EMPLOYEES SET LAST_NAME = 'King Kong' where employee_id = 100;	select * from Employees VERSIONS BETWEEN SCN MINVALUE AND MAXVALUE WHERE employee_id= 100;

## Section 14 – Constraints

### 14-1 Intro to Constraints; NOT NULL and UNIQUE Constraints

<b>Constraint</b>	Database rule.
<b>PRIMARY KEY</b>	Constraint ensures that the column contains no null values and uniquely identifies each row of the table
<b>UNIQUE KEY</b>	An integrity constraint that requires every value in a column or set of columns be unique
<b>UNIQUE constraint</b>	Every value in a column or set of columns (a composite key) must be unique
<b>FOREIGN KEY</b>	Designates a column (child table) that establishes a relationship between a primary key in the same table and a different table (parent table)
<b>REFERENCES</b>	Identifies that table and column in the parent table
<b>NOT NULL constraint</b>	For every row entered into the table, there must be a value for that column
<b>CHECK constraint</b>	Specifies a condition for a column that must be true for each row of data
<b>Table level constraint</b>	References one or more columns and is defined separately from the definitions of the columns in the table
<b>Column-level constraint</b>	Database rule that references a single column

### 14-2 PRIMARY KEY, FOREIGN KEY, and CHECK Constraints

### 14-3 Managing Constraints

## Section 15 – Views

### 15-1 Creating Views

### 15-2 DML Operations and Views

### 15-3 Managing Views