

CL908 Technical Questions & Answers

Prepared for: Carlos

Model: CL908 Automatic Touchless Car Wash Machine

Thank you very much for your detailed and professional questions. I have reviewed them carefully with our engineering team. Please find our answers in red:

1. DIMENSIONS AND INSTALLATION**1. CL908 installation height****Question:**

The detail sheet says 3,650 mm and the quotation says 4,000 mm. Which one is correct?

Answer:

The standard installation height of CL908 is **3,650 mm**.

The recommended installation height is **4,000 mm**, because we reserve additional space to make installation, commissioning, and future maintenance easier.

2. Rail length**Question:**

The sheet says 7.5 m and the quotation says 9.0 m. Which one is correct?

Answer:

If I remember correctly, **7.5 m is the rail length for CL808**.

The CL908 uses a **9 m rail**, because it is designed to clean larger vehicles, including pickup trucks.

If you find any other differences between documents, please feel free to send us screenshots, and we will confirm them for you.

3. Concrete slab requirement**Question:**

The sheet says 20 cm and the quotation says 15 cm. Which one do I need?

Answer:

We recommend a **20 cm concrete slab**.

The minimum requirement is **15 cm**.

Thank you for pointing out this difference. We will update our documents and unify the requirement as **≥15 cm**.

4. Compatibility with standard classic pre-housing bay**Question:**

Does the CL908 fit inside the standard classic pre-housing bay (inner size 9,000 × 5,000 × 4,000 mm)?

If not, what is the price and size of a customized bay?

Answer:

The standard bay length needs to be extended slightly, but the required modification is not

significant.

The additional cost will not increase too much.

The exact dimensions and cost can be calculated in detail after the project is confirmed.

5. Actual weight and shipping volume

Question:

The CL908 weight is listed as 2,900 kg and 2,921 kg. Shipping volume is listed as 16 CBM and 19.8 CBM. Which one is correct?

Answer:

These values are estimated, so there may be small differences between different machines.

They are mainly used as reference information.

For shipping calculation, we recommend using the maximum value to avoid unexpected problems.

2. MACHINE SPECIFICATIONS

6. Maximum power demand

Question:

What is the real maximum power demand during operation:

- Pump phase
- Drying phase with all 6 fans (4 top + 2 side)?

Answer:

The pump motor power is:

22 kW

The drying system consists of 6 fans:

$6 \times 5.5 \text{ kW} = 33 \text{ kW}$

The pump and drying fans do not operate at the same time.

Therefore, the maximum power demand is approximately:

33 kW

7. Top nozzle height and small vehicle washing performance

Question:

The 35 cm washing distance applies to the side swing arm. For hood, roof, and trunk, what is the height of the top nozzles?

Can the moving body be installed lower?

Many customers have small cars with:

- Hood height around 0.9 m
- Roof height around 1.5 m

Answer:

The top nozzles are approximately **2.5 m above the ground**.

If you require a lower installation height, we can adjust the design according to the CL808 structure.

However, this will reduce the maximum washing height.

A lower installation height can provide better cleaning performance for small cars, but it may affect the ability to fully clean larger vehicles such as pickup trucks.

Therefore, the best model depends on your local vehicle structure:

- If your market mainly has small cars, CL808 may provide better washing coverage.
- If your market has more SUVs and pickup trucks, CL908 is the better choice.

CL808 can safely wash large vehicles, but it cannot fully cover every roof area.

CL908 can fully clean large vehicles, but small low vehicles may not achieve the same optimization level.

The final choice depends on your local market situation.

8. Width sensor height and pickup truck mirrors

Question:

At what height do the width sensors measure the vehicle?

Can CL908 wash a full-size pickup truck with mirrors open (2,430 mm width)?

Answer:

We will confirm the exact sensor height with our engineering team.

For reference:

- CL808 maximum washing width: **2,600 mm**
- CL908 maximum washing width: **2,690 mm**

Therefore, both models can safely wash vehicles with open side mirrors.

9. Operating temperature

Question:

My site reaches 48–50°C in summer. Do you have installations in similar climates?

Answer:

Yes.

We have many installations in Middle East countries such as Saudi Arabia and Dubai, where summer temperatures can reach around 50°C.

However, we recommend installing the electrical control cabinet inside an air-conditioned control room.

Keeping the control room temperature below **40°C** helps electrical components dissipate heat better and improves long-term reliability.

Because the control room is small, a small air conditioner is sufficient.

10. Moving body material

Question:

Is the moving body galvanized and painted, or stainless steel?

Your website and listing show different information.

Answer:

The main frame is made of carbon steel with double anti-corrosion protection:

- Galvanized treatment
- Surface painting

All metal parts that directly contact water and chemicals are stainless steel, including:

- Mechanical arms
- Rotary joints
- Connectors

- Pipelines
-

3. WATER SYSTEM

11. Water consumption

Question:

Is the 130–180 L water consumption for CL908 per car or per rinse cycle?

Answer:

The water consumption figure is an approximate value for reference only.

Our machine supports:

- 4 different washing programs
- Maximum 12 steps for each program
- Adjustable operation speed
- Three water pressure levels (High / Medium / Low)

Therefore, the actual water consumption depends on:

- Vehicle type
- Washing program
- Operation speed
- Water pressure setting

Normally, the average water consumption is approximately:

120-150 liters per vehicle

12. Ground sprayer

Question:

Does CL908 include a standard ground sprayer?

Is the vertical ground spray (USD 175) an upgrade or separate option?

Answer:

Yes, the standard CL908 includes a ground sprayer.

The vertical ground spray is an upgraded option based on the standard ground sprayer.

We do not include it as standard because customer requirements vary by market.

For example, some customers in the United States do not prefer vertical ground spray because:

- Some states allow alcohol consumption before driving.
- Large pickup trucks are very common.
- Some drivers may have difficulty parking or may not see the vertical spray unit clearly, which creates a risk of collision.

Therefore, we provide it as an optional upgrade depending on local requirements.

13. Soft water rinsing system

Question:

What is included in the soft water rinsing circuit?

Is it the only way to deliver RO water for final rinsing?

Answer:

The soft water system option includes:

- Soft water treatment tank

The tank itself needs to be filled and installed locally.

Please note:

Soft water system and RO water system are different solutions.

Please refer to the optional equipment introduction for detailed information.

14. Two water sources

Question:

Can CL908 use recycled water for pre-wash/high pressure and softened fresh water for foam, wax, and final rinse?

Answer:

Yes, it is possible.

For our RO system, we already reserve two water inlets and configure both hardware and software accordingly.

If you purchase a local water treatment system, we can also reserve an additional water inlet.

The port reservation cost is:

USD 295

4. WARRANTY AND SPARE PARTS

15. Spare parts and warranty coverage

Question:

What is included in the spare parts kit?

Please provide recommended spare parts for one year operation.

What does the 3-year whole machine warranty cover?

Answer:

We will share the detailed spare parts kit list with you separately.

The spare parts package contains the main wearing parts of the machine.

Together with commonly available local parts, it can cover approximately **65% of common after-sales issues**.

For one machine installation, we normally do not recommend customers purchasing an additional spare parts package unless they have special requirements.

Regarding warranty:

We provide a **3-year full machine warranty**.

During the warranty period:

- Any damaged parts caused by machine quality issues will be replaced free of charge.
- The customer only needs to cover the shipping cost.

The warranty covers the complete machine, not only selected key components.

5. WATER TREATMENT

16. Reverse Osmosis unit and softener specifications

Question:

Reverse Osmosis unit 1,000 L/h and softener 3 t/h:

- What are the brands of the softener valve, RO membranes, and RO pump?
- Does the softener need a 60 Hz version?
- My water has 350–530 mg/L TDS and pH 7.3–7.8.

Answer:

The RO system is supplied by a carefully selected third-party supplier. Since the RO system is not manufactured by us directly, I do not have all the detailed technical specifications at this moment, including the exact brands of the valves, membranes, and pump. I will contact our supplier and confirm the detailed information for you. Alternatively, you can also purchase the RO system locally according to your requirements. For your local power condition, the RO system can be customized for **60 Hz** if required. Based on the water quality information you provided, we recommend using an RO system for the final rinse process to achieve better washing results and avoid water spots on vehicles.

17. Softener 3 t/h capacity and regeneration information**Question:**

My water hardness is 220–260 mg/L as CaCO₃ (13–15 grains per gallon). How many liters can it treat between regenerations at this hardness? What is the resin volume, and is regeneration controlled by time or water volume?

Answer:

The softener technical details are also provided by our selected water treatment supplier. I will confirm the following information with them:

- Resin volume
- Water treatment capacity between regenerations
- Regeneration method (time-based or volume-based)
- Control valve specifications

I will update you after receiving the detailed information from the supplier.

18. Water recycling system 2 m³/h**Question:**

Do you sell a water recycling system of 2 m³/h? Please provide the price and maintenance requirements.

Answer:

Previously, we also offered water recycling systems as an optional solution. However, based on feedback from our customers and practical operating experience, we finally removed it from our standard optional equipment list. The main reasons are:

1. Current water recycling technology still has limitations

In our experience, a truly effective water recycling system that can achieve high recycling rates is usually very expensive. In many cases, the cost is close to the price of the car wash machine itself.

Lower-cost recycling systems often only meet basic environmental inspection requirements but cannot provide a truly effective recycling solution.

2. Maintenance requirements increase operating costs

The original purpose of an automatic touchless car wash system is to reduce labor costs. However, water recycling systems require regular manual maintenance, including:

- Sludge removal
- Chemical dosing

- Wastewater discharge management

These processes usually cannot be fully automated.

Additionally, after long-term operation, recycled water may inevitably develop odor issues if not managed properly.

Therefore, for most customers, especially for their first machine installation, we do not recommend purchasing a water recycling system.

6. PAYMENT SYSTEM

19. Payment System A – Banknote validator and Nayax card reader

Question:

Is the banknote validator configured for Mexican pesos?

Is the card reader Nayax, and does it work in Mexico?

How do I open the Nayax account?

Answer:

The banknote validator can be configured according to the local currency requirements, including Mexican pesos.

For the Nayax payment system, we will provide you with the local contact information. You can open the Nayax account directly with them, and we will cooperate with the setup and integration process.

20. VIP cards

Question:

Are the VIP cards standard RFID (Mifare)?

Can I encode them myself from the terminal?

Answer:

Yes, the VIP cards can be encoded and managed directly through the terminal system.

Regarding whether the cards are standard RFID Mifare cards, I need to confirm this information with our supplier.

I will get the exact information on Monday and update you.

7. COMMERCIAL AND SHIPPING

21. CIF shipping quotation to Mexico

Question:

Please quote CIF Manzanillo and CIF Ensenada for a 40 ft container.

Is there any shipping route to Guaymas?

Answer:

The current freight cost to Manzanillo is:

USD 9,210

This is the latest shipping cost from China to Mexico based on another Mexican customer's shipment this week.

Currently, it is the weekend in China, and the shipping companies are not working, so we cannot get the latest quotation for Ensenada and Guaymas at this moment.

I will contact the shipping companies on Monday, check the latest freight rates, and update you.

In addition, if you only purchase one CL908 machine, using a 40HQ container may not be the most economical solution.

Our distributor in Mexico currently has three machines ready to be shipped. If you are interested, I can help coordinate and combine your machine shipment with theirs to share one container.

This solution may help reduce your shipping cost.

22. Delivery time and customized pre-housing bay

Question:

Does the 45-day delivery time include the customized pre-housing bay?

Answer:

Yes, the 45-day delivery time includes the customized pre-housing bay.

23. Payment terms and import documents

Question:

What are your payment terms?

Which documents do you provide for import into Mexico?

(Packing list, invoice, CE certificate, HS code, etc.)

Answer:

Our payment terms are:

- **30% deposit** to start production
- **70% balance payment** before shipment

For import clearance, we will provide the necessary documents, including:

- Packing list (including package dimensions and weight)
- Commercial invoice
- CE certificate
- HS code

If you need any additional documents required by Mexican customs, please let us know in advance, and we will cooperate accordingly.