

ENERGYPETROL S.A.

Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador Telf: (593) 2 922-064 E-mail: energypetrol@energypetrol.net FECHA DE ACTUALIZACIÓN: 1/2/2017

STOCK DE MATERIALES PARA ENTREGA INMEDIATA SALVO VENTA PREVIA

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

| ITEM | NUM. PARTE | DESCRIPCION | CANT | Unidad |
|------|------------|--|------|--------|
| 1 | 05701236 | OPLFC-S-200-ES PRESSURE SWITCHGEAR Swichgage, panel mount: Range: 0–200 psi Option: Environmentally sealed Bourdon Tube and Tip Material: 316 Stainless Steel Voltaje: 120 Vac P\N 5701236 Nota: Swicth de presión Marca: Murphy Pais de Origen: Estados Unidos | 10 | EA |
| 2 | 05705091 | 45APE-S-400 Pressure Swichgage® 45APE Series Instrument Dial:4-1/2 in. (114 mm) Dual scale: psi and kPa Range:0-400 PSI Voltage: 120 VAC Brand Murphy PN: 05705091 Nota: Swict contralados de nivel Pais de origen; USA | 4 | EA |
| 3 | 05707736 | PXT-K-200 Pressure Transmitters Range: 0-200 PSIG Operating Temperature :-40 to 180°F Process Conecction: ¼ NPT, Body: 316I Stainless steel, Enclosure: Nema 4/ IP 65. Transmisor de presión P\N 0570736 Nota: Transmisor de presion Marca: Murphy Pais de Origen: Estados Unidos | 10 | EA |
| 4 | PTXK400 | 45APE-S-400 Pressure Swichgage® 45APE Series Instrument Dial:4-1/2 in. (114 mm) Dual scale: psi and kPa PTX-K-400 PXT-K Series Pressure Transmitters 4-20 mA Output Signal Piezoresistive Pressure Transmitter Corrosion Resistant Construction High Stability Operating Temperature: -40 to 180°F Range: 0- 400 psi Process Connection: 1/4 NPT femal Area Classification: Class I / II / III, Div 1 , Groups A-F T4 Class I / II / III, Div 2, Groups A-D,F,G T4 Brand Murphy NN: 05707738 Nota: Swicht controlador de nivel Pais de origen: | 3 | EA |
| 5 | 10706790 | 25T-HL-120-25-1/2 TEMPERATURE SWICHGAGE, HL = High and low contacts Range: 32-120 ° F / 0-49 °C (Dual Scale), Capillary length :25 ft Adapter Nuts : ½ SPST contact, pilot duty only,2A @ 30 Vac/Vdc Indicador de Temperatura P/N 10706790 Nota:Swicth de Temperatura Marca: Murphy Pais de Origen: Estados Unidos | 9 | EA |
| | | | | |

|--|



ENERGYPETROL S.A.

Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador Telf: (593) 2 922-064 E-mail: energypetrol@energypetrol.net FECHA DE ACTUALIZACIÓN: 1/2/2017

STOCK DE MATERIALES PARA ENTREGA INMEDIATA SALVO VENTA PREVIA

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

| ITEM | NUM. PARTE | DESCRIPCION | CANT | Unidad |
|------|------------|--|------|--------|
| 6 | 5704360 | A25P-HL-200 PRESSURE SWICHGAGE Dial: White on black, dual scale Case: Polycarbonate/glass filled, corrosion-resistant; steel mounting clamp included. Bezel: Polished stainless steel, standard Oil: Silicon Oil. Range: 0-200 psi HL = High and low contacts Temperature Range: Ambient: -40°F (-40°C) thru 150°F (66°C). Process: -40°F (-40°C) thru 250°F (121°C). Process: Connection: 1/8-27 NPTM brass. SPST contact; pilot-duty only, 2A@30 VAC/DC; Number 6 screw terminals P\N 5704360 Nota: Swicth de presion Marca: Murphy Pais de Origen: Estados Unidos | 9 | EA |
| 7 | 30700010 | W0168-SS ENGINE PANEL Voltage: 24 Vdc Brand: MURPHY P/N: 30700010 | 1 | EA |
| 8 | 20700225 | ATHS-40-B TACH/HOURMETER Voltage: 24 Vdc Brand: MURPHY P/N: 20700225 | 1 | EA |
| 9 | 20700162 | MP3298 MAGNETIC SPEED SENSOR Brand: MURPHY P/N: 20700162 Nota: sensor de velocidad | 1 | EA |
| 10 | 10002444 | ADAPTER KIT,M16 A BULB ADAPTER KIT Brand: MURPHY P/N: 10002444 | 1 | EA |
| | | IVA EN VENTAS | | |

| Elaborado por: | |
|----------------|--|
|----------------|--|