



R.U.C.: 1791403916001
www.energypetrol.net

ENERGYPETROL S.A.

Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador
Telf: (593) 2 922-064
E-mail: energypetrol@energypetrol.net

FECHA DE ACTUALIZACIÓN:

27/3/2017

STOCK DE MATERIALES PARA ENTREGA INMEDIATA SALVO VENTA PREVIA

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

ITEM	NUM. PARTE	DESCRIPCION	CANT	Unidad
1	GA01011XU-3"	Gate Valve 3" ANSI 150 RF Flanged Carbon Steel Body per ASME B16.5 and Bonnet ASTM A216 Gr WCB, , OS&Y, Bolted Bonnet, Flexible Wedge Gate, trim 8 and HF Stellite Seats. Gear operated. With per API 600/602. KF Canada PN GA01011XU-3" Nota: Valvula de Compuerta de 2' Pais de Origen: China	1	EA
2	GA01011XU-4"	Gate Valve 4" ANSI 150 RF Flanged Carbon Steel Body per ASME B16.5 and Bonnet ASTM A216 Gr WCB, , OS&Y, Bolted Bonnet, Flexible Wedge Gate, trim 8 and HF Stellite Seats. Gear operated. With per API 600/602. KF Canada PN GA01011XU-4" Nota: Valvula de Compuerta de 2' Pais de Origen: China	1	EA
3	SC03011XU-4"	VALVE, CHECK, 4", CLASS 300#, CS BODY AND COVER (ASTM-A216 GR WCB), TRIM 8, FLANGED ENDS PER ASME B16.5, HORIZONTAL SWING, BOLTED COVER. DESIGN PER API 600 TEST PER API 598. Marca: KF P/N: SC03011XU-4"	63	EA
4	E3782-129G613	Ball Valve 4" ANSI 300 Full port, Series FAE, Trunnion Mounted, RF flanged ends, double block and bleed sealing injection fittings, carbon steel body A216 WCB, 316 SS ball and trim, devlon seats, HNBR seals, bolting specification NACE Class II, Firesafe API 607, black finish standar, Gear Operator. KF Industries PN:E3782-129G613 Nota: Valvula de bola de 4" Pais de Origen: China.	1	EA
5	E3782-129G613GV	Ball Valve 4" ANSI 300 Full port, Series FAE, Trunnion Mounted, RF flanged ends, double block and bleed sealing injection fittings, carbon steel body A216 WCB, 316 SS ball and trim, devlon seats, HNBR seals, bolting specification NACE Class II, Firesafe API 607, black finish standar, Gear Operator, Test API 598. KF Industries PN E3782-129G613GV Nota: Valvula de bola de 4fp Pais de Origen: China	44	EA
6	E3784-129G613	Ball Valve 6" ANSI 300 Full port, Series FAE, Trunnion Mounted, RF flanged ends, double block and bleed sealing injection fittings, carbon steel body A216 WCB, 316 SS ball and trim, devlon seats, HNBR seals, bolting specification NACE Class II, Firesafe, black finish standar, Gear Operator. KF Industries PN E3784-129G613 Nota: Valvula de bola de 6" Pais de Origen: China.	51	EA
7	E3784-129G613GV	Ball Valve 6" ANSI 300 Full port, Series FAE, Trunnion Mounted, RF flanged ends, double block and bleed sealing injection fittings, carbon steel body A216 WCB, 316 SS ball and trim, devlon seats, HNBR seals, bolting specification NACE Class II, Firesafe API 607, black finish standar, Gear Operator, Test API 598 KF Industries PN E3784-129G613GV Nota: Valvula de bola de 6fp Pais de Origen: China	14	EA
8	E3786-129G613	Ball Valve 8" ANSI 300 Full port, Series FAE, Trunnion Mounted, RF flanged ends, double block and bleed sealing injection fittings, carbon steel body A216 WCB, 316 SS ball and trim, devlon seats, HNBR seals, bolting specification NACE Class II, Firesafe API 607, black finish standar, Gear Operator. KF Industries PN E3786-129G613 Nota: Valvula de bola de 8" Pais de Origen: China.	17	EA
9	E3786-129G613GV	Ball Valve 8" ANSI 300 Full port, Series FAE, Trunnion Mounted, RF flanged ends, double block and bleed sealing injection fittings, carbon steel body A216 WCB, 316 SS ball and trim, devlon seats, HNBR seals, bolting specification NACE Class II, Firesafe API 607, black finish standar, Gear Operator, Test API 598. KF Industries PN E3786-129G613GV Nota: Valvula de bola de 8fp Pais de Origen: China	4	EA
10	E7805-1139KC2992	Check Valve 4" ANSI 300 Full Bore RF Flanged Ends, Serie 35E, Swing Check Carbon Steel Body ASTM A216 WCB, 316SS disc, shaft and bushings, Non-Replaceable Seat, Metal Seals, Top Entry, API-6D, Horizontal Swing, 1/2" NPT Body Drain. KF Industries PN E7805-1139KC2992 Nota: Valvula check de acero de 4" Pais de Origen: China.	15	EA

Elaborado por:



R.U.C.: 1791403916001
www.energypetrol.net

ENERGYPETROL S.A.

Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador
Telf: (593) 2 922-064
E-mail: energypetrol@energypetrol.net

FECHA DE ACTUALIZACIÓN:

27/3/2017

STOCK DE MATERIALES PARA ENTREGA INMEDIATA SALVO VENTA PREVIA

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

ITEM	NUM. PARTE	DESCRIPCION	CANT	Unidad
11	E7807-1139KC2992	Check Valve 6" ANSI 300 Full Bore RF Flanged Ends, Serie 35E, Swing Check Carbon Steel Body ASTM A216 WCB, 316SS disc, shaft and bushings, Non-Replaceable Seat, Metal Seals Top Entry, API-6D, Horizontal Swing, 1/2" NPT Body Drain. KF Industries PN E7807-1139KC2992 Nota: Valvula check de acero de 6" Pais de Origen: China.	20	EA
12	N2456-012	Gear Operatrpr for Ser FAE Trunnion Ball Valve E3784- (6" FP CL300) KF Industries N2456-012 Nota: Accesorio para valvula Pais de Origen: China	20	EA
13	01504-72911SK	Ball Valve 3" 2500 psi, Reducer Port, SS Body, Ball & Stem, Seat and seals Teflon/ Viton, Lever Operated Floating Ball Type Fire Tested. Test API 598. TAG: CA1-2S. Brand KF-Industries P/N: 01504-72911SK NOTA: VALVULA DE BOLA PAIS DE ORIGEN: USA	3	EA
14	02742-1255493	Ball Valve 8" ANSI 900 Full Port RF Flanged Ends, Trunnion Type Series T, Carbon Steel A216 WCB Body, 316 SS Ball & Stem, PEEK Seats, Atlas Seals, Firesafe, with Gear Operator. KF Industries PN 02742-1255493	2	EA
15	03770-169G41A	1 PUEMBO 1 OFICINA Ball Valve 12" ANSI 150 Full Port RF Flanged Ends, Series FA Trunnion Mounted, Double Block & Bleed Sealing Injection Fittings, ASTM A216 WCB/Black, NACE III Body, ASTM A105 w/3mil ENP Ball & Trim, Devlon Seats, HNBR Seals, Firesafe, Bare Stem for Actuator.; KF Industries n/p 03770-169G41A	1	EA
16	03788-169G413	Ball Valve 10" ANSI 300 Full Port RF Flanged ends per ANSI/ASME B16.5, Trunion Ball Series FA, Double Block and Bleed and Sealant Injection Fittings, Carbon Steel ASTM A216 WCB/Black, ASTM A105 w/3mil ENP Ball and stem, Seats Devlon, Seals HNBR, NACE Class III Firesafe, Gear Operator, Brand: KF P/N: 03788-169G413	2	EA
17	05004-221	Ball Valve 1" 2000 psi Reduce Port, Series W Female NPT ends, CF8M Body, Ball & Stem, Teflon Seats, Teflon Seals, Handle Actuation KF Industries PN 05004-221	42	EA
18	3005-21911	Ball Valve 2-1/2" Serie 'CH' 3000 Psi, Regular Port, Carbon Steel Body, 316SS Trim, Buna N Seal, Include Locking Handle, weighth : 13 lbs, KF Industries, Made in USA p/n 3005-21911	5	
19	3781-122G411	Ball Valve 4" Class 300 RF Regular Port Body CS Trim 316SS Seat Teflon, HNBR Nace CL III, with Actuation Handle	1	
20	6100-11111	1/4 FP 3000 FP 3000 FNPT SERIES B FLOATING VALVE BODY ADAPTER: ASTM A216 WCB, BALL STEM & PACKING: CARBON STEEL w/CHROME NICKEL, PLATING, ACTUATION: HANDLE, ADAPTER AND CONNECTIONS: FEMALE NPT, SEAT&SEAL: DELRIN/BUNA-N P/N: 6100-11111	120	EA
21	6103-11111	Ball Valve 3/4" 3000 psi FNTP Screwed Ends, Floating Valve, Carbon Steel Body ASTM A216 WCB Body, Carbon Steel with Nickel Plated Ball & stem, Buna-N Seals, Derlin Seats, Grafoil Stem Packing, Handle Actuation. KF Industries PN 6103-11111	119	EA
22	6104-11111	Ball Valve 1" 3000 psi @ 200°F Reduce Port Threaded Ends FNP, Series B, Floating Ball Valve, ASTM A216 WCB Carbon Steel Body, Carbon Steel with Chrome Plated 3Mil ENP, Derling Seats, Buna-N Seals, Handle Actuation KF Industries PN 6104-11111	95	EA
23	6105-21221	BALL VALVE 1" FP Threaded Ends NPT, 2250 psi @ 200 °F, Body ASTM A351-CF8M, 316SS Ball & Stem, Seats and Seals Teflon, Adapters; 316 Stainless Steel 3-PC Construction, Nace MR-01-75, Firesafe API-607, Floating Design, w/lever Operated KF Industries 6105-21221	24	EA
24	AA10155-099 - V315-1...	Ball Valve 4" Full Port ANSI 600 RF Flanged Ends, Trunnion Type Series P3, Three Split Body, Double Block & Bleed Sealing Injections Fittings, ASTM A105 Carbon Steel Bod, ASTM A105 with 3mil ENP Ball & Stem, Devlon Seat, HNBR Seals, Bare Stem for actuator, Include Enduro Bond Coating KF Industries PN V315-199A6AGAX / PLACA AA10155-099 Nota: Valvula de Bola 4"	1	EA
25	E2297-1922291	Ball Valve 1", Class 300, RF, Full Port, Carbon Steel Body, 316SS Trim, Teflon Seat/VTN Nace Ser FE Ball Valve with Handle, KF Industries N/P E2297 Chinnesse	3	EA
26	E2303-1922291	Ball Valve 3", Class 300, RF, Regular Port, Carbon Steel Body, 316SS Trim, Teflon Seat/VTN Nace Ser FE Ball Valve with Handle, KF Industries N/P E2303-1922291	2	EA
27	E2306-1922291	Ball Valve 4", Class 300, RF, Full Port, Carbon Steel Body, 316SS Trim, Teflon Seat/VTN Nace Ser FE Ball Valve with Handle, KF Industries N/P E2306 Chinnesse	5	DIA

Elaborado por:



R.U.C.: 1791403916001
www.energypetrol.net

ENERGYPETROL S.A.

Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador
Telf: (593) 2 922-064
E-mail: energypetrol@energypetrol.net

FECHA DE ACTUALIZACIÓN:

27/3/2017

STOCK DE MATERIALES PARA ENTREGA INMEDIATA SALVO VENTA PREVIA

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

ITEM	NUM. PARTE	DESCRIPCION	CANT	Unidad
28	E3758-129G614	Ball Valve 2", Double block and bleed, Class #150, Full Port, Body / Bolting Material: CS / CS, Trim & Drain: 316SS; Seat Insert: Devlon; O-Ring: HNBR; Specifications: NACE Cl. II B7M/2HM Bolting / Firesafe; Bolting Finish /Body & Adaptor: Black; Actuation: Handle w/Locking. Two-piece split body trunnion mounted ball valve conforms to API 6D, ASME B16.34 and ASTM specifications. P/N: E3758-129G614 KF	1	EA
29	G2157-1812G91LD	Ball Valve 6" ANSI 150 Reduce Port, RF Flanged Ends per ANSI/ASME B16.5, Floating Ball Series F, Carbon Steel ASTM-A216 WCB Body, Carbon Steel 3Mil ENP Ball & Stem, HNBR Seats, Teflon Seats, Bolting Class III Firesafe, Lever Operated. Include Enduro Bond Coating KF Industries PN G2157-1812G91LD	12	EA
30	G2157-1822E91	Ball Valve 6" ANSI 150 Reduce Port RF Flanged Ends, Floating Type Series F, Carbon Steel Body, 316SS Ball & Stem, PTFE Seats, Viton Seats, Firesafe, Handle Actuation KF Industries PN G2157-1822E91	12	EA
31	U5002-D21X	Ball Valve 1/2" Full Port 2000 WOG; Series HS810 Floating; 316SS Body, Ball /Stem 316SS; RTFE Seats; Firesafe; Handle Actuation. TEST PER API 598, TAG: CA1-2S. P/N: U5002-D21X	12	EA
32	U5007-D21X	Ball Valves 2" Reducer Port, Serie HS810 Floating Ball , 316 Stainless Steel Body Ball and Stem for Pressure up to 2000# CWP. FNPT, Threaded end connections. Teflon Seats and Manual Handle Operation, Fire Safe Certified. Test API 598. TAG: CA1-2S. Brand KF-Industries P/N: U5007-D21X	1	EA
33	BG-0400411125	Butterfly Valve 4" 200 psi Wafer type, Cast Iron Body, Ductile Iron with Nickel Plating Disc, Buna N Seats, Standard Locking DI Handle. KF Industries PN BG-0400411125	18	EA
34	BG-0600411125	Butterfly Valve 6" 200 psi, Wafer Desing, Cast Iron body, Ductile Iron with Nickel Plating Disc, 431SS Stem, Buna N Seats, Standard Locking DI Handle. KF Industries PN BG-060041125	22	EA
35	7121-1139K21911	CHECK VALVE 2-1/2", Ansi 300, Serie 10, RF, Carbon Steel Body, 316SS disc, shaft, bushing and spring, Buna N seal, weight : 9 lbs, KF Industries n/p 7121-1139K21911	2	
36	7123-1139K21911	CHECK VALVE 4", Ansi 300, Serie 10, Carbon Steel Body, 316SS disc, shaft, bushing and spring, Buna N seal, weight : 23 lbs, KF Industries n/p 7123-1139K21911	1	EA
37	0898331	Solenoid Valve, 1/2 NPT, 24 VDC, Accesories Model No. BMS-1N 24 vdc, enclosure Nema 4, 24VDC Voltage EDP Code: 0898331	19	EA
38	15-345	NEEDLE VALVE 3/4 6000 Psi CWP, 316SS, Male x Female NPT, Fab. KF Industries No.Part. 15-345	5	EA
39		G2153-1822G91LD	1	
40		BALL VALVE 4" #150 CF8M	2	
41		VALVE 6", 200 PSI BG ASTM	2	
42	E2154-1922G91	Ball Valve 3" ANSI 150 Full Port, RF Flanged ends; Floating Ball Series F, Body API 6D, ASTM A216 WCB Body, 316SS Ball & Stem, Teflon Seats, HNBR Seats, Handle actuation. TAG: AA1-2RF. Brand KF Industries PN: E2154-1922G91 Procedencia China	4	EA
46	E2156-1922G91	Ball Valve 4" ANSI 150 Full Port, RF Flanged ends; Floating Ball Series F, Body API 6D, ASTM A216 WCB Body, 316SS Ball & Stem, Teflon Seats, HNBR Seats, Handle actuation. TAG: AA1-2RF. Brand KF Industries PN: E2154-1922G91 Procedencia China	4	EA
47	E2153-1922G91	Ball Valve 3", ANSI 150 Reducer Port, RF flanged ends; Conforms to API 6D for designed, ASTM A216 WCB Body & Bolting, 316 Stainles Steel Ball & Stem, Teflon (Uniseal) Seats, HNBR Seats, Handle actuation. Fire safe to API 607, n/p E2153-1922291, KF Industries, Made in China	22	EA
49		GATE VALVE 4" #150, WCB,	3	
51	05002-221	Ball Valve 1/2", 2000 psi Full Port, FNPT, Serie W Floating Ball Valve, Carbon Steel Body, All Stainless Steel NACE Trim, KF Industries PN 05002-221	2	EA
50	05003-221	Ball Valve 3/4", 2000 psi Full Port, FNPT, Serie W Floating Ball Valve, SSI Body, All Stainless Steel NACE Trim, KF Industries PN 05003-221	288	EA
53		BALL VALVE 2", CF8M 2000 PSI, WOP	4	
54		BALL VALVE 2", #300, WCB	1	
55	N14-125HT	Needle Valve 1/2"; 10,000 lbs, max WOG @ 200 Deg F; metal seated, All Valve in 316 Stainless Steel. KF industries PN N14-125HT	38	EA
56		VALVULA DE ALIVIO 1/2" TYPE HM-2	1	

Elaborado por:



R.U.C.: 1791403916001
www.energypetrol.net

ENERGYPETROL S.A.

Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador
Telf: (593) 2 922-064
E-mail: energypetrol@energypetrol.net

FECHA DE ACTUALIZACIÓN:

27/3/2017

STOCK DE MATERIALES PARA ENTREGA INMEDIATA SALVO VENTA PREVIA

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

ITEM	NUM. PARTE	DESCRIPCION	CANT	Unidad
57	05038-002	316 SS Ball INDEX 4 KF Industries PN 05038-002 Nota: Bola de acero inoxidable para valvula Pais de Origen: Estados Unidos	1	EA
58		E2150-1922G91LD	12	
59		147XU - J3615060287	2	
60		G2150-1822G91LD	2	
66	02639-012	Gear Operatr for Series FAE Trunnion Ball Valve E3782- (4" FP CL300) KF Industries PN 02639-012 Nota: Accesorio para valvula Pais de Origen: China	20	EA
62	03765-169G613	Ball Valve 8" ANSI 150 Reduce Port, Series FA, Trunion Mounted Type, Duoble Block and Bleed Sealing Fitting, ASTM A216 WCB Body, Ball and Stem ASTM A105 w/ 3mil ENP Devlon Seats, HNBR seal, NACE class II Fire Safe, Bolting Finish B7 Standar Black, Include Gear Operator KF Industries PN 03765-169G613 Nota: Valvula esferica de 8" Pais de Origen: Estados Unidos	11	EA
67	E3781-169G411	Ball Valve 4", Class 300#, CS body (ASTM-A216 Gr WCB or ASTMA105), CS 3 mil ENP ball and stem, RF flanged ends per ASME B16.5, reduced port, lever operated. Trunnion mounted, double block and bleed and sealant injection fittings. Fire safe. Design and test per API 6D TAG: C2-2R Brand: KF P/N: E3781-169G411	62	EA
61	G2150-1822G91	Ball Valve 2" ANSI 150 RF Flanged Ends Reduce Port, Series F Floating Ball, WCB Carbon Steel Body, 316 Stainless Steel Ball & Stem, PTFE Seats, HNBR Seals, NACE III Bolting specifications, Handle Actuation KF INDUSTRIES PN G2150-1822G91	7	EA
63	G2157-1812G91LD	Ball Valve 6" ANSI 150 Reduce Port, RF Flanged Ends per ANSI/ASME B16.5, Floating Ball Series F, Carbon Steel ASTM-A216 WCB Body, Carbon Steel 3Mil ENP Ball & Stem, HNBR Seals, Teflon Seats, Bolting Class III Firesafe, Lever Operated. Include Enduro Bond Coating KF Industries PN G2157-1812G91LD	12	EA
65	N14-10HT	Needle Valve 1" 6000 PSI @ 200 °F, bar stock body (316 SS), Teflon stem seat, soft or hard seats, FM x FM threaded ends per ASME B1.20.1. Design per MSS SP-105TAG: C2-6SFM Brand: KF P/N: N14-10HT	39	EA
68		G2155-1822G91LD	1	
75	03768-169G41A	Ball Valve 10" ANSI 150 Full port RF Series FA Trunnion Ball Valve; Body/Bolting ASTM A216 WCB/Black; Ball/Stem ASTM A105 w/3mil ENP; Seat Insert Devlon; Seal HNBR; Bolting material Nace Class III/Firesafe; Bolting Finish Standar-Black; Bare Stem for Actuator KF Industries PN: 03768-169G41A	1	EA
73	03770-169G41A	Ball Valve 12" ANSI 150 Full Port RF Fanged Ends, Series FA Trunnion Mounted, Double Block & Bleed Sealing Injection Fittings, ASTM A216 WCB/Black, NACE III Body, ASTM A105 w/3mil ENP Ball & Trim, Devlon Seats, HNBR Seals, Firesafe, Bare Stem for Actuator.; KF Industries n/p 03770-169G41A	2	EA
69	E1720-1922G91	Ball Valve 6" ANSI 150 Full, Port RF Flanged Ends, Carbon Steel Body, 316 Stainless Steel Trim, Teflon Seats, HNBR Seals, NACE CL III, Handle Operator KF Industries PN E1720-1922G91, Made in China Nota: Valvula de bola	6	EA
70	E3766-169G613	8" Ball Valve Class 150#, CS body (ASTM-A216 Gr WCB or ASTMA105), CS 1 mil ENP ball and stem, RF flanged ends per ASME B16.5, full port, gear operated. Trunnion mounted, double block and bleed and sealant injection fittings. Fire safe. Design and test per API 6D Brand: KF P/N: E3766-169G613	4	EA
76	E3766-169G613	8" Ball Valve Class 150#, CS body (ASTM-A216 Gr WCB or ASTMA105), CS 1 mil ENP ball and stem, RF flanged ends per ASME B16.5, full port, gear operated. Trunnion mounted, double block and bleed and sealant injection fittings. Fire safe. Design and test per API 6D Brand: KF P/N: E3766-169G613	2	EA
74	E3790-169G613	12" Ball Valve Class 300#, CS body (ASTM-A216 Gr WCB or ASTMA105), CS 3 mil ENP ball and stem, RF flanged ends per ASME B16.5, full port, lever or gear (6" and larger) operated. Trunnion mounted, double block and bleed and sealant injection fittings. Fire safe. Design and test per API 6D Brand: KF P/N: E3790-169G613	1	EA

Elaborado por:



Calle José Puerta N39-155 y Av. Eloy Alfaro - Quito - Ecuador
Telf: (593) 2 922-064
E-mail: energypetrol@energypetrol.net

27/3/2017

"PARA PEDIDOS FORMALES Y CONFIRMACIÓN DE DISPONIBILIDAD CONTÁCTESE CON NOSOTROS"

Elaborado por:	
----------------	--