

The schematic diagram illustrates the internal wiring of a USB-C to USB-A adapter. On the left, the USB-C connector (J1) is shown with its pins: VBUS, A4, A5, B5, A7, B7, A6, B6, AB, and BB. The USB-A connector (D1) is shown on the right with its pins: D+, D-, D+, and D-. The internal components include a USBLC6-25C6 chip, capacitors C1 and C2, and resistors R1 and R2. The shield connection is also shown. The USB-C connector is connected to the USB-A connector via the USBLC6-25C6 chip. The USB-C connector has a shield connection (SH) and a ground connection (GND). The USB-A connector has a ground connection (GND). The schematic shows the internal connections and components like capacitors (C1, C2), resistors (R1, R2), and a shield connection.

The diagram shows the RP2354A microcontroller with the following connections:

- Power:**
 - VREG_AVDD: +3V3
 - USB_OTF_VDD: +3V3
 - ADC_VDD: +3V3
 - QSPI_VDD: +3V3
 - VREG_VIN: +3V3
 - VREG_V: +1V1
 - DVDD: +1V1
- I2C:**
 - SDA (pin 2): +1V1
 - SCL (pin 3): +1V1
- USB:**
 - USB_DM (pin 51): +1V1
 - USB_DP (pin 52): +1V1
 - USB_DP (pin 52): +1V1
- QSPI:**
 - QSPI_SS (pin 60): +3V3
 - QSPI_SCLK (pin 66): +3V3
 - QSPI_SD0 (pin 67): +3V3
 - QSPI_SD1 (pin 68): +3V3
 - QSPI_SD2 (pin 69): +3V3
 - QSPI_SD3 (pin 70): +3V3
- Other:**
 - RUN (pin 26): RUN
 - XIN (pin 21): XIN
 - XOUT (pin 22): XOUT
 - SWCLK (pin 24): SWCLK
 - SWDIO (pin 25): SWDIO
 - VREG_PND (pin 47): GND
 - GND (pin 61): GND

External components shown include capacitors C13, C14, C15, C16, C17, C18 and a ferrite bead FB1.

[illegible]

The schematic shows three main components connected to a +3V3 VTT supply:

- Top Section:** A network of five 100nF capacitors (C30-C34) connected to GND.
- Middle Section:** An SN74LVC1T45PW comparator (U4). Its inputs are TCK_3V3 (A1), TDI_3V3 (A2), TMS_3V3 (A3), and NRST_3V3 (A4). Its outputs are TCK_B (B1), TDI_B (B2), TMS_B (B3), and NRST_B (B4). The output DIR (B8) is connected to XLAT_OE via a 10k pull-up resistor (N22).
- Bottom Section:** Two SN74LVC1T45DBV comparators (U5 and U6). U5 has inputs DATA_3V3 (A) and DATA_DIR (B). U6 has inputs KEY_3V3 (A) and KEY_DIR (B). Both have their DIR pins (B8) connected to GND via 10k pull-down resistors (N24).

[illegible][illegible]

The diagram illustrates the connection of the PWR_FLAG pin to different power supply rails across four mounting holes (H1, H2, H3, H4). The connections are as follows:

- H1 MountingHole:** PWR_FLAG is connected to GND.
- H2 MountingHole:** PWR_FLAG is connected to VBUS.
- H3 MountingHole:** PWR_FLAG is connected to +5V.
- H4 MountingHole:** PWR_FLAG is connected to +1V1.

Below the main diagram, two additional connections are shown:

- ADC_AVDD:** PWR_FLAG is connected to ADC_AVDD.
- VREG_AVDD:** PWR_FLAG is connected to VREG_AVDD.

Title: sinodeude-rp2354		
Size: A2	Date:	Rev: A
KiCad E.D.A. 10.0.6		Id: 1/1